


OpenGL[®] SuperBible



Seventh Edition

Comprehensive Tutorial and Reference



Graham Sellers ■ Richard S. Wright, Jr. ■ Nicholas Haemel

FREE SAMPLE CHAPTER

SHARE WITH OTHERS







OpenGL[®]

SuperBible

Seventh Edition

OpenGL Series

from Addison-Wesley



◆◆Addison-Wesley

Visit informit.com/opengl for a complete list of available products.

The OpenGL graphics system is a software interface to graphics hardware. ("GL" stands for "Graphics Library".) It allows you to create interactive programs that produce color images of moving, three-dimensional objects. With OpenGL, you can control computer-graphics technology to produce realistic pictures, or ones that depart from reality in imaginative ways.

The **OpenGL Series** from Addison-Wesley Professional comprises tutorial and reference books that help programmers gain a practical understanding of OpenGL standards, along with the insight needed to unlock OpenGL's full potential.



Make sure to connect with us!
informit.com/socialconnect

informit.com
the trusted technology learning source

◆◆Addison-Wesley

▶Safari

OpenGL[®]

SuperBible

Seventh Edition

*Comprehensive Tutorial
and Reference*

Graham Sellers

Richard S. Wright, Jr.

Nicholas Haemel

◆ Addison-Wesley

New York • Boston • Indianapolis • San Francisco
Toronto • Montreal • London • Munich • Paris • Madrid
Capetown • Sydney • Tokyo • Singapore • Mexico City

Many of the designations used by manufacturers and sellers to distinguish their products are claimed as trademarks. Where those designations appear in this book, and the publisher was aware of a trademark claim, the designations have been printed with initial capital letters or in all capitals.

OpenGL® is a registered trademark of Silicon Graphics Inc. and is used by permission of Khronos.

The authors and publisher have taken care in the preparation of this book, but make no expressed or implied warranty of any kind and assume no responsibility for errors or omissions. No liability is assumed for incidental or consequential damages in connection with or arising out of the use of the information or programs contained herein.

For information about buying this title in bulk quantities, or for special sales opportunities (which may include electronic versions; custom cover designs; and content particular to your business, training goals, marketing focus, or branding interests), please contact our corporate sales department at corpsales@pearsoned.com or (800) 382-3419.

For government sales inquiries, please contact governmentsales@pearsoned.com.

For questions about sales outside the United States, please contact international@pearsoned.com.

Visit us on the Web: informit.com/aw

Library of Congress Cataloging-in-Publication Data

Wright, Richard S., Jr., 1965- author.

OpenGL superBible : comprehensive tutorial and reference.—

Seventh edition / Graham Sellers, Richard S. Wright, Jr., Nicholas Haemel.

pages cm

Includes bibliographical references and index.

ISBN 978-0-672-33747-5 (pbk. : alk. paper)—ISBN 0-672-33747-9 (pbk. : alk. paper)

1. Computer graphics. 2. OpenGL. I. Sellers, Graham, author. II.

Haemel, Nicholas, author. III. Title.

T385.W728 2016

006.6'8—dc23

2015014278

Copyright © 2016 Pearson Education, Inc.

All rights reserved. Printed in the United States of America. This publication is protected by copyright, and permission must be obtained from the publisher prior to any prohibited reproduction, storage in a retrieval system, or transmission in any form or by any means, electronic, mechanical, photocopying, recording, or likewise. To obtain permission to use material from this work, please submit a written request to Pearson Education, Inc., Permissions Department, 200 Old Tappan Road, Old Tappan, New Jersey 07675, or you may fax your request to (201) 236-3290.

ISBN-13: 978-0-672-33747-5

ISBN-10: 0-672-33747-9

Text printed in the United States on recycled paper at RR Donnelley in Crawfordsville, Indiana.

First printing, July 2015

Editor-in-Chief

Mark L. Taub

Executive Editor

Laura Lewin

Managing Editor

John Fuller

Full-Service

Production

Manager

Julie B. Nahil

Copy Editor

Jill Hobbs

Indexer

Larry D. Sweazy

Proofreader

Anna Popick

Technical Reviewer

Matias Goldberg

Editorial Assistant

Olivia Basegio

Compositor

diacriTech

For you, the reader.
—*Graham Sellers*

This page intentionally left blank

Contents

Figures	xv
Tables	xxi
Listings	xxiii
Foreword	xxxii
Preface	xxxiii
The Architecture of the Book	xxxiv
What's New in This Edition	xxxvi
How to Build the Examples	xxxvii
Errata	xxxviii
Note from the Publisher	xxxviii
Acknowledgments	xxxix
About the Author	xli
I Foundations	1
1 Introduction	3
OpenGL and the Graphics Pipeline	4
The Origins and Evolution of OpenGL	6
Core Profile OpenGL	8
Primitives, Pipelines, and Pixels	10
Summary	11
2 Our First OpenGL Program	13
Creating a Simple Application	14
Using Shaders	17

Drawing Our First Triangle	24
Summary	26
3 Following the Pipeline	27
Passing Data to the Vertex Shader	28
Vertex Attributes	28
Passing Data from Stage to Stage	30
Interface Blocks	31
Tessellation	33
Tessellation Control Shaders	33
The Tessellation Engine	35
Tessellation Evaluation Shaders	35
Geometry Shaders	37
Primitive Assembly, Clipping, and Rasterization	39
Clipping	39
Viewport Transformation	40
Culling	41
Rasterization	43
Fragment Shaders	43
Framebuffer Operations	47
Pixel Operations	47
Compute Shaders	48
Using Extensions in OpenGL	49
Enhancing OpenGL with Extensions	50
Summary	54
4 Math for 3D Graphics	55
Is This the Dreaded Math Chapter	56
A Crash Course in 3D Graphics Math	57
Vectors, or Which Way Is Which?	57
Common Vector Operators	60
Matrices	64
Matrix Construction and Operators	66
Understanding Transformations	69
Coordinate Spaces in OpenGL	70
Coordinate Transformations	72
Concatenating Transformations	80
Quaternions	81
The Model-View Transform	83
Projection Transformations	86
Interpolation, Lines, Curves, and Splines	89

Curves	91
Splines	94
Summary	97
5 Data	99
Buffers	100
Creating Buffers and Allocating Memory	100
Filling and Copying Data in Buffers	107
Feeding Vertex Shaders from Buffers	109
Uniforms	117
Default Block Uniforms	117
Uniform Blocks	121
Using Uniforms to Transform Geometry	135
Shader Storage Blocks	140
Synchronizing Access to Memory	145
Atomic Counters	147
Synchronizing Access to Atomic Counters	151
Textures	152
Creating and Initializing Textures	152
Texture Targets and Types	154
Reading from Textures in Shaders	156
Loading Textures from Files	160
Controlling How Texture Data Is Read	164
Array Textures	177
Writing to Textures in Shaders	182
Synchronizing Access to Images	194
Texture Compression	195
Texture Views	199
Summary	203
6 Shaders and Programs	205
Language Overview	206
Data Types	206
Built-In Functions	213
Compiling, Linking, and Examining Programs	219
Getting Information from the Compiler	219
Getting Information from the Linker	223
Separate Programs	225
Shader Subroutines	231
Program Binaries	235
Summary	238

II In Depth

239

7	Vertex Processing and Drawing Commands	241
	Vertex Processing	242
	Vertex Shader Inputs	242
	Vertex Shader Outputs	247
	Drawing Commands	249
	Indexed Drawing Commands	249
	Instancing	255
	Indirect Draws	269
	Storing Transformed Vertices	278
	Using Transform Feedback	279
	Starting, Pausing, and Stopping Transform Feedback	284
	Ending the Pipeline with Transform Feedback	286
	Transform Feedback Example: Physical Simulation	286
	Clipping	296
	User-Defined Clipping	300
	Summary	303
8	Primitive Processing	305
	Tessellation	306
	Tessellation Primitive Modes	307
	Tessellation Subdivision Modes	316
	Passing Data between Tessellation Shaders	319
	Communication between Shader Invocations	322
	Tessellation Example: Terrain Rendering	323
	Tessellation Example: Cubic Bézier Patches	329
	Geometry Shaders	333
	The Pass-Through Geometry Shader	334
	Using Geometry Shaders in an Application	336
	Discarding Geometry in the Geometry Shader	341
	Modifying Geometry in the Geometry Shader	344
	Generating Geometry in the Geometry Shader	346
	Changing the Primitive Type in the Geometry Shader	349
	Multiple Streams of Storage	352
	New Primitive Types Introduced by the Geometry Shader	353
	Multiple Viewport Transformations	361
	Summary	364
9	Fragment Processing and the Framebuffer	365
	Fragment Shaders	366
	Interpolation and Storage Qualifiers	366

Per-Fragment Tests	369
Scissor Testing	369
Stencil Testing	372
Depth Testing	376
Early Testing	380
Color Output	382
Blending	382
Logical Operations	387
Color Masking	388
Off-Screen Rendering	390
Multiple Framebuffer Attachments	395
Layered Rendering	397
Framebuffer Completeness	403
Rendering in Stereo	407
Antialiasing	412
Antialiasing by Filtering	413
Multi-Sample Antialiasing	415
Multi-Sample Textures	417
Sample Rate Shading	421
Centroid Sampling	424
Advanced Framebuffer Formats	428
Rendering with No Attachments	428
Floating-Point Framebuffers	430
Integer Framebuffers	444
The sRGB Color Space	446
Point Sprites	448
Texturing Points	449
Rendering a Star Field	450
Point Parameters	453
Shaped Points	454
Rotating Points	456
Getting at Your Image	458
Reading from a Framebuffer	458
Copying Data between Framebuffers	461
Reading Back Texture Data	464
Summary	466

10 Compute Shaders 467

Using Compute Shaders	468
Executing Compute Shaders	469
Compute Shader Communication	474
Examples	479

Compute Shader Parallel Prefix Sum	479
Compute Shader Flocking	492
Summary	502

11 Advanced Data Management 503

Eliminating Binding	504
Sparsely Populated Textures	509
Texture Compression	516
The RGTC Compression Scheme	516
Generating Compressed Data	519
Packed Data Formats	525
High-Quality Texture Filtering	527
Summary	531

12 Controlling and Monitoring the Pipeline 533

Queries	534
Occlusion Queries	535
Timer Queries	545
Transform Feedback Queries	549
Pipeline State Queries	555
Synchronization in OpenGL	556
Draining the Pipeline	557
Synchronization and Fences	557
Summary	562

III In Practice 565

13 Rendering Techniques 567

Lighting Models	568
The Phong Lighting Model	568
Blinn-Phong Lighting	577
Rim Lighting	579
Normal Mapping	582
Environment Mapping	587
Material Properties	597
Casting Shadows	599
Atmospheric Effects	605
Non-Photo-Realistic Rendering	610
Cell Shading: Texels as Light	610

Alternative Rendering Methods	613
Deferred Shading	613
Screen-Space Techniques	624
Rendering without Triangles	631
Two-Dimensional Graphics	647
Distance Field Textures	647
Bitmap Fonts	656
Summary	659
 14 High-Performance OpenGL	 661
Optimizing CPU Performance	661
Multi-Threading in OpenGL	662
Packet Buffers	668
Low-Overhead OpenGL	677
Indirect Rendering	678
GPU Work Generation	683
Zero Copy	691
Performance Analysis Tools	699
Windows Performance Toolkit and GPUView	699
GPU PerfStudio	703
Tuning Your Application for Speed	706
Summary	726
 15 Debugging and Stability	 729
Debugging Your Applications	730
Debug Contexts	730
Security and Robustness	737
Graphics Reset	737
Range-Checked Reads	740
Summary	742
 A Further Reading	 743
 B The SBM File Format	 749
 C The SuperBible Tools	 759
 Glossary	 797
Index	805

This page intentionally left blank

Figures

Figure 1.1	Simplified graphics pipeline	6
Figure 1.2	Future Crew’s 1992 demo—Unreal	9
Figure 2.1	The output of our first OpenGL application	16
Figure 2.2	Rendering our first point	23
Figure 2.3	Making our first point bigger	24
Figure 2.4	Our very first OpenGL triangle	26
Figure 3.1	Our first tessellated triangle	37
Figure 3.2	Tessellated triangle after adding a geometry shader . .	39
Figure 3.3	Clockwise (left) and counterclockwise (right) winding order	42
Figure 3.4	Result of Listing 3.10	45
Figure 3.5	Result of Listing 3.12	46
Figure 3.6	Realtech VR’s OpenGL Extensions Viewer	51
Figure 4.1	A point in space is both a vertex and a vector	58
Figure 4.2	The dot product: cosine of the angle between two vectors	61
Figure 4.3	A cross product returns a vector perpendicular to its parameters	62
Figure 4.4	Reflection and refraction	64
Figure 4.5	A 4×4 matrix representing rotation and translation	68
Figure 4.6	Modeling transformations: (a) rotation, then translation and (b) translation, then rotation	69

Figure 4.7	Two perspectives of view coordinates	72
Figure 4.8	The modeling transformations	73
Figure 4.9	A cube translated ten units in the positive y direction	75
Figure 4.10	A cube rotated about an arbitrary axis	78
Figure 4.11	A non-uniform scaling of a cube	80
Figure 4.12	A side-by-side example of an orthographic versus perspective projection	88
Figure 4.13	Finding a point on a line	90
Figure 4.14	A simple Bézier curve	91
Figure 4.15	A cubic Bézier curve	93
Figure 4.16	A cubic Bézier spline	95
Figure 5.1	Binding buffers and uniform blocks to binding points	133
Figure 5.2	A few frames from the spinning cube application . . .	139
Figure 5.3	Many cubes!	140
Figure 5.4	A simple textured triangle	157
Figure 5.5	A full-screen texture loaded from a .KTX file	162
Figure 5.6	An object wrapped in simple textures	164
Figure 5.7	Texture filtering—nearest neighbor (left) and linear (right)	169
Figure 5.8	A series of mipmapped images	171
Figure 5.9	A tunnel rendered with three textures and mipmapping	174
Figure 5.10	Example of texture coordinate wrapping modes	176
Figure 5.11	GL_MIRROR_CLAMP_TO_EDGE in action	177
Figure 5.12	Output of the alien rain sample	182
Figure 5.13	Resolved per-fragment linked lists	194
Figure 6.1	Shape of a Hermite curve	217
Figure 7.1	Indices used in an indexed draw	250
Figure 7.2	Base vertex used in an indexed draw	253
Figure 7.3	Triangle strips (a) without primitive restart and (b) with primitive restart	255
Figure 7.4	First attempt at an instanced field of grass	260
Figure 7.5	Slightly perturbed blades of grass	260
Figure 7.6	Control over the length and orientation of our grass	262
Figure 7.7	The final field of grass	263
Figure 7.8	Result of instanced rendering	268
Figure 7.9	Result of asteroid rendering program	277
Figure 7.10	Relationship of transform feedback binding points . .	282
Figure 7.11	Connections of vertices in the spring mass system . .	287
Figure 7.12	Simulation of points connected by springs	295

Figure 7.13	Visualizing springs in the spring mass system	296
Figure 7.14	Clipping lines	297
Figure 7.15	Clipping triangles	298
Figure 7.16	Clipping triangles using a guard band	299
Figure 7.17	Rendering with user clip distances	303
Figure 8.1	Schematic of OpenGL tessellation	307
Figure 8.2	Tessellation factors for quad tessellation	308
Figure 8.3	Quad tessellation example	309
Figure 8.4	Tessellation factors for triangle tessellation	310
Figure 8.5	Triangle tessellation example	311
Figure 8.6	Tessellation factors for isoline tessellation	313
Figure 8.7	Isoline tessellation example	314
Figure 8.8	Tessellated isoline spirals example	315
Figure 8.9	Triangle tessellated using point mode	316
Figure 8.10	Tessellation using different subdivision modes	318
Figure 8.11	Displacement map used in terrain example	323
Figure 8.12	Terrain rendered using tessellation	328
Figure 8.13	Tessellated terrain in wireframe	328
Figure 8.14	Final rendering of a cubic Bézier patch	332
Figure 8.15	A Bézier patch and its control cage	333
Figure 8.16	Geometry culled from different viewpoints	344
Figure 8.17	Exploding a model using the geometry shader	345
Figure 8.18	Basic tessellation using the geometry shader	348
Figure 8.19	Displaying the normals of a model using a geometry shader	352
Figure 8.20	Lines produced using lines with adjacency primitives	354
Figure 8.21	Triangles produced using GL_TRIANGLES_ADJACENCY	355
Figure 8.22	Triangles produced using GL_TRIANGLE_STRIP_ADJACENCY	355
Figure 8.23	Ordering of vertices for GL_TRIANGLE_STRIP_ADJACENCY	356
Figure 8.24	Rendering a quad using a pair of triangles	357
Figure 8.25	Parameterization of a quad	358
Figure 8.26	Quad rendered using a geometry shader	359
Figure 8.27	Result of rendering to multiple viewports	363
Figure 9.1	Contrasting perspective-correct and linear interpolation	369
Figure 9.2	Rendering with four different scissor rectangles	372
Figure 9.3	Effect of depth clamping at the near plane	379
Figure 9.4	A clipped object with and without depth clamping	380

Figure 9.5	All possible combinations of blending functions . . .	386
Figure 9.6	Result of rendering into a texture	395
Figure 9.7	Result of the layered rendering example	401
Figure 9.8	Result of stereo rendering to a stereo display	412
Figure 9.9	Antialiasing using line smoothing	413
Figure 9.10	Antialiasing using polygon smoothing	414
Figure 9.11	Antialiasing sample positions	415
Figure 9.12	No antialiasing (left) and eight-sample antialiasing (center and right)	416
Figure 9.13	Antialiasing of high-frequency shader output	422
Figure 9.14	Partially covered multi-sampled pixels	425
Figure 9.15	Different views of an HDR image	433
Figure 9.16	Histogram of levels for treelights.ktx	434
Figure 9.17	Naïve tone mapping by clamping	435
Figure 9.18	Transfer curve for adaptive tone mapping	436
Figure 9.19	Result of adaptive tone-mapping program	438
Figure 9.20	The effect of light bloom on an image	439
Figure 9.21	Original and thresholded output for bloom example	441
Figure 9.22	Blurred thresholded bloom colors	443
Figure 9.23	Result of the bloom program	444
Figure 9.24	Gamma curves for sRGB and simple powers	447
Figure 9.25	A particle effect in the flurry screen saver	449
Figure 9.26	The star texture map	451
Figure 9.27	Flying through space with point sprites	453
Figure 9.28	Two potential orientations of textures on a point sprite	454
Figure 9.29	Analytically generated point sprite shapes	455
Figure 10.1	Global and local compute work group dimensions . . .	473
Figure 10.2	Effect of race conditions in a compute shader	478
Figure 10.3	Effect of barrier() on race conditions	478
Figure 10.4	Sample input and output of a prefix sum operation . .	480
Figure 10.5	Breaking a prefix sum into smaller chunks	482
Figure 10.6	A 2D prefix sum	484
Figure 10.7	Computing the sum of a rectangle in a summed area table	487
Figure 10.8	Variable filtering applied to an image	487
Figure 10.9	Depth of field in a photograph	488
Figure 10.10	Applying depth of field to an image	491
Figure 10.11	Effects achievable with depth of field	491
Figure 10.12	Stages in the iterative flocking algorithm	493
Figure 10.13	Output of compute shader flocking program	501

Figure 11.1	Output of the <code>bindlesstex</code> example application . . .	508
Figure 11.2	Output of the <code>sparsetexture</code> example application . .	514
Figure 11.3	Representation of image data as endpoints of a line	517
Figure 11.4	Result of using RGTC texture compression on a distance field	525
Figure 11.5	Linear interpolation under high magnification	528
Figure 11.6	Graph showing linear interpolation	529
Figure 11.7	Graph showing smooth interpolation	529
Figure 11.8	Result of smooth interpolation	531
Figure 13.1	Vectors used in Phong lighting	570
Figure 13.2	Per-vertex lighting (Gouraud shading)	573
Figure 13.3	Per-fragment lighting (Phong shading)	574
Figure 13.4	Varying specular parameters of a material	577
Figure 13.5	Phong lighting (left) versus Blinn-Phong lighting (right)	579
Figure 13.6	Rim lighting vectors	580
Figure 13.7	Result of rim lighting example	581
Figure 13.8	Example normal map	583
Figure 13.9	Result of normal mapping example	586
Figure 13.10	A selection of spherical environment maps	588
Figure 13.11	Result of rendering with spherical environment mapping	589
Figure 13.12	Example equirectangular environment map	591
Figure 13.13	Rendering result of equirectangular environment map	591
Figure 13.14	The layout of six cube faces in the cubemap sample program	593
Figure 13.15	Cubemap environment rendering with a skybox . . .	597
Figure 13.16	Pre-filtered environment maps and gloss map	598
Figure 13.17	Result of per-pixel gloss example	599
Figure 13.18	Depth as seen from a light	602
Figure 13.19	Results of rendering with shadow maps	605
Figure 13.20	Graphs of exponential decay	608
Figure 13.21	Applying fog to a tessellated landscape	609
Figure 13.22	A one-dimensional color lookup table	610
Figure 13.23	A toon-shaded torus	613
Figure 13.24	Visualizing components of a G-buffer	618
Figure 13.25	Final rendering using deferred shading	620
Figure 13.26	Deferred shading with (left) and without (right) normal maps	622
Figure 13.27	Bumpy surface occluding points	625
Figure 13.28	Selection of random vector in an oriented hemisphere	626

Figure 13.29	Effect of increasing direction count on ambient occlusion	627
Figure 13.30	Effect of introducing noise in ambient occlusion	628
Figure 13.31	Ambient occlusion applied to a rendered scene	629
Figure 13.32	A few frames from the Julia set animation	635
Figure 13.33	Simplified 2D illustration of ray tracing	636
Figure 13.34	Our first ray-traced sphere	640
Figure 13.35	Our first lit ray-traced sphere	641
Figure 13.36	Implementing a stack using framebuffer objects	642
Figure 13.37	Ray-traced spheres with increasing ray bounces	643
Figure 13.38	Adding a ray-traced plane	645
Figure 13.39	Ray-traced spheres in a box	646
Figure 13.40	Low-resolution texture used for a logo	648
Figure 13.41	High-resolution texture used for a logo	649
Figure 13.42	Distance field of the OpenGL logo	650
Figure 13.43	Distance fields for a line	650
Figure 13.44	Output of distance field rendering application	651
Figure 13.45	Distance field for English characters	652
Figure 13.46	Distance field of a Chinese character	653
Figure 13.47	Chinese text rendered using distance fields	653
Figure 13.48	Two textures to be mixed using a distance field	654
Figure 13.49	Landscape map texture and distance field	655
Figure 13.50	Result of landscape texturing with distance fields	655
Figure 13.51	Output of font rendering demo	659
Figure 14.1	Output of the OpenMP particle simulator	667
Figure 14.2	CPU utilization of the ompparticles application	667
Figure 14.3	Indirect material parameters	683
Figure 14.4	Output of the cullindirect application	690
Figure 14.5	Synchronizing access to a mapped buffer	695
Figure 14.6	Persistent mapped Julia fractal	698
Figure 14.7	GPUView in action	700
Figure 14.8	Vsync seen in GPUView	701
Figure 14.9	A packet dialog in GPUView	703
Figure 14.10	GPU PerfStudio running an example application	704
Figure 14.11	GPU PerfStudio frame debugger	705
Figure 14.12	GPU PerfStudio HUD control window	705
Figure 14.13	GPU PerfStudio overlaying information	706
Figure 14.14	GPU PerfStudio showing AMD performance counters	707
Figure 14.15	GPUView showing the effect of <code>glReadPixels()</code> into system memory	708
Figure 14.16	GPUView showing the effect of <code>glReadPixels()</code> into a buffer	709
Figure B.1	Dump of example SBM file	757

Tables

Table 1.1	OpenGL Versions and Publication Dates	7
Table 4.1	Common Coordinate Spaces Used in 3D Graphics . . .	70
Table 5.1	Buffer Storage Flags	102
Table 5.2	Buffer-Mapping Flags	106
Table 5.3	Basic OpenGL Type Tokens and Their Corresponding C Types	108
Table 5.4	Uniform Parameter Queries via glGetActiveUniformsiv()	127
Table 5.5	Atomic Operations on Shader Storage Blocks	143
Table 5.6	Texture Targets and Description	155
Table 5.7	Basic Texture Targets and Sampler Types	157
Table 5.8	Texture Filters, Including Mipmapped Filters	172
Table 5.9	Image Types	183
Table 5.10	Image Data Format Classes	185
Table 5.11	Image Data Format Classes	186
Table 5.12	Atomic Operations on Images	189
Table 5.13	Native OpenGL Texture Compression Formats	195
Table 5.14	Texture View Target Compatibility	200
Table 5.15	Texture View Format Compatibility	201
Table 6.1	Scalar Types in GLSL	206
Table 6.2	Vector and Matrix Types in GLSL	208

Table 7.1	Vertex Attribute Types	244
Table 7.2	Draw Type Matrix	250
Table 7.3	Values for <code>primitiveMode</code>	285
Table 8.1	Allowed Draw Modes for Geometry Shader Input Modes	337
Table 8.2	Sizes of Input Arrays to Geometry Shaders	339
Table 9.1	Stencil Functions	373
Table 9.2	Stencil Operations	375
Table 9.3	Depth Comparison Functions	377
Table 9.4	Blend Functions	384
Table 9.5	Blend Equations	387
Table 9.6	Logic Operations	388
Table 9.7	Framebuffer Completeness Return Values	405
Table 9.8	Floating-Point Texture Formats	432
Table 11.1	First RGTC Encoding for RED Images	518
Table 11.2	Second RGTC Encoding for RED Images	519
Table 11.3	Packed Data Formats Supported in OpenGL	527
Table 12.1	Possible Return Values for <code>glClientWaitSync()</code>	560
Table 14.1	Map Buffer Access Types	710
Table C.1	OpenGL Functions	760
Table C.2	OpenGL Extensions (Core)	777

Listings

Listing 2.1	Our first OpenGL application	14
Listing 2.2	Animating color over time	16
Listing 2.3	Our first vertex shader	18
Listing 2.4	Our first fragment shader	18
Listing 2.5	Compiling a simple shader	18
Listing 2.6	Creating the program member variable	21
Listing 2.7	Rendering a single point	22
Listing 2.8	Producing multiple vertices in a vertex shader	25
Listing 2.9	Rendering a single triangle	25
Listing 3.1	Declaration of a vertex attribute	28
Listing 3.2	Updating a vertex attribute	29
Listing 3.3	Vertex shader with an output	30
Listing 3.4	Fragment shader with an input	31
Listing 3.5	Vertex shader with an output interface block	31
Listing 3.6	Fragment shader with an input interface block	32
Listing 3.7	Our first tessellation control shader	34
Listing 3.8	Our first tessellation evaluation shader	36
Listing 3.9	Our first geometry shader	38
Listing 3.10	Deriving a fragment's color from its position	44
Listing 3.11	Vertex shader with an output	45
Listing 3.12	Deriving a fragment's color from its position	46
Listing 3.13	Simple do-nothing compute shader	49
Listing 5.1	Creating and initializing a buffer	103
Listing 5.2	Updating the content of a buffer with glBufferSubData()	104

Listing 5.3	Mapping a buffer's data store with <code>glMapNamedBuffer()</code>	104
Listing 5.4	Setting up a vertex attribute	112
Listing 5.5	Using an attribute in a vertex shader	113
Listing 5.6	Declaring two inputs to a vertex shader	113
Listing 5.7	Multiple separate vertex attributes	114
Listing 5.8	Multiple interleaved vertex attributes	115
Listing 5.9	Example uniform block declaration	121
Listing 5.10	Declaring a uniform block with the <code>std140</code> layout	123
Listing 5.11	Example uniform block with offsets	124
Listing 5.12	Uniform block with user-specified offsets	125
Listing 5.13	Uniform block with user-specified alignments	125
Listing 5.14	Retrieving the indices of uniform block members	126
Listing 5.15	Retrieving the information about uniform block members	127
Listing 5.16	Setting a single float in a uniform block	129
Listing 5.17	Retrieving the indices of uniform block members	129
Listing 5.18	Specifying the data for an array in a uniform block	129
Listing 5.19	Setting up a matrix in a uniform block	130
Listing 5.20	Specifying bindings for uniform blocks	133
Listing 5.21	Uniform blocks binding layout qualifiers	134
Listing 5.22	Setting up cube geometry	136
Listing 5.23	Building the model-view matrix for a spinning cube	137
Listing 5.24	Updating the projection matrix for the spinning cube	137
Listing 5.25	Rendering loop for the spinning cube	137
Listing 5.26	Spinning cube vertex shader	138
Listing 5.27	Spinning cube fragment shader	138
Listing 5.28	Rendering loop for the spinning cube	139
Listing 5.29	Example shader storage block declaration	141
Listing 5.30	Using a shader storage block in place of vertex attributes	142
Listing 5.31	Setting up an atomic counter buffer	148
Listing 5.32	Setting up an atomic counter buffer	148
Listing 5.33	Counting area using an atomic counter	150
Listing 5.34	Using the result of an atomic counter in a uniform block	151
Listing 5.35	Generating, initializing, and binding a texture	152
Listing 5.36	Updating texture data with <code>glTexSubImage2D()</code>	153
Listing 5.37	Reading from a texture in GLSL	156
Listing 5.38	The header of a .KTX file	160
Listing 5.39	Loading a .KTX file	161
Listing 5.40	Vertex shader with a single texture coordinate	162
Listing 5.41	Fragment shader with a single texture coordinate	163

Listing 5.42	Initializing an array texture	178
Listing 5.43	Vertex shader for the alien rain sample	179
Listing 5.44	Fragment shader for the alien rain sample	180
Listing 5.45	Rendering loop for the alien rain sample	181
Listing 5.46	Fragment shader performing image loads and stores	188
Listing 5.47	Filling a linked list in a fragment shader	191
Listing 5.48	Traversing a linked list in a fragment shader	193
Listing 6.1	Retrieving the compiler log from a shader	221
Listing 6.2	Fragment shader with external function declaration	224
Listing 6.3	Configuring a separable program pipeline	226
Listing 6.4	Printing interface information	230
Listing 6.5	Example subroutine uniform declaration	231
Listing 6.6	Setting values of subroutine uniforms	234
Listing 6.7	Retrieving a program binary	236
Listing 7.1	Declaration of multiple vertex attributes	243
Listing 7.2	Setting up indexed cube geometry	251
Listing 7.3	Drawing indexed cube geometry	252
Listing 7.4	Drawing the same geometry many times	256
Listing 7.5	Pseudocode for glDrawArraysInstanced()	258
Listing 7.6	Pseudocode for glDrawElementsInstanced()	258
Listing 7.7	Simple vertex shader with per-vertex color	264
Listing 7.8	Simple instanced vertex shader	265
Listing 7.9	Getting ready for instanced rendering	266
Listing 7.10	Example use of an indirect draw command	272
Listing 7.11	Setting up the indirect draw buffer for asteroids . . .	273
Listing 7.12	Vertex shader inputs for asteroids	274
Listing 7.13	Per-indirect draw attribute setup	274
Listing 7.14	Asteroid field vertex shader	275
Listing 7.15	Drawing asteroids	276
Listing 7.16	Spring mass system vertex setup	288
Listing 7.17	Spring mass system vertex shader	291
Listing 7.18	Spring mass system iteration loop	293
Listing 7.19	Spring mass system rendering loop	294
Listing 7.20	Clipping an object against a plane and a sphere . . .	302
Listing 8.1	Simple quad tessellation control shader example . . .	308
Listing 8.2	Simple quad tessellation evaluation shader example	310
Listing 8.3	Simple triangle tessellation control shader example	311
Listing 8.4	Simple triangle tessellation evaluation shader example	312

Listing 8.5	Simple isoline tessellation control shader example . .	313
Listing 8.6	Simple isoline tessellation evaluation shader example	313
Listing 8.7	Isoline spirals tessellation evaluation shader	315
Listing 8.8	Vertex shader for terrain rendering	324
Listing 8.9	Tessellation control shader for terrain rendering . . .	325
Listing 8.10	Tessellation evaluation shader for terrain rendering	326
Listing 8.11	Fragment shader for terrain rendering	327
Listing 8.12	Cubic Bézier patch vertex shader	329
Listing 8.13	Cubic Bézier patch tessellation control shader	330
Listing 8.14	Cubic Bézier patch tessellation evaluation shader . .	331
Listing 8.15	Cubic Bézier patch fragment shader	332
Listing 8.16	Source code for a simple geometry shader	334
Listing 8.17	Geometry shader layout qualifiers	334
Listing 8.18	Iterating over the elements of <code>gl_in[]</code>	335
Listing 8.19	Definition of <code>gl_in[]</code>	338
Listing 8.20	Configuring the custom culling geometry shader . . .	342
Listing 8.21	Finding a face normal in a geometry shader	343
Listing 8.22	Conditionally emitting geometry in a geometry shader	343
Listing 8.23	Setting up the “explode” geometry shader	345
Listing 8.24	Pushing a face out along its normal	345
Listing 8.25	Pass-through vertex shader	346
Listing 8.26	Setting up the “tessellator” geometry shader	347
Listing 8.27	Generating new vertices in a geometry shader	347
Listing 8.28	Emitting a single triangle from a geometry shader . .	347
Listing 8.29	Using a function to produce faces in a geometry shader	348
Listing 8.30	A pass-through vertex shader that includes normals	349
Listing 8.31	Setting up the “normal visualizer” geometry shader	350
Listing 8.32	Producing lines from normals in the geometry shader	350
Listing 8.33	Drawing a face normal in the geometry shader	351
Listing 8.34	Geometry shader for rendering quads	359
Listing 8.35	Fragment shader for rendering quads	360
Listing 8.36	Rendering to multiple viewports in a geometry shader	362
Listing 9.1	Setting up scissor rectangle arrays	371
Listing 9.2	Example stencil buffer usage and stencil border decorations	375
Listing 9.3	Rendering with all blending functions	384
Listing 9.4	Setting up a simple framebuffer object	393
Listing 9.5	Rendering to a texture	394

Listing 9.6	Setting up an FBO with multiple attachments	396
Listing 9.7	Declaring multiple outputs in a fragment shader . . .	396
Listing 9.8	Setting up a layered framebuffer	397
Listing 9.9	Layered rendering using a geometry shader	398
Listing 9.10	Displaying an array texture—vertex shader	399
Listing 9.11	Displaying an array texture—fragment shader	400
Listing 9.12	Attaching texture layers to a framebuffer	402
Listing 9.13	Checking completeness of a framebuffer object	406
Listing 9.14	Creating a stereo window	408
Listing 9.15	Drawing into a stereo window	408
Listing 9.16	Rendering to two layers with a geometry shader . . .	410
Listing 9.17	Copying from an array texture to a stereo back buffer	411
Listing 9.18	Turning on line smoothing	414
Listing 9.19	Choosing eight-sample antialiasing	416
Listing 9.20	Setting up a multi-sample framebuffer attachment . .	418
Listing 9.21	Simple multi-sample “maximum” resolve	419
Listing 9.22	Fragment shader producing high-frequency output	422
Listing 9.23	A 100-megapixel virtual framebuffer	430
Listing 9.24	Applying a simple exposure coefficient to an HDR image	435
Listing 9.25	Adaptive HDR to LDR conversion fragment shader . .	437
Listing 9.26	Bloom fragment shader—output bright data to a separate buffer	440
Listing 9.27	Blur fragment shader	442
Listing 9.28	Adding a bloom effect to the scene	443
Listing 9.29	Creating integer framebuffer attachments	445
Listing 9.30	Texturing a point sprite in the fragment shader . . .	450
Listing 9.31	Vertex shader for the star field effect	452
Listing 9.32	Fragment shader for the star field effect	453
Listing 9.33	Fragment shader for generating shaped points	455
Listing 9.34	Naïve rotated point sprite fragment shader	456
Listing 9.35	Rotated point sprite vertex shader	457
Listing 9.36	Rotated point sprite fragment shader	457
Listing 9.37	Taking a screenshot with glReadPixels()	460
Listing 10.1	Creating and compiling a compute shader	468
Listing 10.2	Compute shader image inversion	473
Listing 10.3	Dispatching the image copy compute shader	474
Listing 10.4	Compute shader with race conditions	476
Listing 10.5	Simple prefix sum implementation in C++	480
Listing 10.6	Prefix sum implementation using a compute shader .	483
Listing 10.7	Compute shader to generate a 2D prefix sum	485
Listing 10.8	Depth of field using summed area tables	489

Listing 10.9	Initializing shader storage buffers for flocking	494
Listing 10.10	The rendering loop for the flocking example	495
Listing 10.11	Compute shader for updates in flocking example . . .	496
Listing 10.12	The first rule of flocking	497
Listing 10.13	The second rule of flocking	497
Listing 10.14	Main body of the flocking update compute shader . .	498
Listing 10.15	Inputs to the flock rendering vertex shader	500
Listing 10.16	Flocking vertex shader body	500
Listing 11.1	Declaring samplers inside uniform blocks	505
Listing 11.2	Declaring samplers inside uniform blocks	506
Listing 11.3	Making textures resident	507
Listing 11.4	Creating a sparse texture	510
Listing 11.5	Determining supported sparse texture page sizes . . .	511
Listing 11.6	Simple texture commitment management	513
Listing 11.7	Sampling a sparse texture with clamped level-of-detail (LoD)	515
Listing 11.8	Fetching a block of texels using textureGatherOffset	520
Listing 11.9	Generating a palette for RGTC encoding	521
Listing 11.10	Palettizing an RGTC block	521
Listing 11.11	Packing an RGTC block	522
Listing 11.12	Generating a palette for RGTC encoding	523
Listing 11.13	Main function for RGTC compression	524
Listing 11.14	High-quality texture filtering function	530
Listing 12.1	Getting the result from a query object	538
Listing 12.2	Figuring out if occlusion query results are ready . . .	538
Listing 12.3	Simple, application-side conditional rendering	539
Listing 12.4	Rendering when query results aren't available	540
Listing 12.5	Basic conditional rendering example	541
Listing 12.6	A more complete conditional rendering example . . .	543
Listing 12.7	Simple control flow using queries	544
Listing 12.8	Timing operations using timer queries	546
Listing 12.9	Timing operations using glQueryCounter()	547
Listing 12.10	Drawing data written to a transform feedback buffer	552
Listing 12.11	Working while waiting for a sync object	558
Listing 13.1	The Gouraud shading vertex shader	571
Listing 13.2	The Gouraud shading fragment shader	572
Listing 13.3	The Phong shading vertex shader	574
Listing 13.4	The Phong shading fragment shader	575

Listing 13.5	Blinn-Phong fragment shader	578
Listing 13.6	Rim lighting shader function	580
Listing 13.7	Vertex shader for normal mapping	584
Listing 13.8	Fragment shader for normal mapping	585
Listing 13.9	Spherical environment mapping vertex shader	588
Listing 13.10	Spherical environment mapping fragment shader . .	588
Listing 13.11	Equirectangular environment mapping fragment shader	590
Listing 13.12	Loading a cubemap texture	592
Listing 13.13	Vertex shader for skybox rendering	594
Listing 13.14	Fragment shader for skybox rendering	595
Listing 13.15	Vertex shader for cubemap environment rendering	595
Listing 13.16	Fragment shader for cubemap environment rendering	596
Listing 13.17	Fragment shader for per-fragment shininess	598
Listing 13.18	Getting ready for shadow mapping	600
Listing 13.19	Setting up matrices for shadow mapping	601
Listing 13.20	Setting up a shadow matrix	602
Listing 13.21	Simplified vertex shader for shadow mapping	603
Listing 13.22	Simplified fragment shader for shadow mapping . . .	604
Listing 13.23	Displacement map tessellation evaluation shader . .	606
Listing 13.24	Application of fog in a fragment shader	608
Listing 13.25	The toon vertex shader	611
Listing 13.26	The toon fragment shader	612
Listing 13.27	Initializing a G-buffer	615
Listing 13.28	Writing to a G-buffer	616
Listing 13.29	Unpacking data from a G-buffer	617
Listing 13.30	Lighting a fragment using data from a G-buffer . . .	618
Listing 13.31	Deferred shading with normal mapping (fragment shader)	621
Listing 13.32	Ambient occlusion fragment shader	630
Listing 13.33	Setting up the Julia set renderer	633
Listing 13.34	Inner loop of the Julia renderer	633
Listing 13.35	Using a gradient texture to color the Julia set	634
Listing 13.36	Ray-sphere interesection test	638
Listing 13.37	Determining closest intersection point	639
Listing 13.38	Ray-plane interesection test	644
Listing 13.39	Fragment shader for distance field rendering	651
Listing 13.40	Getting ready for bitmap fonts	656
Listing 13.41	Bitmap font rendering shader	657
Listing 13.42	Bitmap font rendering shader	658
Listing 14.1	OpenMP particle updater	663
Listing 14.2	Setting up a persistent mapped buffer	665

Listing 14.3	OpenMP particle rendering loop	665
Listing 14.4	Example packet data structure	669
Listing 14.5	Union of all packets	670
Listing 14.6	Appending a packet to a packet buffer	670
Listing 14.7	Executing a packet buffer	671
Listing 14.8	Disassembly of packet_stream::execute	672
Listing 14.9	Implementation of packet_stream::EnableDisable	673
Listing 14.10	Optimized packet insertion	676
Listing 14.11	Optimized packet execution	677
Listing 14.12	Uniform block declarations for indirect materials	680
Listing 14.13	Passing material index through a vertex shader	681
Listing 14.14	Declaration of material properties	681
Listing 14.15	Passing material index through a vertex shader	682
Listing 14.16	Candidate draws used for culling	685
Listing 14.17	Matrix data used for compute shader culling	685
Listing 14.18	Object culling in a compute shader	686
Listing 14.19	Driving compute culling shaders	687
Listing 14.20	Julia fractals on the CPU	696
Listing 14.21	Persistent mapped fractal rendering	697
Listing 15.1	Creating a debug context with the sb7 framework	730
Listing 15.2	Setting the debug callback function	731
Listing 15.3	Shader with an infinite loop	738

Foreword

When OpenGL was young, the highest-end SGI systems like the Reality Engine 2 cost \$80,000 and could render 200,000 textured triangles per second, or 3,333 triangles per frame at 60 Hz. The CPUs of that era were slower than today, to be sure, but at around 100 MHz, that's still 500 CPU cycles for each triangle. It was pretty easy to be graphics limited back then, and the API reflected that—the only way to specify geometry was immediate mode! Well, there were also display lists for static geometry, which made being graphics-limited even easier.

OpenGL is not young anymore, the highest-end GPUs that it can run on cost around \$1000, and they don't even list triangles per second in their basic product description anymore, but the number is north of 6 billion. Today these GPUs are in the middle of the single digit teraflops and several hundred gigabytes per second of bandwidth. CPUs have gotten faster, too: With 4 cores and around 3 GHz, they are shy of 200 gigaflops and have around 20 gigabytes per second of memory bandwidth. So where we had 500 CPU cycles for a triangle in the early days, we now have 0.5 cycles. Even if we could perfectly exploit all 4 cores, that would give us a paltry 2 CPU cycles for each triangle!

All that is to say that the growth in hardware graphics performance has outstripped conventional CPU performance growth by several orders of magnitude, and the consequences are pretty obvious today. Not only is the CPU frequently the limiting factor in graphics performance, we have an API that was designed against a different set of assumptions.

The good news with OpenGL is that it has evolved too. First it added vertex arrays so that a single draw command with fairly low CPU overhead gets amplified into a lot of GPU work. This helped for a while, but it

wasn't enough. We added instancing to further increase the amount of work, but this was a somewhat limited form of work amplification, as we don't always want many instances of the same object in an organic, believable rendering.

Recognizing that these emerging limitations in the API had to be circumvented somehow, OpenGL designers began extending the interface to remove as much CPU-side overhead from the interface as possible. The “bindless” family of extensions allows the GPU to reference buffers and textures directly rather than going through expensive binding calls in the driver. Persistent maps allow the application to scribble on memory at the same time the GPU is referencing it. This sounds dangerous—and it can be!—but allowing the application to manage memory hazards relieves a tremendous burden from the driver and allows for far simpler, less general mechanisms to be employed. Sparse texture arrays allow applications to manage texture memory as well with similar, very low-overhead benefits. And finally multi-draw and multi-draw indirect added means the GPU can generate the very buffers that it sources for drawing, leaving the CPU a lot more available for other work.

All of these advances in OpenGL have been loosely lumped under the AZDO (Approaching Zero Driver Overhead) umbrella, and most of them have been incorporated into the core API. There are still significant areas for improvement as we try to get to an API that allows developers to render as much as they want, the way they want, without worrying that the CPU or driver overhead will get in the way. These features require a bit more work to make use of, but the results can be truly amazing! This edition of the *OpenGL[®] SuperBible* includes many new examples that make use of AZDO features and provide good guidance on how to get the CPU out of the way. In particular, you'll learn good ways to make use of zero copy, proper fencing, and bindless.

*Cass Everitt
Oculus*

Preface

This book is designed both for people who are learning computer graphics through OpenGL and for people who may already know about graphics but want to learn about OpenGL. The intended audience is students of computer science, computer graphics, or game design; professional software engineers; or simply just hobbyists and people who are interested in learning something new. We begin by assuming that the reader knows nothing about either computer graphics or OpenGL. The reader should be familiar with computer programming in C++, however.

One of our goals with this book was to ensure that there were as few forward references as possible and to require little or no assumed knowledge. The book is accessible and readable, and if you start from the beginning and read all the way through, you should come away with a good comprehension of how OpenGL works and how to use it effectively in your applications. After reading and understanding the content of this book, you will be well positioned to read and learn from more advanced computer graphics research articles and confident that you can take the principles that they cover and implement them in OpenGL.

It is *not* a goal of this book to cover every last feature of OpenGL—that is, to mention every function in the specification or every value that can be passed to a command. Rather, we intend to provide a solid understanding of OpenGL, introduce the fundamentals, and explore some of its more advanced features. After reading this book, readers should be comfortable looking up finer details in the OpenGL specification, experimenting with

OpenGL on their own machines, and using extensions (bonus features that add capabilities to OpenGL not required by the main specification).

The Architecture of the Book

This book is subdivided into three parts. In Part I, “Foundations,” we explain what OpenGL is and how it connects to the graphics pipeline, and we give minimal working examples that are sufficient to demonstrate each section of it without requiring much, if any, knowledge of any other part of the whole system. We lay a foundation for the math behind three-dimensional computer graphics, and describe how OpenGL manages the large amounts of data that are required to provide a compelling experience to the users of such applications. We also describe the programming model for *shaders*, which form a core part of any OpenGL application.

In Part II, “In Depth,” we introduce features of OpenGL that require some knowledge of multiple parts of the graphics pipeline and may refer to concepts mentioned in Part I. This allows us to cover more complex topics without glossing over details or telling you to skip forward in the book to find out how something really works. By taking a second pass over the OpenGL system, we are able to delve into where data goes as it leaves each part of OpenGL, as you’ll already have been (at least briefly) introduced to its destination.

Finally, in Part III, “In Practice,” we dive deeper into the graphics pipeline, cover some more advanced topics, and give a number of examples that use multiple features of OpenGL. We provide a number of worked examples that implement various rendering techniques, give a series of suggestions and advice on OpenGL best practices and performance considerations, and end up with a practical overview of OpenGL on several popular platforms, including mobile devices.

In Part I, we start gently and then blast through OpenGL to give you a taste of what’s to come. Then, we lay the groundwork of knowledge that will be essential to you as you progress through the rest of the book. In this part, you will find the following chapters:

- Chapter 1, “Introduction,” provides a brief introduction to OpenGL, including its origins, history, and current state.
- Chapter 2, “Our First OpenGL Program,” jumps right into OpenGL and shows you how to create a simple OpenGL application using the source code provided with this book.

-
- Chapter 3, “Following the Pipeline,” takes a more careful look at OpenGL and its various components, introducing each in a little more detail and adding to the simple example presented in the previous chapter.
 - Chapter 4, “Math for 3D Graphics,” introduces the foundations of math that is essential for effective use of OpenGL and the creation of interesting 3D graphics applications.
 - Chapter 5, “Data,” provides you with the tools necessary to manage data that will be consumed and produced by OpenGL.
 - Chapter 6, “Shaders and Programs,” takes a deeper look at *shaders*, which are fundamental to the operation of modern graphics applications.

In Part II, we take a more detailed look at several of the topics introduced in the first chapters. We dig deeper into each of the major parts of OpenGL and our example applications start to become a little more complex and interesting. In this part, you will find these six chapters:

- Chapter 7, “Vertex Processing and Drawing Commands,” covers the inputs to OpenGL and the mechanisms by which semantics are applied to the raw data you provide.
- Chapter 8, “Primitive Processing,” covers some higher-level concepts in OpenGL, including connectivity information, higher-order surfaces, and tessellation.
- Chapter 9, “Fragment Processing and the Framebuffer,” looks at how high-level 3D graphics information is transformed by OpenGL into 2D images, and how your applications can determine the appearance of objects on the screen.
- Chapter 10, “Compute Shaders,” illustrates how your applications can harness OpenGL for more than just graphics and make use of the incredible computing power locked up in a modern graphics card.
- Chapter 11, “Advanced Data Management,” discusses topics related to managing large data sets, loading data efficiently, and arbitrating access to that data once loaded.
- Chapter 12, “Controlling and Monitoring the Pipeline,” shows you how to get a glimpse into how OpenGL executes the commands you give it—including how long they take to execute, and how much data they produce.

In Part III, we build on the knowledge that you will have gained in reading the first two parts of the book and use it to construct example applications that touch on multiple aspects of OpenGL. We also get into the practicalities of building larger OpenGL applications and deploying them across multiple platforms. In this part, you will find three chapters:

- Chapter 13, “Rendering Techniques,” covers several applications of OpenGL for graphics rendering, including simulation of light, artistic methods and even some nontraditional techniques.
- Chapter 14, “High-Performance OpenGL,” digs into some topics related to getting the highest possible performance from OpenGL.
- Chapter 15, “Debugging and Stability,” provides advice and tips on how to get your applications running without errors and how to debug problems with your programs.

Finally, several appendices are provided that describe the tools and file formats used in this book, discuss which versions of OpenGL support which features and list which extensions introduced those features, and give pointers to more useful OpenGL resources.

What’s New in This Edition

In this book, we have expanded on the sixth edition to cover new features and topics introduced in OpenGL in versions 4.4 and 4.5 of the API. In the previous edition, we did not cover extensions—features that are entirely optional and not a mandatory part of the OpenGL core—and so left out a number of interesting topics. Since the release of the sixth edition of this book, some of these extensions have become fairly ubiquitous; in turn, we have decided to cover the ARB and KHR extensions. Thus extensions that have been ratified by Khronos (the OpenGL governing body) are part of this book.

We have built on the previous edition by expanding the book’s application framework and adding new chapters and appendices that provide further insight and cover new topics. One important set of features enabled by the extensions that are now part of the book are the AZDO (Approaching Zero Driver Overhead) features, which are a way of using OpenGL that produces very low software overhead and correspondingly high performance. These features include *persistent maps* and *bindless textures*.

To make room for the new content, we decided to remove the chapter on platform specifics, which covered per-platform window system bindings. Also gone is official support for the Apple Mac platform. Almost all of the new content in this edition requires features introduced with OpenGL 4.4 or 4.5, or recent OpenGL extensions—none of which were supported by OS X at the time of writing. There is no expectation that Apple will further invest in its OpenGL implementation, so we encourage our readers to move away from the platform. To support multiple platforms, we recommend the use of cross-platform toolkits such as the excellent SDL (<https://www.libsdl.org/>) or glfw (<http://www.glfw.org/>) libraries. In fact, this book's framework is built on glfw, and it works well for us.

This book includes several new example applications, including demonstrations of new features, a texture compressor, text drawing, font rendering using distance fields, high-quality texture filtering, and multi-threaded programs using OpenMP. We also tried to address all of the errata and feedback we've received from our readers since the publication of the previous edition. We believe this to be the best update yet to the *OpenGL® SuperBible* yet.

We hope you enjoy it.

How to Build the Examples

Retrieve the sample code from the book's companion Web site, <http://www.openglsuperbible.com>, unpack the archive to a directory on your computer, and follow the instructions in the included HOWTOBUILD.TXT file for your platform of choice. The book's source code has been built and tested on Microsoft Windows (Windows 7 or later is required) and Linux (several major distributions). It is recommended that you install any available operating system updates and obtain the most recent graphics drivers from your graphics card manufacturer.

You may notice some minor discrepancies between the source code printed in this book and that in the source files. There are a number of reasons for this:

- This book is about OpenGL 4.5—the most recent version at the time of writing. The examples printed in the book are written assuming that OpenGL 4.5 is available on the target platform. However, we understand that in practice, operating systems, graphics drivers, and platforms may not have the *latest and greatest* available.

Consequently, where possible, we've made minor modifications to the example applications to allow them to run on earlier versions of OpenGL.

- Several months passed between when this book's text was finalized for printing and when the sample applications were packaged and posted to the Web. In that time, we discovered opportunities for improvement, whether that was uncovering new bugs, platform dependencies, or optimizations. The latest version of the source code on the Web will have those fixes and tweaks applied and will therefore deviate from the necessarily static copy printed in the book.
- There is not necessarily a one-to-one mapping of listings in the book's text and example applications in the Web package. Some example applications demonstrate more than one concept, some aren't mentioned in the book at all, and some listings in the book don't have an equivalent example application. Where possible, we've mentioned which of the example applications correspond to the listings in the book. We recommend that the reader take a close look at the example application package, as it includes some nuggets that may not be mentioned in the book.

Errata

We made a bunch of mistakes—we're certain of it. It's incredibly frustrating as an author to spot an error that you made and know that it has been printed, in books that your readers paid for, thousands and thousands of times. We have to accept that this will happen, though, and do our best to correct issues as we are able. If you think you see something that doesn't quite gel, check the book's Web site for errata:

<http://www.openglsuperbible.com>

Note from the Publisher

Some of the figures in the print edition of the book are dark due to the nature of the images themselves. To assist readers, color PDFs of figures are freely available at <http://www.openglsuperbible.com> and <http://informit.com/title/9780672337475>. In addition, PowerPoint slides of the figures for professors' classroom use are available at www.pearsonhighered.com/educator/product/OpenGL-Superbible-Comprehensive-Tutorial-and-Reference/9780672337475.page.

Acknowledgments

First, thanks to you—the reader. The best part of what I do is knowing that someone I’ve never met might benefit from all this. It’s the biggest thrill, and the reason why people like me do this. I appreciate that you’re reading this now and hope you get as much out of this book as I put into it.

I’d like to thank my wonderful wife, Chris, who’s put up with me disappearing into my office for three editions of this book now. She’s worked around my deadlines and cheered me on as I made (sometimes slow and painful) progress. I couldn’t have done this without her. Thanks, too, to my kids, Jeremy and Emily. The answer to “What are you doing, dad?” is almost always “Working”—and you’ve always taken it in stride.

Thanks to my coauthors, Richard and Nick. You’ve let me run alone on this edition, but your names are on the cover because of your contributions—your fingerprints are etched into this book. Many thanks to Matías Goldberg, who performed a thorough technical review of the book on short notice.

Thanks again to Laura Lewin and Olivia Basegio and the Pearson team for letting me be me and just dropping random files and documents off whenever I felt like it. I don’t work well with a plan, but seem to relish pressure and am really excellent at procrastination. I’m glad you guys put up with me.

Graham Sellers

This page intentionally left blank

About the Author

Graham Sellers is a classic geek. His family got their first computer (a BBC Model B) right before his sixth birthday. After his mum and dad stayed up all night programming it to play “Happy Birthday,” he was hooked and determined to figure out how it worked. Next came basic programming and then assembly language. His first real exposure to graphics was via “demos” in the early 1990s, and then through Glide, and finally OpenGL in the late 1990s. Graham holds a master’s in engineering from the University of Southampton, England.

Currently, Graham is a software architect at AMD. He represents AMD at the OpenGL ARB and has contributed to many extensions and to the core OpenGL Specification. Prior to that, he was a team lead at Epsom, implementing OpenGL-ES and OpenVG drivers for embedded products. Graham holds several patents in the fields of computer graphics and image processing. When he’s not working on OpenGL, he likes to disassemble and reverse-engineer old video game consoles (just to see how they work and what he can make them do). Originally from England, Graham now lives in Orlando, Florida, with his wife and two children.

This page intentionally left blank

Chapter 3

Following the Pipeline

WHAT YOU'LL LEARN IN THIS CHAPTER

- What each of the stages in the OpenGL pipeline does.
- How to connect your shaders to the fixed-function pipeline stages.
- How to create a program that uses every stage of the graphics pipeline simultaneously.

In this chapter, we will walk all the way along the OpenGL pipeline from start to finish, providing insight into each of the stages, which include fixed-function blocks and programmable shader blocks. You have already read a whirlwind introduction to the vertex and fragment shader stages. However, the application that you constructed simply drew a single triangle at a fixed position. If we want to render anything interesting with OpenGL, we're going to have to learn a lot more about the pipeline and all of the things you can do with it. This chapter introduces every part of the pipeline, hooks them up to one another, and provides an example shader for each stage.

Passing Data to the Vertex Shader

The vertex shader is the first *programmable* stage in the OpenGL pipeline and has the distinction of being the only mandatory stage in the graphics pipeline. However, before the vertex shader runs, a fixed-function stage known as *vertex fetching*, or sometimes *vertex pulling*, is run. This automatically provides inputs to the vertex shader.

Vertex Attributes

In GLSL, the mechanism for getting data in and out of shaders is to declare global variables with the **in** and **out** storage qualifiers. You were briefly introduced to the **out** qualifier in Chapter 2, “Our First OpenGL Program,” when Listing 2.4 used it to output a color from the fragment shader. At the start of the OpenGL pipeline, we use the **in** keyword to bring inputs into the vertex shader. Between stages, **in** and **out** can be used to form conduits from shader to shader and pass data between them. We’ll get to that shortly. For now, consider the input to the vertex shader and what happens if you declare a variable with an **in** storage qualifier. This marks the variable as an input to the vertex shader, which means that it is essentially an input to the OpenGL graphics pipeline. It is automatically filled in by the fixed-function vertex fetch stage. The variable becomes known as a *vertex attribute*.

Vertex attributes are how vertex data is introduced into the OpenGL pipeline. To declare a vertex attribute, you declare a variable in the vertex shader using the **in** storage qualifier. An example of this is shown in Listing 3.1, where we declare the variable **offset** as an input attribute.

```
#version 450 core

// 'offset' is an input vertex attribute
layout (location = 0) in vec4 offset;

void main(void)
{
    const vec4 vertices[3] = vec4[3](vec4( 0.25, -0.25, 0.5, 1.0),
                                       vec4(-0.25, -0.25, 0.5, 1.0),
                                       vec4( 0.25,  0.25, 0.5, 1.0));

    // Add 'offset' to our hard-coded vertex position
    gl_Position = vertices[gl_VertexID] + offset;
}
```

Listing 3.1: Declaration of a vertex attribute

In Listing 3.1, we have added the variable **offset** as an input to the vertex shader. As it is an input to the first shader in the pipeline, it will be filled automatically by the vertex fetch stage. We can tell this stage what to fill the variable with by using one of the many variants of the vertex attribute functions, **glVertexAttrib*()**. The prototype for **glVertexAttrib4fv()**, which we use in this example, is

```
void glVertexAttrib4fv(GLuint index,
                      const GLfloat * v);
```

Here, the parameter *index* is used to reference the attribute and *v* is a pointer to the new data to put into the attribute. You may have noticed the **layout** (*location* = 0) code in the declaration of the **offset** attribute. This is a *layout qualifier*, which we have used to set the *location* of the vertex attribute to zero. This location is the value we'll pass in *index* to refer to the attribute.

Each time we call one of the **glVertexAttrib*()** functions (of which there are many), it will update the value of the vertex attribute that is passed to the vertex shader. We can use this approach to animate our one triangle. Listing 3.2 shows an updated version of our rendering function that updates the value of **offset** in each frame.

```
// Our rendering function
virtual void render(double currentTime)
{
    const GLfloat color[] = { (float)sin(currentTime) * 0.5f + 0.5f,
                              (float)cos(currentTime) * 0.5f + 0.5f,
                              0.0f, 1.0f };
    glClearBufferfv(GL_COLOR, 0, color);

    // Use the program object we created earlier for rendering
    glUseProgram(rendering_program);

    GLfloat attrib[] = { (float)sin(currentTime) * 0.5f,
                        (float)cos(currentTime) * 0.6f,
                        0.0f, 0.0f };

    // Update the value of input attribute 0
    glVertexAttrib4fv(0, attrib);

    // Draw one triangle
    glDrawArrays(GL_TRIANGLES, 0, 3);
}
```

Listing 3.2: Updating a vertex attribute

When we run the program with the rendering function of Listing 3.2, the triangle will move in a smooth oval shape around the window.

Passing Data from Stage to Stage

So far, you have seen how to pass data into a vertex shader by creating a vertex attribute using the `in` keyword, how to communicate with fixed-function blocks by reading and writing built-in variables such as `gl_VertexID` and `gl_Position`, and how to output data from the fragment shader using the `out` keyword. However, it's also possible to send your own data from shader stage to shader stage using the same `in` and `out` keywords. Just as you used the `out` keyword in the fragment shader to create the output variable to which it writes its color values, so you can also create an output variable in the vertex shader by using the `out` keyword. Anything you write to an output variable in one shader is sent to a similarly named variable declared with the `in` keyword in the subsequent stage. For example, if your vertex shader declares a variable called `vs_color` using the `out` keyword, it would match up with a variable named `vs_color` declared with the `in` keyword in the fragment shader stage (assuming no other stages were active in between).

If we modify our simple vertex shader as shown in Listing 3.3 to include `vs_color` as an output variable, and correspondingly modify our simple fragment shader to include `vs_color` as an input variable as shown in Listing 3.4, we can pass a value from the vertex shader to the fragment shader. Then, rather than outputting a hard-coded value, the fragment can simply output the color passed to it from the vertex shader.

```
#version 450 core

// 'offset' and 'color' are input vertex attributes
layout (location = 0) in vec4 offset;
layout (location = 1) in vec4 color;

// 'vs_color' is an output that will be sent to the next shader stage
out vec4 vs_color;

void main(void)
{
    const vec4 vertices[3] = vec4[3](vec4( 0.25, -0.25, 0.5, 1.0),
                                       vec4(-0.25, -0.25, 0.5, 1.0),
                                       vec4( 0.25,  0.25, 0.5, 1.0));

    // Add 'offset' to our hard-coded vertex position
    gl_Position = vertices[gl_VertexID] + offset;

    // Output a fixed value for vs_color
    vs_color = color;
}
```

Listing 3.3: Vertex shader with an output

As you can see in Listing 3.3, we declare a second input to our vertex shader, color (this time at location 1), and write its value to the `vs_output` output. This is picked up by the fragment shader of Listing 3.4 and written to the framebuffer. This allows us to pass a color all the way from a vertex attribute that we can set with `glVertexAttrib*()` through the vertex shader, into the fragment shader, and out to the framebuffer. As a consequence, we can draw different-colored triangles!

```
#version 450 core

// Input from the vertex shader
in vec4 vs_color;

// Output to the framebuffer
out vec4 color;

void main(void)
{
    // Simply assign the color we were given by the vertex shader to our output
    color = vs_color;
}
```

Listing 3.4: Fragment shader with an input

Interface Blocks

Declaring interface variables one at a time is possibly the simplest way to communicate data between shader stages. However, in most nontrivial applications, you will likely want to communicate a number of different pieces of data between stages; these may include arrays, structures, and other complex arrangements of variables. To achieve this, we can group together a number of variables into an *interface block*. The declaration of an interface block looks a lot like a structure declaration, except that it is declared using the `in` or `out` keyword depending on whether it is an input to or output from the shader. An example interface block definition is shown in Listing 3.5.

```
#version 450 core

// 'offset' is an input vertex attribute
layout (location = 0) in vec4 offset;
layout (location = 1) in vec4 color;

// Declare VS_OUT as an output interface block
out VS_OUT
{
    vec4 color;    // Send color to the next stage
} vs_out;
```

```

void main(void)
{
    const vec4 vertices[3] = vec4[3](vec4( 0.25, -0.25, 0.5, 1.0),
                                         vec4(-0.25, -0.25, 0.5, 1.0),
                                         vec4( 0.25,  0.25, 0.5, 1.0));

    // Add 'offset' to our hard-coded vertex position
    gl_Position = vertices[gl_VertexID] + offset;

    // Output a fixed value for vs_color
    vs_out.color = color;
}

```

Listing 3.5: Vertex shader with an output interface block

Note that the interface block in Listing 3.5 has both a block name (VS_OUT, uppercase) and an instance name (vs_out, lowercase). Interface blocks are matched between stages using the block name (VS_OUT in this case), but are referenced in shaders using the instance name. Thus, modifying our fragment shader to use an interface block gives the code shown in Listing 3.6.

```

#version 450 core

// Declare VS_OUT as an input interface block
in VS_OUT
{
    vec4 color;    // Send color to the next stage
} fs_in;

// Output to the framebuffer
out vec4 color;

void main(void)
{
    // Simply assign the color we were given by the vertex shader to our output
    color = fs_in.color;
}

```

Listing 3.6: Fragment shader with an input interface block

Matching interface blocks by block name but allowing block instances to have different names in each shader stage serves two important purposes. First, it allows the name by which you refer to the block to be different in each stage, thereby avoiding confusing things such as having to use `vs_out` in a fragment shader. Second, it allows interfaces to go from being single items to arrays when crossing between certain shader stages, such as the vertex and tessellation or geometry shader stages, as we will see in a short while. Note that interface blocks are only for moving data from

shader stage to shader stage—you can't use them to group together inputs to the vertex shader or outputs from the fragment shader.

Tessellation

Tessellation is the process of breaking a high-order primitive (which is known as a *patch* in OpenGL) into many smaller, simpler primitives such as triangles for rendering. OpenGL includes a fixed-function, configurable tessellation engine that is able to break up quadrilaterals, triangles, and lines into a potentially large number of smaller points, lines, or triangles that can be directly consumed by the normal rasterization hardware further down the pipeline. Logically, the tessellation phase sits directly after the vertex shading stage in the OpenGL pipeline and is made up of three parts: the tessellation control shader, the fixed-function tessellation engine, and the tessellation evaluation shader.

Tessellation Control Shaders

The first of the three tessellation phases is the tessellation control shader (TCS; sometimes known as simply the control shader). This shader takes its input from the vertex shader and is primarily responsible for two things: the determination of the level of tessellation that will be sent to the tessellation engine, and the generation of data that will be sent to the tessellation evaluation shader that is run after tessellation has occurred.

Tessellation in OpenGL works by breaking down high-order surfaces known as *patches* into points, lines, or triangles. Each patch is formed from a number of *control points*. The number of control points per patch is configurable and set by calling `glPatchParameteri()` with `pname` set to `GL_PATCH_VERTICES` and `value` set to the number of control points that will be used to construct each patch. The prototype of `glPatchParameteri()` is

```
void glPatchParameteri(GLenum pname,  
                        GLint value);
```

By default, the number of control points per patch is three. Thus, if this is what you want (as in our example application), you don't need to call it at all. The maximum number of control points that can be used to form a single patch is implementation defined, but is guaranteed to be at least 32.

When tessellation is active, the vertex shader runs once per control point, while the tessellation control shader runs in batches on groups of control points where the size of each batch is the same as the number of vertices per patch. That is, vertices are used as control points and the result of the vertex shader is passed in batches to the tessellation control shader as its input. The number of control points per patch can be changed such that the number of control points that is output by the tessellation control shader can differ from the number of control points that it consumes. The number of control points produced by the control shader is set using an output layout qualifier in the control shader's source code. Such a layout qualifier looks like this:

```
layout (vertices = N) out;
```

Here, N is the number of control points per patch. The control shader is responsible for calculating the values of the output control points and for setting the tessellation factors for the resulting patch that will be sent to the fixed-function tessellation engine. The output tessellation factors are written to the `gl_TessLevelInner` and `gl_TessLevelOuter` built-in output variables, whereas any other data that is passed down the pipeline is written to user-defined output variables (those declared using the **out** keyword, or the special built-in `gl_out` array) as normal.

Listing 3.7 shows a simple tessellation control shader. It sets the number of output control points to three (the same as the default number of input control points) using the **layout (vertices = 3) out;** layout qualifier, copies its input to its output (using the built-in variables `gl_in` and `gl_out`), and sets the inner and outer tessellation level to 5. Higher numbers would produce a more densely tessellated output, and lower numbers would yield a more coarsely tessellated output. Setting the tessellation factor to 0 will cause the whole patch to be thrown away.

The built-in input variable `gl_InvocationID` is used as an index into the `gl_in` and `gl_out` arrays. This variable contains the zero-based index of the control point within the patch being processed by the current invocation of the tessellation control shader.

```
#version 450 core

layout (vertices = 3) out;

void main(void)
{
    // Only if I am invocation 0 ...
    if (gl_InvocationID == 0)
```

```
{
    gl_TessLevelInner[0] = 5.0;
    gl_TessLevelOuter[0] = 5.0;
    gl_TessLevelOuter[1] = 5.0;
    gl_TessLevelOuter[2] = 5.0;
}
// Everybody copies their input to their output
gl_out[gl_InvocationID].gl_Position =
    gl_in[gl_InvocationID].gl_Position;
}
```

Listing 3.7: Our first tessellation control shader

The Tessellation Engine

The tessellation engine is a fixed-function part of the OpenGL pipeline that takes high-order surfaces represented as patches and breaks them down into simpler primitives such as points, lines, or triangles. Before the tessellation engine receives a patch, the tessellation control shader processes the incoming control points and sets tessellation factors that are used to break down the patch. After the tessellation engine produces the output primitives, the vertices representing them are picked up by the tessellation evaluation shader. The tessellation engine is responsible for producing the parameters that are fed to the invocations of the tessellation evaluation shader, which it then uses to transform the resulting primitives and get them ready for rasterization.

Tessellation Evaluation Shaders

Once the fixed-function tessellation engine has run, it produces a number of output vertices representing the primitives it has generated. These are passed to the tessellation evaluation shader. The tessellation evaluation shader (TES; also called simply the evaluation shader) runs an invocation for each vertex produced by the tessellator. When the tessellation levels are high, the tessellation evaluation shader could run an extremely large number of times. For this reason, you should be careful with complex evaluation shaders and high tessellation levels.

Listing 3.8 shows a tessellation evaluation shader that accepts input vertices produced by the tessellator as a result of running the control shader shown in Listing 3.7. At the beginning of the shader is a layout qualifier that sets the tessellation mode. In this case, we selected the mode

to be triangles. Other qualifiers, `equal_spacing` and `cw`, indicate that new vertices should be generated equally spaced along the tessellated polygon edges and that a clockwise vertex winding order should be used for the generated triangles. We will cover the other possible choices in the “Tessellation” section in Chapter 8.

The remainder of the shader assigns a value to `gl_Position` just like a vertex shader does. It calculates this using the contents of two more built-in variables. The first is `gl_TessCoord`, which is the *barycentric coordinate* of the vertex generated by the tessellator. The second is the `gl_Position` member of the `gl_in[]` array of structures. This matches the `gl_out` structure written to in the tessellation control shader given in Listing 3.7. This shader essentially implements pass-through tessellation. That is, the tessellated output patch is exactly the same shape as the original, incoming triangular patch.

```
#version 450 core

layout (triangles, equal_spacing, cw) in;

void main(void)
{
    gl_Position = (gl_TessCoord.x * gl_in[0].gl_Position +
                  gl_TessCoord.y * gl_in[1].gl_Position +
                  gl_TessCoord.z * gl_in[2].gl_Position);
}
```

Listing 3.8: Our first tessellation evaluation shader

To see the results of the tessellator, we need to tell OpenGL to draw only the outlines of the resulting triangles. To do this, we call `glPolygonMode()`, whose prototype is

```
void glPolygonMode(GLenum face,
                  GLenum mode);
```

The `face` parameter specifies which type of polygons we want to affect. Because we want to affect everything, we set it to `GL_FRONT_AND_BACK`. The other modes will be explained shortly. `mode` says how we want our polygons to be rendered. As we want to render in wireframe mode (i.e., lines), we set this to `GL_LINE`. The result of rendering our one triangle




Figure 3.1: Our first tessellated triangle

example with tessellation enabled and the two shaders of Listing 3.7 and Listing 3.8 is shown in Figure 3.1.

Geometry Shaders

The geometry shader is logically the last shader stage in the front end, sitting after the vertex and tessellation stages and before the rasterizer. The geometry shader runs once per primitive and has access to all of the input vertex data for all of the vertices that make up the primitive being processed. The geometry shader is also unique among the shader stages in that it is able to increase or reduce the amount of data flowing through the pipeline in a programmatic way. Tessellation shaders can also increase or decrease the amount of work in the pipeline, but only implicitly by setting the tessellation level for the patch. Geometry shaders, in contrast, include two functions—`EmitVertex()` and `EndPrimitive()`—that explicitly produce vertices that are sent to primitive assembly and rasterization.

Another unique feature of geometry shaders is that they can change the primitive mode mid-pipeline. For example, they can take triangles as input

and produce a bunch of points or lines as output, or even create triangles from independent points. An example geometry shader is shown in Listing 3.9.

```
#version 450 core

layout (triangles) in;
layout (points, max_vertices = 3) out;

void main(void)
{
    int i;

    for (i = 0; i < gl_in.length(); i++)
    {
        gl_Position = gl_in[i].gl_Position;
        EmitVertex();
    }
}
```

Listing 3.9: Our first geometry shader

The shader shown in Listing 3.9 acts as another simple pass-through shader that converts triangles into points so that we can see their vertices. The first layout qualifier indicates that the geometry shader is expecting to see triangles as its input. The second layout qualifier tells OpenGL that the geometry shader will produce points and that the maximum number of points that each shader will produce will be three. In the `main` function, a loop runs through all of the members of the `gl_in` array, which is determined by calling its `.length()` function.

We actually know that the length of the array will be three because we are processing triangles and every triangle has three vertices. The outputs of the geometry shader are again similar to those of a vertex shader. In particular, we write to `gl_Position` to set the position of the resulting vertex. Next, we call `EmitVertex()`, which produces a vertex at the output of the geometry shader. Geometry shaders automatically call `EndPrimitive()` at the end of your shader, so calling this function explicitly is not necessary in this example. As a result of running this shader, three vertices will be produced and rendered as points.

By inserting this geometry shader into our simple one tessellated triangle example, we obtain the output shown in Figure 3.2. To create this image, we set the point size to 5.0 by calling `glPointSize()`. This makes the points large and highly visible.




Figure 3.2: Tessellated triangle after adding a geometry shader

Primitive Assembly, Clipping, and Rasterization

After the front end of the pipeline has run (which includes vertex shading, tessellation, and geometry shading), a fixed-function part of the pipeline performs a series of tasks that take the vertex representation of our scene and convert it into a series of pixels, which in turn need to be colored and written to the screen. The first step in this process is primitive assembly, which is the grouping of vertices into lines and triangles. Primitive assembly still occurs for points, but it is trivial in that case.

Once primitives have been constructed from their individual vertices, they are *clipped* against the displayable region, which usually means the window or screen, but can also be a smaller area known as the *viewport*. Finally, the parts of the primitive that are determined to be potentially visible are sent to a fixed-function subsystem called the rasterizer. This block determines which pixels are covered by the primitive (point, line, or triangle) and sends the list of pixels on to the next stage—that is, fragment shading.

Clipping

As vertices exit the front end of the pipeline, their position is said to be in *clip space*. This is one of the many coordinate systems that can be used to represent positions. You may have noticed that the `gl_Position` variable

that we have written to in our vertex, tessellation, and geometry shaders has a `vec4` type, and that the positions we have produced by writing to it are all four-component vectors. This is what is known as a *homogeneous* coordinate. The homogeneous coordinate system is used in projective geometry because much of the math ends up being simpler in homogeneous coordinate space than it does in regular Cartesian space. Homogeneous coordinates have one more component than their equivalent Cartesian coordinate, which is why our three-dimensional position vector is represented as a four-component variable.

Although the output of the front end is a four-component homogeneous coordinate, clipping occurs in Cartesian space. Thus, to convert from homogeneous coordinates to Cartesian coordinates, OpenGL performs a *perspective division*, which involves dividing all four components of the position by the last, w component. This has the effect of projecting the vertex from the homogeneous space to the Cartesian space, leaving w as 1.0. In all of the examples so far, we have set the w component of `gl_Position` as 1.0, so this division has not had any effect. When we explore projective geometry in a short while, we will discuss the effect of setting w to values other than 1.0.

After the projective division, the resulting position is in *normalized device space*. In OpenGL, the visible region of normalized device space is the volume that extends from -1.0 to 1.0 in the x and y dimensions and from 0.0 to 1.0 in the z dimension. Any geometry that is contained in this region may become visible to the user and anything outside of it should be discarded. The six sides of this volume are formed by planes in three-dimensional space. As a plane divides a coordinate space in two, the volumes on each side of the plane are called *half-spaces*.

Before passing primitives on to the next stage, OpenGL performs clipping by determining which side of each of these planes the vertices of each primitive lie on. Each plane effectively has an “outside” and an “inside.” If a primitive’s vertices all lie on the “outside” of any one plane, then the whole thing is thrown away. If all of primitive’s vertices are on the “inside” of all the planes (and therefore inside the view volume), then it is passed through unaltered. Primitives that are partially visible (which means that they cross one of the planes) must be handled specially. More details about how this works is given in the “Clipping” section in Chapter 7.

Viewport Transformation

After clipping, all of the vertices of the geometry have coordinates that lie between -1.0 and 1.0 in the x and y dimensions. Along with a z coordinate

that lies between 0.0 and 1.0, these are known as normalized device coordinates. However, the window that you're drawing to has coordinates that usually¹ start from (0, 0) at the bottom left and range to ($w - 1, h - 1$), where w and h are the width and height of the window in pixels, respectively. To place your geometry into the window, OpenGL applies the *viewport transform*, which applies a scale and offset to the vertices' normalized device coordinates to move them into *window coordinates*. The scale and bias to apply are determined by the viewport bounds, which you can set by calling `glViewport()` and `glDepthRange()`. Their prototypes are

```
void glViewport(GLint x, GLint y, GLsizei width, GLsizei height);
```

and

```
void glDepthRange(GLdouble nearVal, GLdouble farVal);
```

This transform takes the following form:

$$\begin{pmatrix} x_w \\ y_w \\ z_w \end{pmatrix} = \begin{pmatrix} \frac{p_x}{2}x_d + o_x \\ \frac{p_y}{2}y_d + o_y \\ \frac{f-n}{2}z_d + \frac{n+f}{2} \end{pmatrix}$$

Here, x_w , y_w , and z_w are the resulting coordinates of the vertex in window space, and x_d , y_d , and z_d are the incoming coordinates of the vertex in normalized device space. p_x and p_y are the width and height of the viewport in pixels, and n and f are the near and far plane distances in the z coordinate, respectively. Finally, o_x , o_y , and o_z are the origins of the viewport.

Culling

Before a triangle is processed further, it may be optionally passed through a stage called *culling*, which determines whether the triangle faces toward or away from the viewer and can decide whether to actually go ahead and draw it based on the result of this computation. If the triangle faces toward the viewer, then it is considered to be *front-facing*; otherwise, it is said to be *back-facing*. It is very common to discard triangles that are back-facing because when an object is closed, any back-facing triangle will be hidden by another front-facing triangle.

1. It's possible to change the coordinate convention such that the (0, 0) origin is at the upper-left corner of the window, which matches the convention used in some other graphics systems.

To determine whether a triangle is front- or back-facing, OpenGL will determine its *signed* area in window space. One way to determine the area of a triangle is to take the cross product of two of its edges. The equation for this is

$$a = \frac{1}{2} \sum_{i=0}^{n-1} x_w^i y_w^{i \oplus 1} - x_w^{i \oplus 1} y_w^i$$

Here, x_w^i and y_w^i are the coordinates of the i th vertex of the triangle in window space and $i \oplus 1$ is $(i + 1) \bmod 3$. If the area is positive, then the triangle is considered to be front-facing; if it is negative, then it is considered to be back-facing. The sense of this computation can be reversed by calling **glFrontFace()** with `dir` set to either `GL_CW` or `GL_CCW` (where `CW` and `CCW` stand for clockwise and counterclockwise, respectively). This is known as the *winding order* of the triangle, and the clockwise or counterclockwise terms refer to the order in which the vertices appear in window space. By default, this state is set to `GL_CCW`, indicating that triangles whose vertices are in counterclockwise order are considered to be front-facing and those whose vertices are in clockwise order are considered to be back-facing. If the state is `GL_CW`, then a is simply negated before being used in the culling process. Figure 3.3 shows this pictorially for the purpose of illustration.

Once the direction that the triangle is facing has been determined, OpenGL is capable of discarding either front-facing, back-facing, or even both types of triangles. By default, OpenGL will render all triangles, regardless of which way they face. To turn on culling, call **glEnable()** with `cap` set to `GL_CULL_FACE`. When you enable culling, OpenGL will cull back-facing triangles by default. To change which types of triangles are




Figure 3.3: Clockwise (left) and counterclockwise (right) winding order

culled, call `glCullFace()` with face set to `GL_FRONT`, `GL_BACK`, or `GL_FRONT_AND_BACK`.

As points and lines don't have any geometric area,² this facing calculation doesn't apply to them and they can't be culled at this stage.

Rasterization

Rasterization is the process of determining which fragments might be covered by a primitive such as a line or a triangle. There are myriad algorithms for doing this, but most OpenGL systems will settle on a half-space-based method for triangles, as it lends itself well to parallel implementation. Essentially, OpenGL will determine a bounding box for the triangle in window coordinates and test every fragment inside it to determine whether it is inside or outside the triangle. To do this, it treats each of the triangle's three edges as a half-space that divides the window in two.

Fragments that lie on the interior of all three edges are considered to be inside the triangle and fragments that lie on the exterior of any of the three edges are considered to be outside the triangle. Because the algorithm to determine which side of a line a point lies on is relatively simple and is independent of anything besides the position of the line's endpoints and of the point being tested, many tests can be performed concurrently, providing the opportunity for massive parallelism.

Fragment Shaders

The fragment³ shader is the last programmable stage in OpenGL's graphics pipeline. This stage is responsible for determining the color of each fragment before it is sent to the framebuffer for possible composition into the window. After the rasterizer processes a primitive, it produces a list of fragments that need to be colored and passes this list to the fragment

2. Obviously, once they are rendered to the screen, points and lines have area; otherwise, we wouldn't be able to see them. However, this area is artificial and can't be calculated directly from their vertices.

3. The term *fragment* is used to describe an element that may ultimately contribute to the final color of a pixel. The pixel may not end up being the color produced by any particular invocation of the fragment shader due to a number of other effects such as depth or stencil tests, blending, and multi-sampling, all of which will be covered later in the book.

shader. Here, an explosion in the amount of work in the pipeline occurs, as each triangle could produce hundreds, thousands, or even millions of fragments.

Listing 2.4 in Chapter 2 contains the source code of our first fragment shader. It's an extremely simple shader that declares a single output and then assigns a fixed value to it. In a real-world application, the fragment shader would normally be substantially more complex and be responsible for performing calculations related to lighting, applying materials, and even determining the depth of the fragment. Available as input to the fragment shader are several built-in variables such as `gl_FragCoord`, which contains the position of the fragment within the window. It is possible to use these variables to produce a unique color for each fragment.

Listing 3.10 provides a shader that derives its output color from `gl_FragCoord`. Figure 3.4 shows the output of running our original single-triangle program with this shader installed.

```
#version 450 core

out vec4 color;

void main(void)
{
    color = vec4(sin(gl_FragCoord.x * 0.25) * 0.5 + 0.5,
                  cos(gl_FragCoord.y * 0.25) * 0.5 + 0.5,
                  sin(gl_FragCoord.x * 0.15) * cos(gl_FragCoord.y * 0.15),
                  1.0);
}
```

Listing 3.10: Deriving a fragment's color from its position

As you can see, the color of each pixel in Figure 3.4 is now a function of its position and a simple screen-aligned pattern has been produced. The shader of Listing 3.10 created the checkered patterns in the output.

The `gl_FragCoord` variable is one of the built-in variables available to the fragment shader. However, just as with other shader stages, we can define our own inputs to the fragment shader, which will be filled in based on the outputs of whichever stage is last before rasterization. For example, if we have a simple program with only a vertex shader and fragment shader in it, we can pass data from the fragment shader to the vertex shader.

The inputs to the fragment shader are somewhat unlike inputs to other shader stages, in that OpenGL *interpolates* their values across the primitive




Figure 3.4: Result of Listing 3.10

that's being rendered. To demonstrate, we take the vertex shader of Listing 3.3 and modify it to assign a different, fixed color for each vertex, as shown in Listing 3.11.

```
#version 450 core

// 'vs_color' is an output that will be sent to the next shader stage
out vec4 vs_color;

void main(void)
{
    const vec4 vertices[3] = vec4[3](vec4( 0.25, -0.25, 0.5, 1.0),
                                       vec4(-0.25, -0.25, 0.5, 1.0),
                                       vec4( 0.25,  0.25, 0.5, 1.0));
    const vec4 colors[] = vec4[3](vec4( 1.0, 0.0, 0.0, 1.0),
                                   vec4( 0.0, 1.0, 0.0, 1.0),
                                   vec4( 0.0, 0.0, 1.0, 1.0));

    // Add 'offset' to our hard-coded vertex position
    gl_Position = vertices[gl_VertexID] + offset;

    // Output a fixed value for vs_color
    vs_color = color[gl_VertexID];
}
```

Listing 3.11: Vertex shader with an output

As you can see, in Listing 3.11 we added a second constant array that contains colors and index into it using `gl_VertexID`, writing its content to the `vs_color` output. In Listing 3.12 we modify our simple fragment shader to include the corresponding input and write its value to the output.

```
#version 450 core

// 'vs_color' is the color produced by the vertex shader
in vec4 vs_color;

out vec4 color;

void main(void)
{
    color = vs_color;
}
```

Listing 3.12: Deriving a fragment's color from its position

The result of using this new pair of shaders is shown in Figure 3.5. As you can see, the color changes smoothly across the triangle.




Figure 3.5: Result of Listing 3.12

Framebuffer Operations

The framebuffer is the last stage of the OpenGL graphics pipeline. It can represent the visible content of the screen and a number of additional regions of memory that are used to store per-pixel values other than color. On most platforms, this means the window you see on your desktop (or possibly the whole screen if your application covers it), which is owned by the operating system (or windowing system to be more precise). The framebuffer provided by the windowing system is known as the default framebuffer, but it is possible to provide your own if you wish to do things like render into off-screen areas. The state held by the framebuffer includes information such as where the data produced by your fragment shader should be written, what the format of that data should be, and so on. This state is stored in a *framebuffer object*. Also considered part of the framebuffer, but not stored per framebuffer object, is the pixel operation state.

Pixel Operations

After the fragment shader has produced an output, several things may happen to the fragment before it is written to the window, such as a determination of whether it even belongs in the window. Each of these things may be turned on or off by your application. The first thing that could happen is the *scissor test*, which tests your fragment against a rectangle that you can define. If it's inside the rectangle, then it will be processed further; if it's outside, it will be thrown away.

Next comes the *stencil test*. This compares a reference value provided by your application with the contents of the stencil buffer, which stores a single⁴ value per pixel. The content of the stencil buffer has no particular semantic meaning and can be used for any purpose.

After the stencil test has been performed, the *depth test* is performed. The depth test is an operation that compares the fragment's *z* coordinate against the contents of the *depth buffer*. The depth buffer is a region of memory that, like the stencil buffer, is part of the framebuffer with enough space for a single value for each pixel; it contains the depth (which is related to distance from the viewer) of each pixel.

4. It's possible for a framebuffer to store multiple depth, stencil, or color values per pixel when a technique called *multi-sampling* is employed. We'll dig into this later in the book.

Normally, the values in the depth buffer range from 0 to 1, with 0 being the closest possible point in the depth buffer and 1 being the furthest possible point in the depth buffer. To determine whether a fragment is closer than other fragments that have already been rendered in the same place, OpenGL can compare the z component of the fragment's window-space coordinate against the value already in the depth buffer. If this value is less than what's already there, then the fragment is visible. The sense of this test can also be changed. For example, you can ask OpenGL to let fragments through that have a z coordinate that is greater than, equal to, or not equal to the content of the depth buffer. The result of the depth test also affects what OpenGL does to the stencil buffer.

Next, the fragment's color is sent to either the blending or logical operation stage, depending on whether the framebuffer is considered to store floating-point, normalized, or integer values. If the content of the framebuffer is either floating-point or normalized integer values, then blending is applied. Blending is a highly configurable stage in OpenGL and will be covered in detail in its own section.

In short, OpenGL is capable of using a wide range of functions that take components of the output of your fragment shader and of the current content of the framebuffer and calculate new values that are written back to the framebuffer. If the framebuffer contains unnormalized integer values, then logical operations such as logical AND, OR, and XOR can be applied to the output of your shader and the value currently in the framebuffer to produce a new value that will be written back into the framebuffer.

Compute Shaders

The first sections of this chapter describe the *graphics pipeline* in OpenGL. However, OpenGL also includes the *compute shader* stage, which can almost be thought of as a separate pipeline that runs independently of the other graphics-oriented stages.

Compute shaders are a way of getting at the computational power possessed by the graphics processor in the system. Unlike the graphics-centric vertex, tessellation, geometry, and fragment shaders, compute shaders could be considered as a special, single-stage pipeline all on their own. Each compute shader operates on a single unit of work known as a *work item*; these items are, in turn, collected together into small groups called *local workgroups*. Collections of these workgroups can

be sent into OpenGL's compute pipeline to be processed. The compute shader doesn't have any fixed inputs or outputs besides a handful of built-in variables to tell the shader which item it is working on. All processing performed by a compute shader is explicitly written to memory by the shader itself, rather than being consumed by a subsequent pipeline stage. A very basic compute shader is shown in Listing 3.13.

```
#version 450 core

layout (local_size_x = 32, local_size_y = 32) in;

void main(void)
{
    // Do nothing
}
```

Listing 3.13: Simple do-nothing compute shader

Compute shaders are otherwise just like any other shader stage in OpenGL. To compile one, you create a shader object with the type `GL_COMPUTE_SHADER`, attach your GLSL source code to it with `glShaderSource()`, compile it with `glCompileShader()`, and then link it into a program with `glAttachShader()` and `glLinkProgram()`. The result is a program object with a compiled compute shader in it that can be launched to do work for you.

The shader in Listing 3.13 tells OpenGL that the size of the local workgroup will be 32 by 32 work items, but then proceeds to do nothing. To create a compute shader that actually does something useful, you need to know a bit more about OpenGL—so we'll revisit this topic later in the book.

Using Extensions in OpenGL

All of the examples shown in this book so far have relied on the core functionality of OpenGL. However, one of OpenGL's greatest strengths is that it can be extended and enhanced by hardware manufacturers, operating system vendors, and even publishers of tools and debuggers. Extensions can have many different effects on OpenGL functionality.

An extension is any addition to a core version of OpenGL. Extensions are listed in the OpenGL extension registry⁵ on the OpenGL Web site. These

5. Find the OpenGL extension registry at <http://www.opengl.org/registry/>.

extensions are written as a list of differences from a particular version of the OpenGL specification, and note what that version of OpenGL is. That means the text of the extensions describes how the core OpenGL specification must be changed if the extension is supported. However, popular and generally useful extensions are normally “promoted” into the core versions of OpenGL; thus, if you are running the latest and greatest version of OpenGL, there might not be that many extensions that are interesting but not part of the core profile. A complete list of the extensions that were promoted to each version of OpenGL and a brief synopsis of what they do is included in Appendix C, “OpenGL Features and Versions.”

There are three major classifications of extensions: vendor, EXT, and ARB. Vendor extensions are written and implemented on one vendor’s hardware. Initials representing the specific vendor are usually part of the extension name—“AMD” for Advanced Micro Devices or “NV” for NVIDIA, for example. It is possible that more than one vendor might support a specific vendor extension, especially if it becomes widely accepted. EXT extensions are written together by two or more vendors. They often start their lives as vendor-specific extensions, but if another vendor is interested in implementing the extension, perhaps with minor changes, it may collaborate with the original authors to produce an EXT version. ARB extensions are an official part of OpenGL because they are approved by the OpenGL governing body, the Architecture Review Board (ARB). These extensions are often supported by most or all major hardware vendors and may also have started out as vendor or EXT extensions.

This extension process may sound confusing at first. Hundreds of extensions currently are available! But new versions of OpenGL are often constructed from extensions programmers have found useful. In this way each extension gets its time in the sun. The ones that shine can be promoted to core; the ones that are less useful are not considered. This “natural selection” process helps to ensure only the most useful and important new features make it into a core version of OpenGL.

A useful tool to determine which extensions are supported in your computer’s OpenGL implementation is Realtech VR’s OpenGL Extensions Viewer. It is freely available from the Realtech VR Web site (see Figure 3.6).

Enhancing OpenGL with Extensions

Before using any extensions, you *must* make sure that they’re supported by the OpenGL implementation that your application is running on. To find




Figure 3.6: Realtech VR's OpenGL Extensions Viewer

out which extensions OpenGL supports, there are two functions that you can use. First, to determine the *number* of supported extensions, you can call `glGetIntegerv()` with the `GL_NUM_EXTENSIONS` parameter. Next, you can find out the name of each of the supported extensions by calling

```
const GLubyte* glGetStringi(GLenum name,
                             GLuint index);
```

You should pass `GL_EXTENSIONS` as the name parameter, and a value between 0 and 1 less than the number of supported extensions in index. The function returns the name of the extension as a string. To see if a specific extension is supported, you can simply query the number of extensions, and then loop through each supported extension and compare its name to the one you're looking for. The book's source code comes with a simple function that does this for you. `sb7IsExtensionSupported()` has the prototype

```
int sb7IsExtensionSupported(const char * extname);
```

This function is declared in the `<sb7ext.h>` header, takes the name of an extension, and returns non-zero if it is supported by the current OpenGL context and zero if it is not. Your application should always check for support for extensions you wish to use before using them.

Extensions generally add to OpenGL in some combination of four different ways:

- They can make things legal that weren't before, by simply removing restrictions from the OpenGL specification.
- They can add tokens or extend the range of values that can be passed as parameters to existing functions.
- They can extend GLSL to add functionality, built-in functions, variables, or data types.
- They can add entirely new functions to OpenGL itself.

In the first case, where things that once were considered errors no longer are, your application doesn't need to do anything besides start using the newly allowed behavior (once you have determined that the extension is supported, of course). Likewise, for the second case, you can just start using the new token values in the relevant functions, presuming that you have their values. The values of the tokens are in the extension specifications, so you can look them up there if they are not included in your system's header files.

To enable use of extensions in GLSL, you must first include a line at the beginning of shaders that use them to tell the compiler that you're going to need their features. For example, to enable the hypothetical `GL_ABC_foobar_feature` extension in GLSL, include the following in the beginning of your shader:

```
#extension GL_ABC_foobar_feature : enable
```

This tells the compiler that you intend to use the extension in your shader. If the compiler knows about the extension, it will let you compile the shader, even if the underlying hardware doesn't support the feature. If this is the case, the compiler should issue a warning if it sees that the extension is actually being used. Typically, extensions to GLSL will add preprocessor tokens to indicate their presence. For example, `GL_ABC_foobar_feature` will implicitly include

```
#define GL_ABC_foobar_feature 1
```

This means that you could write code such as

```
#if GL_ABC_foobar_feature
    // Use functions from the foobar extension
#else
```

```
    // Emulate or otherwise work around the missing functionality
#endif
```

This allows you to conditionally compile or execute functionality that is part of an extension that may or may not be supported by the underlying OpenGL implementation. If your shader absolutely requires support for an extension and will not work at all without it, you can instead include this more assertive code:

```
#extension GL_ABC_foobar_feature : require
```

If the OpenGL implementation does not support the `GL_ABC_foobar_feature` extension, then it will fail to compile the shader and report an error on the line including the `#extension` directive. In effect, GLSL extensions are opt-in features, and applications must⁶ tell compilers up front which extensions they intend to use.

Next we come to extensions that introduce new functions to OpenGL. On most platforms, you don't have direct access to the OpenGL driver and extension functions don't just magically appear as available to your applications to call. Rather, you must ask the OpenGL driver for a *function pointer* that represents the function you want to call. Function pointers are generally declared in two parts; the first is the definition of the function pointer type, and the second is the function pointer variable itself. Consider this code as an example:

```
typedef void
(APIENTRY PFNGLDRAWTRANSFORMFEEDBACKPROC) (GLenum mode,
                                             GLuint id);
PFNGLDRAWTRANSFORMFEEDBACKPROC glDrawTransformFeedback = NULL;
```

This declares the `PFNGLDRAWTRANSFORMFEEDBACKPROC` type as a pointer to a function taking `GLenum` and `GLuint` parameters. Next, it declares the `glDrawTransformFeedback` variable as an instance of this type. In fact, on many platforms, the declaration of the `glDrawTransformFeedback()` function is actually just like this. This seems pretty complicated, but fortunately the following header files include declarations of all of the

6. In practice, many implementations enable functionality included in some extensions by default and don't require that your shaders include these directives. However, if you rely on this behavior, your application is likely to not work on other OpenGL drivers. Because of this risk, you should always explicitly enable the extensions that you plan to use.

function prototypes, function pointer types, and token values introduced by all registered OpenGL extensions:

```
#include <glxext.h>
#include <glxext.h>
#include <wglxext.h>
```

These files can be found at the OpenGL extension registry Web site. The `glxext.h` header contains both standard OpenGL extensions and many vendor-specific OpenGL extensions, the `wglxext.h` header contains a number of extensions that are Windows specific, and the `glxext.h` header contains definitions that are X specific (X is the windowing system used on Linux and many other UNIX derivatives and implementations).

The method for querying the address of extension functions is actually platform specific. The book's application framework wraps up these intricacies into a handy function that is declared in the `<sb7ext.h>` header file. The function **`sb7GetProcAddress()`** has this prototype:

```
void * sb7GetProcAddress(const char * funcname);
```

Here, `funcname` is the name of the extension function that you wish to use. The return value is the address of the function, if it's supported, and `NULL` otherwise. Even if OpenGL returns a valid function pointer for a function that's part of the extension you want to use, that doesn't mean the extension is present. Sometimes the same function is part of more than one extension, and sometimes vendors ship drivers with partial implementations of extensions present. Always check for support for extensions using the official mechanisms or the **`sb7IsExtensionSupported()`** function.

Summary

In this chapter, you have taken a whirlwind trip down OpenGL's graphics pipeline. You have been (very) briefly introduced to each major stage and have created a program that uses each one of them, if only to do nothing impressive. We've glossed over or even neglected to mention several useful features of OpenGL with the intention of getting you from zero to rendering in as few pages as possible. You've also seen how OpenGL's pipeline and functionality can be enhanced by using extensions, which some of the examples later in the book will rely on. Over the next few chapters, you'll learn more fundamentals of computer graphics and of OpenGL, and then we'll take a second trip down the pipeline, dig deeper into the topics from this chapter, and get into some of the things we skipped in this preview of what OpenGL can do.

Index

- { } (curly braces), 211
- 2D
 - array textures, 178–180
 - graphics, 647–659
 - prefix sums, 484
 - projection, 69
 - ray tracing, 636
- 3D graphics
 - coordinate spaces used in, 70
 - math for, 55. *See also* Math
- Abstraction layers, 4
- Acceleration
 - graphics, 8
 - structures, 646
- Access
 - map buffer types, 710–711
 - memory, 692
 - synchronizing
 - atomic counters, 151–152
 - to buffers, 692–694
 - images, 194
 - memory, 145–147
 - texture arrays, 181–182
 - vectors, 208
- Adaptive tone mapping, 436
- Adding. *See also* Inserting
 - detail to images, 586
 - directions, 627
 - fog effects, 606–609
 - planes, 645
- Advanced occlusion queries, 543–545
- AFR (alternate frame rendering) mode, 719
- Algorithms
 - flocking, 492–501
 - prefix sum operations, 479–492
 - shading, 599. *See also* Shadows
- Aliasing artifacts, 169
- Aligning uniform blocks, 125. *See also* Moving
- Allocating
 - data stores, 101
 - memory, 100–107
 - storage, 509, 691
- Alpha-to-coverage approach, 420
- Alternate frame rendering. *See* AFR mode
- Alternative rendering methods, 613–647
 - deferred shading, 613–624
 - rendering without triangles, 631–647
 - screen-space techniques, 624–631
- ALU (arithmetic and logic unit) performance, 715
- Ambient light, 568
- Ambient occlusion, 624–631
- AMD hardware, 704. *See also* Hardware
- Angles, Euler, 78–79
- Antialiasing, 412–428
 - centroid sampling, 424–428
 - filtering, 413–415
 - multi-sample, 156, 415–417
 - sample rate shading, 421–423
 - textures, 417–421
- AoSs (array-of-structures), 115
- APIs (application programming interfaces), 3, 6
- Appending packets to packet buffers, 670
- Application programming interfaces. *See* APIs
- Applications
 - barriers, inserting, 146–147
 - building, 717
 - debugging, 717, 729–737
 - geometry shaders in, 336–341
 - performance, 661. *See also* Performance

-
- Applications (*continued*)
 - rendering. *See* Rendering
 - simple example of, 14–16
 - sparsetexture, 512–514
 - speed, tuning for, 706–726
 - textures, unbinding, 504
 - Applying
 - attributes in vertex shaders, 113
 - barriers in shaders, 147
 - centroid qualifiers, 424
 - compression, 197–198
 - compute shaders, 468–469
 - extensions, 49–54
 - features, 713
 - fog, 609
 - instanced arrays, 265–271
 - mipmaps, 174
 - multiple GPUs, 719–721
 - multiple vertex shader inputs, 113–116
 - multi-threading, 721–723
 - query results, 537–540
 - roughness, 597
 - shaders, 17–24
 - transform feedback, 280–298
 - Approaching Zero Driver Overhead.
 - See* AZDO
 - ARB (Architectural Review Board), 7, 8, 50
 - Architectural Review Board. *See* ARB
 - Architecture, 5
 - Arithmetic and logic unit performance. *See* ALU performance
 - Array-of-structures. *See* AoSs
 - Arrays, 115, 210–212
 - declaring, 211
 - floats, 120
 - inputs, 339
 - instancing, 265–271
 - props, 229
 - scissor testing, configuring, 372
 - textures, 177–182, 397, 400, 411
 - VAOs (vertex array objects), 295, 493
 - Artifacts, aliasing, 169
 - ASCII characters, 652
 - Asteroids, drawing, 274–279
 - Atlas textures, 509
 - Atmospheric effects, 605–609
 - Atomic counters, 147–152, 151–152
 - Atomic operations, 140
 - images, 188–194
 - memory, 142–144
 - Attachments
 - completeness, 404
 - framebuffers
 - integers, 444–446
 - multiple, 395–397
 - rendering with no, 428–430
 - rendering, 392
 - textures, 392
 - Attributes
 - indirect draws, 276
 - interleaved, 114, 116
 - separate, 114
 - vertex shaders, 113
 - vertices, 28–29, 110
 - configuring, 112
 - disabling, 113
 - types, 246
 - AZDO (Approaching Zero Driver Overhead), 677
 - Back buffers, 390
 - Back end, 12
 - Back-facing, 41, 342
 - Back-to-back waiting, 536
 - Backward compatibility, 8, 9
 - Bandwidth, memory, 195, 614
 - barrier() function, 476, 478
 - Barriers, 476
 - applications, inserting, 146–147
 - shaders, 147
 - Barycentric coordinates, 36, 306–307, 311
 - Base vertex, 254–255
 - Bézier curves, 91. *See also* Curves
 - cubic, 92, 93
 - quadratic, 92
 - quintic, 94
 - Bézier splines, 95
 - BGRA ordering, 247
 - Big-picture views, 11
 - Binaries, programs, 235–238, 719
 - Binding, 100
 - buffers, 110, 133
 - eliminating, 504–509
 - image units, 184
 - points
 - assigning, 131
 - transform feedback, 284
 - bindingindex parameter, 110
 - Bindless textures, 504, 682
 - Bitangent vectors, 582
 - Bitmaps, fonts, 655–659
 - Blend equations, 383, 386–387
 - Blending, 382–387, 413
 - Blinn-Phong lighting models, 577–579
 - Blit, 461
 - Block Partitioned Texture Compression.
 - See* BPTC
 - Blocks, 516
 - atomic operations, 143–144
 - interfaces, 31–33
 - packing RGTC, 522
 - palettizing RGTC, 522
 - shader storage, 140–147
 - texels, fetching, 520
 - uniforms, 121–135. *See also* Uniforms
 - declaring, 121, 680

- default, 117–120
- indexes, 126
- Bloom programs, 438–444
- Boolean occlusion queries, 543
- bool scalar type, 206
- Bounces, increasing, 643
- Bound buffers, copying, 109
- Boxes
 - bounding, 537
 - filters, 486
 - ray tracing, 646
- BPTC (Block Partitioned Texture Compression), 196
- Brute force approaches, 646
- Bubbles, 557
- Buffers, 10, 100–117
 - access to, synchronizing, 692–694
 - atomic counters, 149
 - back, 390
 - bindings, 110, 133
 - commands, 668, 699
 - copying, 107–109
 - depth, 626
 - feedback, 549
 - filling, 107–109
 - formatting, 103
 - G-buffers, 614
 - indirect draws, configuring, 275
 - initializing, 103
 - mapping, 100, 102–103, 104, 699, 709–713
 - memory, allocating, 100–107
 - objects, updating, 104
 - packets, 668–677, 676–677
 - persistent maps, 665, 691–692
 - ranges, mapping, 106
 - stencil, 373–374
 - storage flags, 102
 - TBOs (texture buffer objects), 288
 - UBOs (uniform buffer objects), 121
 - unmapping, 105
 - updating, 378–379
 - velocity, 493
 - vertex shaders, feeding from, 109–117
 - write combined memory, 699
- Building applications, 717
- Built-in data manipulation functions, 218–219
- Built-in functions, 213–219
- Built-in math functions, 215–217
- Built-in matrices, 213–215
- Built-in variables, 25
- Bump mapping, 582
- Bumpy surfaces, 625
- C, corresponding OpenGL type tokens, 108
- Calculating
 - ambient light, 568
 - bitangent vectors, 582
 - Blinn-Phong lighting models, 577
 - indexes, 270
 - light, 619
 - lighting, 640
 - rim lighting, 580
 - shadows, 600
 - TBN (tangent, bitangent, normal) matrix, 584
- Callback functions, 731
- Cameras, 490. *See also* Images
- Candidate draws, culling, 685
- Cartesian coordinates, 40, 583
- Casting shadows, 599–605
- ccw layout qualifiers, 319
- Cell shading, 610–613
- Central processing units. *See* CPUs
- Centroid sampling, 424–428
- Chaining packet buffers, 675
- Characters, ASCII, 652
- Clamping
 - depth, enabling, 379–380
 - levels of detail, 515
 - tone mapping, 435
- Classes, image data formats, 185
- Classifications of extensions, 50
- Clipping, 39–40, 298–305
 - depth clamping, 380
 - guard bands, 301–302
 - objects, 304
 - user-defined, 302–305
- Clip spaces, 18, 39, 72
- Clocks, 5
- Coefficients, exposure, 435
- Colors
 - distance fields, 654–655
 - fragments, 44, 46, 48
 - Julia sets, 634
 - masking, 388–390
 - one-dimensional color lookup tables, 610
 - outputs, 382–387
 - specular highlights, 569
 - sRGB color spaces, 446–448
 - vertex shaders, 266
- Column-major layouts, 66
- Column-primary layouts, 66
- Columns, 485
- Commands, 4. *See also* Functions
 - buffers, 668, 699
 - drawing, 251–280
 - applying instanced arrays, 265–271
 - indexed, 251–257
 - indirect draws, 271–280
 - instancing, 257–265
 - formatting, 662
 - SwapBuffers(), 702
- Comment chunks, 755

-
- Committing
 - pages, 510
 - textures, 513
 - Common vector operators, 60–64
 - cross products, 62–63
 - dot products, 60–61
 - length of vectors, 63
 - reflection, 63–64
 - refraction, 63–64
 - Communication
 - compute shaders, 474–479
 - between tessellation shader invocations, 322
 - Comparisons, depth testing, 377
 - Compatibility
 - APIs (application programming interfaces), 6
 - backward, 8, 9
 - profiles, 9
 - texture target view, 200
 - Compilers, 219–224
 - retrieving logs, 221
 - Compiling shaders, performance, 716–719
 - Completeness, framebuffers, 403–407
 - Components, G-buffers, 618
 - Compression, textures, 195–199, 516–525, 715
 - Computer programs, 468
 - Compute shaders, 48–49, 467, 704
 - applying, 468–469
 - communication, 474–479
 - culling, 685
 - examples, 479–501
 - executing, 469–474
 - flocking, 492–501
 - objects, culling, 686
 - parallel prefix sums, 479–492
 - synchronizing, 475–479
 - Concatenating transformations, 80–81
 - Conditional rendering, 541–543
 - Conditions
 - inverting, 544
 - race, 476, 477, 478, 692
 - Configuring
 - atomic counters, 149
 - cube geometry, 136, 253
 - custom culling geometry shaders, 342
 - framebuffers, 390, 398
 - indirect draws, 275
 - Julia sets, 633
 - pipelines (graphics), 226
 - scissor testing, 372
 - shadow matrices, 603
 - tessellation geometry shaders, 347
 - uniforms, 119–120
 - values, subroutine uniforms, 235
 - vertices, attributes, 112
 - Connecting vertices, 289
 - Consuming G-buffers, 617–619
 - Control flow, queries, 545
 - Control points, 33, 91, 94, 306, 319, 329
 - Control shaders (tessellation), 33–35
 - Conventions, coordinates, 41
 - Converting .DDS files, 745–746
 - Coordinates
 - barycentric, 36, 306–307, 311
 - Cartesian, 40, 583
 - clip spaces, 72
 - conventions, 41
 - floating-point textures, 167
 - interpolation, 368
 - normalized device space, 72
 - objects, 71
 - spaces, 70–72
 - textures, 162–164, 209
 - transformations, 65, 72–80
 - views, 71–72
 - windows, 41
 - world, 71
 - world-space, 615
 - Copying
 - arrays, textures, 411
 - buffers, 107–109
 - data, 696
 - between framebuffers, 461–464
 - zero copy, 691–699
 - Cores
 - profile OpenGL, 8–10
 - shaders, 5
 - Counters
 - atomic, 147–152
 - performance, 706
 - C++ prefix sum implementation, 480
 - CPUs (central processing units), 102
 - multi-threading, 662–667
 - optimization, 661–677
 - packet buffers, 668–677
 - performance analysis tools, 699–726
 - queues, 700
 - zero copy, 691–699
 - Cross products, 62–63
 - Cube geometry, 136
 - configuring, 253
 - drawing, 254
 - Cubemaps, 592–597
 - rendering to, 402–403
 - Cubic Bézier curves, 92, 93
 - Cubic Bézier patches, tessellation, 329–333
 - Cubic Bézier splines, 95
 - Cubic Hermite splines, 97
 - Culling, 41–43
 - back-face, 342
 - computer shaders, 685
 - objects, 686
 - Curly braces ({}), 211
 - Curves, 89
 - Hermite, 217

-
- math (for 3D graphics), 91–94
 - transfer, 436
 - Custom culling geometry shaders, 342
 - Customizing resolve operations, 419
 - cw layout qualifiers, 319
 - Data, 99
 - atomic counters, 147–152
 - buffers, 100–117
 - allocating memory, 100–107
 - copying/filling, 107–109
 - feeding vertex shaders from, 109–117
 - chunks, 751–752
 - copying, 696
 - fixed-point, 246
 - G-buffers, unpacking from, 617
 - management, 503
 - eliminating binding, 504–509
 - generating compressed data, 519–525
 - high-quality texture filtering, 527–531
 - packed data formats, 525–527
 - RGTC (Red–Green Texture Compression)
 - compression schemes, 516–519
 - sparsely populated textures, 509–515
 - texture compression, 516–525
 - packed data formats, 247
 - partitioning, 692
 - per patch, 306
 - reading, 707–709
 - shader storage blocks, 140–147
 - tessellation, passing between shaders, 319–322
 - textures, 152–202
 - copying into, 463–464
 - reading back, 464–466
 - threading, generating, 662–667
 - under-sampling, 412
 - uniforms, 117–140
 - Data manipulation functions, built-in, 218–219
 - Data stores, 100, 664
 - allocating, 101
 - mapping, 105
 - Data types, 206–212
 - scalars, 206–207
 - support, 119
 - dds2ktx program, 745–746
 - .DDS files, converting, 745–746
 - Debug contexts, 730–737
 - Debuggers, 705, 717
 - Debugging applications, 729–737
 - Decay, 608
 - DECLARE_MAIN macro, 14
 - Declaring
 - arrays, 211
 - atomic counters, 148
 - interface variables, 31
 - multiple inputs in vertex shaders, 113
 - multiple outputs in fragment shaders, 396
 - shader storage blocks, 140, 141
 - uniforms, 121
 - blocks, 123, 680
 - subroutines, 232
 - vertices, 28, 247
 - Decommitting pages, 510
 - Decompressors, 519. *See also* Compression
 - Decrementing atomic counters, 149
 - Default blocks, uniforms, 117–120
 - Deferred procedure calls. *See* DPCs
 - Deferred shading, 613–624
 - downsides to, 622–624
 - normal mapping, 619–622
 - Degenerate primitives, 24
 - Dependency (blocks), 516
 - Depth
 - buffers, 47, 48, 378–379, 626
 - clamping, enabling, 379–380
 - of field, 488, 490
 - in lighting models, 602
 - testing, 376–380
 - Depth testing, 47
 - Design, 4
 - Desktop Window Manager. *See* DWM
 - Destination factors, 383
 - Detail to images, adding, 586
 - Detecting edges, 426–428
 - Diffuse albedo, 576
 - Diffuse light, 569
 - Directions, adding, 627
 - Disabling
 - interpolation, 366–367
 - rasterizers, 288
 - scissor testing, 371
 - vertex attributes, 113
 - Disassembling packets, 672
 - Discarding
 - geometry in geometry shaders, 341–344
 - rasterizers, 296
 - Displacement mapping, 323
 - tessellation evaluation shaders, 607
 - Distance
 - fields, textures, 647–655
 - focal, 488
 - Division, perspective, 40
 - Domains, patches, 329
 - Do-nothing computer shaders, 468
 - Dot products, 60–61, 584
 - double scalar type, 206
 - Downsides to deferred shading, 622–624
 - DPCs (deferred procedure calls), 702
 - Draining pipelines, 557
 - Drawing
 - asteroids, 274–279
 - commands, 251–280
 - applying instanced arrays, 265–271

-
- Drawing (*continued*)
 - indexed, 251–257
 - indirect draws, 271–280
 - instancing, 257–265
 - cube geometry, 254
 - data written to transform feedback buffers, 553
 - geometry, 258
 - grass, 261–262
 - points, 250
 - stereo windows, 409
 - triangles, 24–26
 - Dual encodings (RGTC), 519
 - Dual-source blending, 385–386
 - DWM (Desktop Window Manager), 701
 - EAC (Ericsson Alpha Compression), 197
 - Early testing, fragments, 380–382
 - Edges, detecting, 426–428
 - Editions, 7
 - Effects, atmospheric, 605–609
 - Elements
 - iterating, 325
 - types, 211
 - Eliminating binding, 504–509
 - EmitVertex() function, 37, 38, 335, 340
 - Enabledisable function, 674
 - Enabling depth clamping, 379–380
 - Encoding ASCII characters, 652
 - Ending pipelines with transform feedback, 288
 - Endpoints, 517
 - EndPrimitive() function, 37, 38, 335, 341
 - Engines, tessellation, 35. *See also* Tessellation
 - Environment maps, 587–597
 - filtering, 598
 - equal_spacing mode, 317
 - Equations. *See also* Math (for 3D graphics)
 - blend, 383, 386–387
 - quadratic, 92
 - Equirectangular environment maps, 590–591
 - Ericsson Alpha Compression. *See* EAC
 - Ericsson Texture Compression. *See* ETC2
 - ETC2 (Ericsson Texture Compression), 197
 - Euler angles, 78–79
 - Evaluation shaders (tessellation), 35–37, 607
 - Evolution of OpenGL, 6–10
 - Examples of compute shaders, 479–501
 - Exclusive prefix sums, 480
 - Executing
 - compute shaders, 469–474
 - hardware, 4
 - packet buffers, 671, 677
 - Exploding models, 344, 345
 - Exponents, sharing, 198–199
 - Exposure coefficients, 435
 - Extensions, 8, 49–54
 - Extinction, 606
 - Faces
 - finding normal, 342
 - pushing, 345
 - Factors, shininess, 570
 - Features, 713, 759–796
 - Feedback
 - buffers, 549
 - transform, 280–298
 - Fences, synchronization, 557–562
 - Fetching
 - blocks, texels, 520
 - vertices, 28
 - Fields
 - distance, textures, 647–655
 - stacking, 209
 - stars, rendering, 450–453
 - Files
 - .DDS, converting, 745–746
 - .KTX, 160–161, 743–745
 - objects, loading, 116–117
 - .SBM, 746–748, 749–757
 - chunk headers, 750–751
 - comment chunks, 755
 - defined chunks, 751–755
 - file headers, 749–750
 - object list chunks, 755–757
 - textures, loading from, 160–164
 - Filling buffers, 107–109
 - Filtering, 412
 - antialiasing, 413–415
 - box filters, 486
 - environment maps, 598
 - high-quality texture, 527–531
 - mipmaps, 171–173
 - textures, 167–169
 - variables, 487
 - Filtering modes, samplers, 164
 - Fixed-function stages, 5
 - Fixed-point data, 246
 - Flags
 - buffers
 - mapping, 106
 - storage, 102
 - GL_DYNAMIC_STORAGE_BIT, 102
 - flags parameter, 101
 - Flat inputs, 366
 - flat qualifier, 367
 - Flexible indirect rendering, 678–683
 - Floating-point framebuffers, 430–444
 - Floating-point numbers, 525
 - Floating-point textures, 167
 - Floats, arrays, 120
 - float scalar type, 206
 - Flocking compute shaders, 492–501
 - Flow control barriers, 476
 - Focal depth, 488
 - Focal distance, 488

-
- Focus, images, 488
 - Fog, 606–609. *See also* Atmospheric effects
 - Fonts
 - bitmaps, 655–659
 - distance fields, 652–654
 - Format layout qualifiers, 186
 - Formatting
 - applications, simple example of, 14–16
 - buffers, 103
 - commands, 662
 - compression, 195
 - framebuffers, 390, 428–448
 - internal formats, 153
 - .KTX (Khronos TeXture), 160–161
 - multi-sample textures, 417
 - packed data formats, 247, 525–527
 - packet buffers, 668–672
 - RGTC (Red–Green Texture Compression), 516–519
 - screenshots, 460–461
 - stereo windows, 408
 - textures, 152–154, 199–202
 - Fractals
 - Julia sets, 696, 697
 - rendering, 698
 - `fractional_even_spacing` mode, 317
 - `fractional_odd_spacing` mode, 317
 - Fractional segments, 317
 - Fragments
 - colors, 48
 - depth testing, 376–380
 - lighting, 619
 - Phong shading, 574
 - quad, 556
 - Fragment shaders, 17, 43–46, 366–369
 - ambient occlusion, 631
 - array textures, 400
 - colors
 - masking, 388–390
 - output, 382–387
 - cubemaps, 596
 - deferred shading, 621
 - distance field rendering, 651
 - equiangular environment maps, 590–591
 - fog, 609
 - Gouraud shading, 572
 - high-frequency output, 422
 - images loads/stores, 188
 - interpolation, 366–369
 - logical operations, 387–388
 - normal mapping, 586
 - off-screen rendering, 390–412
 - per-fragment shininess, 598–599
 - Phong shaders, 575–576
 - pre-fragment tests, 369–382
 - ray tracing in, 634–647
 - shadow mapping, 604
 - skybox rendering, 595
 - spherical environment mapping, 589
 - spinning cubes, 138
 - terrain rendering, 327
 - texture coordinates, 163
 - toon, 612
 - Framebuffers, 704
 - antialiasing. *See* Antialiasing
 - attachments
 - multiple, 395–397
 - rendering with no, 428–430
 - completeness, 403–407
 - configuring, 390
 - copying between, 461–464
 - floating-point, 430–444
 - formatting, 390, 428–448
 - G-buffers. *See* G-buffers
 - integers, 444–446
 - layers, 397
 - operations, 47–48
 - reading from, 458–461
 - sRGB color spaces, 446–448
 - stacks, implementing, 642
 - Frame Profiler, 706
 - Frames, AFR (alternate frame rendering) mode, 719
 - Free-form Bézier patches, 329
 - Front end, 12
 - Front-facing, 41
 - Frustum matrices, 88
 - Functionality of extensions, 53
 - Functions, 759–796. *See also* Methods
 - `barrier()`, 476, 478
 - `blend`, 383–385
 - `built-in`, 213–219
 - `built-in data manipulation`, 218–219
 - `built-in math`, 215–217
 - `callback`, 731
 - `EmitVertex()`, 37, 38, 335, 340
 - `EnableDisable`, 674
 - `EndPrimitive()`, 37, 38, 335, 341
 - `glAttachShader()`, 20, 468
 - `glBeginConditionalRender()`, 541541
 - `glBeginQuery()`, 535, 545, 551
 - `glBeginQueryIndexed()`, 551
 - `glBeginTransformFeedback()`, 287
 - `glBindBuffer()`, 101, 284, 710
 - `glBindBufferRange()`, 284
 - `glBindFramebuffer()`, 391, 393
 - `glBindSampler()`, 165
 - `glBindTexture()`, 152
 - `glBindTransformFeedback()`, 553, 713
 - `glBindVertexArray()`, 713
 - `glBindVertexArrays()`, 21
 - `glBindVertexBuffer()`, 249
 - `glBlendColor()`, 383
 - `glBlendEquation()`, 386

Functions (*continued*)

glBlendEquationSeparate(), 386
glBlendFunc(), 383
glBlendFuncSeparate(), 383
glBlitFramebuffer(), 463
glBufferData(), 122, 141, 709
glBufferStorage(), 101, 107, 696
glBufferSubData(), 102, 128, 666
glCheckFramebufferStatus(), 406
glClear(), 372
glClearBufferfv(), 372
glClearBufferiv(), 374
glClearBufferSubData(), 687
glClearBufferfv(), 541
glClearTexSubImage(), 154
glClientWaitSync(), 559, 560, 692
glColorMask(), 389, 537
glColorMaski(), 389
glCompilerShader(), 220
glCompileShader(), 19, 468, 717
glCopyBufferSubData(), 108, 109
glCopyImageSubData(), 464
glCopyNamedBufferSubData(), 108, 696
glCreateBuffers(), 100
glCreateFramebuffers(), 390
glCreateProgram(), 20
glCreateShader(), 19, 336, 468
glCreateTextures(), 152
glCreateVertexArrays(), 20
glDebugMessageCallback(), 731, 734
glDebugMessageControl(), 734
glDeleteQueries(), 535
glDeleteShader(), 20
glDeleteSync(), 562
glDeleteTextures(), 161
glDepthFunc(), 377
glDepthMask(), 378
glDepthRange(), 41, 361
glDisable(), 378, 674
glDispatchCompute(), 469, 474, 541
glDispatchComputeIndirect(), 469
glDrawArrays(), 22, 24, 25, 113, 137, 251, 257, 344, 541, 666
glDrawArraysIndirect(), 273, 469
glDrawArraysInstanced(), 260, 265
glDrawArraysInstancedBaseInstance(), 469
glDrawArraysInstancedBaseInstanced(), 270
glDrawArraysInstancedBaseVertex(), 678
glDrawBuffer(), 393, 397, 538
glDrawBuffers(), 397
glDrawElements(), 251, 272, 344, 545
glDrawElementsBaseVertex(), 678
glDrawElementsIndirect(), 272, 273
glDrawElementsInstanced(), 260, 265
glDrawTransformFeedback(), 713
glEnable(), 674
glEndConditionalRender(), 541, 541
glEndQuery(), 536, 545, 551
glEndQueryIndexed(), 551
glEndTransformFeedback(), 287
glFenceSync(), 558, 692
glFinish(), 557, 692
glFlush(), 557
glFlushMappedBufferRange(), 666
glFramebufferParameteri(), 429
glFramebufferTexture(), 395, 403, 418, 419
glFramebufferTextureLayer(), 401
glFrontFace(), 42
glGenerateMipMap(), 466
glGenFramebuffers(), 391
glGenQueries(), 534
glGenTransformFeedbacks(), 553
glGetCompressedTexImage(), 741
glGetError(), 406, 534, 733
glGetGraphicsResetStatus(), 739
glGetIntegeri(), 470
glGetIntegerv(), 135, 340
glGetInternalformativ(), 511
glGetProgramBinary(), 236
glGetProgramiv(), 471
glGetQueryObjectiv(), 536, 538, 545
glGetShaderiv(), 221
glGetShaderiv(), 717
glGetTexImage(), 465, 740
glGetTextureHandleARB(), 504
glGetTextureSamplerHandleARB(), 504
glGetTextureStorage2D(), 509
glGetUniformBlockIndex(), 131
glGetUniformLocation(), 118–119
glLinkProgram(), 20, 224, 468, 717
glLogicOp(), 388
glMakeCurrent(), 721
glMakeTextureHandleResidentARB(), 507
glMapBuffer(), 105, 122, 709
glMapBufferRange(), 128, 141, 666, 710
glMapNamedBufferRange(), 691, 692
glMapNamedBufferRange(), 106
glMapNamedBufferStorage(), 691, 692
glMemoryBarrier(), 146, 147, 151
glMinSampleShading(), 423
glMultiDrawArraysIndirect(), 678
glMultiDrawArraysIndirectCountARB(), 684
glMultiDrawElementsIndirect(), 678
glMultiDrawElementsIndirectCountARB(), 684
glNamedBufferStorage(), 101, 103
glNamedFramebufferDrawBuffer(), 393
glNamedFramebufferTexture(), 395
glObjectLabel(), 736
glObjectPtrLabel(), 736
glPatchParameteri(), 33
glPointParameteri(), 453
glPointSize(), 23, 38, 250
glPolygonMode(), 319

- glPopDebugGroup(), 733
- glPrimitiveRestartIndex(), 257
- glPushDebugGroup(), 733
- glQueryCounter(), 547, 548
- glReadBuffer(), 459
- glReadPixels(), 458, 465, 683, 707, 708, 709, 740
- glSampleCoverage(), 420
- glScissor(), 370
- glScissorIndexed(), 370
- glScissorIndexedv(), 370
- glShaderSource(), 19, 468
- glStencilFuncSeparate(), 375, 376
- glStencilMaskSeparate(), 376
- glStencilOpSeparate(), 374, 375
- glTexPageCommitmentARB(), 510, 512
- glTexparameteri(), 601
- glTexStorage2D(), 152, 592
- glTexStorageSubImage2D(), 658
- glTexSubImage2D(), 466, 524, 592, 697
- glTextBuffer(), 295
- glTexturePageCommitmentEXT(), 510, 512
- glTextureParameteri(), 510
- glTextureStorage2DMultisample(), 417
- glTextureStorage3DMultisample(), 417
- glTextureStorageSubImage2D(), 512
- glTextureSubImage2D(), 170
- glTextureView(), 199
- glTransformFeedbackVaryings(), 281
- glUniform(), 469
- glUniform*(), 119
- glUniformMatrix*(), 120
- glUseProgram(), 22, 134, 469
- glVertexArrayAttribFormat(), 111
- glVertexArrayVertexBuffer(), 112
- glVertexAttrib*(), 29, 31
- glVertexAttribDivisor(), 500
- glVertexAttribFormat(), 525
- glVertexAttribPointer(), 244–246, 714, 715
- glVertexAttribDivisor(), 266
- glViewport(), 41, 137, 361
- glViewportArrayv, 370
- glWaitSync(), 559, 560
- glXMakeCurrent(), 721
- init(), 731
- main(), 17, 335, 342, 524
- make_face, 348
- matrixCompMult(), 214
- max, 569
- MemoryBarrier(), 147, 687
- NextPacket, 671
- overloading, 183, 213
- packRGTC, 523
- palettizeTexel, 523
- startup(), 663
- stencil, 373–374
- texelFetch(), 167
- texture(), 167
- textureGatherOffset, 520
- vectors, 213–215
- Gamma correction, 446
- G-buffers, 614
 - components, 618
 - consuming, 617–619
 - generating, 614–617
 - initializing, 616
 - writing to, 616
- Generating
 - compressed data, 519–525
 - data, applying threads to, 662–667
 - distance fields, 648
 - G-buffers, 614–617
 - geometry in geometry shaders, 346–349
 - query objects, 549
 - vertices, 347
- Geometry
 - cubes
 - configuring, 253
 - drawing, 254
 - displacement mapping, 323
 - drawing, 258
 - Phong shading, 573
 - primitive restarts, 255–257
 - rendering, 267
 - uniforms, transforming, 135–140
- Geometry shaders, 37–39, 333–334, 704
 - geometry
 - discarding in, 341–344
 - generating, 346–349
 - modifying in, 344–345
 - layers, rendering with, 399, 411
 - multiple streams of storage, 352–353
 - multiple viewport transformations, 361–364
 - new primitive types, 353–361
 - pass-through, 334–336
 - primitive types, modifying, 349–352
 - quads, rendering, 355–361
 - tessellation, configuring, 347
 - triangles, 348
- Gimbal locks, 79
- GL_DYNAMIC_STORAGE_BIT flag, 102
- GL (graphics library) functions, 6
 - glAttachShader() function, 20, 468
 - glBeginConditionalRender() function, 541541
 - glBeginQuery() function, 535, 545, 551
 - glBeginQueryIndexed() function, 551
 - glBeginTransformFeedback() function, 287
 - glBindBuffer() function, 101, 284, 710
 - glBindBufferRange() function, 284
 - glBindFramebuffer() function, 383, 391
 - glBindSampler() function, 165

GL (graphics library) functions (*continued*)

`glBindTexture()` function, 152
`glBindTransformFeedback()` function, 553, 713
`glBindVertexArray()` function, 713
`glBindVertexArrays()` function, 21
`glBindVertexBuffer()` function, 249
`glBlendColor()` function, 383
`glBlendEquation()` function, 386
`glBlendEquationSeparate()` function, 386
`glBlendFunc()` function, 383
`glBlendFuncSeparate()` function, 383
`glBlitFramebuffer()` function, 463
`glBufferData()` function, 122, 141, 709
`glBufferStorage()` function, 101, 107, 696
`glBufferSubData()` function, 102, 128, 666
`glCheckFramebufferStatus()` function, 406
`glClearBufferfv()` function, 15, 372
`glClearBufferiv()` function, 374
`glClearBufferSubData()` function, 687
`glClearBufferv()` function, 541
`glClear()` function, 372
`glClearTexSubImage()` function, 154
`glClientWaitSync()` function, 559, 560, 692
`glColorMask()` function, 389, 537
`glColorMaski()` function, 389
`glCompilerShader()` function, 220
`glCompileShader()` function, 19, 468, 717
`glCopyBufferSubData()` function, 108, 109
`glCopyImageSubData()` function, 464
`glCopyNamedBufferSubData()` function, 108, 696
`glCreateBuffers()` function, 100
`glCreateFramebuffers()` function, 390
`glCreateProgram()`, 20
`glCreateShader()` function, 19, 336, 468
`glCreateTextures()` function, 152
`glCreateVertexArrays()` function, 20
`glDebugMessageCallback()` function, 731, 734
`glDebugMessageControl()` function, 734
`glDeleteQueries()` function, 535
`glDeleteShader()` function, 20
`glDeleteSync()` function, 562
`glDeleteTextures()` function, 161
`glDepthFunc()` function, 377
`glDepthMask()` function, 378
`glDepthRange()` function, 41, 361
`glDisable()` function, 378, 674
`glDispatchCompute()` function, 469, 474, 541
`glDispatchComputeIndirect()` function, 469
`glDrawArrays()` function, 22, 24, 25, 113, 137, 251, 257, 344, 541, 666
`glDrawArraysIndirect()` function, 273, 469
`glDrawArraysInstancedBaseInstanced()` function, 270
`glDrawArraysInstancedBaseInstance()` function, 469
`glDrawArraysInstancedBaseVertex()` function, 678
`glDrawArraysInstanced()` function, 260, 265
`glDrawBuffer()` function, 393, 397, 538
`glDrawBuffers()` function, 397
`glDrawElementsBaseVertex()` function, 678
`glDrawElements()` function, 251, 272, 344, 545
`glDrawElementsIndirect()` function, 272, 273
`glDrawElementsInstanced()` function, 260, 265
`glDrawTransformFeedback()` function, 713
`glEnable()` function, 674
`glEndConditionalRender()` function, 541541
`glEndQuery()` function, 536, 545, 551
`glEndQueryIndexed()` function, 551
`glEndTransformFeedback()` function, 287
`glFenceSync()` function, 558, 692
`glFinish()` function, 557, 692
`glFlush()` function, 557
`glFlushMappedBufferRange()` function, 666
`glFramebufferParameteri()` function, 429
`glFramebufferTexture()` function, 395, 403, 418, 419
`glFramebufferTextureLayer()` function, 401
`glFrontFace()` function, 42
`glGenerateMipMap()` function, 466
`glGenFramebuffers()` function, 391
`glGenQueries()` function, 534
`glGenTransformFeedbacks()` function, 553
`glGetCompressedTexImage()` function, 741
`glGetError()` function, 406, 534, 733
`glGetGraphicsResetStatus()` function, 739
`glGetIntegeri()` function, 470
`glGetIntegeriv()` function, 135, 340
`glGetInternalformativ()` function, 511
`glGetProgramBinary` function, 236
`glGetProgramiv()` function, 471
`glGetQueryObjectiv()` function, 536, 538, 545
`glGetShaderiv()` function, 221, 717
`glGetTexImage()` function, 465, 740
`glGetTextureHandleARB()` function, 504
`glGetTextureSamplerHandleARB()` function, 504
`glGetTextureStorage2D()` function, 509
`glGetUniformBlockIndex()` function, 131
`glGetUniformLocation()` function, 118–119
`glLinkProgram()` function, 20, 224, 468, 717
`glLogicOp()` function, 388
`glMakeCurrent()` function, 721
`glMakeTextureHandleResidentARB()` function, 507
`glMapBuffer()` function, 105, 122, 709

glMapBufferRange() function, 128, 141, 666, 710
 glMapNamedBufferRange() function, 106, 691, 692
 glMapNamedBufferStorage() function, 691, 692
 glMemoryBarrier() function, 146, 147, 151
 glMinSampleShading() function, 423
 glMultiDrawArraysIndirectCountARB() function, 684
 glMultiDrawArraysIndirect() function, 678
 glMultiDrawElementsIndirectCountARB() function, 684
 glMultiDrawElementsIndirect() function, 678
 glNamedBufferStorage() function, 101, 103
 glNamedFramebufferDrawBuffer() function, 393
 glNamedFramebufferTexture() function, 395
 glObjectLabel() function, 736
 glObjectPtrLabel() function, 736
 glPatchParameteri() function, 33
 gl_PerVertex structure, 320
 glPointParameteri() function, 453
 glPointSize() function, 20, 38, 250
 glPolygonMode() function, 319
 glPopDebugGroup() function, 733
 glPrimitiveRestartIndex() function, 257
 glPushDebugGroup() function, 733
 glQueryCounter() function, 547, 548
 glReadBuffer() function, 459
 glReadPixels() function, 458, 465, 683, 707, 708, 709, 740
 glSampleCoverage() function, 420
 glScissor() function, 370
 glScissorIndexed() function, 370
 glScissorIndexeddv() function, 370
 glShaderSource() function, 19, 468
 glStencilFuncSeparate() function, 375, 376
 glStencilMaskSeparate() function, 376
 glStencilOpSeparate() function, 374, 375
 glTexPageCommitmentARB() function, 510, 512
 glTexparameteri() function, 601
 glTexStorage2D() function, 152, 592
 glTexStorageSubImage2D() function, 658
 glTexSubImage2D() function, 466, 524, 592, 697
 glTextBuffer() function, 295
 glTexturePageCommitmentEXT() function, 510, 512
 glTextureParameteri() function, 510
 glTextureStorage2DMultisample() function, 417
 glTextureStorage3DMultisample() function, 417
 glTextureStorageSubImage2D() function, 512
 glTextureSubImage2D() function, 170
 glTextureView() function, 199
 glTransformFeedbackVaryings() function, 281
 glUniform() function, 469
 glUniform*() function, 119
 glUniformMatrix*() function, 120
 glUseProgram() function, 22, 134, 469
 glVertexArrayAttribFormat() function, 111
 glVertexArrayVertexBuffer() function, 112
 glVertexAttribDivisor() function, 500
 glVertexAttribFormat() function, 525
 glVertexAttrib*() function, 29, 31
 glVertexAttribPointer() function, 244–246, 714, 715
 glVertexAttribDivisor() function, 268
 glVertexAttribPointer() function, 266
 glViewportArrayv function, 370
 glViewport() function, 41, 137, 361
 glWaitSync() function, 559, 560
 glXMakeCurrent() function, 721
 Global illumination, 624
 Global work groups, 470–471, 473
 GLSL (OpenGL Shading Language)
 built-in functions, 213–219
 compilers, 219–224
 data types, 206–212
 overview of, 206–219
 storage qualifiers, 366
 GLuint variables, 100
 Gouraud shading, 571, 572
 GPU PerfStudio, 703–706
 GPUs (graphics processing units), 4, 5, 102
 multiple GPUs, 719–721
 work generation, 683–690
 GPUView, 699–703
 Gradients, 528, 634
 Graphics
 3D. *See* 3D graphics
 acceleration, 8
 pipelines, 3. *See also* Pipelines (graphics)
 programs, 468
 resetting, 737–740
 two-dimensional, 647–659
 Graphics library functions. *See* GL functions
 Graphics processing units. *See* GPUs
 Grass, drawing, 261–262
 Grids, 262
 Groups, debug, 735
 Guard bands, 301–302
 Half-spaces, 40
 Handles, 504
 Hangs, 738
 Hardware, 4
 queues, 700
 timer queries, 546

- Hatching patterns, 517
- Hazards, 151
- HDR (high dynamic range), 431, 432–433, 615
- Heads-up display. *See* HUD
- Height maps. *See* Displacement mapping
- Hermite curves, 217
- Hermite interpolation, 216
- Hermite splines, 97
- High dynamic range. *See* HDR
- Higher-order surfaces, 329
- High-frequency output, 422
- Highlights, specular, 569–573. *See also* Lighting
- High-quality texture filtering, 527–531
- Histograms, 434
- History of OpenGL, 6–10
- Homogeneous vectors, 59
- HUD (heads-up display), 546, 705

- Identify matrices, 73–75
- IEEE standards, 206
- Illumination, global, 624. *See also* lighting
- Images
 - access, synchronizing, 194
 - atomic operations, 188–194
 - blocks, 516
 - columns, 485
 - data format classes, 185
 - depth of field, 488, 490
 - detail to, adding, 586
 - focus, 488
 - mipmaps, 171
 - RED, 518
 - types, 183
 - units, 183, 184
 - variables, 182
 - viewing, 458–466
- Immutable objects, 101
- Implementation, 206, 642
- Inclusive prefix sums, 480
- Indexes
 - calculating, 270
 - data chunks, 752–753
 - drawing commands, 251–257
 - queries, 551–552
 - regions, 517
 - restart, 257
 - uniform blocks, 126
- indices parameter, 272
- Indirect draws, 271–280. *See also* Drawing
- Indirect rendering, 678–683
- Infinite loops, shaders, 738
- In flight, 4
- Inheriting states, 675
- init() function, 731
- Initializing
 - buffers, 103
 - G-buffers, 616
 - textures, 152–154
- in keyword, 30
- Inner loops, Julia sets, 633
- Inner products, 60
- Inputs
 - arrays, 339
 - compute shaders, 471–474
 - flat, 366
 - multiple vertex shaders, 113–116
 - naming, 230
 - smooth, 366
 - vertex shaders, 244–249, 276
- Inscattering, 606
- Inserting
 - barriers into applications, 146–147
 - packets, optimizing, 676
- Instancing, 257–265
 - arrays, applying, 265–271
 - rendering, 269, 270
 - vertex shaders, 267
- Integers
 - framebuffers, 444–446
 - interpolation, 366
 - signed/unsigned, 207
 - types, 183
- Interfaces, 3
 - blocks, 31–33
 - matching, 227–231
 - variables, declaring, 31
- Interleaved attributes, 114, 116
- Internal formats, 153
- Interpolation, 44, 89
 - curves, 91
 - fragment shaders, 366–369
 - Gouraud shading, 571
 - linear, 528, 529
 - smooth, 529
 - splines, 95
- Interrupt service routine. *See* ISR
- Intersections
 - points, 639
 - ray-sphere intersection tests, 638
 - testing, 645
- Intra-member rules, 497
- int scalar type, 206
- Inverting conditions, 544
- Invocations, 206
- IRIS GL, 6
- Isolines, tessellation using, 312–315
- ISR (interrupt service routine), 702
- Items, work, 48, 470
- Iterating
 - elements, 325
 - flocking algorithms, 493
- Jaggies, 422
- Julia sets
 - fractals, 696, 697
 - rendering, 632–634

-
- Keywords
 - in, 30
 - out, 30
 - .KTX files, 160–161, 743–745
 - ktxtool program, 743–745
 - Landscapes
 - distance fields, 655
 - fog, applying, 609
 - Languages
 - built-in functions, 213–219
 - compilers, 219–224
 - data types, 206–212
 - overview of, 206–219
 - Layers, 178
 - abstraction, 4
 - framebuffers, 397
 - geometry shaders, rendering with, 411
 - off-screen rendering, 397–403
 - Layouts
 - column-major, 66
 - column-primary, 66
 - format layout qualifiers, 186
 - qualifiers, 29
 - ccw, 319
 - cw, 319
 - geometry shaders, 334
 - multiple framebuffer attachments, 396
 - uniforms, 122
 - .length() method, 212
 - Length of vectors, 63
 - Levels, generating mipmaps, 173
 - Levels of detail, clamping, 515
 - Libraries, `sb7::vmath`, 135
 - Light bloom, 438–444
 - Lighting, 568–609
 - atmospheric effects, 605–609
 - Blinn-Phong, 577–579
 - calculating, 619, 640
 - casting shadows, 599–605
 - environment mapping, 587–597
 - fragments, 619
 - material properties, 597–599
 - normal mapping, 582–586
 - Phong, 568–577
 - ambient light, 568
 - diffuse light, 569
 - shading, 573–577, 584
 - specular highlights, 569–573
 - rim lighting, 579–582
 - Linear interpolation, 369, 528, 529. *See also* Interpolation
 - Linear texture filtering, 527
 - Lines, 89
 - clipping, 298–305
 - endpoints, 517
 - Linkers, logs, 223–225
 - Linking programs, 225–227
 - Lists, object chunks, 755–757
 - Loading
 - 2D array textures, 178–180
 - objects from files, 116–117
 - textures from files, 160–164
 - Local workgroups, 48, 470–471, 473
 - Locations, uniforms, 118–119
 - Logical operations, 387–388
 - Logs
 - compilers, retrieving, 221
 - linkers, 223–225
 - Lookout matrices, 84–86
 - Loops
 - infinite, shaders, 738
 - inner, Julia sets, 633
 - rendering, 137, 139
 - Macros, `DECLARE_MAIN`, 14
 - Magnification, 168
 - `main()` function, 17, 335, 342, 524
 - `make_face` function, 348
 - Management
 - data, 503
 - eliminating binding, 504–509
 - generating compressed data, 519–525
 - high-quality texture filtering, 527–531
 - packed data formats, 525–527
 - RGTC (Red–Green Texture Compression)
 - compression schemes, 516–519
 - sparsely populated textures, 509–515
 - texture compression, 516–525
 - pipelines (graphics), 533
 - occlusion queries, 535–545
 - pipeline state queries, 555–556
 - queries, 534–556
 - synchronization, 556–562
 - timer queries, 545–549
 - transform feedback queries, 549–555
 - textures, committing, 513
 - Mandelbrot sets, rendering, 632
 - `ManuallyLaidOutBlock` uniform blocks, 125
 - Mapping
 - buffers, 100, 102–103, 104, 699
 - optimizing, 709–713
 - ranges, 106
 - bump, 582
 - cubemaps, 402–403, 592–597
 - data stores, 105
 - displacement, 323
 - environment, 587–597
 - mipmaps, 153. *See also* Mipmaps
 - normal, 582–586
 - persistent maps, 664, 665, 691–692
 - shadows, 600–605
 - texture compression, 715
 - tone, 434–438
 - unmappable resources, 694–699
 - vertex shaders, 248

- Masking
 - colors, 388–390
 - sample masks, 420
- Matching
 - blocks, 32
 - interfaces, 227–231
- Material properties, 597–599, 680
- Math
 - for 3D graphics, 55
 - common vector operators, 60–64
 - curves, 91–94
 - matrices, 64–69
 - overview of, 56–57
 - splines, 94–97
 - transformations, 69–89
 - vectors, 57–60
 - built-in math functions, 215–217
- Matrices, 208–210
 - built-in, 213–215
 - construction of, 66–69
 - frustum, 88
 - identify, 73–75
 - lookout, 84–86
 - math (for 3D graphics), 64–69
 - operators, 66–69
 - orthographic, 89
 - perspective, 88–89
 - rotating, 68, 76–79
 - scaling, 79–80
 - shadows, 602
 - TBN (tangent, bitangent, normal), 583, 619
 - transformation, 72, 117
 - translating, 68, 75–76
 - updating, 137
- MatrixCompMult() function, 214
- max function, 569
- Memory
 - access, 692
 - allocating, 100–107
 - atomic operations, 142–144
 - bandwidth, 195, 614
 - buffers. *See* Buffers
 - optimization, 723–726
 - resident, 506
 - synchronizing, 145–147
- MemoryBarrier() function, 147, 687
- Meshes, transforming, 492
- Methods
 - glClearBufferfv(), 15
 - length(), 212
 - render(), 14, 16
 - run, 14
 - special, 212
 - startup(), 14
- Minification, 168
- Mipmaps, 153, 169–171
 - applying, 174
 - filtering, 171–173
 - levels, generating, 173
 - tails, 512
- Models
 - exploding, 344, 345
 - lighting, 568–609. *See also* Lighting spaces, 71
- Model-view transformations, 83–84, 137
- Modes
 - AFR (alternate frame rendering), 719
 - equal_spacing, 317
 - filtering, samplers, 164
 - fractional_even_spacing, 317
 - fractional_odd_spacing, 317
 - GPU PerfStudio, 704
 - points, tessellation, 315–316
 - polygons, 319
 - subdivision, tessellation, 316–319
 - texture filtering, 527
 - wrapping
 - samplers, 164
 - textures, 174–177
- Modifying
 - geometry in geometry shaders, 344–345
 - patterns, 507
 - primitive types in geometry shaders, 349–352
 - vertex shaders, 30
- Moving uniforms, 118–119
- Multiple framebuffer attachments, 395–397
- Multiple GPUs, 719–721
- Multiple outputs in fragment shaders, declaring, 396
- Multiple streams of storage, 352–353
- Multiple textures, 166–167
- Multiple vertex shader inputs, 113–116
- Multiple viewport transformations, 361–364
- Multi-sample antialiasing, 156, 415–417
- Multi-sample textures, 417–421
- Multi-sampling, 47
- Multi-threading, 662–667, 721–723
- Naming, 100
 - inputs, 230
 - output, 230
 - packed data formats, 526
 - textures, 392
- NaN (not a number), 207
- N-bytes, 123
- Nearest texture filtering, 527
- Negative reflection, 570
- New primitive types, geometry shaders, 353–361
- NextPacket function, 671
- Noise in ambient occlusion, 628
- Non-photo-realistic rendering, 610–613
- noperspective qualifier, 368, 369

-
- Normalization, 58, 246
 - Normalized device spaces, 40, 72
 - Normal mapping, 582–586
 - deferred shading, 619–622
 - texture compression, 715
 - Not a number. *See* NaN
 - Numbers, floating-point, 525
 - NVIDIA GeForce GTX 560 SE graphics cards, 701
 - Nyquist rates, 412
 - Objects
 - buffers, updating, 104
 - clipping, 304
 - coordinates, 71
 - culling, 686
 - depth clamping, 380
 - files, loading, 116–117
 - framebuffers, 390
 - immutable, 101
 - lighting models. *See* Lighting
 - list chunks, 755–757
 - pipelines, 718
 - programs, 17
 - queries, generating, 549
 - samplers, 164
 - separable program, 717
 - shaders, 17
 - shadows. *See* Shadows
 - spaces, 71
 - stacks, 642
 - synchronization, 557–562
 - TBOs (texture buffer objects), 288
 - UBOs (uniform buffer objects), 121
 - VAOs (vertex array objects), 295, 493
 - Occlusion queries, 535–545
 - Off-screen rendering, 390–412
 - framebuffer completeness, 403–407
 - layers, 397–403
 - multiple framebuffer attachments, 395–397
 - in stereo, 407–412
 - Offsets
 - polygons, 604
 - uniform blocks with, 124, 125
 - One-dimensional color lookup tables, 610
 - Opacity, 15
 - OpenGL Shading Language. *See* GLSL
 - OpenMP (Open Multi-Processing), 662–664
 - Open Multi-Processing. *See* OpenMP
 - Operating systems, 5
 - Operations
 - logical, 387–388
 - resolve, customizing, 419
 - stencil, 375
 - Operators, 210
 - common vector, 60–64
 - matrices, 66–69
 - Optimization, 661. *See also* Performance
 - buffers, mapping, 709–713
 - CPUs (central processing units), 661–677
 - GPU work generation, 683–690
 - indirect rendering, 678–683
 - memory, 723–726
 - multi-threading, 662–667
 - overhead, reducing, 677–699
 - packet buffers, 668–677
 - performance analysis tools, 699–726
 - rules for shaders, 576
 - zero copy, 691–699
 - Order, winding, 42
 - Origins of OpenGL, 6–10
 - Orthogonal, 67
 - Orthographic matrices, 89
 - Orthonormal, 67
 - out keyword, 30
 - Outputs
 - colors, 382–387
 - compute shaders, 471–474
 - control points, 319
 - font rendering demos, 659
 - high-frequency, 422
 - naming, 230
 - patches, 36
 - variables, 228
 - vertex shaders, 30, 249–251
 - Overdrawing, 614
 - Overhead, reducing, 677–699
 - Overloading, 15, 183, 213
 - Packed data formats, 247, 525–527
 - Packets
 - buffers, 668–677
 - present, 702
 - specialization, 676–677
 - standard DMA, 702
 - standard queue, 702
 - Packing RGTC blocks, 522
 - PackRGTC function, 523
 - Pages, 509, 510
 - PalettizeTexel function, 523
 - Palettizing RGTC blocks, 522
 - Parallelism, 4
 - Parallel prefix sums, 479–492
 - Parameters
 - bindingindex, 110
 - flags, 101
 - indices, 272
 - points, 453–454
 - primitiveMode, 287
 - readoffset, 109
 - shininess, 570
 - stride, 111, 115
 - uniforms, queries, 127–128
 - writeoffset, 109

-
- Particle systems, 448
 - OpenMP (Open Multi-Processing), 664
 - Partitioning data, 692
 - Passing
 - data
 - between shaders, 319–322
 - into shaders, 117
 - from stage to stage, 30–33
 - to vertex shaders, 28–28
 - primitives, 40
 - Pass-through geometry shaders, 334–336
 - Pass-through vertex shaders, 346
 - Patches, 33, 305, 306
 - cubic Bézier, tessellation, 329–333
 - output, 36
 - Patterns
 - hatching, 517
 - modifying, 507
 - Pausing transform feedback, 286–288
 - Pentium processors, 8
 - Performance, 8, 661
 - ALU (arithmetic and logic unit), 715
 - bubbles, 557
 - counters, 706
 - CPUs (central processing units), 661–677
 - extensions, 50. *See also* Extensions
 - GPU work generation, 683–690
 - indirect rendering, 678–683
 - memory, 723–726
 - multi-threading, 662–667
 - overhead, reducing, 677–699
 - packet buffers, 668–677
 - shaders, compiling, 716–719
 - zero copy, 691–699
 - Performance analysis tools, 699–726
 - applications, tuning for speed, 706–726
 - GPU PerfStudio, 703–706
 - GPUView, 699–703
 - WPT (Windows Performance Toolkit), 699–703
 - Per-fragment shininess, 598–599
 - Per patch data, 306
 - Persistent maps, 103, 664, 665, 691–692.
 - See also* Mapping
 - fractals, rendering, 698
 - Perspective
 - division, 40
 - matrices, 88–89
 - Perspective-correct interpolation, 367–369
 - Phong lighting models, 568–577
 - ambient light, 568
 - diffuse light, 569
 - shading, 573–577, 584
 - specular highlights, 569–573
 - Physical simulation (transform feedback), 288–298
 - Pipelines (graphics), 3, 10–11, 27
 - clipping, 39–40
 - compute shaders, 48–49
 - configuring, 226
 - culling, 41–43
 - draining, 557
 - extensions, 49–54
 - fragment shaders, 43–46
 - framebuffer operations, 47–48
 - geometry shaders, 37–39
 - management, 533
 - overview of, 4–6
 - program objects, 718
 - queries, 534–556
 - occlusion, 535–545
 - pipeline state, 555–556
 - timer, 545–549
 - transform feedback, 549–555
 - rasterization, 43
 - synchronization, 556–562
 - tessellation, 33–37
 - transform feedback, 280–298
 - vertex shaders, 17
 - inputs, 244–249
 - passing data from stage to stage, 30–33
 - passing data to, 28–28
 - viewports, transforming, 40–41
 - Pixels, 10–11, 17
 - framebuffer operations, 47–48
 - interpolation. *See* Interpolation
 - Planes
 - adding, 645
 - depth clamping, 379
 - Points
 - binding, 100
 - assigning, 131
 - transform feedback, 284
 - control, 306. *See also* Control points
 - drawing, 250
 - intersections, 639
 - parameters, 453–454
 - rotating, 456–458
 - sampling, 168, 527
 - shaped, 454–456
 - sizes, 250
 - sprites, 448–458
 - tessellation, 315–316
 - textures, 449–450
 - Polygons, 11
 - modes, 319
 - offsets, 604
 - smoothing, 414
 - Populating sparsely populated textures, 509–515
 - Positioning vertices, 117
 - Post-rasterization processing, 370
 - PowerPC processors, 8

-
- Prefixes, parallel prefix sums, 479–492
 - Pre-fragment tests, 369–382
 - depth testing, 376–380
 - early testing, 380–382
 - scissor testing, 369–372
 - stencil testing, 372–376
 - Pre-optimizing shaders, 719
 - Present packets, 702
 - PrimitiveMode parameter, 287
 - Primitive processing, 305
 - geometry shaders, 333–334
 - changing primitive types, 349–352
 - discarding geometry in, 341–344
 - generating geometry in, 346–349
 - modifying geometry in, 344–345
 - multiple streams of storage, 352–353
 - multiple viewport transformations, 361–364
 - new primitive types, 353–361
 - pass-through, 334–336
 - using in applications, 336–341
 - tessellation, 306–322
 - communication between shader invocations, 322
 - cubic Bézier patches, 329–333
 - passing data between shaders, 319–322
 - primitive modes, 307–316
 - subdivision modes, 316–319
 - terrain rendering, 323–328
 - Primitives, 10–11
 - geometry shaders, 37
 - passing, 40
 - query results, 552–555
 - restarts, geometry, 255–257
 - synchronization, 107
 - tessellation. *See* Tessellation
 - types
 - geometry shaders, modifying, 349–352
 - new in geometry shaders, 353–361
 - winding order of, 318–319
 - Printing interface information, 231
 - Processing
 - .KTX files, 743–745
 - post-rasterization, 370
 - primitives. *See* Primitive processing
 - vertices, 244–251
 - Processors, 8–10
 - Products
 - cross, 62–63
 - dot, 60–61
 - inner, 60
 - vectors, 62
 - Profiles, 9
 - Programs, 13. *See also* Applications; Tools
 - binaries, 235–238, 719
 - bloom, 438–444
 - computer, 468
 - creating, 14–16
 - dds2ktx, 745–746
 - graphics, 468
 - ktxtool, 743–745
 - linking, 225–227
 - objects, 17
 - pipeline objects, 225, 718
 - sb6mtool, 746–748
 - separable objects, 717
 - shaders, 17–24
 - triangles, drawing, 24–26
 - Projection
 - 2D data, 69
 - matrices, updating, 137
 - transformations, 86–88
 - Properties, material, 597–599
 - props arrays, 229
 - Publication dates, 7
 - Pulling (vertex), 28
 - Pythagoras's theorem, 63
 - Quad fragments, 556
 - Quadratic Bézier curves, 92
 - Quads
 - geometry shaders, rendering, 355–361
 - tessellation using, 307–310
 - Qualifiers
 - centroid, applying, 424
 - flat, 367
 - format layout, 186
 - interpolation, 367
 - layouts, 29
 - ccw, 319
 - cw, 319
 - geometry shaders, 334
 - multiple framebuffer attachments, 396
 - noperspective, 368, 369
 - shared storage, 475
 - smooth, 367
 - storage, fragment shaders, 366–369
 - Quaternions, 79, 81–83
 - Queries, 534–556
 - control flow, 545
 - indexes, 551–552
 - objects, generating, 549
 - occlusion, 535–545
 - pipeline state, 555–556
 - results
 - applying, 537–540
 - primitive, 552–555
 - rendering, 540
 - retrieving, 536–537
 - timer, 545–549
 - transform feedback, 549–555
 - uniform parameters, 127–128

-
- Queues
 - CPUs (central processing units), 700
 - hardware, 700
 - software, 700
 - standard queue packets, 702
 - Quintic Bézier curve, 94
 - Race conditions, 476, 477, 478, 692
 - Radians, 217
 - Range-checked reads, 740–742
 - Ranges, mapping buffers, 106
 - Rasterization, 43, 365, 366
 - fragment shaders. *See* Fragment shaders
 - post-rasterization processing, 370
 - Rasterizers, 11
 - disabling, 288
 - discarding, 296
 - Rates, sample rate shading, 421–423
 - RAW (read-after-write) hazard. *See* RAW145
 - Ray-sphere intersection tests, 638
 - Ray tracing in fragment shaders, 634–647
 - Read-after-write. *See* RAW
 - Reading
 - from framebuffers, 458–461
 - range-checked reads, 740–742
 - states, 707–709
 - textures, 156–160, 164–177
 - Read-modify-write cycle, 143
 - readoffset parameter, 109
 - Rectangles
 - pages, 509
 - scissor testing, 369–372
 - summed area tables, 487
 - textures, 155
 - Red-Green Texture Compression. *See* RGTC
 - RED images, 518
 - Reducing overhead, 677–699
 - Redundancy, state setting commands, 672
 - Reflection, 63–64
 - negative, 570
 - vectors, 571
 - Refraction, 63–64
 - ref value, 374
 - Regions
 - hatching patterns, 517
 - pages, 509
 - Rendering, 11, 567
 - AFR (alternate frame rendering) mode, 719
 - alternative rendering methods, 613–647
 - attachments, 392
 - with blending functions, 385
 - colors, distance fields, 654–655
 - conditional, 541–543
 - to cubemaps, 402–403
 - flexible indirect, 678–683
 - fonts, distance fields, 652–654
 - fractals, 698
 - framebuffers with no attachments, 428–430
 - geometry, 267
 - indirect, 678–683
 - instancing, 258, 269, 270
 - Julia sets, 632–634
 - layers with geometry shaders, 411
 - lighting models, 568–609
 - loops, 137, 139
 - Mandlebrot sets, 632
 - multiple viewports, 363
 - non-photo-realistic, 610–613
 - off-screen, 390–412
 - framebuffer completeness, 403–407
 - layers, 397–403
 - multiple framebuffer attachments, 395–397
 - quads using geometry shaders, 355–361
 - query results, 540
 - shadow maps, 605
 - skyboxes, 594
 - spherical environment maps, 587–589
 - star fields, 450–453
 - in stereo, 407–412
 - terrain, 323–328
 - textures, 394, 395
 - two-dimensional graphics, 647–659
 - with user clip distances, 305
 - without tessellation control shaders, 321–322
 - without triangles, 631–647
 - render() method, 14, 16
 - Resetting
 - graphics, 737–740
 - packet buffers, 674
 - Resident memory, 506
 - Resolution, 5
 - Resolve operations, customizing, 419
 - Resources, unmapable, 694–699
 - Results
 - atomic counters, 151
 - queries
 - applying, 537–540
 - primitive, 552–555
 - rendering, 540
 - retrieving, 536–537
 - Retrieving query results, 536–537
 - Return values, framebuffer completeness, 405
 - RGTC (Red-Green Texture Compression), 196, 516–519
 - Rim lighting, 579–582
 - Robustness, 737–742
 - Rotating
 - matrices, 68, 76–79
 - points, 456–458
 - Roughness, applying, 597
 - Rules
 - flocking algorithms, 497
 - shaders, 576
 - run() method, 14

- Sample masks, 420
- Sample rate shading, 421–423
- Samplers
 - antialiasing, 415. *See also* Antialiasing
 - filtering modes, 164
 - types, 157–160
 - uniform blocks, declaring inside, 505, 507
 - variables, 156, 504
 - wrapping modes, 164
- Sampling
 - centroid, 424–428
 - points, 168, 527
- sb6mtool program, 746–748
- sb7::vmath library, 135
- .SBM files, 746–748, 749–757
 - chunk headers, 750–751
 - comment chunks, 755
 - defined chunks, 751–755
 - file headers, 749–750
 - object list chunks, 755–757
- Scalability, 4
- Scalars, 65, 206–207
- Scaling matrices, 79–80
- Schematics, tessellation, 307
- Scintillation (aliasing artifacts), 169
- Scissor testing, 47, 369–372
- Screenshots, formatting, 460–461
- Screen-space ambient occlusion. *See* SSAO
- Screen-space techniques, 624–631
- Security, 737–742
- Segments, fractional, 317
- Separable program objects, 717
- Separate attributes, 114
- Separate programs, 225–227
- Serialization, 144
- SGI (Silicon Graphics Inc.), 6
- Shaders
 - applying, 17–24
 - atomic counters, declaring, 148
 - atomic operations, 143–144
 - barriers, applying, 147
 - compiling, 716–719
 - compute, 48–49. *See also* Compute shaders
 - control (tessellation), 33–35
 - cores, 5
 - evaluation (tessellation), 35–37
 - fragments, 17, 43–46. *See also* Fragment shaders
 - spinning cubes, 138
 - terrain rendering, 327
 - geometry, 37–39. *See also* Geometry shaders
 - infinite loops, 738
 - logs, retrieving compiler, 221
 - objects, 17
 - optimization rules, 576
 - pre-optimizing, 719
 - programs, linking, 225–227
 - rim lighting, 581
 - storage, blocks, 140–147
 - subroutines, 231–235
 - TCSs (tessellation control shaders), 306
 - testing, 381. *See also* Testing
 - textures
 - reading from, 156–160
 - writing in, 182–194
 - updating, 112
 - vertex, passing data to, 28–28
 - vertices, 17
- Shading. *See also* Shadows
 - cell, 610–613
 - deferred, 613–624
 - Gouraud, 571, 572
 - normal mapping, 619–622
 - Phong lighting models, 573–577, 584
 - ray tracing, 636
 - sample rate, 421–423
- Shadows
 - casting, 599–605
 - mapping, 600–605
 - matrices, 602
- Shaped points, 454–456
- shared storage qualifier, 475
- Sharing
 - data, partitioning, 692
 - exponents, 198–199
 - layouts, uniforms, 122
- Shininess, per-fragment, 598–599
- Shininess factors, 570
- Side effects, 473
- Signaled state, 557
- Silicn Graphics Inc. *See* SGI
- Sizes of input arrays to geometry shaders, 339
- Skyboxes, rendering, 594
- Slices, time, 475
- Smoothing polygons, 414
- Smooth inputs, 366
- Smooth interpolation, 529
- smooth qualifier, 367
- SoAs (structure-of-arrays), 115
- Software, 700. *See also* Applications
- Sorting values, 521
- Source factors, 383
- Spaces
 - clip, 72
 - coordinates, 70–72
 - models, 71
 - normalized device, 72
 - objects, 71
- Sparsely populated textures, 509–515
- sparsetexture application, 512–514
- Specialization, packet buffers, 676–677
- Special methods, 212
- Specifying bindings, uniform blocks, 133
- Specular albedo, 576
- Specular highlights, 569–573
- Speed, tuning applications for, 706–726

-
- Spherical environment maps, 587–589
 - Splines, 89, 94–97
 - Sprites (points), 448–458
 - SRGB color spaces, 446–448
 - SSAO (screen-space ambient occlusion), 624
 - Stacking
 - fields, 209
 - implementation, 642
 - Stages, 5
 - data from stage to, passing, 30–33
 - of pipelines, 28
 - Standard DMA packets, 702
 - Standard layouts, 123. *See also* Layouts
 - Standard operators, 210
 - Standard queue packets, 702
 - Standards, IEEE, 206
 - Star fields, rendering, 450–453
 - Starting
 - occlusion queries, 537
 - transform feedback, 286–288
 - startup() function, 14, 663
 - States
 - packet buffers, chaining, 675
 - reading, 707–709
 - Stencil testing, 47, 372–376
 - Stereo, rendering in, 407–412
 - Stopping transform feedback, 286–288
 - Storage, 101. *See also* Data stores
 - allocating, 509, 691
 - atomic counters, 148
 - atomic operations, 143–144
 - buffers, flags, 102
 - multiple streams of, geometry shaders, 352–353
 - qualifiers, fragment shaders, 366–369
 - resident memory, 506
 - shaders, blocks, 140–147
 - textures. *See* Textures
 - world-space coordinates, 615
 - Streams, transform feedbacks, 554
 - stride parameter, 111, 115
 - Stripping tools, 255
 - Structure-of-arrays. *See* SoAs
 - Structures, 210–212
 - acceleration, 646
 - gl_PerVertex, 320
 - packet data, 669
 - VERTEX, 245
 - Subdivision modes, tessellation, 316–319
 - Subroutines
 - shaders, 231–235
 - uniforms
 - configuring values, 235
 - declaring, 232
 - Summed area tables, 485, 487
 - Sums, parallel prefix, 479–492
 - Support
 - data types, 119
 - packed data formats, 527
 - swizzling, 209
 - textures, 510
 - types, 108
 - Surfaces
 - bumpy, 625
 - higher-order, 329
 - SwapBuffers() command, 702
 - Swizzling, 209
 - Synchronizing, 666, 701
 - access
 - to atomic counters, 151–152
 - images, 194
 - memory, 145–147
 - access to buffers, 692–694
 - compute shaders, 475–479
 - objects, 557–562
 - pipelines (graphics), 556–562
 - primitives, 107
 - Systems, updating, 291
 - Tables
 - one-dimensional color lookup, 610
 - summed area, 485, 487
 - Tails, mipmaps, 512
 - Tangent, bitangent, normal. *See* TBN matrix
 - Tangents
 - space normals, 619
 - vectors, 582
 - Targets, 100
 - textures, 154–156
 - views, 200
 - TBN (tangent, bitangent, normal) matrix, 583, 584, 619
 - TBOs (texture buffer objects), 288
 - TCSs (tessellation control shaders), 306, 704
 - Terrain, rendering, 323–328
 - TEs (tessellation evaluation shaders), 306, 704
 - Tessellation, 33–37, 227, 250
 - communication between shader invocations, 322
 - control shaders, 33–35
 - cubic Bézier patches, 329–333
 - data, passing between shaders, 319–322
 - engines, 35
 - evaluation shaders, 35–37, 607
 - geometry shaders, configuring, 347
 - landscapes, applying fog, 609
 - point modes, 315–316
 - primitives
 - modes, 307–316
 - processing, 306–322
 - schematics, 307
 - subdivision modes, 316–319
 - terrain rendering, 323–328

transform feedback queries, 549
triangles, 37
using isolines, 312–315
using quads, 307–310
using triangles, 310–312
Tessellation control shaders. *See* TCSs
Tessellation evaluation shaders. *See* TESs
Testing
 depth, 47
 intersections, 645
 pre-fragment, 369–382
 depth testing, 376–380
 early testing, 380–382
 scissor testing, 369–372
 stencil testing, 372–376
 ray-sphere intersection, 638
 ray-sphere intersection tests, 638
 scissor, 47
 stencil, 47
texelFetch() function, 167
Texels
 blocks, fetching, 520
 as light, 610
 texture filtering, 528
Texture buffer objects. *See* TBOs
texture() function, 167
textureGatherOffset function, 520
Textures, 11, 152–202
 arrays, 177–182, 397
 copying, 411
 viewing, 400
 atlas, 509
 attachments, 392
 bindless, 504, 682
 committing, 513
 compression, 195–199, 516–525, 715
 coordinates, 162–164, 209
 data
 copying into, 463–464
 reading back, 464–466
 distance fields, 647–655
 files, loading from, 160–164
 filtering, 167–169
 floating-point formats, 432
 formatting, 152–154
 framebuffers, configuring, 390
 gradients, 634
 high-quality texture filtering, 527–531
 initializing, 152–154
 interpolation, 368
 mipmaps, 169–171
 multiple, 166–167
 multi-sample, 417–421
 points, 449–450
 reading, 164–177
 rectangles, 155
 rendering, 394, 395
 resident, applying, 508
 shaders
 reading from, 156–160
 writing in, 182–194
 sparsely populated, 509–515
 support, 510
 targets, 154–156
 types, 154–156
 unbinding, 504
 units, 152
 updating, 153
 views, 199–202
 wrapping modes, 174–177
Threading
 data, generating, 662–667
 multi-threading, 662–667, 721–723
Tightly packed arrays, 115
Time, slices, 475
Timer queries, 545–549
Tokens, types, 108
Tone mapping, 434–438
Tools, 743
 dds2ktx program, 745–746
 ktxtool program, 743–745
 performance analysis, 699–726
 GPU PerfStudio, 703–706
 GPUView, 699–703
 tuning applications for speed, 706–726
 WPT (Windows Performance Toolkit), 699–703
 sb6mtool program, 746–748
 stripping, 255
Toon shaders, 611, 612
Transfer curves, 436
Transformation, 69–89
 concatenation, 80–81
 coordinates, 65, 70–72, 72–80
 geometry, uniforms, 135–140
 matrices, 72, 117
 meshes, 492
 model-view, 83–84, 137
 multiple viewport, geometry shaders, 361–364
 projection, 86–88
 transform feedback, 280–298
 ending pipelines with, 288
 physical simulation, 288–298
 viewports, 40–41
Transform feedback queries, 549–555
Translating matrices, 68, 75–76
Triangles, 11
 clipping, 299, 300. *See also* Clipping
 drawing, 24–26
 geometry shaders, 348
 Phong shading, 573
 rendering without, 631–647

-
- Triangles (*continued*)
 - strips, 257
 - tessellation, 37, 310–312
 - Tuning applications for speed, 706–726
 - Two-dimensional graphics, 647–659, 655–659
 - Types
 - data, 206–212
 - packed, 525
 - support, 119
 - elements, 211
 - images, 183
 - integers, 183
 - rendering, 11
 - samplers, 157–160
 - textures, 154–156
 - tokens, 108
 - vertices, attributes, 246
 - UBOs (uniform buffer objects), 121
 - Unbinding textures, 504
 - Under-sampling data, 412
 - Uniform buffer objects. *See* UBOs
 - Uniforms, 117–140
 - blocks, 121–135
 - declaring, 121, 680
 - defaults, 117–120
 - indexes, 126
 - specifying bindings, 133
 - configuring, 119–120
 - geometry, transforming, 135–140
 - moving, 118–119
 - parameters, queries, 127–128
 - samplers, declaring blocks inside, 505, 507
 - subroutines
 - configuring values, 235
 - declaring, 232
 - Unions of packets, 670
 - Units
 - images, 183, 184
 - textures, 152
 - vectors, 58
 - Unmappable resources, 694–699
 - Unmapping buffers, 105. *See also* Mapping
 - Unpacking data from G-buffers, 617
 - Unsigned state, 557
 - unsigned int scalar type, 206
 - Updating
 - buffers, objects, 104
 - depth buffers, 378–379
 - flocking, 499
 - OpenMP (Open Multi-Processing), 664
 - projection matrices, 137
 - shaders, 112
 - stencil buffers, 376
 - systems, 291
 - textures, 153
 - vertices, attributes, 29
 - User-defined clipping, 302–305
 - User-defined framebuffers, 392. *See also* Framebuffers
 - Values
 - primitiveMode parameter, 287
 - ref, 374
 - return, framebuffer completeness, 405
 - sorting, 521
 - VAOs (vertex array objects), 20, 109, 295, 493, 704
 - Variables, 25
 - filtering, 487
 - GLuint, 100
 - images, 182
 - interfaces, declaring, 31
 - output, 228
 - point sizes, 250
 - samplers, 156, 504
 - Varyings, 281–285
 - geometry shaders, 338
 - Vectors, 57–60, 208–210
 - bitangent, 582
 - common operators, 60–64
 - functions, 213–215
 - length of, 63
 - products, 62
 - reflection, 571
 - rim lighting, 580
 - tangent, 582
 - Velocity, buffers, 493
 - Versions, 7, 759–796
 - Vertex array objects. *See* VAOs
 - Vertex shaders
 - array textures, 400
 - attributes, applying, 113
 - buffers, feeding from, 109–117
 - colors, 266
 - cubemaps, 596
 - flocking, 500
 - Gouraud shading, 572
 - inputs, 244–249, 276
 - instancing, 267
 - mapping, 248
 - material indexes, passing through, 681
 - multiple inputs, 113–116
 - normal mapping, 585
 - outputs, 249–251
 - passing data, 28–29, 30–33
 - pass-through, 346
 - Phong shading, 575
 - shadow mapping, 603
 - skybox rendering, 594
 - spherical environment mapping, 588
 - spinning cubes, 138
 - systems, updating, 291
 - texture coordinates, 163
 - toon, 611

VERTEX structure, 245

Vertices, 6, 12

- attributes, 28–29, 110
 - configuring, 112
 - disabling, 113
 - shader storage blocks, 142
 - types, 246
- base vertex, 254–255
- buffers, bindings, 110
- chunks, 753–755
- connections, 289
- declaring, 247
- generating, 347
- positioning, 117
- processing, 244–251
- shaders. *See* Vertex shaders

Viewing

- array textures, 400
- extensions, 51
- images, 458–466

Viewports

- multiple transformation, 361–364
- transformation, 40–41

Views

- big-picture, 11
- coordinates, 71–72
- model-view transformations, 83–84
- space, 620
- textures, 199–202

Virtual framebuffers, 430. *See also* Framebuffers

vmath library, 61

VSync, 701

Waiting, back-to-back, 536

WAR (write-after-read) hazard, 145

WAW (write-after-write) hazard, 145

Weather, 605–609

Whole framebuffer completeness, 404

Winding order, 42

- of primitives, 318–319

Windows

- coordinates, 41
- stereo
 - drawing, 409
 - formatting, 408

Windows Performance Toolkit. *See* WPT

Workgroups, 470–471, 473

- local, 48

Work items, 48, 470

Workstations, 6

World coordinates, 71

World-space coordinates, 615

WPT (Windows Performance Toolkit), 699–703

Wrapping modes

- samplers, 164
- textures, 174–177

Write-after-read. *See* WAR

Write-after-write. *See* WAW

Write combined memory buffers, 699

writeoffset parameter, 109

Writing

- to G-buffers, 616
- textures in shaders, 182–194

Zero copy, 691–699

This page intentionally left blank

PEARSON

InformIT is a brand of Pearson and the online presence for the world's leading technology publishers. It's your source for reliable and qualified content and knowledge, providing access to the leading brands, authors, and contributors from the tech community.

↕ Addison-Wesley **Cisco Press** **IBM Press** Microsoft Press

PEARSON
IT CERTIFICATION

PRENTICE
HALL

QUE

SAMS

vmware PRESS

LearnIT at InformIT

Looking for a book, eBook, or training video on a new technology? Seeking timely and relevant information and tutorials. Looking for expert opinions, advice, and tips? **InformIT has a solution.**

- Learn about new releases and special promotions by subscribing to a wide variety of monthly newsletters. Visit informit.com/newsletters.
- FREE Podcasts from experts at informit.com/podcasts.
- Read the latest author articles and sample chapters at informit.com/articles.
- Access thousands of books and videos in the Safari Books Online digital library. safari.informit.com.
- Get Advice and tips from expert blogs at informit.com/blogs.

Visit informit.com to find out all the ways you can access the hottest technology content.

Are you part of the **IT** crowd?

Connect with Pearson authors and editors via RSS feeds, Facebook, Twitter, YouTube and more! Visit informit.com/socialconnect.



REGISTER



THIS PRODUCT

informit.com/register

Register the Addison-Wesley, Exam Cram, Prentice Hall, Que, and Sams products you own to unlock great benefits.

To begin the registration process, simply go to **informit.com/register** to sign in or create an account.

You will then be prompted to enter the 10- or 13-digit ISBN that appears on the back cover of your product.

Registering your products can unlock the following benefits:

- Access to supplemental content, including bonus chapters, source code, or project files.
- A coupon to be used on your next purchase.

Registration benefits vary by product. Benefits will be listed on your Account page under Registered Products.

About InformIT — THE TRUSTED TECHNOLOGY LEARNING SOURCE


INFORMIT IS HOME TO THE LEADING TECHNOLOGY PUBLISHING IMPRINTS Addison-Wesley Professional, Cisco Press, Exam Cram, IBM Press, Prentice Hall Professional, Que, and Sams. Here you will gain access to quality and trusted content and resources from the authors, creators, innovators, and leaders of technology. Whether you're looking for a book on a new technology, a helpful article, timely newsletters, or access to the Safari Books Online digital library, InformIT has a solution for you.

informIT.com

THE TRUSTED TECHNOLOGY LEARNING SOURCE

Addison-Wesley | Cisco Press | Exam Cram
IBM Press | Que | Prentice Hall | Sams


SAFARI BOOKS ONLINE



Color Plate 1: All possible combinations of blend function




Color Plate 2: Rendering to a stereo display




Color Plate 3: Different views of an HDR image




Color Plate 4: Adaptive tone mapping




Color Plate 5: Bloom filtering: no bloom (left) and bloom (right)




Color Plate 6: Depth of field applied to an image




Color Plate 7: Output of bindless texture example



Color Plate 8: Varying specular parameters of a material



Color Plate 9: Result of rim lighting example



Color Plate 10: Normal mapping in action




Color Plate 11: Depth of field applied in a photograph




Color Plate 12: A selection of spherical environment maps




Color Plate 13: A golden environment-mapped dragon




Color Plate 14: Result of per-pixel gloss example



Color Plate 15: Toon shading output with color ramp



Color Plate 16: Real-time rendering of the Julia set



Color Plate 17: Ray tracing with four bounces