

Aggregating Data Using Group Functions

Objectives

- After completing this lesson, you should be able to do the following:
 - Identify the available group functions
 - Describe the use of group functions
 - Group data by using the `GROUP BY` clause
 - Include or exclude grouped rows by using the `HAVING` clause

What Are Group Functions?

- Group functions operate on sets of rows to give one result per group.

EMPLOYEES

DEPARTMENT_ID	SALARY
90	24000
90	17000
90	17000
60	9000
60	6000
60	4200
50	5800
50	3500
50	3100
50	2600
50	2500
80	10500
80	11000
80	8600
	7000
10	4400

Maximum salary in
EMPLOYEES table


MAX(SALARY)
24000

■ ■ ■

20 rows selected.

Types of Group Functions

- AVG
- COUNT
- MAX
- MIN
- STDDEV
- SUM
- VARIANCE



Group Functions: Syntax

```
SELECT      [column,] group_function(column), ...  
FROM        table  
[WHERE      condition]  
[GROUP BY   column]  
[ORDER BY   column];
```

Using the AVG and SUM Functions

- You can use AVG and SUM for numeric data.

```
SELECT AVG(salary), MAX(salary),  
       MIN(salary), SUM(salary)  
FROM   employees  
WHERE  job_id LIKE '%REP%';
```

AVG(SALARY)	MAX(SALARY)	MIN(SALARY)	SUM(SALARY)
8150	11000	6000	32600

Using the MIN and MAX Functions

- You can use MIN and MAX for numeric, character, and date data types.

```
SELECT MIN(hire_date), MAX(hire_date)  
FROM employees;
```

MIN(HIRE_	MAX(HIRE_
17-JUN-87	29-JAN-00

Using the COUNT Function

- COUNT (*) returns the number of rows in

1

```
SELECT COUNT(*)  
FROM employees  
WHERE department_id = 50;
```

COUNT(*)

5

2

```
SELECT COUNT(commission_pct)  
FROM employees  
WHERE department_id = 80;
```

COUNT(COMMISSION_PCT)

3

ROWS WITH NULL-VALUE VALUES FOR THE EXP.

Using the DISTINCT Keyword

- `COUNT (DISTINCT expr)` returns the number of distinct non-null values of the *expr*.
- To display the number of distinct department values in the `EMPLOYEES` table:

```
SELECT COUNT(DISTINCT department_id)  
FROM employees;
```

COUNT(DISTINCTDEPARTMENT_ID)
7

Group Functions and Null Values

- Group functions ignore null values in the

1

```
SELECT AVG (commission_pct)  
FROM   employees;
```

AVG(COMMISSION_PCT)

.2125

2

```
SELECT AVG (NVL (commission_pct, 0))  
FROM   employees;
```

AVG(NVL(COMMISSION_PCT,0))

.0425

Creating Groups of Data

EMPLOYEES

DEPARTMENT_ID	SALARY
10	4400
20	13000
20	6000
50	5800
50	3500
50	3100
50	2500
50	2600
60	9000
60	6000
60	4200
80	10500
80	8600
80	11000
90	24000
90	17000

4400

9500

3500

6400

10033

Average
salary in
EMPLOYEES
table for each
department

DEPARTMENT_ID	AVG(SALARY)
10	4400
20	9500
50	3500
60	6400
80	10033.3333
90	19333.3333
110	10150
	7000

...

20 rows selected.

Creating Groups of Data:

GROUP BY Clause Syntax

```
SELECT      column, group_function(column)
FROM        table
[WHERE      condition]
[GROUP BY  group_by_expression]
[ORDER BY  column];
```

- You can divide rows in a table into smaller groups by using the GROUP BY clause.

Using the GROUP BY Clause

- All columns in the SELECT list that are not in group functions must be in the GROUP BY clause.

```
SELECT department_id, AVG(salary)
FROM employees
GROUP BY department_id;
```

DEPARTMENT_ID	AVG(SALARY)
10	4400
20	9500
50	3500
60	6400
80	10033.3333
90	19333.3333
110	10150
	7000

8 rows selected.

Using the GROUP BY Clause

- The GROUP BY column does not have to be in the SELECT list.

```
SELECT    AVG(salary)
FROM      employees
GROUP BY  department_id ;
```

AVG(SALARY)	
	4400
	9500
	3500
	6400
	10033.3333
	19333.3333
	10150
	7000

Grouping by More Than One Column

EMPLOYEES

DEPARTMENT_ID	JOB_ID	SALARY
90	AD_PRES	24000
90	AD_VP	17000
90	AD_VP	17000
60	IT_PROG	9000
60	IT_PROG	6000
60	IT_PROG	4200
50	ST_MAN	5800
50	ST_CLERK	3500
50	ST_CLERK	3100
50	ST_CLERK	2600
50	ST_CLERK	2500
80	SA_MAN	10500
80	SA_REP	11000
80	SA_REP	8600
...		
20	MK_REP	6000
110	AC_MGR	12000
110	AC_ACCOUNT	8300

20 rows selected.

Add the salaries in the EMPLOYEES table for each job, grouped by department

DEPARTMENT_ID	JOB_ID	SUM(SALARY)
10	AD_ASST	4400
20	MK_MAN	13000
20	MK_REP	6000
50	ST_CLERK	11700
50	ST_MAN	5800
60	IT_PROG	19200
80	SA_MAN	10500
80	SA_REP	19600
90	AD_PRES	24000
90	AD_VP	34000
110	AC_ACCOUNT	8300
110	AC_MGR	12000
	SA_REP	7000

13 rows selected.

Using the GROUP BY Clause on Multiple Columns

```
SELECT    department_id dept_id, job_id, SUM(salary)
FROM      employees
GROUP BY  department id, job id ;
```

DEPT_ID	JOB_ID	SUM(SALARY)
10	AD_ASST	4400
20	MK_MAN	13000
20	MK_REP	6000
50	ST_CLERK	11700
50	ST_MAN	5800
60	IT_PROG	19200
80	SA_MAN	10500
80	SA_REP	19600
90	AD PRES	24000
90	AD_VP	34000
110	AC_ACCOUNT	8300
110	AC_MGR	12000
	SA_REP	7000

13 rows selected.

Illegal Queries

Using Group Functions

- Any column or expression in the `SELECT` list that is not an aggregate function must be in

the `GROUP BY` clause

```
SELECT department_id, COUNT(last_name)
FROM   employees;
```

```
SELECT department_id, COUNT(last_name)
      *
```

ERROR at line 1:

ORA-00937: not a single-group group function

Column missing in the `GROUP BY` clause

Illegal Queries

Using Group Functions

- You cannot use the `WHERE` clause to restrict groups.
- You use the `HAVING` clause to restrict groups.
- You cannot use group functions in the `WHERE` clause.

```
SELECT    department_id, AVG(salary)
FROM      employees
WHERE     AVG(salary) > 8000
GROUP BY department_id;
```

```
WHERE     AVG(salary) > 8000
```

```
      *
```

```
ERROR at line 3:
```

```
ORA-00934: group function is not allowed here
```

Cannot use the `WHERE` clause to restrict groups

Restricting Group Results

EMPLOYEES

DEPARTMENT_ID	SALARY
90	24000
90	17000
90	17000
60	9000
60	6000
60	4200
50	5800
50	3500
50	3100
50	2600
50	2500
80	10500
80	11000
80	8600

...

20	6000
110	12000
110	8300

20 rows selected.

The maximum salary per department when it is greater than \$10,000

DEPARTMENT_ID	MAX(SALARY)
20	13000
80	11000
90	24000
110	12000

Restricting Group Results with the HAVING Clause

- When you use the HAVING clause, the Oracle server restricts groups as follows:

1. Rows are grouped.
2. The group function is applied.
3. Groups matching the HAVING clause are

displayed.

```
SELECT      column, group_function
FROM        table
[WHERE      condition]
[GROUP BY  group_by_expression]
[HAVING     group_condition]
[ORDER BY  column];
```

Using the HAVING Clause

```
SELECT    department_id, MAX(salary)
FROM      employees
GROUP BY  department_id
HAVING    MAX(salary) > 10000 ;
```

DEPARTMENT_ID	MAX(SALARY)
20	13000
80	11000
90	24000
110	12000

Using the HAVING Clause

```
SELECT  job_id, SUM(salary) PAYROLL
FROM    employees
WHERE   job_id NOT LIKE '%REP%'
GROUP BY job_id
HAVING  SUM(salary) > 13000
ORDER BY SUM(salary);
```

JOB_ID	PAYROLL
IT_PROG	19200
AD_PRES	24000
AD_VP	34000

Nesting Group Functions

- Display the maximum average salary:

```
SELECT  MAX(AVG(salary))  
FROM    employees  
GROUP BY department_id;
```

MAX(AVG(SALARY))	
	19333.3333

Summary

- In this lesson, you should have learned how to:

- Use the group functions COUNT, MAX, MIN, and AVG

- Write queries that use the GROUP BY clause

```
SELECT    column, group_function  
FROM      table  
[WHERE    condition]
```

- Write queries that use the HAVING clause

```
[GROUP BY group_by_expression]  
[HAVING  group_condition]  
[ORDER BY column];
```


Practice 4: Overview

- This practice covers the following topics:
 - Writing queries that use the group functions
 - Grouping by rows to achieve more than one result
 - Restricting groups by using the `HAVING` clause