SUBSTRING:-
INPUT-

```c
#include <stdio.h>

int main()
{
   char str[100];
   int start, n, i;

   printf("Enter a string: ");
   scanf("%s", str);

   printf("Enter starting position: ");
   scanf("%d", &start);

   printf("Enter length: ");
   scanf("%d", &n);

   printf("Substring = ");

   for(i = start; i < start + n && str[i] != '\0'; i++)
   {
      printf("%c", str[i]);
   }

   return 0;
}
```

OUTPUT-

```
Enter a string: HELLO
Enter starting position: 1
Enter length: 3
Substring = ELL
```

PALINDROME:-
INPUT-

```c
#include <stdio.h>
#include <string.h>

int main()
{
   char str[100], rev[100];
   int i, len;

   printf("Enter a string: ");
   scanf("%s", str);

   len = strlen(str);

   for(i = 0; i < len; i++)
   {
      rev[i] = str[len - 1 - i];
   }

   rev[len] = '\0';

   if(strcmp(str, rev) == 0)
      printf("String is Palindrome");
   else
      printf("String is Not Palindrome");
```

```
    return 0;
}
```

OUTPUT-

```
Enter a string: LEVEL
String is Palindrome
```

COMPARE:-

INPUT-

```
#include <stdio.h>
#include <string.h>

int main()
{
    char str1[100], str2[100];

    printf("Enter first string: ");
    scanf("%s", str1);

    printf("Enter second string: ");
    scanf("%s", str2);

    if(strcmp(str1, str2) == 0)
        printf("Strings are Equal");
    else
        printf("Strings are Not Equal");

    return 0;
}
```

OUTPUT-

```
Enter first string: HELLO
Enter second string: HELLO
Strings are Equal
```

COPY:-

INPUT-

```
#include <stdio.h>
#include <string.h>

int main()
{
   char str1[100], str2[100];

   printf("Enter a string: ");
   scanf("%s", str1);

   strcpy(str2, str1);

   printf("Copied String = %s", str2);

   return 0;
}
```

OUTPUT-

```
Enter a string: HELLO
Copied String = HELLO
```

REVERSE:-

INPUT-

```
#include <stdio.h>
#include <string.h>
```

```c
int main()
{
   char str[100], rev[100];
   int i, len;

   printf("Enter a string: ");
   scanf("%s", str);

   len = strlen(str);

   for(i = 0; i < len; i++)
   {
      rev[i] = str[len - 1 - i];
   }

   rev[len] = '\0';

   printf("Reversed String = %s", rev);

   return 0;
}
```

OUTPUT-

```
Enter a string: HELLO
Reversed String = OLLEH
```