

Return-Conservative Distributional Jump Bridges for Financial Disclosure Modeling

Aryan Gupta
aryan.cs.app@gmail.com

Preprint, May 2026

Abstract

Financial disclosure models often let event text directly alter every predicted market-response target, including abnormal return. This is a flexible design, but it can destroy the weaker cross-sectional ranking signal carried by pre-event market state. We propose the Return-Conservative Distributional Jump Bridge (RC-DJB), a neural architecture that first estimates a no-event response distribution and then lets SEC filing text transport volatility, volume, and predictive uncertainty while imposing a hard firewall on the abnormal-return mean. The constraint is falsifiable: if disclosure text contains robust near-term return-ranking signal, blocking its direct return-mean path should hurt; if not, the bridge should improve event-response modeling without overwriting rank information. On a leakage-controlled public-data study with 7,236 SEC 8-K events, 7,236 matched controls, and 2,463 held-out rows from 98 large U.S. firms, RC-DJB obtains abnormal return rank IC 0.0546 with 95% ticker-clustered interval [0.0104, 0.0948]. It is the only tested model that both beats concat fusion on multi-target MSE by a positive paired interval (0.0043, [0.0023, 0.0061]) and has a strictly positive ticker-clustered rank-IC interval. Event bridge interventions increase held-out event-row MSE by 0.0066, 0.0049, and 0.0081 when the bridge is removed, text is zeroed, or text is shuffled. The result does not establish a complete trading system; it supports a sharper modeling claim: disclosure text is useful for response-distribution transport, but directly using it to move the return mean is harmful in this setting.

1 Introduction

Public disclosures are timed interventions in the market information set [Fama, 1970, Beaver, 1968, Patell and Wolfson, 1984]. A filing can change volatility, liquidity, and uncertainty even when its effect on cross-sectional abnormal-return ranking is weak or unstable [Bamber, 1986, Kothari, 2001]. Standard multimodal forecasters typically concatenate price history and text embeddings, then predict all targets with a shared head [Vaswani et al., 2017, Lim et al., 2021, Chen et al., 2025]. This design asks the same text representation to explain risk response, volume response, uncertainty, and return ranking. In financial data, that coupling is a liability: return labels are noisy, text is high dimensional, and small leakage, data snooping, or backtest overfitting can look like alpha [Campbell et al., 1997, Gu et al., 2020, White, 2000, Bailey et al., 2014, López de Prado, 2018].

This paper studies a stricter architectural hypothesis. SEC disclosure text should be allowed to transport the event-response distribution, but it should not directly overwrite the mean abnormal return predicted from the no-event market state. We call the resulting model a Return-Conservative Distributional Jump Bridge (RC-DJB). The model first predicts a no-event Gaussian response distribution from pre-event price, volume, and market-relative features. It then uses disclosure text to generate bounded shifts in volatility-jump mean, volume-jump mean, and predictive log-variance. The abnormal-return mean shift is constrained to zero.

The contributions are:

1. A return-conservative distributional bridge architecture for event-driven financial modeling.
2. A leakage-controlled SEC 8-K experiment with matched no-event controls and public post-filing market outcomes.

3. Evidence that blocking direct text-to-return-mean transport recovers statistically positive rank IC while preserving response-regression gains over fusion baselines.
4. Intervention tests showing that the disclosure bridge contributes to event-row MSE even though return ranking is intentionally anchored to the no-event state.

2 Related Work

Classical event studies estimate abnormal returns around information releases [Fama et al., 1969, Brown and Warner, 1985, MacKinlay, 1997]. Disclosure and earnings-announcement studies document price, volatility, and trading-volume responses after public information releases [Beaver, 1968, Patell and Wolfson, 1984, Bamber, 1986, Boehmer et al., 1991, Kothari and Warner, 2007]. RC-DJB keeps this information boundary but replaces scalar event-window estimation with a neural distributional response model. The abnormal-return construction follows the market-model and factor-model tradition [Sharpe, 1964, Fama and French, 1993, Carhart, 1997, Kothari and Warner, 2007]; this study uses a SPY-adjusted public-data variant rather than CRSP/factor residuals.

The architecture is related to recurrent, state-space, and dynamical-system methods, including LSTMs and gated recurrent units [Hochreiter and Schmidhuber, 1997, Cho et al., 2014], Koopman operators [Koopman, 1931], neural differential equations [Chen et al., 2018], structured state-space sequence models [Gu et al., 2022], and selective state-space models [Gu and Dao, 2023]. It also draws on probabilistic forecasting and time-series foundation model work [Dawid, 1984, Gneiting and Raftery, 2007, Salinas et al., 2020, Lim et al., 2021, Nie et al., 2023, Wu et al., 2023a, Ansari et al., 2024, Wu et al., 2024, Jin et al., 2023]. Marked point processes model event arrivals [Hawkes, 1971, Mei and Eisner, 2017]; here the disclosure time is observed and the task is post-event response prediction.

Financial text contains information relevant to prices and fundamentals [Tetlock, 2007, Tetlock et al., 2008, Kogan et al., 2009, Loughran and McDonald, 2011, Cohen et al., 2020]. Recent financial NLP systems and benchmarks study domain language models, multimodal financial forecasting, SEC filing reasoning, and leakage in financial agents [Jegadeesh and Wu, 2013, Araci, 2019, Wu et al., 2023b, Yang et al., 2023, Chen et al., 2025, Islam et al., 2023, Jiang et al., 2026, Li et al., 2025]. RC-DJB is also adjacent to causal representation and counterfactual outcome models [Rubin, 1974, Rosenbaum and Rubin, 1983, Melnychuk et al., 2022, Feng et al., 2024]. It differs by imposing a target-specific architectural restriction: disclosure text may transport response distribution components, but the abnormal-return mean remains no-event anchored.

3 Method




Figure 1: RC-DJB first estimates a no-event response distribution from market history. Disclosure text generates a bounded bridge for risk/liquidity response and predictive uncertainty, but a return-mean firewall enforces $\Delta\mu_r = 0$.

Inputs and targets. Each sample i has label start date τ_i , a 40-trading-day pre-event tensor $X_i \in \mathbb{R}^{40 \times 8}$, disclosure embedding e_i , metadata $m_i \in \mathbb{R}^6$, and target vector $y_i \in \mathbb{R}^3$. The targets are five-trading-day SPY-adjusted return, realized-volatility jump, and volume jump. The headline variant uses chunk-pooled BGE-small disclosure embeddings, following the dense sentence and passage embedding literature [Reimers and Gurevych, 2019, Karpukhin et al., 2020, Xiao et al., 2023].

Event-study labels. Let $P_{i,t}$, $V_{i,t}$, and $r_{i,t}$ denote adjusted close, volume, and daily close return for firm i , and let r_t^M denote the SPY return. The label window $\mathcal{W}_i = \{\tau_i, \dots, \eta_i\}$ starts on the disclosure date for before-close traded-day filings and on the next traded date otherwise; η_i is the fifth tradable session in the window. The pre-window $\mathcal{P}_i$ is the 20 traded sessions strictly before τ_i . These choices follow the event-study convention that features must precede the public event time while outcomes are measured only after the event window begins [Brown and Warner, 1985, MacKinlay, 1997, Patell and Wolfson, 1984, Boehmer et al., 1991]. Realized-volatility differences are reported as a simple daily-data analogue of the realized-variation literature [Andersen et al., 2003]. The implemented targets are

$$y_{i,r} = \frac{P_{i,\eta_i}}{P_{i,\tau_i}} - 1 - \left(\prod_{t \in \mathcal{W}_i} (1 + r_t^M) - 1 \right), \quad (1)$$

$$y_{i,\sigma} = \text{sd}_{t \in \mathcal{W}_i}(r_{i,t}) - \text{sd}_{t \in \mathcal{P}_i}(r_{i,t}), \quad (2)$$

$$y_{i,V} = \frac{|\mathcal{P}_i|}{|\mathcal{W}_i|} \frac{\sum_{t \in \mathcal{W}_i} V_{i,t}}{\sum_{t \in \mathcal{P}_i} V_{i,t}} - 1. \quad (3)$$

Rows are admissible only when their maximum feature date is strictly before the label start, $\max\{t : t \in X_i\} < \tau_i$.

No-event distribution. A recurrent encoder maps pre-event market history to a latent state [Cho et al., 2014]:

$$h_i = \text{GRU}_\theta(X_i) + W_m m_i. \quad (4)$$

A bounded gate produces the no-event state $\tilde{s}_i$, from which the model predicts a diagonal Gaussian distribution, a standard proper-scoring-rule choice for probabilistic forecasts [Gneiting and Raftery, 2007, Salinas

et al., 2020]:

$$\tilde{s}_i = h_i \odot (1 + 0.1 \tanh(g_\theta(h_i, m_i))), \quad (5)$$

$$[\mu_{0,i}, \ell_{0,i}] = f_\theta(\tilde{s}_i, m_i), \quad (6)$$

where $\ell_{0,i}$ is log-variance.

Distributional bridge. Disclosure text generates a bounded latent state jump and distributional transport:

$$b_i = B_\theta(e_i), \quad (7)$$

$$j_i = \alpha \tanh(u_\theta(b_i)) \odot \sigma(v_\theta(b_i)), \quad (8)$$

$$[\Delta\mu_i, \Delta\ell_i] = T_\theta(\text{LN}(\tilde{s}_i + j_i), b_i, m_i). \quad (9)$$

Here LN denotes layer normalization [Ba et al., 2016]. The central architectural constraint is $\Delta\mu_{i,\text{return}} = 0$. Thus,

$$\mu_{1,i} = \mu_{0,i} + [0, \Delta\mu_{i,\text{volatility}}, \Delta\mu_{i,\text{volume}}], \quad \ell_{1,i} = \text{clip}(\ell_{0,i} + \Delta\ell_i). \quad (10)$$

The model predicts $p_\theta(y_i) = \mathcal{N}(\mu_{1,i}, \text{diag}(\exp(\ell_{1,i})))$.

Objective. For target dimension k , the Gaussian negative log likelihood used for probabilistic training and evaluation is a proper likelihood-based scoring objective [Gneiting and Raftery, 2007]:

$$\mathcal{L}_{NLL} = \frac{1}{2NK} \sum_{i=1}^N \sum_{k=1}^K [\exp(-\ell_{1,ik})(y_{ik} - \mu_{1,ik})^2 + \ell_{1,ik}], \quad K=3, \quad \ell_{1,ik} \in [-7, 3]. \quad (11)$$

The pairwise rank regularizer is computed only over real-disclosure pairs in a minibatch, following pairwise learning-to-rank objectives [Burges et al., 2005, Cao et al., 2007]:

$$\mathcal{L}_{rank} = \frac{1}{|\mathcal{Q}|} \sum_{(i,j) \in \mathcal{Q}} \log \left(1 + \exp \left[-\text{sign}(y_{i,r} - y_{j,r}) \frac{\mu_{1,i,r} - \mu_{1,j,r}}{T} \right] \right), \quad (12)$$

where $\mathcal{Q}$ contains event pairs with unequal abnormal-return labels and $T = 0.02$. The supervised term is the weighted Smooth-L1 loss after optional target standardization [Huber, 1964]:

$$\mathcal{L}_{Huber} = \frac{1}{NK} \sum_{i=1}^N \sum_{k=1}^K w_k \text{SmoothL1}_\beta \left(\frac{\mu_{1,ik} - \bar{y}_k}{s_k}, \frac{y_{ik} - \bar{y}_k}{s_k} \right). \quad (13)$$

For bottleneck models with posterior parameters (μ_i^z, ℓ_i^z) , the KL penalty follows variational and information-bottleneck regularization [Kingma and Welling, 2013, Tishby et al., 2000],

$$\mathcal{L}_{KL} = -\frac{1}{2} \text{mean}_{i,k} (1 + \ell_{ik}^z - (\mu_{ik}^z)^2 - \exp(\ell_{ik}^z)). \quad (14)$$

The control and consistency penalties are

$$\mathcal{L}_{control} = \frac{\sum_i \mathbb{I}\{a_i = 0\} \|\Delta\mu_i\|_2^2}{\sum_i \mathbb{I}\{a_i = 0\}}, \quad (15)$$

$$\mathcal{L}_{consistency} = \frac{1}{K} \sum_{k=1}^K \text{Var}_i(\Delta\mu_{i,k}), \quad (16)$$

where $a_i = 1$ for real disclosures and $a_i = 0$ for matched controls. The full training loss combines target-standardized Huber regression, Gaussian likelihood, control suppression, bottleneck regularization, bridge sparsity, residual consistency, and rank learning:

$$\mathcal{L} = \lambda_y \mathcal{L}_{Huber} + \lambda_n \mathcal{L}_{NLL} + \lambda_c \mathcal{L}_{control} + \lambda_{KL} \mathcal{L}_{KL} + \lambda_s \|z_i\|_1 + \lambda_v \mathcal{L}_{consistency} + \lambda_r \mathcal{L}_{rank}. \quad (17)$$

Here z_i is the stored disclosure-bridge latent used for sparsity diagnostics. The main run uses $w_y = (3.0, 1.0, 0.25)$, $\lambda_n = 0.10$, $\lambda_c = 0.35$, $\lambda_{KL} = 0.01$, $\lambda_s = 0.001$, $\lambda_v = 0.05$, and $\lambda_r = 0.15$.

4 Data and Leakage Controls

The experiment uses public SEC EDGAR APIs [U.S. Securities and Exchange Commission, 2026]. The sample covers 98 usable large U.S. firms, SEC 8-K filings from 2020–2025, and public daily prices. Tickers are mapped to CIKs through the SEC company-tickers file. Filings are read from SEC submissions JSON, including archived submissions, using `acceptanceDateTime` and the primary EDGAR document URL. The parser stores source URL, accession number, accepted timestamp, available timestamp, extracted text, and text hash. Prior filing-text studies motivate using public SEC text as a market-response substrate [Loughran and McDonald, 2011, Jegadeesh and Wu, 2013, Cohen et al., 2020].

Daily prices are downloaded from public price endpoints, with SPY used as the market proxy for abnormal returns. The trading calendar is inferred from observed price rows. Event label windows start on the same observed trading day for filings accepted before 16:00 ET; filings accepted after 16:00 ET or on non-trading days start on the next observed trading day. Features use only prices strictly before the label start date. Labels use future returns only as targets. One deterministic same-ticker no-event control is constructed for each filing, excluding dates within a 10-calendar-day blackout window around known events. The no-lookahead rule and blackout controls are motivated by standard event-study design and known financial backtesting leakage failure modes [MacKinlay, 1997, White, 2000, Hansen, 2005, Bailey et al., 2014, López de Prado, 2018, Li et al., 2025].

Table 1: Main public-data sample.

Artifact	Count
Usable companies	98
SEC 8-K events	7,236
Matched no-event controls	7,236
Feature rows	14,472
Public price rows	159,093
Held-out rows	2,463

5 Experiments

Rows with $\tau_i \leq 2023-12-31$ are training rows, rows from 2024 are validation rows, and later rows are held out. This yields 9,729 training rows, 2,280 validation rows, and 2,463 held-out rows across 98 held-out tickers and 13 held-out label-start months. The headline RC-DJB checkpoint is selected by validation loss. All models use fixed seed 29 and are evaluated once on the held-out split. The chronological split follows time-series evaluation practice, where future observations must not influence model selection or feature construction [Bergmeir and Benítez, 2012, Hyndman and Athanasopoulos, 2021, López de Prado, 2018].

Baselines include no-event dynamics, text-only MLP, concat fusion, Counterfactual Event Bottleneck Transformer (CEBT), Disclosure Operator Transformer (DOT), Event-Jump State Space Model (EJSSM), and an unconstrained Distributional Jump Bridge (DJB). Confidence intervals use percentile bootstrap resampling; ticker-clustered intervals resample tickers with replacement [Efron, 1979, Efron and Tibshirani, 1993, Davison and Hinkley, 1997, Cameron et al., 2008, Cameron and Miller, 2015]. Paired comparisons use row-paired bootstrap resampling. Rank IC is Spearman correlation between predicted and realized abnormal return [Spearman, 1904, Grinold and Kahn, 2000].

Evaluation statistics. For model m , the reported multi-target error is

$$\text{MSE}(m) = \frac{1}{NK} \sum_{i=1}^N \sum_{k=1}^K \left(y_{ik} - \hat{y}_{ik}^{(m)} \right)^2. \quad (18)$$

Rank IC is the Spearman correlation between predicted and realized abnormal return:

$$\text{IC}(m) = \rho_P \left(\text{rank}(\hat{y}_{1:N,r}^{(m)}), \text{rank}(y_{1:N,r}) \right). \quad (19)$$

For a statistic S , bootstrap replicates $S^{*(1)}, \dots, S^{*(B)}$ form percentile intervals

$$\text{CI}_{0.95}(S) = \left[Q_{0.025} \{S^{*(b)}\}_{b=1}^B, Q_{0.975} \{S^{*(b)}\}_{b=1}^B \right], \quad (20)$$

The model-level intervals in Table 2 use $B = 1000$. Ticker-clustered intervals sample tickers with replacement and include all held-out rows for each sampled ticker. Rank IC uses integer ranks of predicted and realized abnormal returns. Paired MSE comparisons against RC-DJB use $B = 2000$ row-paired bootstrap replicates and

$$\Delta_{\text{MSE}}(m) = \frac{1}{N} \sum_{i=1}^N \left[\frac{1}{K} \|y_i - \hat{y}_i^{(m)}\|_2^2 - \frac{1}{K} \|y_i - \hat{y}_i^{RC}\|_2^2 \right], \quad (21)$$

with rows resampled as matched pairs. Paired rank comparisons use the same joined rows but report $\text{IC}(RC) - \text{IC}(m)$.

Probabilistic diagnostics. For nominal level $1 - \alpha$, the diagonal Gaussian predictive interval for target k is

$$I_{ik}(1 - \alpha) = [\mu_{1,ik} - z_{1-\alpha/2} \exp(\ell_{1,ik}/2), \mu_{1,ik} + z_{1-\alpha/2} \exp(\ell_{1,ik}/2)], \quad (22)$$

and empirical coverage is

$$\hat{C}(1 - \alpha) = \frac{1}{NK} \sum_{i=1}^N \sum_{k=1}^K \mathbb{1}\{y_{ik} \in I_{ik}(1 - \alpha)\}. \quad (23)$$

Mean predictive standard deviation is $\frac{1}{NK} \sum_{i,k} \exp(\ell_{1,ik}/2)$. Interval coverage is reported because calibrated predictive uncertainty is distinct from point forecast error [Winkler, 1972, Gneiting and Raftery, 2007, Gneiting et al., 2007, Gneiting and Katzfuss, 2014].

Table 2: Held-out results. MSE is over abnormal return, volatility jump, and volume jump. Intervals are 95% ticker-clustered bootstrap intervals.

Model	MSE	MSE CI	Rank IC	Rank IC CI
No-event	0.0696	[0.0519, 0.0936]	-0.0411	[-0.0840, 0.0016]
Concat fusion	0.0597	[0.0442, 0.0817]	-0.0182	[-0.0597, 0.0267]
CEBT	0.0660	[0.0488, 0.0898]	0.0463	[0.0052, 0.0893]
DOT	0.0596	[0.0449, 0.0804]	-0.0131	[-0.0510, 0.0291]
EJSSM-BGE	0.0547	[0.0395, 0.0764]	0.0099	[-0.0329, 0.0556]
DJB	0.0539	[0.0389, 0.0757]	0.0128	[-0.0290, 0.0547]
RC-DJB	0.0554	[0.0400, 0.0776]	0.0546	[0.0104, 0.0948]

Table 3: Paired comparisons against RC-DJB. Positive MSE values mean RC-DJB has lower MSE. Positive rank values mean RC-DJB has higher rank IC.

Baseline	MSE Diff.	95% CI	Rank IC Diff.	95% CI
No-event	0.01417	[0.01150, 0.01747]	0.0956	[0.0412, 0.1504]
Concat fusion	0.00427	[0.00230, 0.00612]	0.0728	[0.0197, 0.1249]
CEBT	0.01057	[0.00825, 0.01311]	0.0083	[-0.0500, 0.0668]
DOT	0.00418	[0.00180, 0.00638]	0.0677	[0.0186, 0.1180]
EJSSM-BGE	-0.00076	[-0.00163, 0.00005]	0.0447	[-0.0072, 0.0952]

Bridge diagnostics. The response-transport statistic for group $c \in \{0, 1\}$ is

$$T_c = \text{mean}_{i:a_i=c,k} |\Delta\mu_{i,k}|, \quad (24)$$

where $c = 1$ denotes real 8-K rows and $c = 0$ denotes controls. Latent bridge AUC uses the score $s_i = \text{mean}_k |z_{i,k}|$ to classify real disclosures against matched controls, with average ranks used for tied scores [Hanley and McNeil, 1982].

Table 4: RC-DJB diagnostics on the held-out split.

Diagnostic	Value
Gaussian NLL	-2.2864
Observed 80% interval coverage	0.9011
Observed 95% interval coverage	0.9602
Mean predictive standard deviation	0.1302
Mean response transport, real 8-Ks	0.0358
Mean response transport, controls	0.0073
Latent bridge AUC, events vs. controls	0.6038

Intervention definitions. The no-bridge intervention is the implementation’s no-jump forward pass: it sets the bridge state jump, bridge hidden state, mean delta, and log-variance delta to zero, so $\mu_1 = \mu_0$ and $\ell_1 = \ell_0$. The zero-text intervention replaces e_i with the zero vector before the forward pass. The shuffled-text intervention applies one deterministic held-out permutation of disclosure embeddings. For RC-DJB, $\Delta\mu_{\text{return}} = 0$ in every variant, so abnormal-return point predictions and rank IC are invariant to these bridge interventions. These ablations are intervention-style tests of a learned component rather than causal identification of market effects [Rubin, 1974, Imbens and Rubin, 2015].

Table 5: RC-DJB intervention tests. Rank IC is unchanged by bridge interventions because the return-mean firewall fixes the abnormal-return point prediction to the no-event mean.

Variant	All MSE	Event MSE	Event NLL	Rank IC	Bridge AUC
Full RC-DJB	0.0554	0.0843	-2.2115	0.0546	0.6038
No bridge	0.0586	0.0909	-2.1204	0.0546	0.5000
Zero text	0.0578	0.0892	-2.1886	0.0546	0.4843
Shuffled text	0.0597	0.0924	-2.1765	0.0546	0.5057

Table 6: Paired event-row MSE stress tests. Positive values mean full RC-DJB has lower event-row MSE than the intervention.

Intervention	Event MSE increase	95% paired CI
No bridge	0.0066	[0.0043, 0.0093]
Zero text	0.0049	[0.0027, 0.0073]
Shuffled text	0.0081	[0.0051, 0.0117]




Figure 2: RC-DJB occupies a different point on the response/ranking tradeoff: EJSSM and DJB have lower point MSE, while RC-DJB is the only tested low-error model with a strictly positive ticker-clustered rank-IC interval.




Figure 3: Interventions show that the disclosure bridge matters for event-response error. Rank IC does not move under text interventions because the return-mean firewall prevents direct text-to-return overwriting.




Figure 4: Monthly event-rank IC over held-out real 8-K rows. The model-level rank result is not uniform across months, but RC-DJB has a more positive held-out pattern than fusion and unconstrained event-mean transport baselines.

6 Findings

Return-mean conservation recovers rank signal. RC-DJB obtains rank IC 0.0546 with ticker-clustered interval [0.0104, 0.0948]. In contrast, concat fusion, DOT, EJSSM-BGE, and unconstrained DJB all have rank intervals crossing zero. CEBT also has positive rank IC, but its MSE is much worse than RC-DJB.

The bridge improves response modeling without moving return means. RC-DJB improves paired MSE over concat fusion by 0.0043 and over DOT by 0.0042. Removing the bridge raises event-row MSE by 0.0066; zeroing or shuffling text raises event-row MSE by 0.0049 and 0.0081. These changes occur even though abnormal-return predictions are unchanged by construction, which means the bridge is acting through volatility, volume, and uncertainty transport.

There is a real response/ranking tradeoff. EJSSM-BGE and unconstrained DJB achieve lower point MSE than RC-DJB, but their rank IC intervals include zero. RC-DJB is therefore not a universal winner; it is a Pareto-frontier point that prioritizes statistically reliable ranking while keeping response error below fusion baselines. This tradeoff is the main empirical evidence for the return firewall.

The likelihood result is competitive but not decisive. RC-DJB has Gaussian NLL -2.2864, close to EJSSM-BGE's -2.2839. The paired NLL difference against EJSSM-BGE is small and not statistically decisive. The likelihood evidence supports the bridge as competitive; the distinctive result is the combination of positive rank IC and response-error improvement over fusion baselines.

7 Reproducibility

The artifact records configurations, seeds, processed event metadata, text hashes, price rows, feature meta-data, checkpoints, predictions, table CSVs, and figure outputs used for the reported results. Tests cover timestamp gating, after-hours label starts, feature leakage rejection, control construction, deterministic cached tensors, finite model losses, probabilistic loss integration, and evaluation leakage guards. Labels are computed only from future price windows and are never included in model inputs.

8 Limitations

The study has several limitations. The universe is large-cap biased and may contain survivorship effects, ticker-history issues, and 8-K item-mix sensitivity. The price source is public daily data rather than CRSP or intraday trades and quotes. Abnormal returns are SPY-adjusted rather than factor-model residuals [Fama

and French, 1993, Carhart, 1997]. BGE-small is a general-purpose encoder, and filings are represented by chunk mean pooling rather than a trained long-document financial encoder. Rank IC is statistically positive but economically small; transaction costs, capacity, and portfolio construction are outside the scope of this study [Grinold and Kahn, 2000, Novy-Marx and Velikov, 2016, Frazzini et al., 2018, López de Prado, 2018]. The return firewall is an architectural and predictive constraint, not structural causal identification [Rubin, 1974, Imbens and Rubin, 2015].

9 Ethics and Use

This paper studies event representations using public filings and public daily prices. The results do not constitute trading recommendations. The artifact is intended to support leakage auditing, independent reproduction, and falsification of the empirical claims.

10 Conclusion

RC-DJB shows that the route by which disclosure text enters a financial event model matters. Letting text directly move the abnormal-return mean is not necessary for response modeling and appears to harm ranking in this setting. A return-conservative distributional bridge obtains positive held-out rank IC while still improving multi-target event-response MSE over concat fusion and DOT. The evidence supports a more precise architecture principle for disclosure modeling: use text to transport response risk, liquidity, and uncertainty, but keep near-term return ranking anchored to the no-event market state unless stronger evidence justifies crossing that boundary.

References

- Torben G. Andersen, Tim Bollerslev, Francis X. Diebold, and Paul Labys. Modeling and forecasting realized volatility. *Econometrica*, 71(2):579–625, 2003.
- Abdul Fatir Ansari et al. Chronos: Learning the language of time series. *Transactions on Machine Learning Research*, 2024.
- Dogu Araci. Finbert: Financial sentiment analysis with pre-trained language models, 2019.
- Jimmy Lei Ba, Jamie Ryan Kiros, and Geoffrey E. Hinton. Layer normalization, 2016.
- David H. Bailey, Jonathan M. Borwein, Marcos López de Prado, and Qiji Jim Zhu. The probability of backtest overfitting, 2014. SSRN working paper.
- Linda Smith Bamber. The information content of annual earnings releases: A trading volume approach. *Journal of Accounting Research*, 24(1):40–56, 1986.
- William H. Beaver. The information content of annual earnings announcements. *Journal of Accounting Research*, 6:67–92, 1968.
- Christoph Bergmeir and José M. Benítez. On the use of cross-validation for time series predictor evaluation. *Information Sciences*, 191:192–213, 2012.
- Ekkehart Boehmer, Jim Musumeci, and Annette B. Poulsen. Event-study methodology under conditions of event-induced variance. *Journal of Financial Economics*, 30(2):253–272, 1991.
- Stephen J. Brown and Jerold B. Warner. Using daily stock returns: The case of event studies. *Journal of Financial Economics*, 14(1):3–31, 1985.
- Christopher J. C. Burges, Tal Shaked, Erin Renshaw, Ari Lazier, Matt Deeds, Nicole Hamilton, and Greg Hullender. Learning to rank using gradient descent. In *Proceedings of the 22nd International Conference on Machine Learning*, pages 89–96, 2005.
- A. Colin Cameron and Douglas L. Miller. A practitioner’s guide to cluster-robust inference. *Journal of Human Resources*, 50(2):317–372, 2015.
- A. Colin Cameron, Jonah B. Gelbach, and Douglas L. Miller. Bootstrap-based improvements for inference with clustered errors. *The Review of Economics and Statistics*, 90(3):414–427, 2008.
- John Y. Campbell, Andrew W. Lo, and A. Craig MacKinlay. *The Econometrics of Financial Markets*. Princeton University Press, 1997.
- Zhe Cao, Tao Qin, Tie-Yan Liu, Ming-Feng Tsai, and Hang Li. Learning to rank: From pairwise approach to listwise approach. In *Proceedings of the 24th International Conference on Machine Learning*, pages 129–136, 2007.
- Mark M. Carhart. On persistence in mutual fund performance. *The Journal of Finance*, 52(1):57–82, 1997.
- Ricky T. Q. Chen, Yulia Rubanova, Jesse Bettencourt, and David Duvenaud. Neural ordinary differential equations. In *Advances in Neural Information Processing Systems*, volume 31, 2018.
- Rui Chen et al. Camef: Causal-augmented multi-modal event-driven financial forecasting, 2025.

- Kyunghyun Cho, Bart van Merriënboer, Caglar Gulcehre, Dzmitry Bahdanau, Fethi Bougares, Holger Schwenk, and Yoshua Bengio. Learning phrase representations using RNN encoder–decoder for statistical machine translation. In *Proceedings of the 2014 Conference on Empirical Methods in Natural Language Processing*, pages 1724–1734, 2014.
- Lauren Cohen, Christopher Malloy, and Quoc Nguyen. Lazy prices. *The Journal of Finance*, 75(3):1371–1415, 2020.
- Anthony C. Davison and David V. Hinkley. *Bootstrap Methods and Their Application*. Cambridge University Press, 1997.
- A. Philip Dawid. Statistical theory: The prequential approach. *Journal of the Royal Statistical Society. Series A*, 147(2): 278–292, 1984.
- Bradley Efron. Bootstrap methods: Another look at the jackknife. *The Annals of Statistics*, 7(1):1–26, 1979.
- Bradley Efron and Robert J. Tibshirani. *An Introduction to the Bootstrap*. Chapman and Hall/CRC, 1993.
- Eugene F. Fama. Efficient capital markets: A review of theory and empirical work. *The Journal of Finance*, 25(2):383–417, 1970.
- Eugene F. Fama and Kenneth R. French. Common risk factors in the returns on stocks and bonds. *Journal of Financial Economics*, 33(1):3–56, 1993.
- Eugene F. Fama, Lawrence Fisher, Michael C. Jensen, and Richard Roll. The adjustment of stock prices to new information. *International Economic Review*, 10(1):1–21, 1969.
- Qizhang Feng et al. G-transformer: A graph transformer network for counterfactual prediction, 2024.
- Andrea Frazzini, Ronen Israel, and Tobias J. Moskowitz. Trading costs. Available at SSRN 3229719, 2018.
- Tilmann Gneiting and Matthias Katzfuss. Probabilistic forecasting. *Annual Review of Statistics and Its Application*, 1:125–151, 2014.
- Tilmann Gneiting and Adrian E. Raftery. Strictly proper scoring rules, prediction, and estimation. *Journal of the American Statistical Association*, 102(477):359–378, 2007.
- Tilmann Gneiting, Fadoua Balabdaoui, and Adrian E. Raftery. Probabilistic forecasts, calibration and sharpness. *Journal of the Royal Statistical Society: Series B*, 69(2):243–268, 2007.
- Richard C. Grinold and Ronald N. Kahn. *Active Portfolio Management*. McGraw-Hill, 2 edition, 2000.
- Albert Gu and Tri Dao. Mamba: Linear-time sequence modeling with selective state spaces, 2023.
- Albert Gu, Karan Goel, and Christopher Ré. Efficiently modeling long sequences with structured state spaces. In *International Conference on Learning Representations*, 2022.
- Shihao Gu, Bryan Kelly, and Dacheng Xiu. Empirical asset pricing via machine learning. *The Review of Financial Studies*, 33(5):2223–2273, 2020.
- James A. Hanley and Barbara J. McNeil. The meaning and use of the area under a receiver operating characteristic (ROC) curve. *Radiology*, 143(1):29–36, 1982.
- Peter Reinhard Hansen. A test for superior predictive ability. *Journal of Business & Economic Statistics*, 23(4):365–380, 2005.
- Alan G. Hawkes. Spectra of some self-exciting and mutually exciting point processes. *Biometrika*, 58(1):83–90, 1971.
- Sepp Hochreiter and Jürgen Schmidhuber. Long short-term memory. *Neural Computation*, 9(8):1735–1780, 1997.
- Peter J. Huber. Robust estimation of a location parameter. *The Annals of Mathematical Statistics*, 35(1):73–101, 1964.
- Rob J. Hyndman and George Athanasopoulos. *Forecasting: Principles and Practice*. OTexts, 3 edition, 2021.
- Guido W. Imbens and Donald B. Rubin. *Causal Inference for Statistics, Social, and Biomedical Sciences: An Introduction*. Cambridge University Press, 2015.
- Pranab Islam, Anand Kannappan, Douwe Kiela, Rebecca Qian, Nino Scherrer, and Bertie Vidgen. Financebench: A new benchmark for financial question answering, 2023.
- Narasimhan Jegadeesh and Di Wu. Word power: A new approach for content analysis. *Journal of Financial Economics*, 110(3):712–729, 2013.
- Yidong Jiang, Junrong Chen, Eftychia Makri, Jialin Chen, Peiwen Li, Ali Maatouk, Leandros Tassioulas, Eliot Brenner, Bing Xiang, and Rex Ying. Fin-rate: A real-world financial analytics and tracking evaluation benchmark for llms on sec filings, 2026.
- Ming Jin et al. Time-llm: Time series forecasting by reprogramming large language models, 2023.
- Vladimir Karpukhin, Barlas Oguz, Sewon Min, Patrick Lewis, Ledell Wu, Sergey Edunov, Danqi Chen, and Wen-tau Yih. Dense passage retrieval for open-domain question answering. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing*, pages 6769–6781, 2020.
- Diederik P. Kingma and Max Welling. Auto-encoding variational bayes, 2013.
- Shimon Kogan, Dimitry Levin, Bryan R. Routledge, Jacob S. Sagi, and Noah A. Smith. Predicting risk from financial reports with regression. In *Proceedings of Human Language Technologies: The 2009 Annual Conference of the North American Chapter of the Association for Computational Linguistics*, pages 272–280, 2009.
- B. O. Koopman. Hamiltonian systems and transformation in hilbert space. *Proceedings of the National Academy of Sciences*, 17(5):315–318, 1931.
- S. P. Kothari. Capital markets research in accounting. *Journal of Accounting and Economics*, 31(1–3):105–231, 2001.
- S. P. Kothari and Jerold B. Warner. Econometrics of event studies. In B. Espen Eckbo, editor, *Handbook of Corporate Finance: Empirical Corporate Finance*, volume 1, pages 3–36. Elsevier, 2007.
- Yifei Li et al. Profit mirage: How temporal leakage inflates llm agent performance in financial backtesting, 2025.
- Bryan Lim, Sercan Ö. Arik, Nicolas Loeff, and Tomas Pfister. Temporal fusion transformers for interpretable multi-horizon time series forecasting. *International Journal of Forecasting*, 37(4):1748–1764, 2021.
- Marcos López de Prado. *Advances in Financial Machine Learning*. Wiley, 2018.
- Tim Loughran and Bill McDonald. When is a liability not a liability? textual analysis, dictionaries, and 10-ks. *The Journal of Finance*, 66(1):35–65, 2011.

- A. Craig MacKinlay. Event studies in economics and finance. *Journal of Economic Literature*, 35(1):13–39, 1997.
- Hongyuan Mei and Jason Eisner. The neural hawkes process: A neurally self-modulating multivariate point process. In *Advances in Neural Information Processing Systems*, volume 30, 2017.
- Valentyn Melnychuk, Dennis Frauen, and Stefan Feuerriegel. Causal transformer for estimating counterfactual outcomes, 2022.
- Yuqi Nie, Nam H. Nguyen, Phanwadee Sinthong, and Jayant Kalagnanam. A time series is worth 64 words: Long-term forecasting with transformers. In *International Conference on Learning Representations*, 2023.
- Robert Novy-Marx and Mihail Velikov. A taxonomy of anomalies and their trading costs. *The Review of Financial Studies*, 29(1):104–147, 2016.
- James M. Patell and Mark A. Wolfson. The intraday speed of adjustment of stock prices to earnings and dividend announcements. *Journal of Financial Economics*, 13(2):223–252, 1984.
- Nils Reimers and Iryna Gurevych. Sentence-BERT: Sentence embeddings using siamese BERT-networks. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing*, pages 3982–3992, 2019.
- Paul R. Rosenbaum and Donald B. Rubin. The central role of the propensity score in observational studies for causal effects. *Biometrika*, 70(1):41–55, 1983.
- Donald B. Rubin. Estimating causal effects of treatments in randomized and nonrandomized studies. *Journal of Educational Psychology*, 66(5):688–701, 1974.
- David Salinas, Valentin Flunkert, Jan Gasthaus, and Tim Januschowski. DeepAR: Probabilistic forecasting with autoregressive recurrent networks. *International Journal of Forecasting*, 36(3):1181–1191, 2020.
- William F. Sharpe. Capital asset prices: A theory of market equilibrium under conditions of risk. *The Journal of Finance*, 19(3):425–442, 1964.
- Charles Spearman. The proof and measurement of association between two things. *The American Journal of Psychology*, 15(1):72–101, 1904.
- Paul C. Tetlock. Giving content to investor sentiment: The role of media in the stock market. *The Journal of Finance*, 62(3):1139–1168, 2007.
- Paul C. Tetlock, Maytal Saar-Tsechansky, and Sofus Macskassy. More than words: Quantifying language to measure firms’ fundamentals. *The Journal of Finance*, 63(3):1437–1467, 2008.
- Naftali Tishby, Fernando C. Pereira, and William Bialek. The information bottleneck method, 2000.
- U.S. Securities and Exchange Commission. Edgar application programming interfaces. <https://www.sec.gov/search-filings/edgar-application-programming-interfaces>, 2026. Accessed May 3, 2026.
- Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in Neural Information Processing Systems*, volume 30, 2017.
- Halbert White. A reality check for data snooping. *Econometrica*, 68(5):1097–1126, 2000.
- Robert L. Winkler. A decision-theoretic approach to interval estimation. *Journal of the American Statistical Association*, 67(337):187–191, 1972.
- Haixu Wu, Tengge Hu, Yong Liu, Hang Zhou, Jianmin Wang, and Mingsheng Long. TimesNet: Temporal 2d-variation modeling for general time series analysis. In *International Conference on Learning Representations*, 2023a.
- Haixu Wu et al. Moment: A family of open time-series foundation models, 2024.
- Shijie Wu et al. BloombergGPT: A large language model for finance, 2023b.
- Shitao Xiao, Zheng Liu, Peitian Zhang, Niklas Muennighoff, Defu Lian, and Jian-Yun Nie. C-pack: Packed resources for general chinese embeddings, 2023.
- Hongyang Yang, Xiao-Yang Liu, and Christina Dan Wang. FinGPT: Open-source financial large language models, 2023.