



HUGOPHARM

Systems Engineered with Mind and Spirit

Hugopharm Technologies Pvt. Ltd.

Regd Office: 8, Jogani Industrial
Estate, 541 Senapati Bapat
Marg, Dadar (W), Mumbai 400028

Contact : [Tel:91-22-24226882](tel:91-22-24226882) /91-22-
24222815 ;sales@sbpanchal.com

Our Ref. No. HUGO/0601/2025-3

06-01-2025

To,

Contact	Mr. Jilson
Contact Phone	9961423522
E-mail	rnd@bioextract.co.in
Business Address	Bioextract Banglore

Dear Sir,

We are glad to quote you for,

1. *RAPID MIXER GRANULATOR-300LIT-60 to 120KG WET MASS*

Sincerely,

For Hugopharm Technologies Pvt Ltd.,

Hiren Panchal

1. UNIGRANULATOR 300: Rapid Mixer Granulator

Sr. No	Item	Description
1	Capacity	Suitable for a batch size upto 60 to 120Kg wet mass with bulk density of 0.6gm/cc.
2	General Description	<i>Operations – Dry / Wet mixing, Lubrication / Granulation of powder.</i> Mixing Bowl and Cover: S.S. 316 bowl design in three sections i.e. Flat bottom cylindrical mid portion and conical top portion for efficient mixing operation & provided with counter balanced lid. Lid provided with vents, view ports & charging openings. Thickness of Shell is 6mm, Dish is 8mm and Cone is 4mm.
3	Main Impeller & Drive:	The main impeller consists of 30HP 1500RPM TEFC motor, coupled through a belt drive to a worm reduction gearbox (MAKE RADICON: RATIO 10:1) with chain coupling. The impeller is designed to provide mixing at the bottom and at the center of the bowl and is driven through a specially designed bearing housing that facilities inside wash facility for quick change over and also prevents leakage of powder from bottom entry and leads to longer life of gear box. Thickness of Shell is 6mm, Dish is 8mm and Cone is 4mm.
4	Chopper	The chopper drive consists of 5HP , 3000 RPM TEFC motor. The motor shaft is of SS and the chopper has specially designed 4 blade SS impeller. The shaft is integral with the motor. The assembly mounted horizontally into the bowl.
5	Discharge Port	The discharge port is mounted horizon tally into the bowl with vertical downward opening. The opening is operated by pneumatic cylinder and discharge can be regulated for required opening.
6	Mounting	A sturdy M.S. square section welded structure is designed to mount the mixing bowl and operating panel. All M.S. sections are duly clad with S.S. 304 and are polished. The machine base frame has removable covers for gaining access to gearbox.
8	Main Panel	Main panel consists of all prewired connections and it has only to be connected to the electric supply. The circuit consists of MCCB, relays and contactor in series. Ample overload protection is provided by the MCCB and the relay. Wires coming out of the connections are numbered for easy recognition.
9	Safety Features	a. Locking arrangement for motor to eliminate accidentally starting with open lid. b. Enclosed moving parts.
10	Pneumatic System	a) The pneumatic systems require air pressure 3 to 5 Kg/sq.cm. It is used for operating the discharge valve (opening & closing, also détente). b) Air purging of chopper drive and main impeller drive to prevent cross contamination. The system consists of an air filter pressure gauge air regulator a 2-way solenoid valve (for discharge valve) and other pipes ferules & pneumatic fittings.

11	Control Panel	The control system be of MITSUBISHI JAPAN Make having 10" GT Series Color Touch screen User Interface. The control system shall have the following features: 1. ON/OFF Button and Speed control for main impeller 2. ON/OFF Button and Speed control for chopper motor. 3. Timers for main impeller and chopper motor. 4. Discharge Open/Close 5. Selection between AUTO and Manual Mode
----	----------------------	--

PRICE: UNIGRANULATOR 300: RAPID MIXER GRANULATOR

Sr. No	Price	Description
1.	Rs. 45,00,000/-	For 300 liters capacity Rapid Mixer Granulator as described above including the following: Including Variable Frequency Drive for Impeller and Chopper Mitsubishi PLC and Touchscreen
2.	Rs. 3,75,000/-	For Binder Spraying System comprising of Spray Distributor, Spray Pump and Trolley for Spray Pump. This shall be suitable for pumping non viscous solutions. (Water, PVP or HPMC based systems). Spray Distributor system shall be controlled through the PLC. Note: Starch Paste cannot be pumped using this system if very viscous.
3.	Rs. 3,50,000/-	For WIP System shall consist of the following: 1. Self Rotating WIP Nozzle of JetSpray/ Spraytech make. 2. The WIP Inlet Valve shall be provided on the Body of RMG 3. WIP Drain Valve (Manually Operated) shall be provided. 4. S.S./ Braided Hose high pressure type shall be supplied with 3 meter length on the inlet side 5. Plastic Braided Hose of 5 meter length shall be supplied for drain. 6. WIP Cycle logic shall be incorporated in the PLC logic
4.	Rs. 2,50,000/-	For Impeller Lifting Arrangement using Electrical Motor Driven Hoist Mechanism. It shall be coupled to the PLC for safety interlock. The wire rope shall be of S.S. 304.
5.	Rs. 6,00,000/-	1. Lifting with hydraulic system suitable for lifting 200lit IBC to load to RMG 2. 2 HP, 1440 RPM Non FLP Motor and Drive mounted on service Floor 3. 360 Degree Swinging facility shall be manual 4. Power pack shall be mounted on the service floor. And control panel S.S. mounted on the pillar. 5. Capacity – To lift maximum gross 400kg weight 6. Safety with pilot chuck valves and non return valves 7. Power pack with filter breather, reservoir for oil, level indicator, pressure relief valve, and flow control valve, double acting solenoid valves 8. Flexible hydraulic hose – 2 Nos
6.	Rs. 1,50,000/-	For Installation & Commissioning
7.	Rs. 55,000/-	For Validation Documents Comprising of DQ/IQ and OQ

Terms and Conditions:

Prices : Prices offered are net-ex-works Mumbai exclusive of Packing, Carting, Crating, Forwarding, Freight and any other incidental charges will be extra to your account.

Taxes : GST 18%

Packing : 2.5%

Excise : NIL

Inspection : Final Inspection prior to dispatch will have to be carried out jointly by us and your representative at our Mumbai works only. You will be intimated as soon as the machines are ready for dispatch.

Transport & Insurance : At Actual in clients Scope

Delivery : Within 16-20 Weeks.

Payment : 1. 40% Advance on confirmation of order.
2. 60% Balance against proforma invoice through after FAT

Validity : This offer is valid for 30 days.

Warranty : We undertake to make good by replacement or repair, defects arising out of faulty design, materials or workmanship within 12 months of the date of dispatch, purely on ex-works basis i.e., the defective part will be returned by the buyer to our works and replacement taken by the buyer from our works. Bought-out components are guaranteed by us only to the extent of guarantees given to us by our suppliers. Electrical components, such as heaters, motors, contactors etc. rubber components and instruments such as pressure gauges, thermometers, etc. and other such consumables, etc. are however not covered under this Warranty. Warranty stands void if spare parts other than OEM are used.

Jurisdiction : Any dispute arising out of this quotation is subject to the JURISDICTION OF MUMBAI COURT ONLY. All dimensions are approximate.

We reserve the right of any technical deviations or modifications in design of all our products due to changes in suppliers situation.

Thanking you and awaiting for your favorable reply.

Yours truly,
For HUGOPHARM TECHNOLOGIES PVT LTD.

Hiren Panchal
8, Jogani Industrial Estate,
541, Senapati Bapat Marg,
Dadar West, Mumbai 400028
India
Tel: 022-24226882 / 022-30506882/ 30506884