



HUGOPHARM

Systems Engineered with Mind and Spirit

Hugopharm Technologies Pvt. Ltd.

Regd Office: 8, Jogani Industrial Estate, 541 Senapati Bapat Marg, Dadar (W), Mumbai 400028

Contact : Tel: 91-22-24226882 / 91-22-24222815 ; sales@sbpanchal.com

Our Ref No: HUGO/2301/2025-1

23-01-25

To,

Contact	Dr. Tarak Mehta
Business Address	Aculife Healthcare pvt. Ltd. Ahmedabad, Gujarat
Business Phone	+91 9986553811
E-mail	tarakmehta@aculife.co.in

We are glad to quote for the following R&D formulation line of equipment manufactured by us.

1. **UNIFLUID NANO- RAPID FLUID BED DRYER**
2. **UNIFLUID 1.1- Fluid Bed Coater Granulator (300gm-1000gm)**
3. **UNIEXTRUDE-USSE60-SINGLE SCREW EXTRUDER**
4. **UNISPHERE-USPH150- SPHERONIZER**

Sincerely,

For S.B. Panchal & Company,

Hiren Panchal

Tel: 022-24226882 / 022-24222815

1. UNIFLUID NANO - FLUID BED DRYER (200gm-1000gm)

Sr. No	Item	Description
1.	General Construction	The machine body shall be fabricated from S.S. 304 quality material.
2.	Product Container cum Retarding Chamber	This chamber shall be fabricated from glass. It shall have a capacity of 1 kg.
3.	Air Circulation	The required draught shall be provided with totally enclosed fan cooled electric motor driven centrifugal impeller. The speed of the blower shall be controlled from front panel.
4.	Heating	The air shall be heated with coiled tube air heaters. The heating capacity shall be 2 K.W.
5.	Control	The process control switch board shall comprise of: Process timer, PID Temp. Controller, Air Flow Control Damper and Pilot Lamps.

- All S.S. parts are buffed to mirror finish.

PRICE : UNIFLUID NANO :- LAB MODEL FLUID BED DRYER.

Sr. No	Price	Description
1.	Rs.6,00,000/-	For "Table Top Model 200-1000 gm capacity electrically heated model Fluid Bed Dryer, having all contact parts made from glass. (COMPLETE 1 SET OF UNIFLUID NANO- Rapid Fluid Bed Dryer which includes Glass bowl and a bag)
2.	Rs. 25,000/- per day per Engineer	For Installation & Commissioning at your premises. Client shall provide To and Fro Travel Charges, local lodging, boarding and conveyance.
3.	Rs. 20,000/-	For set of validation documents comprising of DQ, IQ & OQ

OPTIONS FOR EXTRA ACCESSORIES

1.	Rs. 1,25,000/-	For additional change part for product container made from glass for handling products from 50gm to 200gm.
2.	Rs. 1,25,000/-	For additional product container made from S.S. 316 containing glass view port.
3.	Rs. 25,000/-	For Product Temperature Sensor (In S.S. bowl) with indication on the panel. The Product Temperature sensor shall be made from S.S. 316 and shall have quick release connector.
4.	Rs. 1,500 /-	For extra air discharge bags made from cotton cloth. (6lit bowl)
5.	Rs. 2,750/-	For extra air discharge bag made from polyester material. (6lit bowl)
6.	Rs. 5,500/-	For extra air discharge bag made from epitropic polyester material. (6lit bowl)
7.	Rs. 550 /-	For extra air discharge bags made from cotton cloth. (300ml bowl)
8.	Rs. 1,250/-	For extra air discharge bag made from polyester material. (300ml bowl)
9.	Rs. 2,500/-	For extra air discharge bag made from epitropic polyester material. (300ml bowl.)
10.	Rs. 8,500/-	For Surge Suppressor for Protection from any Electrical Power Surge.

UNIFLUID NANO WITH VARIOUS OPTIONS

UNIFLUID NANO with glass bowl



UNIFLUID NANO with interchangeable bowl



UNIFLUID NANO with S.S 316 bowl



UNIFLUID NANO with Product Temp Sensor

2. UNIFLUID1.1- FLUID BED PARTICLE COATER GRANULATOR

Sn.	Item	Description
1.	<u>General Construction</u>	a. All the contact parts shall be made from S.S. 316 quality material and non-contact parts shall be made from S.S. 304 quality material. b. Product Container shall be lifted and sealed against expansion chamber with help of pneumatic cylinders. Or sealing shall be done with help of pneumatically inflatable gaskets. c. Strategically mounted observation windows for viewing coating process.
2	<u>Product Container</u> <u>Wurster Coating</u>	a. Product container shall be made of Stainless Steel AISI 316, for WURSTER coating applications. b. It shall have capacity of 2 liters for pellet coating. c. It shall have an oblong shape observation window duly fitted with toughened observation glass. It shall be mounted on a trolley fixed with nylon castors for movement. d. Height of the Wurster Column shall be adjusted manually against the graduated scale for one Wurster fixed inside e. Product Container shall have temperature sensing port and sampling port for extracting small quantities of coated substrate during operation. f. Product Container shall be mirror polished. g. Air atomizing spray nozzle will be of 1mm size. h. The distribution plate & bottom mesh shall be made from S.S. 316. i. The machine shall be supplied with 4Nos of silicon molded mesh of 60#, 100#, 250# and 24x110# j. The machine shall also be supplied with 4 Nos of Wurster plates, A, B, C and D.

3.	<u>Product Container</u> <u>Top Spray & Drying</u>	a. It shall be made from S.S. 316 for Top-Spray Granulation / Drying applications b. It shall have capacity of 4 liters for Top Spray Granulation. (Minimum 300gm-Maximum 1000gm) c. It shall have oblong observation window at the front fitted with toughened observation glass. d. Spray nozzle of atomizing air shall be of 1 mm size. There shall be 2 ports for adjusting nozzle height. e. Product Container shall have temperature sensing port and sampling port for extracting small quantities of coated substrate during operation. f. Product Container shall be mirror polished. g. The machine shall be supplied with 24x110# and 50 x 250#. h. Blind Ports shall be provided to operate the machine in drying mode.
4	<u>Inlet Air Filtration</u>	a. Air Handling Unit shall be made from S.S. 304. Air Handling Unit shall consists of:- b. 5-micron Pre-Filter. All gaskets used will be in Silicon Rubber. c. Heating coil section 4.5 K.W. electric heaters. The heater box shall be duly insulated. d. Dehumidifier and Humidifier System shall be supplied at an extra cost if required.
5	<u>Spraying System</u>	a. For Top spray nozzles shall be of 1 mm. (0.8mm Nozzles are available as an option). b. Electrically operated peristaltic pump shall be provided for supply of fluid dosing to media nozzle via suitable silicon tubing. c. Pump shall have 1-3000 ml./min flow rate.
6	<u>Filter Chamber</u>	a. There shall be dual bag filtration system. The partition type filtration system shall be designed for smooth uninterrupted coating process. b. Satin cotton bag shall be provided for filtration during granulation and drying. There shall be dual partition system of filter bag c. Epitropic bag shall be provided also for static charge intensive product coating. d. The filter bags shall be cleaned with automatic pneumatic shaking logic in PLC.

7	<u>Exhaust Blower</u>	a. Exhaust Blower shall be driven by inverter based 1 H.P. non-flameproof blower for drawing air through coater and enabling fluidization of particles. b. Required draught of air shall be produced by aluminum impeller housed in S.S. casing. c. Exhaust blower shall be fitted with inverter drive to control the fluidization air.
8	<u>Safety Features</u>	a. Machine shall have Earth Monitoring Device. Proper earthing shall be done for following parts through measurement probes (3 nos.): i. Filter Chamber cum Expansion Chamber ii. Product Chamber. b. Peristaltic Pump shall not start in event of inadequate pressure (less than 3 Kgs) in nozzle line. It shall On the LED for Pump. c. Heaters interlocked with Blower.
9	<u>Automation & Control</u>	Manual Control Panel shall be provided with along with the machine. The panel shall have provision to control the following: 1. Control and Indicate Blower Speed in % 2. Control & Indicate Inlet Air Temperature 3. Indicate Exhaust Air Temperature 4. Indicate Product Temperature 5. Control & Indicate Spray Pump RPM 6. Control & Indicate on Manual Gauge Spray Atomization Pressure

PRICE: UNIFLUID 1.1 LABORATORY MODEL FLUID BED PROCESSING SYSTEM

<i>Sn.</i>	<i>Price</i>	<i>Item</i>
1.	Rs. 28,50,000/-	Fluid Bed Processing System with following: 1. Top spray Bowl. 2. Bottom spray Bowl. 3. Top Spray and Bottom Spray Nozzles. 4. Peristaltic pump. 5. Weighing Scale integrated with PLC 6. Fully automatic control system comprising of Mitsubishi PLC and 10.1" Mitsubishi Touchscreen, 7. EPSON Printer for Datalogging. 8. Four Plates for Wurster Coating A, B, C & D 9. Four Silicon Molded Meshes for Bottom Spray 60#, 80#,100# & 200# 10. Two Different Meshes for Top Spray 24x110# and 50x250# 11. Three different filter bags, PC Satin, Epitropic and Bonnet Bag
2.	Rs. 55,000/-	For Installation and Commissioning. 1. Level floor. 2. Foundation and necessary masonry work if required. 3. Shifting of equipment at site. 4. Electrical wiring upto the equipment as per our instructions. 5. Steam connection along with necessary steam fittings such as steam trap, strainer etc. and steam controlling device. 6. Necessary unskilled help at your cost. To and Fro Travel Charges from site, local lodging, boarding and conveyance to be in clients scope of supply.
3.	Rs. 25,000/-	For set of validation documents comprising of DQ/IQ/OQ

UNIFLUID1.1-FLUID BED PARTICLE COATER GRANULATOR



3. UNIEXTRUDER – SINGLE SCREW EXTRUDER

Sn.	Item	Description
1.	System Description	USSE60– UNIEXTRUDER SINGLE SCREW EXTRUDER for processing extrudates. This method of extrusion has single screw transferring the material to the pressing cam, which in turn press the material on the required size of perforated mesh. Single screw CONICAL discharge design extruder.
2.	Capacity	USSE 60 Maximum processing capacity: 1-5 kg/hr. Note: Output depends upon the Bulk density and material specific properties.
3.	Material Of Construction	All the contact parts shall be made in S.S. 316 quality material. All non-contact parts shall be made from S.S. 304 quality material except bought out materials like motors and gear box.
4.	Extruder	Extruder assembly consists of a conveying screw & pressing flute. The assembly is closed by quick remove tri-clover clamps for ease in operation. Standard conical mesh with 1mm diameter die plate is to be provided along with machine.
5.	Feeding Assembly	Feed hopper shall be mounted above the extrusion assembly, the function of this hopper is to feed the transfer screws. The feeding hopper shall be made from S.S 316 quality material.
6.	Gear Box And Motor Assembly	A suitable gear box (Italian Make or equivalent make) consisting of a pair of Spur Gear & Worm gears shall be used to transmit power. A variable speed drive of ABB OR EQUIVALENT MAKE shall be used to regulate the speed of the screw from minimum to maximum. 1/2 HP TEFC, 1440 RPM, IP-55 flange mounted electric motor shall be provided to drive the gear box assembly.
7.	Controls	It shall be stand alone type. It shall have: - 1. ON/OFF Push button for Motor with MCB 2. Speed Controller for screw. 3. R.P.M. display (digital).

PRICE: UNIEXTRUDE- USSE60 - LABORATORY MODEL EXTRUSION SYSTEM

Sn.	Item	Description
1.	Rs. 6,50,000/-	For Single Screw Extruder as Described Above with conical discharge assembly with 1mm mesh.
2.	Rs. 2,85,000/-	For mesh pack (Set of four different size of meshes for conical extrusion) 0.6mm, 0.8 mm, 1.2mm, 1.5mm (OPTIONAL)
5.	Rs. 35,000/- per day per Engineer	For Installation & Commissioning
6.	Rs. 25,000/-	For Validation Documents comprising of DQ/IQ and OQ

UNIEXTRUDER: SINGLE SCREW EXTRUDER



4. UNISPHERE 250-SPHERONIZER

Sn	Item	Description
1.	System Description	UNISPHERE 150-Spheronizer generates spherical shape pellets which come out from an extruder. It is a downstream process of any extruder.
2.	Capacity	USP-150 Maximum processing capacity: 250-300gm/batch. Note: Output depends upon the Bulk density and material specific properties.
3.	Material of Construction	All the contact parts shall be made in S.S. 316 quality material. All non-contact parts shall be made from S.S. 304 quality material except bought out materials like motors and gear box
4.	Drum Assembly	A 150mm drum product container cylindrical in design shall be provided. Discharge chute shall be provided on the side of the product drum. It shall be fixed with dynamically balanced friction plate of 3.25mm pitch. 0.5 HP TEFC, 3000 RPM ELECTRIC MOTOR shall be provided to rotate the friction plate. It shall be easily removable for cleaning with screw arrangement. Drum cover. Made in Acrylic. It shall have a small opening for feeding material during operation.
5.	Discharge Assembly	Hopper made in Stainless Steel 316 fixed with acrylic cover for discharge.
6.	Controls	To be mounted on machine / fixed separately. ON/OFF Push button for Motor & MCB. RPM indication controlled by Frequency drive

PRICE: UNISPHERE250

Sn.	Price	Description
1)	Rs. 5,50,000/-	For Spheronizer as described above with a Friction plate suitable for 1mm to 2mm pellet size.
2)	Rs. 1,50,500/-	Friction plate with 2mm pitch.
3)	Rs. 1,75,000/-	Friction plate with 1mm pitch.
4)	Rs. 35,000/- per day per Engineer	For Installation & Commissioning
5)	Rs. 25,000/-	For Validation Documents comprising of DQ/IQ and OQ

SPHERONIZER:: USPH 150



LABORATORY INTEGRATED EXTRUDER SPHERONIZER DESIGN



Sn.	Price	Description
1)	Rs. 12,50,000/-	For Integrated Extruder Spheronizer Design comprising of USSE60 – SINGLE SCREW EXTRUDER and UNISPHERE150-SPHERONIZER including 1mm conical mesh for extruder and 3.25mm chequered plate with spheronizer.

Terms and Conditions:

Prices : Prices offered are net-ex-works Mumbai exclusive of Packing, Carting, Crating, Forwarding, Freight and any other incidental charges will be extra to your account.

Taxes : **GST (18%) shall be applied.**

Packing : **2.5% Extra is Packing And Forwarding Charges**

Excise : **NIL**

Inspection : Final Inspection prior to dispatch will have to be carried out jointly by us and your representative at our Mumbai works only. You will be intimated as soon as the machines are ready for dispatch.

Transport : **Extra to be paid by you directly to the transporter.**

Delivery : **Within 16-20 Weeks.**

Payment : 1. 40% Advance on confirmation of order.
2. Balance against proforma invoice through D.D.

Validity : This offer is valid for 30 days.

Warranty : We undertake to make good by replacement or repair, defects arising out of faulty design, materials or workmanship within 12 months of the date of dispatch, purely on ex-works basis i.e., the defective part will be returned by the buyer to our works and replacement taken by the buyer from our works. Bought-out components are guaranteed by us only to the extent of guarantees given to us by our suppliers. Electrical components, such as heaters, motors, contactors etc. rubber components and instruments such as pressure gauges, thermometers, etc. and other such consumables, etc. are however not covered under this Warranty. Warranty stands void if spare parts other than OEM are used.

Jurisdiction : Any dispute arising out of this quotation is subject to the **JURISDICTION OF MUMBAI COURT ONLY**. All dimensions are approximate.

We reserve the right of any technical deviations or modifications in design of all our products due to changes in suppliers situation.

Thanking you and awaiting for your favorable reply.

Yours truly,
For Hugopharm Technologies Pvt. Ltd.

Mr. Hiren Panchal
Tel: 022-24226882 / 022-24222815