



HUGOPHARM

Systems Engineered with Mind and Spirit

Hugopharm Technologies Pvt. Ltd.

Regd Office: 8, Jogani Industrial
Estate, 541 Senapati Bapat
Marg, Dadar (W), Mumbai 400028

Contact : Tel: 91-22-24226882 / 91-22-
24222815 ; sales@sbpanchal.com

Our Ref. No. HUGO/0703/2025-1

07-03-2025

FUDGEKEY SOLUTIONS LLP

***Office 1 & 2, Ground Floor, Unit G-5, Bhumi World Industrial Park,
Mumbai Nashik Highway, Village Pimplas,
Bhiwandi Dist. Thane - 421302***

KIND ATTN: Ms. Aboli Jogji

Dear Sir,

This refers to your requirement of 48 Tray VTD and glad to quote as under:

Sincerely,

For S.B. Panchal & Co
Hiren Panchal

1. 48 Trays Vacuum Tray Dryer GMP Model - Technical Bid

Sn.	Item	Description
1.	<u>General Construction</u>	The inside chamber of the drier shall be fabricated from S.S. 316 quality material. It shall be stiffened from outside using M.S. flats of size 50 x 12mm and 75 x 12 mm. These shall be insulated with glass wool insulation and claded with S.S. 304 quality material. Skirting of S.S. 304 material shall be provided on vacuum dryer body for flush mounting through the wall. <i><u>Optionally this chamber shall be externally heated with S.S. channels from 5 sides at an extra cost.</u></i>
2.	<u>Trays</u>	48 Nos. of trays of size 800mm x 400mm x 50mm high made from S.S. 316 material shall be provided. The tray corner shall be suitably rounded off and shall be free from sharp corners for easy and complete emptying of tray. The tray surface shall be buffed to mirror finish. 4. Nos. of trays shall be placed on each heating pad.
3.	<u>Tray Heating</u>	The trays shall be heated with 16 nos. of hollow pad type heating shelves of size 1225mm x 825mm x 27mm and made from S.S. 316 material. Provision shall be made for having multiple pass of heating medium across the heating shelf. An extra dummy heating shelf shall be provided above the top tray.
4.	<u>Door</u>	The dryer shall be having single door construction which shall be hinged and have 16 point locking. The door shall be sealed with silicon gasket. The door side with vapor contact shall be made from S.S. 316 quality material. Door tightening nuts, hinges, shall be made from S.S. 304 quality material. The door shall be duly insulated and claded with S.S.304
5.	<u>Condenser</u>	Shell and Tube type vertical condenser shall be provided with 2 sq meter area. Tube side material shall be S.S. 316 and shell side material shall be S.S. 304 quality. The condenser shall have provision for connecting cooling water inlet and outlet lines.

6.	<u>Condensate Receiver</u>	50liter capacity condensate receiver tank made from S.S. 316 shall be provided along with dryer. It shall be provided with drain valve and vacuum break valve.
7.	<u>Instrumentation</u>	The dryer shall be provided with following instrumentation and control devices 1. Vacuum Transmitter 2. Inlet Air Temperature Sensor 3. Additional Sensors available at clients request.
8.	<u>Fittings</u>	Following fittings shall be provided for the dryer 1. 1½ " BSP Water Inlet; 17 Nos. 2. 1½ " BSP Water Outlet; 17 Nos. 3. 4" N.B. Vacuum Port. 4. ½" N.B. Vacuum Break Valve 5. Nitrogen Purge Port (If Desired) 6. 1" NB Chamber Drain 7. 1" BSP Header Drain 8. 1" BSP Validation Port (If Desired) 9. ½" BSP RTD Sensor Port.

Price: 48 Tray Vacuum Tray Dryer.

Sn.	Price	Item
1.	Rs. 35,50,000/-	For 48 Tray Vacuum Tray Dryer as described including the following 1. VTD Body made from S.S. 316 inside duly stiffened, insulated and clad with S.S. 304 quality steel. 2. 48 No of trays of size 800mm x 400mm x 50mm made from 16G. S.S. 316 quality steel. 3. 2sq meter condenser made in S.S. 316 quality steel. 4. 50lit Receiver made from S.S. 316 quality steel.
2.	Rs. 6,50,000/-	For 500 liter hot water generation and recirculation system comprising of hot water tank, steam / electrical heating system and hot water re-circulation pump. The hot water tank shall be made from S.S. 304 and shall be heated with electrical heaters. The hot water temperature shall be controlled using PID Control Valve from Dembla / Samson / Siemens make. If electrically heated then PID Controller with SSR controllers shall be used to control the temperature.
3.	Rs. 1,85,000/-	Shall be charged extra if the body of the dryer is to be heated externally from five sides. The external jacketing system shall be made of S.S. Channels with several passes over each surface of the drier body.
4.	Rs. 7,00,000/-	For Imported Italy make Vacuum Pump. The pump shall have a capacity of 205cubic meter per hour and a maximum vacuum of 0.5mbar.
5.	Rs. 4,50,000/-	For Mitsubishi PLC and Touchscreen HMI with 7" touchscreen. The PLC shall be able to perform the following functions: 1. Indicate System Vacuum 2. Control and Indicate the Hot Water Inlet Temperature. 3. Control Pre- Heating Cycle Time 4. Control Drying Cycle- Time

6.	Rs. 1,50,000/-	For steam supply piping line consisting of isolation valves and steam control valves. The line shall be made from S.S. 304 material. It shall have suitable flanges end connection for removal of the valves for maintenance purpose.
7.	Rs. 1,00,000/-	For condensate drain piping assembly comprising of isolation valve, steam trap and bypass line made from Cast Iron.
8.	Rs. 1,75,000/-	For 15 meters of Vacuum Line made from 3"NB S.S. 304 pipe with flange ends to be connected to the receiver at one and vacuum pump skid at the other end.
9.	Rs. 2,00,000/-	For all power and signal cables along with pneumatic tubes to be routed from the power panel to the operating panel and on the equipment at various locations. Maximum Distance between Machine and Power panel is considered as 10m
10.	Rs. 65,000/-	For Validation Documents comprising of DQ/IQ and OQ.
11.	Rs. 1,25,000/-	For Installation and Commissioning

Terms and Conditions:

Prices : Prices offered are net-ex-works Mumbai exclusive of Packing, Carting, Crating, Forwarding, Freight and any other incidental charges will be extra to your account.

Taxes : All applicable taxes(18GST), packing, forwarding, octroi, insurance, excise etc. shall be charged extra as and if applicable at the time of dispatch.

Packing and Fwd: **2.5% Extra**

Excise : **NIL**

Inspection : Final Inspection prior to dispatch will have to be carried out jointly by us and your representative at our Mumbai works only. You will be intimated as soon as the machines are ready for dispatch.

Transport : Shall be paid by you directly to the transporter.

Delivery : Within 14 to 16 Weeks.

Payment : 1. 40% Advance on confirmation of order.
2. Balance against proforma invoice through D.D.

Validity : This offer is valid for 30 days.

Warranty : We undertake to make good by replacement or repair, defects arising out of faulty design, materials or workmanship within 12 months of the date of dispatch, purely on ex-works basis i.e., the defective part will be returned by the buyer to our works and replacement taken by the buyer from our works. Bought-out components are guaranteed by us only to the extent of guarantees given to us by our suppliers. Electrical components, such as heaters, motors, contactors etc. rubber components and instruments such as pressure gauges, thermometers, etc. and other such consumables, etc. are however not covered under this Warranty. Warranty stands void if spare parts other than OEM are used.

Jurisdiction : Any dispute arising out of this quotation is subject to the **JURISDICTION OF MUMBAI COURT ONLY**. All dimensions are approximate.

Design and Specification of all our products are subject to alteration, without notice.

Thanking you and awaiting for your favorable reply.

Yours truly,

For HUGOPHARM TECHNOLOGIES PVT LTD

Hiren Panchal
(Director)