



# HUGOPHARM

*Systems Engineered with Mind and Spirit*

Hugopharm Technologies Pvt. Ltd.

Regd Office: 8, Jogani Industrial

Estate, 541 Senapati Bapat

Marg, Dadar (W), Mumbai 400028

Contact : Tel: [91-22-24226882](tel:91-22-24226882) / [91-22-24222815](tel:91-22-24222815)

; [sales@sbpanchal.com](mailto:sales@sbpanchal.com)

Our Ref No: HUGO/2204/2025-1

22-04-25

To,

|                         |                                    |
|-------------------------|------------------------------------|
| <b>Contact</b>          | Mr. Sandeep Mewada                 |
| <b>Business Address</b> | EXEMED PHARMACEUTICALS<br>Vadodara |
| <b>Business Phone</b>   | 9974383190                         |
| <b>E-mail</b>           | sandip.mewada@exemedpharma.com     |

*We are glad to quote for the following R&D formulation line of equipment manufactured by us.*

1. *UNIGRANULATOR- Rapid Mixer granulator 25L*

Sincerely,

For Hugopharm Technologies Pvt. Ltd.,

Hiren Panchal

Tel: 022-24226882 / 022-24222815

1. **UNIGRANULATOR – RAPID MIXER GRANULATOR ( 25 LTR)**

| Sr. No | Item                              | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|--------|-----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1.     | <b>Capacity</b>                   | <p><b>Bowl with gross capacity of 25liters</b></p> <p>Capacity in gm = Gross volume x 0.7 (Fill volume) x 0.5gm/cc (Bulk Density)</p>                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| 2.     | <b>General Description</b>        | <p><b><i>Operations – Dry / Wet mixing, Lubrication / Granulation of powder.</i></b></p> <p>Mixing Bowl and Cover: S.S. 316 bowl design in three sections i.e. Flat bottom cylindrical mid portion and conical top portion for efficient mixing operation &amp; provided with counter balanced lid. Lid provided with vents, view ports &amp; charging openings.</p> <p>The 5liter bowl shall be jacketed and insulated. Hot Oil Heating System is quoted optionally. It shall have S.S. 304 jacket and S.S. 304 insulation. (Hot Oil System is quoted optionally)</p> |
| 3.     | <b>Main Impeller &amp; Drive:</b> | <p>The main impeller consists of 2HP synchronous motor coupled to a gearbox. The impeller is designed to provide mixing at the bottom and at the center of the bowl and is driven through a specially designed bearing housing. That prevents leakage of powder from bottom entry and leads to longer life of gear box.</p>                                                                                                                                                                                                                                            |
| 4.     | <b>Chopper</b>                    | <p>The chopper drive consists of 1HP synchronous motor. The motor shaft is of SS and the chopper has specially designed 4 blade SS impellers. The shaft is integral with the motor. The assembly mounted horizontally into the bowl.</p>                                                                                                                                                                                                                                                                                                                               |
| 5.     | <b>Discharge</b>                  | <p>The discharge of the machine shall be by pneumatic discharge cylinder. The machine shall not start unless the discharge is closed.</p>                                                                                                                                                                                                                                                                                                                                                                                                                              |
| 6.     | <b>Mounting</b>                   | <p>A sturdy S.S channel frame is used to house the drive assembly at the bottom. The bowl is mounted on the top. The table of the machine shall be provided with wheels.</p>                                                                                                                                                                                                                                                                                                                                                                                           |

|    |               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|----|---------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7. | Control Panel | <p>The RMG shall be controlled using Mitsubishi PLC and 7" Touchscreen from Mitsubishi.</p> <p>The user shall be able to control the following</p> <ol style="list-style-type: none"> <li>1. Indication &amp; Control of Speed of Impeller</li> <li>2. Indication &amp; Control Speed of Chopper</li> <li>3. Indication of Impeller Current</li> <li>4. Indication of Impeller Torque</li> <li>5. Indication of Chopper Current</li> <li>6. Indication of Chopper Torque</li> <li>7. Setting of Process Time</li> <li>8. Setting of Chopper Delay time.</li> </ol> |
|----|---------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

**PRICE : UNIGRANULATOR: RAPID MIXER GRANULATOR**

| S. No. | Price                                    | Description                                                                                                                                                                                                                                                                                                                                        |
|--------|------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1.     | <b>Rs. 8,50,000/-</b>                    | For GMP Rapid Mixer Granulator as described above with <b>25LIT BOWL</b><br><br>Capacity in gm = Gross volume x 0.7 (Fill volume) x 0.6gm/cc (Bulk Density):<br>Including the following:<br>1. Manual Control Panel<br>2. Variable frequency starter for the main drive and chopper drive capable to give motor current and motor torque readings. |
| 2.     | <b>Rs. 3,50,000/-</b>                    | Extra for Mitsubishi PLC with Mitsubishi Touchscreen HMI                                                                                                                                                                                                                                                                                           |
| 3.     | <b>Rs. 2,25,000/-</b>                    | For Binder addition system comprising of Flowtech Make Peristaltic Pump, Silicon Tube and Spray Nozzle (1. No) / Liquid Distributor installed underneath the lid of each bowl.(3 Nos). The liquid distributor shall be removable.<br><br>The Pump shall be integrated with PLC to control its speed.                                               |
| 4.     | <b>Rs. 75,000/- Extra</b>                | For Flame proof motor for Impeller and Chopper                                                                                                                                                                                                                                                                                                     |
| 5.     | <b>Rs. 25,000/- per day per Engineer</b> | <b>For Installation &amp; Commissioning</b>                                                                                                                                                                                                                                                                                                        |
| 6.     | <b>Rs. 20,000/-</b>                      | <b>For Validation Documents comprising of DQ, IQ and OQ</b>                                                                                                                                                                                                                                                                                        |

## Terms and Conditions:

**Prices** : Prices offered are net-ex-works Mumbai exclusive of Packing, Carting, Crating, Forwarding, Freight and any other incidental charges will be extra to your account.

**Taxes** : **GST (18%) shall be applied.**

**Packing** : **2.5% Extra**

**Excise** : **NIL**

**Inspection** : Final Inspection prior to dispatch will have to be carried out jointly by us and your representative at our Mumbai works only. You will be intimated as soon as the machines are ready for dispatch.

**Transport** : **Extra to be paid by you directly to the transporter.**

**Delivery** : **Within 12-16 Weeks from date of Advance Payment.**

**Payment** : 1. 40% Advance on confirmation of order.  
2. Balance against proforma invoice through D.D.

**Validity** : This offer is valid for 30 days.

**Warranty** : We undertake to make good by replacement or repair, defects arising out of faulty design, materials or workmanship within 12 months of the date of dispatch, purely on ex-works basis i.e., the defective part will be returned by the buyer to our works and replacement taken by the buyer from our works. Bought-out components are guaranteed by us only to the extent of guarantees given to us by our suppliers. Electrical components, such as heaters, motors, contactors etc. rubber components and instruments such as pressure gauges, thermometers, etc. and other such consumables, etc. are however not covered under this Warranty. Warranty stands void if spare parts other than OEM are used.

**Jurisdiction** : Any dispute arising out of this quotation is subject to the **JURISDICTION OF MUMBAI COURT ONLY**. All dimensions are approximate.

We reserve the right of any technical deviations or modifications in design of all our products due to changes in suppliers situation.

**Thanking you and awaiting for your favorable reply.**

Yours truly,  
**For Hugopharm Technologies Pvt. Ltd.**

Mr. Hiren Panchal  
Tel: 022-24226882 / 022-24222815