



# HUGOPHARM

*Systems Engineered with Mind and Spirit*

Hugopharm Technologies Pvt. Ltd.

Regd Office: 8, Jogani Industrial Estate, 541 Senapati Bapat Marg, Dadar (W), Mumbai 400028

Contact : Tel: 91-22-24226882 / 91-22-24222815 ; sales@sbpanchal.com

Our Ref No: HUGO/2602/2025-1

26-02-25

To,

|                  |                                                                                      |
|------------------|--------------------------------------------------------------------------------------|
| Contact          | K. Subba Reddy (Sr. Manager-Projects) / Mr. Sandip Salunkhe ( AGM- Application Lab ) |
| Business Address | M/S. Alcedo Pharmachem PVT LTD<br>Hyderabad                                          |
| Business Phone   | Contact No : 7730094222 / 7702233341 / Mob.no: 9503497037.                           |
| E-mail           | projects@alcedo.co.in                                                                |

*We are glad to quote for the following R&D formulation line of equipment manufactured by us.*

1. **UNIGRANULATOR- Rapid Mixer granulator (3lit, 5lit)**
2. **UNIFLUID NANO- RAPID FLUID BED DRYER**
3. **UNIBLEND- Bin Blender(3lit & 5lit)**
4. **UNIFLUID 1.1- Fluid Bed Coater Granulator (300gm-1000gm)**

Sincerely,

For Hugopharm Technologies Pvt. Ltd.,

Hiren Panchal

Tel: 022-24226882 / 022-24222815

**1. UNIGRANULATOR – RAPID MIXER GRANULATOR ( 3lit , 5lit)**

| Sr. No | Item                   | Description                                                                                                                                                                                                                                                                                                                                |
|--------|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1.     | Capacity               | <b>Interchangeable bowls with gross capacity of 3 liters &amp; 5lit</b><br>Capacity in gm = Gross volume x 0.7 (Fill volume) x0.5gm/cc (Bulk Density)                                                                                                                                                                                      |
| 2.     | General Description    | <b>Operations – Dry / Wet mixing, Lubrication / Granulation of powder.</b><br>Mixing Bowl and Cover: S.S. 316 bowl design in three sections i.e. Flat bottom cylindrical mid portion and conical top portion for efficient mixing operation & provided with counter balanced lid. Lid provided with vents, view ports & charging openings. |
| 3.     | Main Impeller & Drive: | The main impeller consists of synchronous motor. The impeller is designed to provide mixing at the bottom and at the center of the bowl and is driven through a specially designed bearing housing. That prevents leakage of powder from bottom entry and leads to longer life of gear box.                                                |
| 4.     | Chopper                | The chopper drive consists of synchronous motor. The motor shaft is of SS and the chopper has specially designed 4 blade SS impellers. The shaft is integral with the motor. The assembly mounted horizontally into the bowl.                                                                                                              |
| 5.     | Discharge              | The discharge of the machine shall be by lifting the bowl manually.                                                                                                                                                                                                                                                                        |
| 6.     | Mounting               | A sturdy S.S channel frame is used to house the drive assembly at the bottom. The bowl is mounted on the top.                                                                                                                                                                                                                              |
| 7.     | Control Panel          | Main panel consists of all prewired connections and it has only to be connected to the electric supply. The circuit consists of MCCB, relays and contactor in series. Ample overload protection is provided by the MCCB and the relay. Wires coming out of the connections are numbered for easy recognition.                              |

**PRICE : UNIGRANULATOR: RAPID MIXER GRANULATOR**

| S. No. | Price                                    | Description                                                                                                                                                                                                                                                                                                                                                                            |
|--------|------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1.     | <b>Rs. 8,50,000/-</b>                    | For GMP Rapid Mixer Granulator as described above with<br><b>3lit (500gm to 1kg).</b><br><b>5lit (700gm to 2kg).</b><br>Capacity in gm = Gross volume x 0.7 (Fill volume) x0.6gm/cc (Bulk Density): Not: Loading capacity may vary based on Bulk Density<br>Including the following:<br>1. Manual Control Panel<br>2. Variable frequency starter for the main drive and chopper drive. |
| 2.     | <b>Rs. 7,22,500/-</b>                    | <b>Discounted Price for Rapid Mixer Granulator as described above.</b>                                                                                                                                                                                                                                                                                                                 |
| 3.     | <b>Rs. 25,000/- per day per Engineer</b> | <b>For Installation &amp; Commissioning</b>                                                                                                                                                                                                                                                                                                                                            |
| 4.     | <b>Rs. 20,000/-</b>                      | <b>For Validation Documents comprising of DQ, IQ and OQ</b>                                                                                                                                                                                                                                                                                                                            |

## **1. UNIFLUID NANO - FLUID BED DRYER (200gm-1000gm)**

| <b>Sr. No</b> | <b>Item</b>                                    | <b>Description</b>                                                                                                                                                                |
|---------------|------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1.            | <b>General Construction</b>                    | The machine body shall be fabricated from S.S. 304 quality material.                                                                                                              |
| 2.            | <b>Product Container cum Retarding Chamber</b> | This chamber shall be fabricated from S.S. 316. It shall have a capacity of 1 kg.                                                                                                 |
| 3.            | <b>Air Circulation</b>                         | The required draught shall be provided with totally enclosed fan cooled electric motor driven centrifugal impeller. The speed of the blower shall be controlled from front panel. |
| 4.            | <b>Heating</b>                                 | The air shall be heated with coiled tube air heaters. The heating capacity shall be 2 K.W.                                                                                        |
| 5.            | <b>Control</b>                                 | The process control switch board shall comprise of: Process timer, PID Temp. Controller, Air Flow Control Damper and Pilot Lamps.                                                 |

- **All S.S. parts are buffed to mirror finish.**

**PRICE : UNIFLUID NANO :- LAB MODEL FLUID BED DRYER.**

| Sr. No    | Price                                    | Description                                                                                                                                                                                                                              |
|-----------|------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1.        | <b>Rs.6,70,000/-</b>                     | For “Table Top Model 200-1000 gm capacity electrically heated model Fluid Bed Dryer, having all contact parts made from S.S.316. ( <b>COMPLETE 1 SET OF UNIFLUID NANO- Rapid Fluid Bed Dryer which includes S.S.316 bowl and a bag</b> ) |
| 2.        | <b>Rs. 8,500/-</b>                       | For Surge Suppressor for Protection from any Electrical Power Surge.                                                                                                                                                                     |
| 3.        | <b>Rs. 6,78,500/-</b>                    | Total Price Including Item 1 and 2 Above.                                                                                                                                                                                                |
| <b>4.</b> | <b>Rs. 5,76,725/-</b>                    | <b>Discounted Price for Fluid Bed Dryer as described above.</b>                                                                                                                                                                          |
| 5.        | <b>Rs. 25,000/- per day per Engineer</b> | For Installation & Commissioning at your premises.<br>Client shall provide To and Fro Travel Charges, local lodging, boarding and conveyance.                                                                                            |
| 6.        | <b>Rs. 20,000/-</b>                      | For set of validation documents comprising of DQ, IQ & OQ                                                                                                                                                                                |

## **UNIFLUID NANO WITH VARIOUS OPTIONS**



**UNIFLUID NANO with S.S 316 bowl**

**RMG WITH 3 INTERCHANGEABLE BOWLS OF  
3lit / 5lit**



## **5. UNIBLEND: - OCTAGONAL BLENDER**

| <b>Sn.</b> | <b>Item</b>                    | <b><u>Description</u></b>                                                                                                                                                                                                                                                                    |
|------------|--------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>1.</b>  | <b>General Construction</b>    | All the contact parts of the blender shall be made from S.S. 316 quality material. Blender stand and railing shall be made from rectangular and square pipes.                                                                                                                                |
| <b>2.</b>  | <b>Capacity</b>                | <p>The blender shall have a facility to replace various blender containers to the common shaft attached to the drive. There shall be three containers to suit, 3liter, 5liter.</p> <p>Working Volume is calculated assuming bulk density of 0.6 g/cc and loading of 70% of gross volume.</p> |
| <b>3.</b>  | <b>Drive Unit</b>              | 0.5 HP, 1440 RPM motor with gear box. Chains and sprockets shall be used to transmit the motion between gear box and blender shaft. Blender shall be fitted with a variable frequency drive for adjusting the speed.                                                                         |
| <b>4.</b>  | <b>Loading &amp; Discharge</b> | Loading shall be manual and unloading shall be through a blender.                                                                                                                                                                                                                            |
| <b>5.</b>  | <b>Controls</b>                | Control panel shall comprise of a main switch, ON-OFF push buttons, indication lamps, fuses, contactors, relays and MCB.                                                                                                                                                                     |

## **PRICE : LAB OCTAGONAL BLENDER**

| <b>Sn.</b> | <b>Price</b>                             | <b>Item</b>                                                                     |
|------------|------------------------------------------|---------------------------------------------------------------------------------|
| <b>1.</b>  | <b>Rs. 6,00,000/-</b>                    | <b>For 'Lab Bin Blender" having facility to engage bowls of 3liter, 5liter.</b> |
| <b>2.</b>  | <b>Rs. 5,10,000/-</b>                    | <b>Discounted Price for Octagonal Blender as described above.</b>               |
| <b>3.</b>  | <b>Rs. 25,000/-</b>                      | For Validation Documents comprising of DQ/IQ and OQ                             |
| <b>4.</b>  | <b>Rs. 25,000/- per day per Engineer</b> | For Installation & Commissioning at your site                                   |



## 7. UNIFLUID1.1- FLUID BED PARTICLE COATER GRANULATOR

| Sn. | Item                                                             | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|-----|------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1.  | <b><u>General Construction</u></b>                               | <ul style="list-style-type: none"> <li>a. All the contact parts shall be made from S.S. 316 quality material and non-contact parts shall be made from S.S. 304 quality material.</li> <li>b. Product Container shall be lifted and sealed against expansion chamber with help of pneumatic cylinders. Or sealing shall be done with help of pneumatically inflatable gaskets.</li> <li>c. Strategically mounted observation windows for viewing coating process.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| 2   | <b><u>Product Container</u></b><br><b><u>Wurster Coating</u></b> | <ul style="list-style-type: none"> <li>a. Product container shall be made of Stainless Steel AISI 316, for WURSTER coating applications.</li> <li>b. It shall have capacity of 2 liters for pellet coating.</li> <li>c. It shall have an oblong shape observation window duly fitted with toughened observation glass. It shall be mounted on a trolley fixed with nylon castors for movement.</li> <li>d. Height of the Wurster Column shall be adjusted manually against the graduated scale for one Wurster fixed inside</li> <li>e. Product Container shall have temperature sensing port and sampling port for extracting small quantities of coated substrate during operation.</li> <li>f. Product Container shall be mirror polished.</li> <li>g. Air atomizing spray nozzle will be of 1mm size.</li> <li>h. The distribution plate &amp; bottom mesh shall be made from S.S. 316.</li> <li>i. The machine shall be supplied with 4Nos of silicon molded mesh of 60#, 100#, 250# and 24x110#</li> <li>j. The machine shall also be supplied with 4 Nos of Wurster plates, A, B, C and D.</li> </ul> |

|    |                                                                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|----|------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 3. | <p><b><u>Product Container</u></b></p> <p><b><u>Top Spray &amp; Drying</u></b></p> | <ul style="list-style-type: none"> <li>a. It shall be made from S.S. 316 for Top-Spray Granulation / Drying applications</li> <li>b. It shall have capacity of 4 liters for Top Spray Granulation.<br/>(Minimum 300gm-Maximum 1000gm)</li> <li>c. It shall have oblong observation window at the front fitted with toughened observation glass.</li> <li>d. Spray nozzle of atomizing air shall be of 1 mm size. There shall be 2 ports for adjusting nozzle height.</li> <li>e. Product Container shall have temperature sensing port and sampling port for extracting small quantities of coated substrate during operation.</li> <li>f. Product Container shall be mirror polished.</li> <li>g. The machine shall be supplied with 24x110# and 50 x 250#.</li> <li>h. Blind Ports shall be provided to operate the machine in drying mode.</li> </ul> |
| 4  | <p><b><u>Inlet Air Filtration</u></b></p>                                          | <ul style="list-style-type: none"> <li>a. Air Handling Unit shall be made from S.S. 304. Air Handling Unit shall consists of:-</li> <li>b. 5-micron Pre-Filter. All gaskets used will be in Silicon Rubber.</li> <li>c. Heating coil section 4.5 K.W. electric heaters. The heater box shall be duly insulated.</li> <li>d. Dehumidifier and Humidifier System shall be supplied at an extra cost if required.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                |
| 5  | <p><b><u>Spraying System</u></b></p>                                               | <ul style="list-style-type: none"> <li>a. For Top spray nozzles shall be of 1 mm. (0.8mm Nozzles are available as an option).</li> <li>b. Electrically operated peristaltic pump shall be provided for supply of fluid dosing to media nozzle via suitable silicon tubing.</li> <li>c. Pump shall have 1-3000 ml./min flow rate.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| 6  | <p><b><u>Filter Chamber</u></b></p>                                                | <ul style="list-style-type: none"> <li>a. There shall be dual bag filtration system. The partition type filtration system shall be designed for smooth uninterrupted coating process.</li> <li>b. Satin cotton bag shall be provided for filtration during granulation and drying. There shall be dual partition system of filter bag</li> <li>c. Epitropic bag shall be provided also for static charge intensive product coating.</li> <li>d. The filter bags shall be cleaned with automatic pneumatic shaking logic in PLC.</li> </ul>                                                                                                                                                                                                                                                                                                               |

|   |                                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|---|----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7 | <b><u>Exhaust Blower</u></b>           | <ul style="list-style-type: none"> <li>a. Exhaust Blower shall be driven by inverter based 1 H.P. non-flameproof blower for drawing air through coater and enabling fluidization of particles.</li> <li>b. Required draught of air shall be produced by aluminum impeller housed in S.S. casing.</li> <li>c. Exhaust blower shall be fitted with inverter drive to control the fluidization air.</li> </ul>                                                                                                                 |
| 8 | <b><u>Safety Features</u></b>          | <ul style="list-style-type: none"> <li>a. Machine shall have Earth Monitoring Device. Proper earthing shall be done for following parts through measurement probes ( 3 nos.):               <ul style="list-style-type: none"> <li>i. Filter Chamber cum Expansion Chamber</li> <li>ii. Product Chamber.</li> </ul> </li> <li>b. Peristaltic Pump shall not start in event of inadequate pressure ( less than 3 Kgs ) in nozzle line. It shall On the LED for Pump.</li> <li>c. Heaters interlocked with Blower.</li> </ul> |
| 9 | <b><u>Automation &amp; Control</u></b> | <p>Manual Control Panel shall be provided with along with the machine. The panel shall have provision to control the following:</p> <ul style="list-style-type: none"> <li>1. Control and Indicate Blower Speed in %</li> <li>2. Control &amp; Indicate Inlet Air Temperature</li> <li>3. Indicate Exhaust Air Temperature</li> <li>4. Indicate Product Temperature</li> <li>5. Control &amp; Indicate Spray Pump RPM</li> <li>6. Control &amp; Indicate on Manual Gauge Spray Atomization Pressure</li> </ul>              |

**PRICE: UNIFLUID 1.1 LABORATORY MODEL FLUID BED PROCESSING SYSTEM**

| <b>Sn.</b> | <b>Price</b>           | <b>Item</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|------------|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>1.</b>  | <b>Rs. 28,50,000/-</b> | Fluid Bed Processing System with following:<br>1. Top spray Bowl.<br>2. Bottom spray Bowl.<br>3. Top Spray and Bottom Spray Nozzles.<br>4. Peristaltic pump.<br>5. Weighing Scale integrated with PLC<br>6. Fully automatic control system comprising of Mitsubishi PLC and 10.1" Mitsubishi Touchscreen,<br>7. EPSON Printer for Datalogging.<br>8. Four Plates for Wurster Coating A, B, C & D<br>9. Four Silicon Molded Meshes for Bottom Spray 60#, 80#,100# & 200#<br>10. Two Different Meshes for Top Spray 24x110# and 50x250#<br>11. Three different filter bags, PC Satin, Epitropic and Bonnet Bag |
| <b>2.</b>  | <b>Rs. 24,22,500/-</b> | <b>Discounted Price for UNIFLUID1.1 Fluid Bed Particle Coater Granulator as described above.</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>3.</b>  | <b>Rs. 75,000/-</b>    | For Installation and Commissioning.<br>1. Level floor.<br>2. Foundation and necessary masonry work if required.<br>3. Shifting of equipment at site.<br>4. Electrical wiring upto the equipment as per our instructions.<br>5. Steam connection along with necessary steam fittings such as steam trap, strainer etc. and steam controlling device.<br>6. Necessary unskilled help at your cost.<br><br>To and Fro Travel Charges from site, local lodging, boarding and conveyance to be in clients scope of supply.                                                                                        |
| <b>4.</b>  | <b>Rs. 25,000/-</b>    | For set of validation documents comprising of DQ/IQ/OQ                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |

## UNIFLUID 1.1-FLUID BED PARTICLE COATER GRANULATOR



## **Terms and Conditions:**

- Prices** : Prices offered are net-ex-works Mumbai exclusive of Packing, Carting, Crating, Forwarding, Freight and any other incidental charges will be extra to your account.
- Taxes** : **GST (18%) shall be applied.**
- Packing** : **1.5% Extra is Packing And Forwarding Charges**
- Excise** : **NIL**
- Inspection** : Final Inspection prior to dispatch will have to be carried out jointly by us and your representative at our Mumbai works only. You will be intimated as soon as the machines are ready for dispatch.
- Transport** : **Extra to be paid by you directly to the transporter.**
- Delivery** : **(FBD shall be delivered in 6 Weeks)**  
**(Blender shall be delivered in 8 Weeks)**  
**(RMG shall be delivered in 10Weeks)**  
**(FBPC shall be delivered in 12-16Weeks)**
- Payment** : 1. 40% Advance on confirmation of order.  
2. 50% against proforma invoice through D.D. after Factory Acceptance Test  
3. 10% Against Installation and Commissioning
- Validity** : This offer is valid for 30 days.
- Warranty** : We undertake to make good by replacement or repair, defects arising out of faulty design, materials or workmanship within 12 months of the date of dispatch, purely on ex-works basis i.e., the defective part will be returned by the buyer to our works and replacement taken by the buyer from our works. Bought-out components are guaranteed by us only to the extent of guarantees given to us by our suppliers. Electrical components, such as heaters, motors, contactors etc. rubber components and instruments such as pressure gauges, thermometers, etc. and other such consumables, etc. are however not covered under this Warranty. Warranty stands void if spare parts other than OEM are used.
- Jurisdiction** : Any dispute arising out of this quotation is subject to the **JURISDICTION OF MUMBAI COURT ONLY**. All dimensions are approximate.

We reserve the right of any technical deviations or modifications in design of all our products due to changes in suppliers situation.

**Thanking you and awaiting for your favorable reply.**

Yours truly,  
**For Hugopharm Technologies Pvt. Ltd.**

Mr. Hiren Panchal  
Tel: 022-24226882 / 022-24222815