



HUGOPHARM

Systems Engineered with Mind and Spirit

Hugopharm Technologies Pvt. Ltd.

Regd Office: 8, Jogani Industrial Estate, 541 Senapati Bapat Marg, Dadar (W), Mumbai 400028

Contact : Tel: 91-22-24226882 / 91-22-24222815 ; sales@sbpanchal.com

Our Ref No: HUGO/JS/FDD2025/2602/2

26-02-2025

To,

Contact	Dr. Manikandan R (Senior VP, R&D)
Business Address	Granules India Limited Hyderabad
Business Phone	9701501878
E-mail	manikandan.r@granulesindia.com

We are glad to quote for the following R&D formulation line of equipment manufactured by us.

1. **UNIFLUID NANO- RAPID FLUID BED DRYER**
2. **UNIGRANULATOR- Rapid Mixer granulator (250ml, 1 liter, 3 liters, 5 liters)**
3. **UNICONEMILL- Lab Comill**
4. **UNISIFT- Lab Sifter**
5. **UNIBLEND- Bin Blender**
6. **UNICOATER LAB- AUTOMATIC TABLET COATER**
7. **UNIFLUID 1.1- Fluid Bed Coater Granulator (300gm-1000gm)**
8. **UNIEXTRUDE-USSE60-SINGLE SCREW EXTRUDER**
9. **UNISPHERE-USPH150- SPHERONIZER**
10. **UNISPRAY - LAB SPRAY DRYER**

Sincerely,

For Hugopharm Technologies Pvt. Ltd.,

JUIE SINGH / 9869923024

Tel: 022-24226882 / 022-24222815

1. UNIFLUID NANO - FLUID BED DRYER (200gm-1000gm)

Sr. No	Item	Description
1.	General Construction	The machine body shall be fabricated from S.S. 304 quality material.
2.	Product Container cum Retarding Chamber	This chamber shall be fabricated from glass. It shall have a capacity of 1 kg.
3.	Air Circulation	The required draught shall be provided with totally enclosed fan cooled electric motor driven centrifugal impeller. The speed of the blower shall be controlled from front panel.
4.	Heating	The air shall be heated with coiled tube air heaters. The heating capacity shall be 2 K.W.
5.	Control	The process control switch board shall comprise of: Process timer, PID Temp. Controller, Air Flow Control Damper and Pilot Lamps.

- **All S.S. parts are buffed to mirror finish.**

PRICE : UNIFLUID NANO :- LAB MODEL FLUID BED DRYER.

Sr. No	Price	Description
1.	Rs.6,50,000/-	For "Table Top Model 200-1000 gm capacity electrically heated model Fluid Bed Dryer, having all contact parts made from glass. (COMPLETE 1 SET OF UNIFLUID NANO- Rapid Fluid Bed Dryer which includes Glass bowl and a bag)
2.	Rs. 25,000/- per day per Engineer	For Installation & Commissioning at your premises. Client shall provide To and Fro Travel Charges, local lodging, boarding and conveyance.
3.	Rs. 20,000/-	For set of validation documents comprising of DQ, IQ & OQ

OPTIONS FOR EXTRA ACCESSORIES

1.	Rs. 1,25,000/-	For additional change part for product container made from glass for handling products from 50gm to 200gm.
2.	Rs. 1,25,000/-	For additional product container made from S.S. 316 containing glass view port.
3.	Rs. 25,000/-	For Product Temperature Sensor (In S.S. bowl) with indication on the panel. The Product Temperature sensor shall be made from S.S. 316 and shall have quick release connector.
4.	Rs. 1,500 /-	For extra air discharge bags made from cotton cloth. (6lit bowl)
5.	Rs. 2,750/-	For extra air discharge bag made from polyester material. (6lit bowl)
6.	Rs. 5,500/-	For extra air discharge bag made from epitropic polyester material. (6lit bowl)
7.	Rs. 550 /-	For extra air discharge bags made from cotton cloth. (300ml bowl)
8.	Rs. 1,250/-	For extra air discharge bag made from polyester material. (300ml bowl)
9.	Rs. 2,500/-	For extra air discharge bag made from epitropic polyester material. (300ml bowl.)
10.	Rs. 8,500/-	For Surge Suppressor for Protection from any Electrical Power Surge.

UNIFLUID NANO WITH VARIOUS OPTIONS

UNIFLUID NANO with glass bowl



UNIFLUID NANO with interchangeable bowl



UNIFLUID NANO with S.S 316 bowl



UNIFLUID NANO with Product Temp Sensor

2. UNIGRANULATOR – RAPID MIXER GRANULATOR (250ml, 1 liter, 3 liters, 5 liters)

)

Sr. No	Item	Description
1.	Capacity	Interchangeable bowls with gross capacity of 250ml, 1 liter, 3 liters, 5 liters Capacity in gm = Gross volume x 0.7 (Fill volume) x 0.5gm/cc (Bulk Density)
2.	General Description	<i>Operations – Dry / Wet mixing, Lubrication / Granulation of powder.</i> Mixing Bowl and Cover: S.S. 316 bowl design in three sections i.e. Flat bottom cylindrical mid portion and conical top portion for efficient mixing operation & provided with counter balanced lid. Lid provided with vents, view ports & charging openings.
3.	Main Impeller & Drive:	The main impeller consists of synchronous motor. The impeller is designed to provide mixing at the bottom and at the center of the bowl and is driven through a specially designed bearing housing. That prevents leakage of powder from bottom entry and leads to longer life of gear box.
4.	Chopper	The chopper drive consists of synchronous motor. The motor shaft is of SS and the chopper has specially designed 4 blade SS impellers. The shaft is integral with the motor. The assembly mounted horizontally into the bowl.
5.	Discharge	The discharge of the machine shall be by lifting the bowl manually.
6.	Mounting	A sturdy S.S channel frame is used to house the drive assembly at the bottom. The bowl is mounted on the top.
7.	Control Panel	Main panel consists of all prewired connections and it has only to be connected to the electric supply. The circuit consists of MCCB, relays and contactor in series. Ample overload protection is provided by the MCCB and the relay. Wires coming out of the connections are numbered for easy recognition.

PRICE : UNIGRANULATOR: RAPID MIXER GRANULATOR

S. No.	Price	Description
1.	Rs. 12,50,000/-	For GMP Rapid Mixer Granulator as described above with 250ml (20gm to 50gm), 1lit (100gm to 250gm), 3lit (300gm to 700GM). 5lit (400gm to 1kg) Capacity in gm = Gross volume x 0.7 (Fill volume) x 0.6gm/cc (Bulk Density): Including the following: 1. Manual Control Panel 2. Variable frequency starter for the main drive and chopper drive.
2.	Rs. 3,50,000/-	For Mitsubishi PLC and Touchscreen for Control instead of Manual Control Panel
3.	Rs. 25,000/- per day per Engineer	For Installation & Commissioning
4.	Rs. 25,000/-	For Validation Documents comprising of DQ, IQ and OQ

**RMG WITH 3 INTERCHANGEABLE BOWLS OF
250ml/1lit/3lit**



3. UNICONEMILL- CONE MILL

Sn.	Item	Description
1.	General Construction	All the contact parts of the blender shall be made from 2 mm thick S.S. 316 quality material. The design of the machine shall be similar to Quadro Cone Mill.
2.	Cone Assembly	Impeller with 1mm round laser drilled hole cone assembly shall be provided with the machine. It shall be made from S.S 316 quality steel.
3.	Capacity	The cone mill shall have an output of 2 kg/hr . The output shall depend on the size of the cone mesh attached, the speed of mill and material characteristics.
4.	Drive Unit	1 HP, 1440 RPM motor with gear box. The cone mill shall have provision of variable speed through a VFD drive coupled to the motor.
5.	Controls	Control panel shall comprise of a main switch, ON-OFF push buttons, indication lamps, fuses, contactors, relays and MCB.

PRICE : CONE MILL

Sn.	Price	Item
1.	Rs. 6,50,000/-	For the above given description Laboratory Model Cone Mill with 1mm mesh.
2	Rs. 75,000/- (each)	Grater sieve of size 1mm, 1.5mm & 2mm Grater hole
3	Rs. 52,500/- (each)	Square mesh of Size 6mm,8mm,10mm,12mm
4	Rs. 60,000/- (each)	Precise Laser driller round holes 0.5mm,1mm, 1.5mm, 2mm, 3mm
5	Rs. 25,000/- per day per Engineer	For Installation & Commissioning.
6	Rs. 25,000/-	For set of validation documents comprising of DQ/IQ/OQ

Note: Any other custom sizes are available on request.

We can match the hole size to exact mesh sizes also.

UNICONEMILL-LAB MODEL



4. UNISIFT : Laboratory Sifter

Sr. No	Price	Description
1	Rs. 1,50,000/-	Model :12"Dia (340mm –o/d) GMP M.O.C :S.S.316 Quality Deck :Single Motor :0.25 H.P. FLP-Good earth make. Mesh :As per customers requirement.
2.	Rs. 3,500/- Each	FOR EACH S.S. 316 SILICON BRADED MESH SIZE AVAILABLE: 10#, 12#, 16#, 20#, 40#, 60#, 80#, 100# and 120#
3.	Rs. 25,000/- per day per Engineer	For Installation & Commissioning.
4.	Rs. 25,000/-	For set of validation documents comprising of DQ/IQ/OQ

LAB SIFTER



5. UNIBLEND: - BIN BLENDER

Sn.	Item	<u>Description</u>
1.	General Construction	All the contact parts of the blender shall be made from S.S. 316 quality material. Blender stand and railing shall be made from rectangular and square pipes.
2.	Capacity	The blender shall have a facility to replace various blender containers to the common shaft attached to the drive. There shall be three containers to suit, 3liter, 5liter, 10liter. Working Volume is calculated assuming bulk density of 0.6 g/cc and loading of 70% of gross volume.
3.	Drive Unit	0.5 HP, 1440 RPM motor with gear box. Chains and sprockets shall be used to transmit the motion between gear box and blender shaft. Blender shall be fitted with a variable frequency drive for adjusting the speed.
4.	Loading & Discharge	Loading shall be manual and unloading shall be through a blender.
5.	Controls	Control panel shall comprise of a main switch, ON-OFF push buttons, indication lamps, fuses, contactors, relays and MCB.

PRICE : LAB OCTAGONAL BLENDER

Sn.	Price	Item
1.	Rs. 6,75,000/-	For 'Lab Bin Blender" having facility to engage bowls of 3liter, 5liter and 10 liters.
2.	Rs. 25,000/-	For Validation Documents comprising of DQ/IQ and OQ
3.	Rs. 25,000/- per day per Engineer	For Installation & Commissioning at your site

6. **UNICOATER LAB: PERFORATE PAN AUTOMATIC TABLET COATER**

Sn	Item	Description
1	Main Unit	Multiples Interchangeable Laboratory Perforated Pan : 1. It shall comprise of 100gm, 200gm, 500gm and 1000gm multiple interchangeable perforated pans of various size having suitable opening for charging and discharging tablets. 2. It shall be fabricated from stainless steel 316 quality 2mm thick sheets. Pan shall be housed in S.S. 304 cabinet. 3. It shall be driven by motor to provide variable speed from 6-40 RPM. 4. S.S. Baffles shall be provided for smooth and gentle mixing and tablet turnover during pan rotation.
2	Aqueous Base Film Coating.	1. Electrically operated Peristaltic Dosing Pump having silicon tubing shall be provided for product dosing 1Nos of air borne spray guns having air inlet and liquid connection mounted on specially designed header assembly.
3	Air Handling Unit	1. Hot Air System: Air Inlet shall be having 5-micron filter. Air Blower shall be driven 0.25 HP 230 V electric motor 2. Heating shall be done with electrical heater having heating load of 3 K.W. 3. Exhaust System: Exhausting of air from the pan shall be done with air blower that shall be driven with 0.5 HP 230 V electric motor.
4.	<u>Control Panel</u>	The control panel comprise of the following: 1. Hot Air Blower RPM – Indication & Control 2. Exhaust Air Blower RPM - Indication & Control 3. Pan Motor RPM – Indication & Control 4. Inlet Air Temperature – Indication & Control 5. Exhaust Air Temperature- Indication 6. Product Temperature – Indication 7. Atomization Pressure – Indication & Control

Price: UNICOATER LAB: PERFORATED PAN AUTOMATIC TABLET COATER

Sn	Price	Item
1.	Rs.15,00,000/-	For UNICOATER LAB Tablet Coater Complete Unit as above with manual control panel and peristaltic pump. The loading capacity of this Auto coater shall be 100gm, 200gm, 500gm to 1kg depending on the interchangeable perforated pan size connected to the machine.
2.	Rs.2,95,000/-	For 100gm and 200gm bowl with 1.2mm hole for coating of COMPRESSED minitabs.
3.	Rs. 5,50,000/-	For Mitsubishi with 5.7" Touchscreen for controlling and monitoring the coating process. The PLC shall be supplied with a Dot Matrix printer for online data recording.
4.	Rs. 85,000/-	For Indication of spray rate in gm/min directly on the PLC. This eliminates the need for calibrating the peristaltic pump for different RPM and different viscosity solution.
5.	Rs. 3,50,000/-	For Dehumidifier based on DX refrigerant type system.
6.	Rs. 55,000/-	For Installation and Commissioning. - Level floor. - Foundation and necessary masonry work if required. - Shifting of equipment at site. - Electrical wiring upto the equipment as per our instructions. - Steam connection along with necessary steam fittings such as steam trap, strainer etc. and steam controlling device. - Necessary unskilled help at your cost. To and Fro Travel Charges from site, local lodging, boarding and conveyance to be in clients scope of supply.
7.	Rs 25,000/-	For validation documents comprising of DQ/IQ/ and OQ

UNICOATER WITH PLC CONTROL PANEL



INTERCHAGEABLE BOWLS



8. UNIFLUID1.1- FLUID BED PARTICLE COATER GRANULATOR

Sn.	Item	Description
1.	<u>General Construction</u>	a. All the contact parts shall be made from S.S. 316 quality material and non-contact parts shall be made from S.S. 304 quality material. b. Product Container shall be lifted and sealed against expansion chamber with help of pneumatic cylinders. Or sealing shall be done with help of pneumatically inflatable gaskets. c. Strategically mounted observation windows for viewing coating process.
2	<u>Product Container</u> <u>Wurster Coating</u>	a. Product container shall be made of Stainless Steel AISI 316, for WURSTER coating applications. b. It shall have capacity of 2 liters for pellet coating. c. It shall have an oblong shape observation window duly fitted with toughened observation glass. It shall be mounted on a trolley fixed with nylon castors for movement. d. Height of the Wurster Column shall be adjusted manually against the graduated scale for one Wurster fixed inside e. Product Container shall have temperature sensing port and sampling port for extracting small quantities of coated substrate during operation. f. Product Container shall be mirror polished. g. Air atomizing spray nozzle will be of 1mm size. h. The distribution plate & bottom mesh shall be made from S.S. 316. i. The machine shall be supplied with 4Nos of silicon molded mesh of 60#, 100#, 250# and 24x110# j. The machine shall also be supplied with 4 Nos of Wurster plates, A, B, C and D.

3.	<u>Product Container</u> <u>Top Spray & Drying</u>	a. It shall be made from S.S. 316 for Top-Spray Granulation / Drying applications b. It shall have capacity of 4 liters for Top Spray Granulation. (Minimum 300gm-Maximum 1000gm) c. It shall have oblong observation window at the front fitted with toughened observation glass. d. Spray nozzle of atomizing air shall be of 1 mm size. There shall be 2 ports for adjusting nozzle height. e. Product Container shall have temperature sensing port and sampling port for extracting small quantities of coated substrate during operation. f. Product Container shall be mirror polished. g. The machine shall be supplied with 24x110# and 50 x 250#. h. Blind Ports shall be provided to operate the machine in drying mode.
4	<u>Inlet Air Filtration</u>	a. Air Handling Unit shall be made from S.S. 304. Air Handling Unit shall consists of:- b. 5-micron Pre-Filter. All gaskets used will be in Silicon Rubber. c. Heating coil section 4.5 K.W. electric heaters. The heater box shall be duly insulated. d. Dehumidifier and Humidifier System shall be supplied at an extra cost if required.
5	<u>Spraying System</u>	a. For Top spray nozzles shall be of 1 mm. (0.8mm Nozzles are available as an option). b. Electrically operated peristaltic pump shall be provided for supply of fluid dosing to media nozzle via suitable silicon tubing. c. Pump shall have 1-3000 ml./min flow rate.
6	<u>Filter Chamber</u>	a. There shall be dual bag filtration system. The partition type filtration system shall be designed for smooth uninterrupted coating process. b. Satin cotton bag shall be provided for filtration during granulation and drying. There shall be dual partition system of filter bag c. Epitropic bag shall be provided also for static charge intensive product coating. d. The filter bags shall be cleaned with automatic pneumatic shaking logic in PLC.

7	<u>Exhaust Blower</u>	a. Exhaust Blower shall be driven by inverter based 1 H.P. non-flameproof blower for drawing air through coater and enabling fluidization of particles. b. Required draught of air shall be produced by aluminum impeller housed in S.S. casing. c. Exhaust blower shall be fitted with inverter drive to control the fluidization air.
8	<u>Safety Features</u>	a. Machine shall have Earth Monitoring Device. Proper earthing shall be done for following parts through measurement probes (3 nos.): i. Filter Chamber cum Expansion Chamber ii. Product Chamber. b. Peristaltic Pump shall not start in event of inadequate pressure (less than 3 Kgs) in nozzle line. It shall On the LED for Pump. c. Heaters interlocked with Blower.
9	<u>Automation & Control</u>	Manual Control Panel shall be provided with along with the machine. The panel shall have provision to control the following: 1. Control and Indicate Blower Speed in % 2. Control & Indicate Inlet Air Temperature 3. Indicate Exhaust Air Temperature 4. Indicate Product Temperature 5. Control & Indicate Spray Pump RPM 6. Control & Indicate on Manual Gauge Spray Atomization Pressure

PRICE: UNIFLUID 1.1 LABORATORY MODEL FLUID BED PROCESSING SYSTEM

Sn.	Price	Item
1.	Rs. 28,50,000/-	Fluid Bed Processing System with following: 1. Top spray Bowl. 2. Bottom spray Bowl. 3. Top Spray and Bottom Spray Nozzles. 4. Peristaltic pump. 5. Weighing Scale integrated with PLC 6. Fully automatic control system comprising of Mitsubishi PLC and 10.1" Mitsubishi Touchscreen, 7. EPSON Printer for Datalogging. 8. Four Plates for Wurster Coating A, B, C & D 9. Four Silicon Molded Meshes for Bottom Spray 60#, 80#, 100# & 200# 10. Two Different Meshes for Top Spray 24x110# and 50x250# 11. Three different filter bags, PC Satin, Epitropic and Bonnet Bag
2.	Rs. 8,50,000/-	For Humidifier System comprising of Steam Generator. It shall be heated electrically. Client shall have to supply pure steam line of ½". The humidifier shall control the pressure of steam to provided necessary flow. It shall be provided with safety relief valve and auto drain.
3.	Rs. 5,50,000/-	For Dehumidifier system comprising of DX system and rotor assembly for low RH conditions.
4.	Rs. 75,000/-	For Installation and Commissioning. 1. Level floor. 2. Foundation and necessary masonry work if required. 3. Shifting of equipment at site. 4. Electrical wiring upto the equipment as per our instructions. 5. Steam connection along with necessary steam fittings such as steam trap, strainer etc. and steam controlling device. 6. Necessary unskilled help at your cost. To and Fro Travel Charges from site, local lodging, boarding and conveyance to be in clients scope of supply.
5.	Rs. 25,000/-	For set of validation documents comprising of DQ/IQ/OQ

UNIFLUID1.1-FLUID BED PARTICLE COATER GRANULATOR



8. UNIEXTRUDER – SINGLE SCREW EXTRUDER

Sn.	Item	Description
1.	System Description	USSE60– UNIEXTRUDER SINGLE SCREW EXTRUDER for processing extrudates. This method of extrusion has single screw transferring the material to the pressing cam, which in turn press the material on the required size of perforated mesh. Single screw CONICAL discharge design extruder.
2.	Capacity	USSE 60 Maximum processing capacity: 1-5 kg/hr. Note: Output depends upon the Bulk density and material specific properties.
3.	Material Of Construction	All the contact parts shall be made in S.S. 316 quality material. All non-contact parts shall be made from S.S. 304 quality material except bought out materials like motors and gear box.
4.	Extruder	Extruder assembly consists of a conveying screw & pressing flute. The assembly is closed by quick remove tri-clover clamps for ease in operation. Standard conical mesh with 1mm diameter die plate is to be provided along with machine.
5.	Feeding Assembly	Feed hopper shall be mounted above the extrusion assembly, the function of this hopper is to feed the transfer screws. The feeding hopper shall be made from S.S 316 quality material.
6.	Gear Box And Motor Assembly	A suitable gear box (Italian Make or equivalent make) consisting of a pair of Spur Gear & Worm gears shall be used to transmit power. A variable speed drive of ABB OR EQUIVALENT MAKE shall be used to regulate the speed of the screw from minimum to maximum. 1/2 HP TEFC, 1440 RPM, IP-55 flange mounted electric motor shall be provided to drive the gear box assembly.
7.	Controls	It shall be stand alone type. It shall have: - 1. ON/OFF Push button for Motor with MCB 2. Speed Controller for screw. 3. R.P.M. display (digital).

PRICE: UNIEXTRUDE- USSE60 - LABORATORY MODEL EXTRUSION SYSTEM

Sn.	Item	Description
1.	Rs. 6,50,000/-	For Single Screw Extruder as Described Above with conical discharge assembly with 1mm mesh.
2.	Rs. 2,85,000/-	For mesh pack (Set of four different size of meshes for conical extrusion) 0.6mm, 0.8 mm, 1.2mm, 1.5mm (OPTIONAL)
5.	Rs. 25,000/- per day per Engineer	For Installation & Commissioning
6.	Rs. 25,000/-	For Validation Documents comprising of DQ/IQ and OQ

UNIEXTRUDER: SINGLE SCREW EXTRUDER



9. UNISPHERE 150-SPHERONIZER

Sn	Item	Description
1.	System Description	UNISPHERE 150-Spheronizer generates spherical shape pellets which come out from an extruder. It is a downstream process of any extruder.
2.	Capacity	USP-150 Maximum processing capacity: 100-200gm/batch. Note: Output depends upon the Bulk density and material specific properties.
3.	Material of Construction	All the contact parts shall be made in S.S. 316 quality material. All non-contact parts shall be made from S.S. 304 quality material except bought out materials like motors and gear box
4.	Drum Assembly	A 150mm drum product container cylindrical in design shall be provided. Discharge chute shall be provided on the side of the product drum. It shall be fixed with dynamically balanced friction plate of 3.25mm pitch. 0.5 HP TEFC, 1500 RPM ELECTRIC MOTOR shall be provided to rotate the friction plate. It shall be easily removable for cleaning with screw arrangement. Drum cover. Made in Acrylic. It shall have a small opening for feeding material during operation.
5.	Discharge Assembly	Hopper made in Stainless Steel 316 fixed with acrylic cover for discharge.
6.	Controls	To be mounted on machine / fixed separately. ON/OFF Push button for Motor & MCB. RPM indication controlled by Frequency drive

PRICE: UNISPHERE150

Sn.	Price	Description
1)	Rs. 3,50,000/-	For Spheronizer as described above with a Friction plate suitable for 1mm to 2mm pellet size.
2)	Rs. 95,500/-	Friction plate suitable for spheronizing extrudates between 0.5mm & 0.8mm size.
3)	Rs. 75,000/-	Friction plate suitable for spheronizing extrudates between 2mm to 4mm.
4)	Rs. 25,000/- per day per Engineer	For Installation & Commissioning
5)	Rs. 25,000/-	For Validation Documents comprising of DQ/IQ and OQ

SPHERONIZER:: USPH 150



4. UNISPRAY - Laboratory Spray Dryer with 1 lit/hr capacity.

Sn	Item	Description
1	Main Unit	1. The main body of dryer shall be made from Stainless Steel 304. It shall be polished to matt finish from outside. 2. The spraying chamber shall be made from toughened borosilicate glass and shall be fitted with easily removable clamps for cleaning purpose. 3. The chamber shall be fitted with a glass bottle at the bottom for recovery of heavy fraction of material. 4. A cyclone separator made from glass shall fitted at the exhaust for recovering of fine fraction. At the exhaust of cyclone separator a fine filter chamber shall be provided which will prevent escape of fines to the exhaust blower. A collection bottle made of glass shall be provided at the bottom of the cyclone separator.
2	Spray Nozzle	1. A air atomised two fluid spray nozzle made from S.S. 316 shall be made for co-current spraying. The nozzle shall be of 0.7mm. Other nozzle sizes are available on request. The spray nozzle shall have an nozzle cleaning facility. 2. Electrically operated Peristaltic Dosing Pump having silicon tubing shall be provided for product dosing 1Nos of air borne spray guns having air inlet and liquid connection mounted on specially designed header assembly.
3	Air Handling Unit	1. Inlet air shall be filtered using pre filter. 2. Heating shall be done with electrical heater having heating load of 2 K.W. 3. Exhaust System: Exhausting of air from the spray chamber shall be passed through an air scrubber (filter). It shall be fitted with Differential pressure gauge for indication of filter cleaning requirement.
4.	<u>Control Panel</u>	The control panel shall be fitted with Manual Switches for switching on the exhaust air blower. There shall be speed controller for Blower and Spray Pump. Inlet and Exhaust Air Temperatures shall be indicated on the control panel.

Price: UNISPRAY Laboratory Spray Dryer.

Sn	Price	Item
1	Rs 8,00,000/-	For complete laboratory spray drying unit as described above with Exhaust Filter System fitted with Differential Pressure Gauge.
2	Rs. 1,15,000/-	For additional Glass parts Set
3	Rs. 5000/-	For additional set of Silicon O-ring for whole machine
4	Rs. 3,000/-	For additional '6' meter Extra Silicon tube
5	Rs. 15,500/-	For additional Spare nozzle and needle set 1 mm
6	Rs. 15,00/- per bag	For additional exhaust filter bag
7	Rs. 2,500/-	For additional electrical heater
8	Rs. 3,000/-	For additional Silicon O-ring set for nozzle
9	Rs. 25,000/- per day per Engineer	For Installation & Commissioning at your premises.
10	Rs. 25,000/-	For set of validation documents comprising of DQ, IQ & OQ

UNISPRAY LAB SPAY DRYER



Terms and Conditions:

Prices : Prices offered are net-ex-works Mumbai exclusive of Packing, Carting, Crating, Forwarding, Freight and any other incidental charges will be extra to your account.

Taxes : **GST (18%) shall be applied.**

Packing : **2.5% Extra is Packing And Forwarding Charges**

Excise : **NIL**

Inspection : Final Inspection prior to dispatch will have to be carried out jointly by us and your representative at our Mumbai works only. You will be intimated as soon as the machines are ready for dispatch.

Transport : **Extra to be paid by you directly to the transporter.**

Delivery : **Within 16-20 Weeks.**

Payment : 1. 40% Advance on confirmation of order.
2. Balance against proforma invoice through D.D.

Validity : This offer is valid for 30 days.

Warranty : We undertake to make good by replacement or repair, defects arising out of faulty design, materials or workmanship within 12 months of the date of dispatch, purely on ex-works basis i.e., the defective part will be returned by the buyer to our works and replacement taken by the buyer from our works. Bought-out components are guaranteed by us only to the extent of guarantees given to us by our suppliers. Electrical components, such as heaters, motors, contactors etc. rubber components and instruments such as pressure gauges, thermometers, etc. and other such consumables, etc. are however not covered under this Warranty. Warranty stands void if spare parts other than OEM are used.

Jurisdiction : Any dispute arising out of this quotation is subject to the **JURISDICTION OF MUMBAI COURT ONLY**. All dimensions are approximate.

We reserve the right of any technical deviations or modifications in design of all our products due to changes in suppliers situation.

Thanking you and awaiting for your favorable reply.

Yours truly,
For Hugopharm Technologies Pvt. Ltd.

Mr. Hiren Panchal
Tel: 022-24226882 / 022-24222815