



HUGOPHARM

Systems Engineered with Mind and Spirit

Hugopharm Technologies Pvt. Ltd.

Regd Office: 8, Jogani Industrial Estate, 541 Senapati Bapat Marg, Dadar (W), Mumbai 400028

Contact : Tel: 91-22-24226882 / 91-22-24222815 ; sales@sbpanchal.com

Our Ref. No. HUGO/0206/2025-1

02-06-2025

To,

Contact	Mr. Raghuvaran Natarajan
Business Phone	7708471877
Business Address	Godrej Agrovat Ltd. Andra Pradesh
E-mail	raghuvarannatarajan55@gmail.com

Dear Sir/ Madam,

We are glad to quote for the following:

- 1. UNIEXTRUDE-USSE60- SINGLE SCREW EXTRUDER*
- 2. UNISPHERE-150- SPHERONIZER*
- 3. UNIFLUID -NANO – RAPID FLUID BED DRYER*
- 4. UNIMIX-S LABORATORY PLANETARY MIXER*

Sincerely,

For Hugopharm Technologies Pvt Ltd.,

Hiren Panchal

1.UNIEXTRUDER – SINGLE SCREW EXTRUDER

Sn.	Item	Description
1.	System Description	USSE60– UNIEXTRUDER SINGLE SCREW EXTRUDER for processing extrudates. This method of extrusion has single screw transferring the material to the pressing cam, which in turn press the material on the required size of perforated mesh. Single screw CONICAL discharge design extruder.
2.	Capacity	USSE 60 Maximum processing capacity: 1-5 kg/hr. Note: Output depends upon the Bulk density and material specific properties.
3.	Material Of Construction	All the contact parts shall be made in S.S. 316 quality material. All non-contact parts shall be made from S.S. 304 quality material except bought out materials like motors and gear box.
4.	Extruder	Extruder assembly consists of a conveying screw & pressing flute. The assembly is closed by quick remove tri-clover clamps for ease in operation. Standard conical mesh with 1mm diameter die plate is to be provided along with machine.
5.	Feeding Assembly	Feed hopper shall be mounted above the extrusion assembly, the function of this hopper is to feed the transfer screws. The feeding hopper shall be made from S.S 316 quality material. S.S. 316 feed tray shall be provided with proximity switch which shall be placed over the screw hopper for feeding with safety interlock.
6.	Gear Box And Motor Assembly	A suitable gear box (Italian Make or equivalent make) consisting of a pair of Spur Gear & Worm gears shall be used to transmit power. A variable speed drive of ABB OR EQUIVALENT MAKE shall be used to regulate the speed of the screw from minimum to maximum. 1/2 HP TEFC, 1440 RPM, IP-55 flange mounted electric motor shall be provided to drive the gear box assembly.
7.	Controls	It shall be stand alone type. It shall have: - 1. ON/OFF Push button for Motor with MCB 2. Speed Controller for screw. 3. R.P.M. display (digital). 4. 30mA ELCB shall be provided in incomer 5. Control Voltage shall be 110V. Any other safety feature required for compliance to unilever standard requiring modification to equipment shall be charged extra.

PRICE: UNIEXTRUDE- USSE60 - LABORATORY MODEL EXTRUSION SYSTEM

Sn.	Item	Descripti on
1.	Rs. 7,75,000/-	For Single Screw Extruder as Described Above with conical discharge assembly with 1mm mesh.
2.	Rs. 4,00,000/-	For mesh pack (Set of four different size of meshes for conical extrusion) 0.5mm, 0.6mm, 0.8 mm, 1.2mm, 1.5mm (OPTIONAL)
3.	Rs. 55,000/- per day per Engineer	For Installation & Commissioning

2. UNISPHERE 150-SPHERONIZER

S n.	Item	Description
1.	System Description	UNISPHERE 150-Spheronizer generates spherical shape pellets which come out from an extruder. It is a downstream process of any extruder.
2.	Capacity	USP-150 Maximum processing capacity: 100-200gm/batch. Note: Output depends upon the Bulk density and material specific properties.
3.	Material of Construction	All the contact parts shall be made in S.S. 316 quality material. All non-contact parts shall be made from S.S. 304 quality material except bought out materials like motors and gear box
4.	Drum Assembly	A 150mm drum product container cylindrical in design shall be provided. Discharge chute shall be provided on the side of the product drum. It shall be fixed with dynamically balanced friction plate of 3.25mm pitch. 1 HP TEFC, 3000 RPM ELECTRIC MOTOR shall be provided to rotate the friction plate. It shall be easily removable for cleaning with screw arrangement. Drum cover. Made in Acrylic. It shall have a small opening for feeding material during operation. Drum cover shall be provided with proximity switch for safety interlock.
5.	Discharge Assembly	Hopper made in Stainless Steel 316 fixed with acrylic cover for discharge.
6.	Controls	To be mounted on machine / fixed separately. ON/OFF Push button for Motor & MCB. RPM indication controlled by Frequency drive Control voltage shall be 110V 30mA ELCB shall be provided. Any other safety feature required for compliance to unilever standard requiring modification to equipment shall be charged extra.

PRICE: UNISPHERE150

Sn.	Price	Description
1)	Rs. 4,50,000/-	For Spheronizer as described above with a Friction plate suitable for 1mm to 2mm pellet size.
2)	Rs. 1,50,000/-	Friction plate suitable for spheronizing extrudates between 0.3mm to 0.5mm.
3)	Rs. 95,500/-	Friction plate suitable for spheronizing extrudates between 0.6mm to 1.5mm.
4)	Rs. 75,000/-	Friction plate suitable for spheronizing extrudates between 2mm to 4mm.
5)	Rs. 55,000/- per day per Engineer	For Installation & Commissioning

3. UNIFLUID NANO - Rapid Fluid Bed Dryer (Capacity: 200gm~1000gm)

Sr. No	Item	Description
1.	General Construction	The machine body shall be fabricated from S.S. 304 quality material.
2.	Product Container cum Retarding Chamber	This chamber shall be fabricated from glass. It shall have a capacity of six liters.
3.	Air Circulation	The required draught shall be provided with totally enclosed fan cooled electric motor driven centrifugal impeller. The speed of the blower shall be controlled from front panel.
4.	Heating	The air shall be heated with coiled tube air heaters. The heating capacity shall be 2 K.W.
5.	Control	The process control switch board shall comprise of: Process timer, PID Temp. Controller, Air Flow Control Damper and Pilot Lamps.

- **All S.S. parts are buffed to mirror finish.**

PRICE : UNIFLUID NANO :- RAPID FLUID BED DRIER.

Sr. No	Price	Description
1.	Rs.6,50,000/-	For "Table Top Model 200-1000 gm capacity electrically heated model Fluid Bed Dryer, having all contact parts made from glass. (COMPLETE 1 SET OF UNIFLUID NANO- Rapid Fluid Bed Dryer which includes Glass bowl and a bag)
2.	Rs 15,000/-	For Validation Documents Comprising of DQ, IQ and OQ
3.	Rs. 25,000/-	For Installation & Commissioning

OPTIONS FOR EXTRA ACCESSORIES

1.	Rs. 1,25,000/-	For additional change part for product container made from glass for handling products from 50gm to 200gm.
2.	Rs. 1,25,000/-	For additional product container made from S.S. 316 containing glass view port.
3.	Rs. 25,000/-	For Product Temperature Sensor (In S.S. bowl) with indication on the panel. The Product Temperature sensor shall be made from S.S. 316 and shall have quick release connector.
4.	Rs. 2,000 /-	For extra air discharge bags made from cotton cloth. (6lit bowl)
5.	Rs. 3,750/-	For extra air discharge bag made from polyester material. (6lit bowl)
6.	Rs. 5,500/-	For extra air discharge bag made from epitropic polyester material. (6lit bowl)
7.	Rs. 550 /-	For extra air discharge bags made from cotton cloth. (300ml bowl)
8.	Rs. 1,250/-	For extra air discharge bag made from polyester material. (300ml bowl)
9.	Rs. 2,500/-	For extra air discharge bag made from epitropic polyester material. (300ml bowl.)
10.	Rs. 8,500/-	For Surge Suppressor for Protection from any Electrical Power Surge.

UNIFLUID NANO: with glass bowl
Standard supply



UNIFLUID NANO with interchangeable bowl (capacity: 50 gm- 200gm) optional



UNIFLUID NANO with S.S Bowl



UNIFLUID NANO with Product Temp Sensor



4. UNIMIX-S Laboratory Planetary Mixer (Capacity: 4.5 liter)

Sr. No	Item	Description
1.	General Construction	The machine body shall be fabricated die cast aluminum and product contact part shall be made from Stainless Steel quality material. The Working capacity of the mixer shall be 4.5 liters.
2.	Mixing Chamber	This mixing chamber shall be fabricated from Stainless Steel quality material. Three types of mixing elements shall be provided.
3.	Drive Mechanism	The Unit will have power consumption of 1400Watts. There shall be 3 speed selection for the mixer selected by geared motor.
4.	Control	The process control switch board shall comprise of: ON/OFF Button and Speed Controller.

PRICE : UNIMIX-S Laboratory Planetary Mixer (Capacity: 4.5 liter)

1.	Rs. 1,55,250/-	For Laboratory Mixer as described above.
----	----------------	--



Terms and Conditions:

Prices : Prices offered are net-ex-works Mumbai exclusive of Packing, Carting, Crating, Forwarding, Freight and any other incidental charges will be extra to your account.

Taxes : **18% GST**

Packing : **2.5%**

Excise : **NIL**

Inspection : Final Inspection prior to dispatch will have to be carried out jointly by us and your representative at our Mumbai works only. You will be intimated as soon as the machines are ready for dispatch.

Transport & Insurance : **At Actual in clients Scope**

Delivery : Within 12-16 Weeks.

Payment : 1. 40% Advance on confirmation of order.
2. 60% Balance against proforma invoice through after FAT

Validity : This offer is valid for 30 days.

Warranty : We undertake to make good by replacement or repair, defects arising out of faulty design, materials or workmanship within 12 months of the date of dispatch, purely on ex-works basis i.e., the defective part will be returned by the buyer to our works and replacement taken by the buyer from our works. Bought-out components are guaranteed by us only to the extent of guarantees given to us by our suppliers. Electrical components, such as heaters, motors, contactors etc. rubber components and instruments such as pressure gauges, thermometers, etc. and other such consumables, etc. are however not covered under this Warranty. Warranty stands void if spare parts other than OEM are used.

Jurisdiction : Any dispute arising out of this quotation is subject to the **JURISDICTION OF MUMBAI COURT ONLY**. All dimensions are approximate.

We reserve the right of any technical deviations or modifications in design of all our products due to changes in suppliers situation.

Thanking you and awaiting for your favorable reply.

Yours truly,
For HUGOPHARM TECHNOLOGIES PVT LTD.
Hiren Panchal
8, Jogani Industrial Estate,
541, Senapati Bapat Marg,
Dadar West, Mumbai 400028
India
Tel: 022-24226882 / 022-30506882/ 30506884