



HUGOPHARM

Systems Engineered with Mind and Spirit

Hugopharm Technologies Pvt. Ltd.

Regd Office: 8, Jogani Industrial Estate, 541 Senapati Bapat Marg, Dadar (W), Mumbai 400028

Contact : Tel: [91-22-24226882](tel:91-22-24226882) / 91-22-24222815 ; sales@sbpanchal.com

Our Ref. No. HUGO/2606/2025-3

26-06-2025

To,

Contact	Mr. Pushpender Singh Chouhan
Business Phone	+91-0294-6651159
Business Address	PI Industries Ltd
E-mail	pushpendra.chouhan@piind.com

Dear Sir,

We are glad to quote you for,

1. UNIFLUID 1.1- Fluid Bed Coater Granulator (300gm-1000gm)

Sincerely,

For Hugopharm Technologies Pvt Ltd.,

Hiren Panchal

1. UNIFLUID1.1- FLUID BED PARTICLE COATER GRANULATOR

Sn.	Item	Description
1.	<u>General Construction</u>	a. All the contact parts shall be made from S.S. 316 quality material and non-contact parts shall be made from S.S. 304 quality material. b. Product Container shall be lifted and sealed against expansion chamber with help of pneumatic cylinders. Or sealing shall be done with help of pneumatically inflatable gaskets. c. Strategically mounted observation windows for viewing coating process.
2	<u>Product Container</u> <u>Wurster Coating</u>	a. Product container shall be made of Stainless Steel AISI 316, for WURSTER coating applications. b. It shall have capacity of 2 liters for pellet coating. c. It shall have an oblong shape observation window duly fitted with toughened observation glass. It shall be mounted on a trolley fixed with nylon castors for movement. d. Height of the Wurster Column shall be adjusted manually against the graduated scale for one Wurster fixed inside e. Product Container shall have temperature sensing port and sampling port for extracting small quantities of coated substrate during operation. f. Product Container shall be mirror polished. g. Air atomizing spray nozzle will be of 1mm size. h. The distribution plate & bottom mesh shall be made from S.S. 316. i. The machine shall be supplied with 4Nos of silicon molded mesh of 60#, 100#, 250# and 24x110# j. The machine shall also be supplied with 4 Nos of Wurster plates, A, B, C and D.

3.	<u>Product Container</u> <u>Top Spray & Drying</u>	a. It shall be made from S.S. 316 for Top-Spray Granulation / Drying applications b. It shall have capacity of 4 liters for Top Spray Granulation. (Minimum 300gm-Maximum 1000gm) c. It shall have oblong observation window at the front fitted with toughened observation glass. d. Spray nozzle of atomizing air shall be of 1 mm size. There shall be 2 ports for adjusting nozzle height. e. Product Container shall have temperature sensing port and sampling port for extracting small quantities of coated substrate during operation. f. Product Container shall be mirror polished. g. The machine shall be supplied with 24x110# and 50 x 250#. h. Blind Ports shall be provided to operate the machine in drying mode.
4	<u>Inlet Air Filtration</u>	a. Air Handling Unit shall be made from S.S. 304. Air Handling Unit shall consists of:- b. 5-micron Pre-Filter. All gaskets used will be in Silicon Rubber. c. Heating coil section 4.5 K.W. electric heaters. The heater box shall be duly insulated. d. Dehumidifier and Humidifier System shall be supplied at an extra cost if required.
5	<u>Spraying System</u>	a. For Top spray nozzles shall be of 1 mm. (0.8mm Nozzles are available as an option). b. Electrically operated peristaltic pump shall be provided for supply of fluid dosing to media nozzle via suitable silicon tubing. c. Pump shall have 1-3000 ml./min flow rate.
6	<u>Filter Chamber</u>	a. There shall be dual bag filtration system. The partition type filtration system shall be designed for smooth uninterrupted coating process. b. Satin cotton bag shall be provided for filtration during granulation and drying. There shall be dual partition system of filter bag c. Epitropic bag shall be provided also for static charge intensive product coating. d. The filter bags shall be cleaned with automatic pneumatic shaking logic in PLC.

7	<u>Exhaust Blower</u>	a. Exhaust Blower shall be driven by inverter based 1 H.P. non-flameproof blower for drawing air through coater and enabling fluidization of particles. b. Required draught of air shall be produced by aluminum impeller housed in S.S. casing. c. Exhaust blower shall be fitted with inverter drive to control the fluidization air.
8	<u>Safety Features</u>	a. Machine shall have Earth Monitoring Device. Proper earthing shall be done for following parts through measurement probes (3 nos.): i. Filter Chamber cum Expansion Chamber ii. Product Chamber. b. Peristaltic Pump shall not start in event of inadequate pressure (less than 3 Kgs) in nozzle line. It shall On the LED for Pump. c. Heaters interlocked with Blower.
9	<u>Automation & Control</u>	Manual Control Panel shall be provided with along with the machine. The panel shall have provision to control the following: 1. Control and Indicate Blower Speed in % 2. Control & Indicate Inlet Air Temperature 3. Indicate Exhaust Air Temperature 4. Indicate Product Temperature 5. Control & Indicate Spray Pump RPM 6. Control & Indicate on Manual Gauge Spray Atomization Pressure

PRICE: UNIFLUID 1.1 LABORATORY MODEL FLUID BED PROCESSING SYSTEM

Sn.	Price	Item
1.	Rs. 28,50,000/-	Fluid Bed Processing System with following: 1. Top spray Bowl. 2. Bottom spray Bowl. 3. Top Spray and Bottom Spray Nozzles. 4. Peristaltic pump. 5. Weighing Scale integrated with PLC 6. Fully automatic control system comprising of Mitsubishi PLC and 10.1" Mitsubishi Touchscreen, 7. EPSON Printer for Datalogging. 8. Four Plates for Wurster Coating A, B, C & D 9. Four Silicon Molded Meshes for Bottom Spray 60#, 80#, 100# & 200# 10. Two Different Meshes for Top Spray 24x110# and 50x250# 11. Three different filter bags, PC Satin, Epitropic and Bonnet Bag
2.	Rs. 8,50,000/-	For Humidifier System comprising of Steam Generator. It shall be heated electrically. Client shall have to supply pure steam line of ½". The humidifier shall control the pressure of steam to provided necessary flow. It shall be provided with safety relief valve and auto drain.
3.	Rs. 5,50,000/-	For Dehumidifier system comprising of DX system and rotor assembly for low RH conditions.
4.	Rs. 75,000/-	For Installation and Commissioning. 1. Level floor. 2. Foundation and necessary masonry work if required. 3. Shifting of equipment at site. 4. Electrical wiring upto the equipment as per our instructions. 5. Steam connection along with necessary steam fittings such as steam trap, strainer etc. and steam controlling device. 6. Necessary unskilled help at your cost. To and Fro Travel Charges from site, local lodging, boarding and conveyance to be in clients scope of supply.
5.	Rs. 25,000/-	For set of validation documents comprising of DQ/IQ/OQ

UNIFLUID1.1-FLUID BED PARTICLE COATER GRANULATOR



Terms and Conditions:

Prices : Prices offered are net-ex-works Mumbai exclusive of Packing, Carting, Crating, Forwarding, Freight and any other incidental charges will be extra to your account.

Taxes : GST 18%

Packing : 2.5%

Excise : NIL

Inspection : Final Inspection prior to dispatch will have to be carried out jointly by us and your representative at our Mumbai works only. You will be intimated as soon as the machines are ready for dispatch.

Transport & Insurance : At Actual in clients Scope

Delivery : Within 12-16 Weeks.

Payment : 1. 40% Advance on confirmation of order.
2. 60% Balance against proforma invoice through after FAT

Validity : This offer is valid for 30 days.

Warranty : We undertake to make good by replacement or repair, defects arising out of faulty design, materials or workmanship within 12 months of the date of dispatch, purely on ex-works basis i.e., the defective part will be returned by the buyer to our works and replacement taken by the buyer from our works. Bought-out components are guaranteed by us only to the extent of guarantees given to us by our suppliers. Electrical components, such as heaters, motors, contactors etc. rubber components and instruments such as pressure gauges, thermometers, etc. and other such consumables, etc. are however not covered under this Warranty. Warranty stands void if spare parts other than OEM are used.

Jurisdiction : Any dispute arising out of this quotation is subject to the **JURISDICTION OF MUMBAI COURT ONLY**. All dimensions are approximate.

We reserve the right of any technical deviations or modifications in design of all our products due to changes in suppliers situation.

Thanking you and awaiting for your favorable reply.

Yours truly,
For HUGOPHARM TECHNOLOGIES PVT LTD.
Hiren Panchal
8, Jogani Industrial Estate,
541, Senapati Bapat Marg,
Dadar West, Mumbai 400028
India
Tel: 022-24226882 / 022-30506882/ 30506884