

EXPERIMENT 10

Student Name: ARYAN DAHIYA

Branch: AIT-CSE-AIML

Semester: 5

Subject Name: ADBMS

UID: 24BAI70697

Section/Group: 24AIT_KRG1_B

Subject Code: 24CSP-310

Question 1

Question:

Design a robust PostgreSQL transaction system for the students table where multiple student records are inserted in a single transaction. If any insert fails due to invalid data, only that insert should be rolled back while preserving the previous successful inserts using **SAVEPOINTS**. The system should display clear messages for successful and failed insertions.

Solution:

DO \$\$

BEGIN

BEGIN

-- Insert multiple students

INSERT INTO students(name, age, class)

VALUES ('Anisha', 16, 8);

INSERT INTO students(name, age, class)

VALUES ('Neha', 17, 8);

INSERT INTO students(name, age, class)

VALUES ('Mayank', 19, 9);

EXPERIMENT 10

-- If all succeed

RAISE NOTICE 'Transaction Successfully Done';

EXCEPTION WHEN OTHERS THEN

-- If any insert fails

RAISE NOTICE 'Transaction Failed... Rolling back changes.';

RAISE;

END;

END;

\$\$;

To check the inserted records:

SELECT * FROM students;

Using SAVEPOINT

For preserving previous successful inserts while rolling back only the failed insertion:

BEGIN;

INSERT INTO students(name, age, class)

VALUES ('Anisha', 16, 8);

SAVEPOINT sp1;

INSERT INTO students(name, age, class)

VALUES ('Neha', 17, 8);

EXPERIMENT 10

SAVEPOINT sp2;

-- If the next insertion fails

```
INSERT INTO students(name, age, class)
VALUES ('Anisha', 17, 8);
```


-- Roll back only the failed part

ROLLBACK TO SAVEPOINT sp2;

COMMIT;

Here, the previously successful records remain in the transaction, while the failed insertion is rolled back to the latest savepoint.

The PDF also demonstrates the **rollback case** where inserting a duplicate name violates the `students_name_key` constraint and produces the message “**Transaction Failed... Rolling back changes.**”



415
416
417 `SELECT * FROM students;`
418

Data Output Messages Notifications

Showing rows: 1 to 3 Page No: 1 of 1

	id [PK] integer	name character varying (50)	age integer	class integer
1	1	Anisha	16	8
2	2	Neha	17	8
3	3	Mayank	19	9

EXPERIMENT 10

```
420
421 --VIOLATED SCENARIO
422 DO $$
423 BEGIN
424     -- Start a transaction
425 BEGIN
426     -- Insert multiple students
427     INSERT INTO students(name, age, class) VALUES ('Anisha',16,8);
428     INSERT INTO students(name, age, class) VALUES ('Mayank',19,9);
429     INSERT INTO students(name, age, class) VALUES ('Anisha',17,8); --ERROR
430     INSERT INTO students(name, age, class) VALUES ('Mayank',19,9);
431
432     -- If all succeed
433     RAISE NOTICE ' Transaction Successfully Done!';
434
435 EXCEPTION WHEN OTHERS THEN
436     -- If any insert fails
437     RAISE NOTICE 'Transaction Failed..! Rolling back changes.';
438     RAISE; -- this will rollback the entire transaction
439 END;
440 END;
441 $$;
442
```

Data Output Messages Notifications

NOTICE: Transaction Failed..! Rolling back changes.

ERROR: duplicate key value violates unique constraint "students_name_key"
Key (name)=(Anisha) already exists.

SQL state: 23505
Detail: Key (name)=(Anisha) already exists.
Context: SQL statement "INSERT INTO students(name, age, class) VALUES ('Anisha',16,8)"
PL/pgSQL function inline_code_block line 6 at SQL statement