
Date Query



DATE()

- `Date()`
 - Returns a date either as a string or as a [Date](#) object.
 - `Date()` returns the current date as a string in the [mongo](#) shell.
 - `new Date()` returns the current date as a [Date](#) object.
The [mongo](#) shell wraps the [Date](#) object with the `ISODate` helper
-

DATE()

- You can specify a particular date by passing an ISO-8601 date string with a year within the inclusive range 0 through 9999 to the new `Date()` constructor or the `ISODate()` function. These functions accept the following formats:
 - `new Date("<YYYY-mm-dd>")` returns the `ISODate` with the specified date.
 - `new Date("<YYYY-mm-ddTHH:MM:ss>")` specifies the datetime in the client's local timezone and returns the `ISODate` with the specified datetime in UTC.
-

DATE()

- `new Date("<YYYY-mm-ddTHH:MM:ssZ>")` specifies the datetime in UTC and returns the `ISODate` with the specified datetime in UTC.
 - `new Date(<integer>)` specifies the datetime as milliseconds since the [Unix epoch](#) (Jan 1, 1970), and returns the resulting `ISODate` instance.
-

BEHAVIOUR:

- Internally, [Date](#) objects are stored as a signed 64-bit integer representing the number of milliseconds since the Unix epoch (Jan 1, 1970).
 - Not all database operations and drivers support the full 64-bit range. You may safely work with dates with years within the inclusive range 0 through 9999
-

Examples:

Use Date In Query.

If no document with `_id` equal to `1` exists in the `products` collection, the following operation inserts a document with the field `dateAdded` set to the current date:

```
db.products.update(  
  { _id: 1 },  
  {  
    $set: { item: "apple" },  
    $setOnInsert: { dateAdded: new Date() }  
  },  
  { upsert: true }  
)
```

Return date as string

To return the date as a string, use the `Date()` method, as in the following example:

```
var myDateString = Date();
```

Return date as date object

The [mongo](#) shell wrap objects of [Date](#) type with the `ISODate` helper; however, the objects remain of type [Date](#).

The following example uses `new Date()` to return [Date](#) object with the specified UTC datetime.

```
var myDate = new Date("2016-05-18T16:00:00Z");
```

Insert and return iso date

The following example creates a `cakeSales` collection with `ISODate` objects in the `orderDate` field:

```
db.cakeSales.insertMany([  
    { _id: 0, type: "chocolate", orderDate: new  
      ISODate("2020-05-18T14:10:30Z") },  
    { _id: 1, type: "strawberry", orderDate: new  
      ISODate("2021-03-20T11:30:05Z") },  
    { _id: 2, type: "vanilla", orderDate: new  
      ISODate("2021-01-15T06:31:15Z") }  
])
```

The following example returns documents where the `orderDate` is less than the `ISODate` specified in the [`\$lt`](#) operator:

```
db.cakeSales.find( { orderDate: { $lt: ISODate("2021-02-25T10:03:46.000Z") } } )
```

Output

```
[
  {
    _id: 0,
    type: 'chocolate',
    orderDate: ISODate("2020-05-18T14:10:30.000Z")
  },
  {
    _id: 2,
    type: 'vanilla',
    orderDate: ISODate("2021-01-15T06:31:15.000Z")
  }
]
```
