✅ STEP 1: Check if kubeconfig exists

Run:

```bash
ls ~/.kube
```

👉 If you see:

```
config
```

✔️ Good → use it in Jenkins

👉 If NOT → follow below 👇

ls ~/.kube

🔷 OPTION A: Using Docker Desktop (EASIEST)

1. Open **Docker Desktop**
2. Go to **Settings → Kubernetes**
3. Enable:
   ✔️ Enable Kubernetes
4. Click **Apply & Restart**

👉 After that run:

```bash
kubectl config view
```

✔️ Now file will be created automatically:

```
~/.kube/config
```

kubectl config view

~/.kube/config

🔷 OPTION B: Using Minikube

Run:

```bash
minikube start
```

👉 Then:

```bash
kubectl config view
```

✔️ This also creates:

```
~/.kube/config
```

minikube start
kubectl config view
~/.kube/config

🔷 OPTION C: Create manually (LAST OPTION)

If nothing works:

```bash
mkdir -p ~/.kube
touch ~/.kube/config
```

👉 But ⚠️ this is empty — not useful unless configured

mkdir -p ~/.kube
touch ~/.kube/config

✅ STEP 3: Add to Jenkins

Once file exists:

👉 Jenkins → Manage Jenkins → Credentials → Add

- Kind: **Secret file**
- Upload: `~/.kube/config`
- ID: `kube-config`

~/.kube/config
kube-config

🔄 ALTERNATIVE (EASIER FOR YOU)

If file upload fails:

👉 Use "Secret Text"

1. Run:

```bash
cat ~/.kube/config
```

2. Copy FULL output
3. In Jenkins:

- Kind: **Secret Text**
- Paste it
- ID: `kube-config`

cat ~/.kube/config

⚠️ VERY IMPORTANT CHECK

Run:

```bash
kubectl get nodes
```

👉 If you see:

```
node    Ready
```

✅ Kubernetes is working

❌ If error → Jenkins deployment will fail

kubectl get nodes

node Ready