

Calcium Stearate (CS) – SCI-105-CS

Stabplast SCI-105- CS (Calcium Stearate) acts as an excellent internal and external lubricant, which reduces, inter frictional heat build up arising out of inter-particle friction during processing of PVC. This non toxic product reduces effective melt viscosity, gives excellent resistance to colour degradation and also helps to impart a smooth surface finish.

Calcium Stearate is being widely used in rigid pipes, fittings, conduits, wires, cables, shoes and leather cloth. The product is also being used in non toxic FDA approved compounds.

Physical and Chemical Properties

Description	Fine White Powder; Insoluble in Water, Ethanol & Ether, soluble in hot pyridine.
Chemical Formula	$\text{Ca}(\text{C}_{17}\text{H}_{35}\text{COO})_2$
CAS RNo	1592-23-0
Calcium Content	8 - 9 %
Specific Gravity	1.0-1.3
Molecular Weight	606.61 g/mol
Melting Point	155-160°C
Free Fatty Acid (FFA)	1% Max
Moisture	3% Max
Particle Size (Microns)	63 (230 Mesh) (Finer material available on request)
Packing	25 Kg HDPE Bag with Liner.

Samples and Further Technical details available on request

Stabplast's products are manufactured under strict process parameters and standardized procedures to provide finest quality product every time.

