

Lead Stearate (LS) SCI-120-LS

Stabplast's SCI -120-LS (Lead Stearate) is an excellent lubricant with a stabilizing action. It is similar to Dibasic Lead stearate SCI-150-DBLS but has a greater lubricity and less stabilizing action. SCI-120-LS has better dispersion in PVC due to its lower melting point. It provides smooth surface to rigid as well as flexible PVC products and is being used as general purpose stabilizer in PVC processing for extrusion, injection moulding, wires and cables, rigid pipes, fitting and profiles.

Lead Stearate is generally used in conjunction with other Lubricants and stabilizers such as TBLS, DBLS, DBLP, CS, etc.

Physical and Chemical Properties

Description	Fine White Powder, Insoluble in Water. Soluble in Hydrochloric and Nitric Acid.
Chemical Formula	$Pb(C_{17}H_{35}COO)_2$
CAS RNo	1072 - 35 - 1
Lead Content (as PbO)	29-30%
Specific Gravity	1.3-1.4
Molecular Weight	773.51 g/mol
Melting Point	105-110°C
Free Fatty Acid (FFA)	1% Max
Moisture	1% Max
Ash Content	28-30%
Particle Size (45 Micron/325 Mesh)	99% Passing (Finer material available on request)
Packing	25 Kg HDPE Bag with Liner.

Samples and Further Technical details available on request

Stabplast's products are manufactured under strict process parameters and standardized procedures to provide finest quality product every time.

