

## **Zinc Stearate (ZS) – SCI-135-ZS**

Stabplast SCI-135- ZS (Zinc Stearate) acts as an excellent lubricant and dispersing agent apart from adding high heat stability in the PVC. It forms the basis of the non lead based stabilizer system and plays the major role in these stabilizers. This non toxic product reduces gives good heat stability when used in conjunctions with other stabilizers.

Zinc Stearate is being widely used in rigid pipes, fittings, conduits, cables, shoes, activator for rubber products and in the paint industry. The product is also being used in non toxic FDA approved compounds, master batches and cosmetics among others.

### **Physical and Chemical Properties**

|                         |                                                                                  |
|-------------------------|----------------------------------------------------------------------------------|
| Description             | Fine White Powder; Insoluble in Water, Ethanol & Ether, soluble in hot pyridine. |
| Chemical Formula        | $Zn(C_{17}H_{35}COO)_2$                                                          |
| CAS RNo                 | 557-05-1                                                                         |
| Zinc Content            | 10 – 11.5 %                                                                      |
| Specific Gravity        | 1.0-1.3                                                                          |
| Molecular Weight        | 632.33 g/mol                                                                     |
| Melting Point           | 118-125°C                                                                        |
| Free Fatty Acid (FFA)   | 1% Max                                                                           |
| Moisture                | 2% Max                                                                           |
| Particle Size (Microns) | 63 (230 Mesh) (Finer material available on request)                              |
| Packing                 | 25 Kg HDPE Bag with Liner.                                                       |

Samples and Further Technical details available on request

Stabplast's products are manufactured under strict process parameters and standardized procedures to provide finest quality product every time.

