

Tri Basic Lead Sulphate (TBLS) SCI-180-TBLS

Tri Basic Lead Sulphate is a non-lubricating type Lead stabilizer, which remains stable at elevated temperature without decomposition, ensuring sound products with absence of porosity. It is an exceptionally powerful heat stabilizer with a low cost. It is pulverized to provide very narrow particle distribution for better dispersion of the product.

TBLS is being used for manufacturing of rigid PVC pipes and fittings, wires and cables, soil pipes for conveyance of gases and liquids, rigid profiles, floor coverings, reinforced suction hoses, etc. It should be used in conjunction with Lubricants and other Stabilisers such as DBLS, DBLP, LS, CS among others.

Physical and Chemical Properties

Description	Fine White powder, insoluble in water, no combustibility, no corrosiveness; Soluble in heated Acetate Ammonium and Nitric Acid.
Chemical Formula	$3\text{PbO} \cdot \text{PbSO}_4 \cdot \text{H}_2\text{O}$
CAS RNo	12202-17-4
Lead Content(as PbO)	88-89%
Specific Gravity	6.5 -7.0
Molecular Weight	990.74 g/mol
Melting Point	900°C
Moisture	1% Max.
Particle Size (Microns)	44 (325 Mesh) (Finer material available on request)
Packing	25 Kg HDPE Bag with Liner.

Samples and Further Technical details available on request

Stabplast's products are manufactured under strict process parameters and standardized procedures to provide finest quality product every time.

