

PART A – THEORY

Difference Between As-Is and To-Be Process Models

As-Is Process Model:

The As-Is process model represents the current state of a business process as it exists today. It documents how activities are actually performed, including workflows, roles, delays, and inefficiencies. The main objective of the As-Is model is to understand the present system and identify problems or bottlenecks.

To-Be Process Model:

The To-Be process model represents the future or desired state of a process after improvements are implemented. It shows how the process should work once changes such as automation, optimization, or new systems are introduced. The To-Be model focuses on efficiency, effectiveness, and alignment with business goals.

Why As-Is and To-Be Should Not Be Mixed:

As-Is and To-Be models should never be mixed in the same diagram because they serve different purposes. Mixing them creates confusion between the current and proposed processes. This can lead to misunderstandings, incorrect analysis, and poor system design decisions. Keeping them separate ensures clarity and accurate communication among stakeholders.

Why UML Use Case and Activity Diagrams Are Both Required

A UML Use Case diagram explains what the system does from the user's perspective. It identifies actors and their interactions with the system, helping define system scope and functional requirements. It answers the question: Who can do what with the system?

A UML Activity diagram explains how the system works internally. It shows the sequence of activities, decisions, and workflow logic. This helps in understanding process flow and system behavior. It answers the question: How does the system operate step by step?

Both diagrams are required together to ensure that user requirements and process logic are accurately converted into a complete and effective system design.