Retrieval-Augmented Generation (RAG) → Perplexity AI



improve the LLM output

1. up to date
2. accuracy ↑
3. fact based ↑


1. Hallucination — making things up
2. Not upto date


Information Retrieval

RAG

Architecture

RAG architecture





SQL - traditional DB based
name = "Harry Potter"


vector DB
→ wizards, children fantasy

RAG

Data Ingestion Pipeline

context size

LLM



text → nums

vector embeddings

① Data Ingestion → ② Embedding → ③ Vector DB → Knowledge Base

pdf
html
db
excel
⋮

⇓


process/clean

⇓

chunks


- OpenAI embedding models
- sentence transformer

Pinecone
FAISS
chromadb
⋮



RAG

Retrieval Pipeline



- Nearest neighbour search

- Cosine Similarity (vectors)

cosine dist ↓

cosine similarity = 1 − cosine dist

semantic / similarity search

① Retrieval

vector DB

④ Query Processing

Query Embeddings

Query

⑥ Augmentation

context

top K similar results

+ prompt

LLM


o/p generate


⑦ Generation

APNA COLLEGE

RAG

Retrieval Pipeline






Query Processing → Retrival → Augmentation → Generation

Python

Ingestion Pipeline Implementaion

using LangChain




① Document → object
& ① text / page_content
② metadata
}

② Document Loaders


Ingestion Pipeline Implementaion

Chunks



Ingestion Pipeline Implementaion

Embedding



Embedding manager


obj

code reusability ↑

Query Embedding

Ingestion Pipeline Implementaion

Vector Store




→ Vector Store Managers

1. initialize vector store – content
2. VS_ initialize → path, collection
3. store docs → VS

APNA COLLEGE

Retrieval Pipeline Implementaion

Retriever





RAG Retriever

return a list of results (context)