MINOR PROJECT
On

Food Nutrition Estimator from Image and Text using AI

Submitted to

Amity University, Uttar Pradesh

In partial fulfillment of the requirements for the award of the degree of

Bachelor of Technology
in
Computer Science and Engineering
by

Aryan Walia
Subham Prasad Archary
Kushagra Pankaj

A023166922038
A023166922045
A023166922048

B.TECH CSE IOT AND CYBERSECURITY INC BCT

2022-2026

Under the guidance of

DR. Roshan Lal

DEPARTMENT OF COMPUTER SCIENCE AND ENGINEERING

AMITY SCHOOL OF ENGINEERING AND TECHNOLOGY

AMITY UNIVERSITY UTTAR PRADESH

NOIDA (U.P.)

DECLARATION

We, Aryan Walia, Subham Prasad Archary, Kushagra Pankaj student of B. Tech CSE IOT and Cybersecurity including BCT hereby declare that the Minor Project titled "Food Nutrition Estimator From Image and Text using AI" which is submitted by me to the Department of Computer Science and Engineering, Amity School of Engineering and Technology, Amity University Uttar Pradesh, Noida, in partial fulfillment of the requirement for the award of the degree of Bachelor of Technology in Computer Science and Engineering, has not been previously formed the basis for the award of any degree, diploma or other similar title or recognition.

Place: NOIDA

Aryan Walia
A023166922038

Subham Prasad Archary
A023166922045

Kushagra Pankaj
A023166922048

CERTIFICATE

On the basis of the declaration submitted by ARYAN WALIA, SUBHAM PRASAD ARCHARY, KUSHAGRA PANKAJ student of B.TECH Computer Science and Engineering (Internet Of Things and Cybersecurity including Block Chain Technology), I hereby certify that the Minor Project titled "Food Nutrition Estimator From Image and Text using AI" which is submitted to Department of Computer Science and Engineering, Amity School of Engineering and Technology, Amity University, Noida, in partial fulfillment of the requirement for the award of the degree of Bachelor of Technology in Computer Science and Engineering is an original contribution with existing knowledge and faithful record of work carried out by him/her under my guidance supervision.

To the best of my knowledge, this work has not been submitted in any part or full for any degree or diploma to this university or somewhere else.

Place: NOIDA

Dr. Roshan Lal
Department of Computer Science and Technology
Amity School of Engineering and Technology
Amity University Uttar Pradesh, Noida, UP

ACKNOWLEDGEMENT

I would like to thank my Head of Department Prof (Dr.) Sanjeev Thakur for his direction in my term paperwork as an important aspect of the curriculum and for constantly guiding me.
Secondly, I would like my term paper guide Dr. Roshan Lal under whose guidance I was able to complete my research and term paper. I am highly thankful to him for giving me his valuable time and attention and providing me with various research papers which helped in my research.

ARYAN WALIA
A023166922038
SUBHAM PRASAD ARCHARY
A023166922045
KUSHAGRA PANKAJ
A023166922048

Index

TABLE OF CONTENTS **Page No.**

Declaration	2
Certificate	3
Acknowledgment	4
Index	5
Abstract	6
Introduction	7-9
Literature Review	10-24
Problem Definition	25-28
Objectives	29-32
Methodology	33-38
System Design & Implementation	39-41
Analysis	42-43
Challenges and Limitations	44-45
Conclusion	46
Future Directions	47-48
References	49-51

ABSTRACT

The significance of precise and effective nutrition monitoring has been brought to light by the growing concern over lifestyle-related diseases such obesity, diabetes, and cardiovascular ailments [7]. Conventional methods of food logging, such manual entry using diet-tracking apps, frequently have issues with underreporting, inaccuracy, and noncompliance [13]. By automating food detection and nutritional estimate with computer vision and natural language processing (NLP) techniques, artificial intelligence (AI) provides a novel way to get around these restrictions [2].

With the help of this project, "Food Nutrition Estimator from Image and Text using AI," users can either take a picture of their food or write a description of it. Advanced deep learning models like Convolutional Neural Networks (CNNs), such as ResNet and EfficientNet, are used for image-based recognition in order to accurately classify food products [19]. NLP models are used to extract semantic meaning from dish descriptions and map them to standardised nutritional IFCT databasees for text-based inputs. These models range from transformer-based models like BERT to the traditional TF-IDF with SVM [4], [21].

The solution ensures precise nutritional profiling, including calorie counts, macronutrient distribution, and micronutrient levels, by integrating the outputs of these AI models with extensive food IFCT databasees, like USDA FoodData Central [10]. By doing this, it tackles important issues including estimating portion sizes, multi-label recognition for complicated meals, and culturally diverse cuisine [16], [23].

A prototype that can give users accurate, real-time nutritional insights is one of the research's expected results; this prototype may find value in fitness tracking, public health research, and personalised healthcare [5]. Additionally, the system establishes the foundation for future expansions, including large-scale implementation for nutritional epidemiology research, multimodal fusion for increased accuracy, and interaction with IoT-based smart health devices [12], [18].

INTRODUCTION

One of the most essential components of human existence is food, which not only provides energy but is also essential for preserving general health and averting chronic diseases. The necessity of eating a balanced diet is becoming more widely recognised as lifestyle-related disorders including obesity, diabetes, and hypertension become more common [12]. However, the absence of practical methods for tracking meals and comprehending their nutritional content makes it difficult for consumers to effectively monitor their diets in today's fast-paced society. Consistent use is discouraged by the time-consuming, error-prone, and inconvenient nature of manual food logging using diaries or mobile applications [4].

A promising answer to this problem can be found in recent developments in artificial intelligence (AI), especially in the domains of computer vision and natural language processing (NLP). By connecting to well-known food IFCT databasees, AI-powered systems are able to automatically identify foods from photos, decipher written meal descriptions, and precisely calculate their nutritional value [7], [19]. Dietary monitoring could be revolutionised by this automation and intelligence combination, becoming simple, dependable, and widely available.

• Background and Insight

In order to maintain human health, boost immunity, and lower the risk of chronic conditions like obesity, diabetes, cardiovascular disease, and hypertension, nutrition is essential [3]. Dietary monitoring is now more crucial than ever due to the growing trend towards sedentary lifestyles and fast-food intake. Recent health surveys indicate that a sizable percentage of people do not reach their daily nutritional needs, frequently as a result of ignorance or trouble monitoring their food intake [14]. Manual tracking techniques, such recording meals or utilising smartphone apps, are frequently cumbersome, prone to mistakes, and unable to keep up with contemporary lifestyles [21].

AI-based systems can automate food recognition and nutrition estimate in response to these issues, providing users with immediate meal insights and facilitating better decision-making [9].

• AI's Role in Nutrition Estimation and Food Recognition

1. **Computer Vision for Food Image:** Food image classification has shown impressive results using deep learning models, especially Convolutional Neural Networks (CNNs) like ResNet, Inception, and EfficientNet [2]. These models are trained and benchmarked using publicly available datasets such as Rajistics Fine tune indian model, Recipe1M+, VIREO Food-172, and Nutrition5k [16]. For common food categories, CNNs can attain recognition accuracies of over 85–90% with enough training [25]. Furthermore, recent approaches are moving beyond classification to include multi-label identification (for meals with several food items) and portion size estimate utilising 3D depth analysis [5].

2. **Text-Based Food Recognition Using NLP:** Some people might not want to upload pictures of food. Some people might just want to type the food they ate. NLP-based models are useful in these situations. Dish names can be efficiently mapped to IFCT databasee records using traditional techniques like SVMs or TF-IDF vectorisation with Logistic Regression [18]. More sophisticated models, such as transformer-based architectures (BERT, RoBERTa), may map complicated meal descriptions to the proper nutritional values and enable semantic interpretation of phrases like "grilled chicken with steamed broccoli" [11].
   The suggested solution guarantees robustness, flexibility, and usability for a range of user preferences by integrating computer vision and natural language processing techniques [6].

• Significance of the Proposed System

A significant weakness in the dietary tracking systems in use today is filled by the "Food Nutrition Estimator from Image and Text using AI." Existing programs for fitness and health mainly rely on human input, however they are not automated and frequently have accuracy issues [8]. Our suggested system:

1. **Reduces Human Error in Food Logging:** Users usually underreport portion sizes or fail to log meals at all since manual logging is time-consuming. By automating word or image identification, our method lessens the need for human judgements and memories. [22].

2. **Provides Reliable Nutritional Information:** The method guarantees that nutritional values (calories, macronutrients, and micronutrients) are standardised and scientifically correct by connecting approved food items to reliable IFCT databasees like USDA FoodData Central and FatSecret [15].

3. **Encourages Dietary Awareness:** Users can consider their food selections in real time thanks to the system's rusda apid feedback. This can eventually encourage better eating practices and assist medical experts in providing nutritional advice [1].

In conclusion, the need for automated nutrition tracking systems is critical given the rising incidence of diet-related disorders worldwide and the shortcomings of current nutritional monitoring techniques. The suggested Food Nutrition Estimator seeks to overcome these obstacles by utilising advances in natural language processing for food description analysis [6], deep learning for image classification [11], and standardised nutrition IFCT databasees like USDA FoodData Central [17].

PROBLEM DEFINITION

Due to the growing global concern for obesity control, diet-related disorders including diabetes, and cardiovascular problems, artificial intelligence-based food recognition and nutrition assessment have attracted increasing attention in recent years. However, because of the substantial intra-class variability, mixed dish contexts, and cultural diversity in cuisines, food analysis poses distinct challenges in contrast to normal computer vision tasks. The challenge lies in developing a comprehensive framework that can provide accurate, tailored, and real-time nutritional information, rather than just identifying foods. These outstanding issues are addressed in this project and are covered in more depth below.

1. Complexity of Food Image Recognition

Compared to commonplace object recognition, food recognition is far more difficult. Food items don't have the same structural characteristics as things like vehicles or chairs. Their presentation, ingredients, and cooking techniques all have a significant impact on how they look.

- **Intra-class variation:** A "sandwich" could be a vegetarian sub, grilled cheese, or a club sandwich. Even though they are in the same category, their internal architecture are different, which makes maintaining visual consistency challenging.

- **Inter-class similarity:** Some meals, such as "dal" and "soup," or "idli" and "rice cake," have similar colors and textures, causing them to fall into different categories. Misclassification is frequently the result of this.

- **Visual noise:** Compared to clean dataset photos, real-world recognition is more difficult because to noise introduced by lighting, camera quality, and angles.

- **Composite meals:** In contrast to independent objects, meals frequently consist of several overlapping components on a single plate (such as thali dinners), making recognition even more difficult.

Together, these elements show that food picture recognition necessitates extremely reliable models that surpass conventional classification methods.

2. **Dataset Limitations and Bias**

The absence of representative and diversified datasets is a significant impediment. Popular datasets like VIREO Food-172, UECFOOD-256, and Rajistics Fine tune indian model frequently feature a preponderance of East Asian or Western foods. As a result, there is significant dataset bias, which restricts how broadly trained models may be used.An algorithm trained on Rajistics Fine tune indian model, for example, would accurately categorize "spaghetti carbonara," but it might not be able to identify "khichdi" or "dal fry," since these categories are either missing or underrepresented in these datasets.

The system's application in multicultural cultures is limited by this lack of inclusivity, especially in places like the Middle East, Africa, and India. Furthermore, a lot of datasets provide controlled settings with particular food products photographed against pristine backdrops

To improve model robustness, the issue is to ensure cultural inclusivity, real-world variation, and annotated multi-item meals in addition to gathering larger datasets.

3. **Portion Size and Nutritional Estimation**

A crucial yet unsolved problem is that nutritional assessment is heavily reliant on portion size, even in cases where classification is precise. Accurately estimating the volume and weight of food is challenging since 2D images are not naturally able to represent depth.

- **Scale ambiguity:** In a photograph, a little cup of rice could appear to be similar to a medium-sized one, yet its calorie count is much different.

- **Problems with practicality:** While sophisticated solutions like 3D reconstruction, depth sensors, or adding reference objects (such a spoon, coin, or typical container) to the image are feasible, they are not feasible for general consumer use.

- **Multi-item complexity:** Because mixed foods (such as salads or biryani) have a variety of items, nutritional assessment must take into account both ingredient proportion and portion size.

Nutritional information becomes deceptive if portion sizes are not measured accurately. For instance, recognizing "pizza" correctly but misjudging a single slice vs half of a pizza can result in hundreds of calorie inaccuracies.

4. **Computational and Deployment Constraints**

Although cutting-edge designs such as ResNet, EfficientNet, and Vision Transformers (ViTs) attain cutting-edge accuracy, their implementation in actual mobile or wearable devices has computational limitations.

Large-scale models require a lot of memory and GPU power, which smartphones usually don't have. Running them in real-time could result in poor user experience, significant latency, and battery waste. Furthermore, in environments with limited resources, nutritional programs must work flawlessly on a variety of devices, including mid-range smartphones.

Pruning, quantization, and knowledge distillation are methods used to reduce the size of models, although they frequently result in decreased accuracy. The main difficulty is striking a balance between accuracy and processing efficiency, particularly for real-time applications were delays compromise usability. For broad acceptance, this trade-off continues to be a major obstacle.

5. **Personalization and Context Awareness**

Personalization is essential to the success of food recognition systems. Cultural customs, consumer preferences, and personal health objectives all have an impact on nutrition. However, most current AI systems categorize food separately, without incorporating these contextual layers.

- **Cultural variation:** A dish like "curry" might imply very different things in different places. For example, the nutritional content of North Indian paneer curry, South Indian sambar, and Japanese curry varies.

- **User-specific requirements:** People may have dietary limitations (like veganism), medical issues (like diabetes that requires carbohydrate control), or allergies (like peanuts). These customized requirements are not met by a generic system.

- **Meal-level comprehension:** Actual meals are eaten in combinations, such as roti, dal, sabzi, and salad. The overall nutritional intake is not captured by a system that merely categorizes individual dishes.

Additionally, nutritional advice systems that go beyond classification must dynamically adjust to user habits, health goals, and progress monitoring. Such systems run the risk of being overly general and having little real-world use if they lack personalization and contextual awareness.

OBJECTIVES

This project's main objective is to use cutting-edge AI and machine learning approaches to design and create an intelligent system that combines nutritional analysis and food image identification. The need for trustworthy food monitoring systems has increased significantly as awareness of lifestyle-related disorders like obesity, diabetes, and cardiovascular problems has expanded. This solution uses deep learning to automate the entire process, making it faster, more accurate, and easier to use than typical calorie counting apps that depend on manual inputs. The project is to close the gap between theoretical research and practical applications that can directly help people, dieticians, and healthcare professionals by emphasizing robustness, efficiency, and personalization.

1. **To Develop a Robust Food Image Recognition Model**

The main goal is to develop a food identification model that can accurately classify foods in a variety of categories. Due to issues including visual similarities between dishes, differences in preparation methods, and mixed ingredients in meals, food recognition is far more difficult than general object recognition.

Advanced deep learning architectures such as Vision Transformers (ViTs), ResNet, EfficientNet, and Convolutional Neural Networks (CNNs) will be used in the model. To improve generalization and adaptability, these designs will be refined on extensive food datasets. In addition to static classification, the focus will be on creating a scalable framework that can be used to a variety of cuisines, including regional meals that are not as well-known.

Particular attention will be paid to improving recognition accuracy in real-world situations, where performance is frequently hampered by crowded backdrops, overlapping dishes, and inadequate lighting. This guarantees that the system is reliable enough to work in real-world applications and beyond laboratory benchmarks.

2. **To Address Dataset Diversity and Inclusivity**

Overcoming the constraints imposed by current food image IFCT databasees is another important goal. Generalization is severely constrained by the fact that many benchmarks (like Rajistics Fine tune indian model or UEC-Food) only reflect a small number of cuisines and controlled settings. The goal of this project is to produce or enhance datasets that represent inclusion and diversity in the real world.

- **Cultural inclusivity:** Creating IFCT databasees that include a variety of international cuisines, such as Mediterranean platters, African stews, Japanese sushi sets, Indian thalis, and other regional dishes, is an example of cultural inclusion.

- **Multi-item meals:** Managing plates of food since real-world meals are frequently combos rather than single dishes (e.g., rice with curry, salad with bread, etc.).

- **Environment realism:** In order to make the model resilient to noisy real-life data, environment realism involves including photos in a variety of settings, such as different lighting, angles, and partially visible objects.

This goal also includes addressing class disparity, which occurs when certain foods are underrepresented in comparison to well-liked ones. By addressing this problem, the AI system will be dependable and equitable across a range of dietary habits and demographics.

3. To Enable Accurate Portion Size and Nutritional Estimation

Without a precise estimate of portion sizes, which are closely related to calorie and nutrient intake, food recognition is not complete. Food volume estimation from a 2D image is a significant computer vision difficulty because depth and scale information are frequently absent. This goal is to integrate hybrid methodologies, including depth sensor data (where available), 3D reconstruction techniques, and reference object scaling.
Following the estimation of portion sizes, the system will compute a comprehensive nutrient profile that includes macronutrients (proteins, fats, and carbs) and micronutrients (vitamins and minerals) in addition to calories. This enhances the system's utility for healthcare applications like tracking diabetic diets, weight-loss strategies, or post-operative nutrition regimens and offers deeper insights into dietary intake.

Additionally, this goal is to link recognition results to reliable food composition IFCT databasees, such as Indian Food Composition Tables, USDA, and other regional repositories. The technology will provide accurate and dependable suggestions by connecting vision-based recognition with verified nutritional IFCT databasees.

4. To Optimize for Real-Time and Resource-Constrained Deployment

Technology needs to be deployable in real-world contexts with constrained computational resources in order to be valuable outside of academic settings. Therefore, designing models that are suited for wearable technology, edge computing platforms, and mobile devices is another essential goal.

- **Model optimization and compression:** To lessen computational burden without sacrificing accuracy, strategies including knowledge distillation, quantization, and pruning will be used.

- **Real-time inference:** Making sure that forecasts are sent in milliseconds so that consumers may easily engage with the system while eating their regular meals.

- **Offline usability:** Allowing a program to function in low-connectivity or offline settings so that those without continuous internet access or in remote locations can use it.

The final objective is to strike a compromise between efficiency and accuracy so that the system may be extensively used in embedded IoT platforms, smartphones, and medical equipment. Scalability is guaranteed by this goal, which is essential for transforming this project from a small endeavor into a significant research-grade system.

5. To Incorporate Personalization and Context-Aware Recommendations

The ultimate goal is to deliver individualized dietary insights by going beyond recognition and nutritional estimate. Everybody has different nutritional needs, depending on factors including age, gender, health, lifestyle, and cultural preferences. As a result, the system seeks to include user-specific profiles that modify suggestions appropriately.For instance, an athlete may be directed toward protein-rich substitutes, while a diabetic patient may be alerted when the identified meal is high in sugar.

In a similar vein, the system might alert people with hypertension to items high in sodium. This guarantees the tool's usefulness for regular users who want to maintain healthy eating habits in addition to making it clinically relevant. Furthermore, rather than focusing on individual products, the personalization module will take into account the context of the entire meal.
Eating rice with lentils, for example, results in a balanced amino acid profile, while eating the same rice with sweet treats can lead to an imbalance. This comprehensive knowledge guarantees that the algorithm provides useful, health-related recommendations.

LITERATURE REVIEW

1. Rajistics Fine tune indian model – Mining Discriminative Components with Random Forests

A significant advancement in computer vision research for dietary applications was made with the release of the Rajistics Fine tune indian model dataset. It was one of the first extensive, publicly accessible IFCT databasees devoted just to food recognition, with 101,000 photos in 101 food categories. Research in this field was limited to smaller, domain-specific datasets, frequently gathered under controlled conditions, prior to its publication. In comparison, Rajistics Fine tune indian model was much more reflective of real-world situations because it included real-world variability like uneven lighting, a variety of plating techniques, and background clutter. Because of this degree of variability, researchers were able to create models that would more accurately generalize outside of lab settings.

Initially, bag-of-visual-words methods and random forest classifiers were used to examine the dataset. These methods made use of hand-crafted features, but they had trouble with the substantial intra-class variety found in food photos, despite their moderate effectiveness. It can be challenging for standard approaches to capture relevant discriminative traits when a dish like "spaghetti" appears with different sauces, toppings, and serving styles. But as deep learning became popularity, CNN-based models like ResNet, DenseNet, and EfficientNet swiftly adopted Rajistics Fine tune indian model as their standard, exhibiting impressive gains in recognition accuracy. Rajistics Fine tune indian model has continued to be a gold standard dataset over time, utilized extensively for training and assessing algorithms that serve as the foundation for nutrition assessment systems.

2. DeepFood: Deep Learning-Based Food Image Recognition for Computer-Aided Dietary Assessment

DeepFood demonstrated a significant improvement above handcrafted features by introducing the concept of employing large-scale CNN architectures for food recognition. In order to adjust to the distinct features of food photos, such as irregular forms, different textures, and various presentation styles, the system made use of pre-trained networks and fine-tuning. The study demonstrated how discriminative features might be automatically learned by deep networks, eliminating the requirement for feature engineering by hand.

Additionally, scalability in practical dietary applications was stressed in this work. CNNs became the industry standard for food picture recognition because to DeepFood's validation of performance across a

variety of food categories. The study's conclusions are still very relevant, especially for wearable and mobile nutrition monitoring devices where automation is essential.

3. Mobile Food Recognition with Convolutional Neural Networks

Lightweight food recognition models were required as smartphone usage increased. This study showed how CNN architectures might be made more accurate while still operating in real-time on mobile devices. In order to balance speed and performance, the models were made to employ fewer parameters while still maintaining accurate categorization.

In dietary logging apps where consumers anticipate quick and easy participation, this improvement is practically significant. With the use of mobile-based solutions, people may instantly record and examine their meals, increasing public accessibility to nutrition monitoring. By emphasizing the transition to consumer-ready applications, the emphasis on mobile deployment also helped close the gap between research prototypes and everyday usability.

4. Multi-Label Food Recognition Using Convolutional Neural Networks

The problem of multi-label food recognition was addressed in this study, in contrast to single-label classifiers that recognize only one item per image. Inaccurate nutritional estimations may result from ignoring secondary foods, as real meals frequently include several dishes or products in a single frame. The scientists changed training methods and loss functions to enable CNNs to predict several food categories at once.

The study emphasized how multi-label systems might enhance nutrition and calorie tracking in addition to identification. For instance, identifying a sandwich and a drink in the same picture results in a more thorough eating log. These techniques are particularly applicable in cafeteria or restaurant settings, where several dishes are usually served on one tray.he

5. NutriNet: A Deep Learning Food and Drink Image Recognition System for Dietary Assessment

By include liquids in addition to solid food items, NutriNet expanded the capabilities of food identification systems and produced a more comprehensive framework for dietary analysis. NutriNet was able to achieve high recognition accuracy with more than 500,000 training photos and was adaptable enough to gradually incorporate new classes without requiring a complete model retraining.

Given how frequently new food items are introduced by regional cuisines and culinary trends, the incremental learning approach made a significant impact. NutriNet guaranteed long-term usability and versatility for dietary monitoring by creating a modular system. The study also highlighted real-world deployment situations, like in clinical settings and health-tracking apps, highlighting its importance for dietary analysis and tailored treatment.

6. Calorie Estimation from Food Images: An Analysis of Portion Size and Volume Estimation Methods

The item recognition tells you what the item is, but calorie estimation tells you how much of it there is. The methods for estimating food volumes and portion sizes from photos were the main topic of this article. To determine the volume of food items, researchers experimented with depth sensors, fiducial markers (such as placing a reference object close to the meal), and 3D reconstruction approaches.Portion estimate is still one of the biggest bottlenecks in automated dietary systems, according to one important discovery.
Underestimating or overestimating food quantity renders even the most precise food classification models useless. In order to obtain clinically valid calorie prediction, the study emphasized the necessity of hybrid approaches that combine image-based recognition with user input (e.g., portion size sliders) or Internet of Things devices (e.g., smart scales).

7. Image-Based Food Recognition for Calorie Intake Estimation on Smartphones

To directly address consumer usability, our effort focused on integrating food identification and calorie estimation within mobile applications. Using smartphone cameras, the suggested method took pictures of food, classified it using CNN, and then mapped the identified items to nutrition IFCT databasees such as USDA FoodData Central. The influence of non-standard presentation methods (e.g., home-cooked vs. restaurant dishes), occlusion when food overlaps, and variations in lighting conditions were among the practical factors that the researchers emphasized.

Their tests revealed that although cellphones are excellent tools for estimating calories, accuracy declined dramatically when it came to soups, mixed meals, and foods with amorphous shapes. They proposed multi-image capture (from several angles) as a remedy to lessen this. Because it connects academic research to the practical limitations of mobile hardware, app usability, and user compliance—factors that are sometimes disregarded in strictly computational studies—this work has a particularly significant impact.

8. Automatic Food Recognition and Nutritional Analysis from Images

The entire pipeline from recognition to real nutritional analysis was investigated in this study. Three parts made up the pipeline: segmentation for estimating portion sizes, picture classification for food identification, and nutritional IFCT databasee mapping for calculating calories and macronutrients. The study offered one of the most comprehensive methods in the area by addressing every stage inside a single, cohesive framework. This paper's two main advantages were its validation on actual user data and its modular system design, which allowed each step to be enhanced separately when better algorithms became available.

This study examined the system over a period of days with real participants, in contrast to many lab-based investigations, enabling a more realistic assessment of accuracy and dependability. Although the results revealed limits, they also demonstrated promising performance. For instance, the system has trouble with composite foods like salads with several dressings, spaghetti with toppings, and curries. This demonstrated that in order to get clinically valid results, strong food segmentation techniques and sizable, properly labeled nutrition datasets are required.

9. FoodLog: Multimedia Mobile Food Recording

One of the first mobile applications for nutritional tracking with multimedia inputs was released by FoodLog. To improve recognition accuracy, FoodLog enabled users to add audio notes or brief text descriptions to photographs, in contrast to systems that just employ image recognition. This multimodal approach acknowledged that even small amounts of human input might greatly increase automatic food recognition systems' dependability. The app's strength was its ability to strike a balance between automation and user control.

For instance, if the picture classifier couldn't decide between "pizza" and "lasagna," the user could easily verify which option was right. User satisfaction increased and errors were decreased as a result of this cooperative interaction. Furthermore, FoodLog was one of the first to establish that mobile-based nutritional self-monitoring is feasible in the long run, proving that user engagement increases when they feel in charge of the process.

While AI systems aim for complete automation, hybrid techniques that combine AI prediction with little user input might ultimately provide the optimal balance between accuracy and usability, according to the study's insightful findings.

10. Using Convolutional Neural Networks for Food Image Recognition in Dietary Assessment

This study compared the advantages and disadvantages of several CNN architectures (AlexNet, VGGNet, GoogLeNet, and ResNet) for dietary evaluation using food picture datasets. The findings demonstrated that deeper architectures, such as ResNet, performed better than previous models when it came to managing intra-class variability, complex backgrounds, and minute variations in the visual appearance of comparable foods.

However, the study also showed that some architectures were more resistant to overfitting on smaller datasets, which is a crucial factor to take into account for specialized or regional food IFCT databasees where data scarcity is a problem. The authors stressed that, especially for deployment on smartphones and embedded devices, model selection should take into account both computing economy and accuracy.

11. A Two-View Approach to Food Recognition Using Deep Learning

By taking into account both global structures (the overall appearance of the meal) and local specifics (fine-grained materials like grains, spices, or garnishes), the two-view method suggested in this study significantly improves recognition. When visually comparable meals have a general structure but small differences, several previous approaches that mostly relied on global aspects frequently failed. The model generated feature maps that were more discriminative and resilient by mixing local and global descriptors. Furthermore, complicated datasets with significant intra-class variance were used to assess the two-view framework. Pasta meals, for example, can have different sauces, toppings, or presentation ways, but they are all in the same class. On the other hand, recognition was difficult due to inter-class similarity between visually comparable categories like soups and curries. Both information spectrums were successfully captured by the two-view deep learning design. This study showed that hybrid viewpoints improve the accuracy of food recognition systems, particularly for applications including nutritional monitoring.

12. Food Recognition Using Multi-Scale Convolutional Neural Networks

Given that food products frequently contain both fine-grained local textures and more general structural patterns, the application of multi-scale convolutional neural networks (CNNs) has been a significant improvement in food recognition. In order to capture the general shape and color distribution of a meal while preserving minute visual signals like seeds, spices, or garnishing, a multi-scale CNN processes input photos at various resolutions. Stronger generalization across intricate food categories results from this dual-level perception, which strikes a balance between macro-level contextual analysis and micro-level information extraction.

In practical terms, this technique significantly reduces classification errors for visually similar foods. For example, noodle soups such as ramen and pho share structural similarities but differ in garnish and broth texture. Multi-scale architectures are able to capture these subtle differences effectively. Another key advantage lies in robustness to environmental noise such as poor lighting, camera blur, or partial occlusion, which are common in mobile food photography. The integration of scale-invariance makes the models better suited for real-world dietary applications where food images are highly unstructured.

13. DeepFood: Deep Learning-Based Food Image Recognition for Computer-Aided Dietary Assessment

One of the first projects to use large-scale CNN architectures especially for dietary assessment was the DeepFood framework. DeepFood proved CNNs perform noticeably better than handmade feature extraction techniques like SIFT or HOG by training deep networks on large datasets like Rajistics Fine tune indian model. Contrary to generic classification tasks, food recognition has two major challenges: (i) inter-class similarity, where different cuisines, such as soups or curries, appear nearly identical in photographs, and (ii) intra-class variability, where the same dish looks different across places or preparation styles. DeepFood took advantage of CNNs' hierarchical feature learning capabilities to handle both.

DeepFood's focus on integration with dietary tracking systems was another significant accomplishment. The methodology automatically estimated calories and macronutrients by mapping identified meals to nutrition IFCT databasees, rather than restricting outputs to projected labels. This link between nutritional knowledge and visual recognition demonstrated the practical applications of food AI. Additionally, DeepFood's mobile platform deployment possibilities demonstrated how users may take a picture of their food and instantly record its nutritional value, connecting AI research with medical applications.

14. Nutrition-Aware Food Recognition for Calorie Estimation

By directly integrating calorie and nutritional calculation into the recognition process, this work went beyond basic food classification. Once a dish was identified, the program used structured IFCT databasees like USDA FoodData Central to retrieve its nutritional profile. By include values for calories, protein, fats, and carbs, this method placed an emphasis on health impact in contrast to conventional classification-only approaches.

Dealing with intra-dish variances was the technological problem here; for instance, depending on how the pasta is prepared, two plates may have wildly disparate portion sizes and calorie counts. Although the

meal could be identified by the recognition model, calorie estimation necessitated connecting classification outputs to nutritional lookup systems and, occasionally, portion estimation methods. Notwithstanding these difficulties, the framework represented a breakthrough toward AI systems that are both aesthetically sophisticated and cognizant of nutrition, allowing for real-time nutritional tracking in mobile health apps.

15. Multi-Task Learning for Food Image Classification and Retrieval

Food identification using multi-task learning (MTL) offered a novel way to maximize categorization and retrieval within a common framework. MTL made it possible for a single CNN-based network to learn embeddings for picture retrieval and predict food labels without the need for training separate models. While retrieval outputs enabled looking for visually comparable items in a IFCT databasee, classification outputs assisted in identifying the dish.

The development of shared representations that captured richer characteristics of food imagery was a significant benefit of this dual-task training. These attributes increased the accuracy of recommendation systems, such as identifying healthier alternatives to high-calorie meals, as well as recognition systems. Furthermore, MTL ensured that performance remained competitive across both tasks while lowering the computational cost of maintaining distinct models. This was also useful for dietary assistance platforms because it allowed a system to not only identify a dish but also provide substitutes or pull recipes from a food IFCT databasee for end-user apps.

16. Cross-Regional Food Recognition Using Domain Adaptation Techniques

Systems for identifying foods frequently have trouble generalizing across cultural boundaries. Because Asian and African cuisines use distinct ingredients, preparation methods, and presentation approaches, models that were predominantly trained on Western datasets, such as Rajistics Fine tune indian model, may not perform well. In order to bridge the distance between source and target domains, this study employed domain adaptation approaches, which allowed CNN features trained on one cuisine to successfully adapt to another.

The application of transfer learning with adversarial domain adaptation, in which a network learnt to reduce regional differences in feature distributions, was a significant contribution. For instance, because they were not included in IFCT databasees with a Western focus, rice-based foods from Asian cuisines were frequently misclassified. Recognition across culturally different datasets improves through the alignment of latent feature spaces. In order to ensure that dietary tracking applications may be used

globally rather than regionally, this research emphasized the need of inclusion and the necessity for globally competent food identification systems.

17. Context-Aware Food Recognition Using Scene Understanding

The Conventional CNN-based methods frequently handle food recognition as a stand-alone object detection issue. However, this study made the case that in order to distinguish between visually similar items, contextual cues in the dining area are crucial. Drinks positioned next to plates, cutlery, or dining areas, for example, reveal more details about the probable food type.

Recognition accuracy for categories with significant inter-class similarity increased with the use of scene understanding models, such as attention-based networks or scene classification CNNs. For instance, depending on whether chopsticks, rice bowls, or bread are present on the table, a bowl of broth may be categorized as either soup or curry. This incorporation of contextual thinking reflects how people often perceive food, which is rarely regarded in isolation but rather as part of a larger eating arrangement. The findings of the study demonstrated that context-aware algorithms can considerably lower classification mistakes, particularly for cluttered or poorly framed real-world mobile photos.

18. Semi-Supervised Food Recognition with Limited Annotations

The diversity of cuisines and meals causes annotation bottlenecks in food recognition, despite the fact that large-scale labeled datasets are essential for CNN training. To get over this restriction, semi-supervised learning (SSL) techniques were presented in this study. Through consistency training, pseudo-labeling, and data augmentation, the model was able to learn meaningful representations by merging a small labeled dataset with a large unlabeled dataset.

The fact that unlabeled food photos frequently have instructive differences that can enhance the feature space was one of the major discoveries. For instance, even if the precise names of unlabeled regional foods were unknown, they could still aid in representation learning. By enabling the model to use such data, SSL considerably decreased the need for costly manual annotations. In addition to improving recognition accuracy, this method allowed the system to scale to international cuisines with sparse labeled data. Because SSL makes training more practical in low-resource settings, it represents a significant step toward democratizing AI for nutrition.

19. Portion Size Estimation Using Depth and Visual Cues in Food Images

The Dietary evaluation necessitates precise portion size calculation, whereas the majority of food identification research concentrates on classification. In order to calculate food amount, this paper suggested combining visual signals such plate size and utensil reference with monocular depth estimation. The method used food density mappings to translate volume into nutritional values by recreating roughly three-dimensional (3D) representations of plates.

A two-step pipeline was used: first, the food type was determined using CNN-based classification, and then the portion size was approximated using geometric reasoning. Quantity estimation, one of the most difficult problems in nutritional AI, was solved by this hybrid approach. Portion estimation, in contrast to binary classification, works with continuous data and has a significant error rate. The system increased accuracy and got closer to providing trustworthy calorie prediction tools by adding depth cues. This is a crucial step in automating dietary recording in hospital settings with clinically acceptable precision levels.

20. Personalized Food Recognition Through User Profiling and Preference Modeling

The significance of customization in food recognition systems was acknowledged by this study. All users are treated identically by generic CNNs, yet eating practices differ greatly depending on one's cultural background, personal preferences, and health limitations. The system tailored recognition outputs to the user by integrating user profiling, which included vegetarian preferences, frequency of meals, and allergies.

Combining probabilistic preference models with CNN-based visual recognition allowed for this customisation. For instance, the algorithm weighted predictions based on the user's profile when an image was unclear between paneer curry and chicken curry, giving preference to vegetarian options if appropriate. In addition to recognition, personalization made recommendation features possible, such recommending healthier options that fit certain objectives (like managing diabetes or losing weight). This study signaled a change from static recognition models to dynamic dietary companions by making AI systems user-adaptive, improving accuracy and user engagement.

21. Multimodal Food Recognition Using Image and Text Fusion

The use of multimodal fusion approaches, which combine linguistic information (dish names, menus, or user descriptions) with visual data (food photographs), has been one of the major advances in food identification research. Food recognition using only visual cues can be challenging when visually comparable foods, like "lentil curry" and "vegetable curry," look almost the same. Contextual text can

offer vital disambiguation in these situations. In order to produce more reliable and accurate predictions, this study suggested a fusion framework that integrated CNN-based image embeddings with TF-IDF or word2vec embeddings using dish names or descriptions.

The system was able to better handle ambiguity in the actual world by integrating text and visual elements. For instance, the identification of an otherwise unclear food photograph could be guided by the description found on a restaurant's menu. Furthermore, when one modality is weak, multimodal techniques offer robustness; for example, text inputs can make up for low image quality, and vice versa. Applications such as interactive diet logging programs, where users contribute photos along with optional text descriptions, were made possible by this research. Since your suggested system similarly estimates food nutrition by combining computer vision and natural language processing (NLP), the relation to your research is obvious.

22. Food Image Segmentation for Ingredient-Level Recognition

Real meals frequently consist of several components with different nutritional values, while traditional food recognition models typically treat a plate as a single item. By using semantic segmentation approaches to recognize and distinguish elements inside a meal image, our study overcomes that constraint. The model identified sections that corresponded to vegetables, cereals, proteins, and sauces using architectures such as U-Net and Mask R-CNN, and each segment was given a label. Instead of depending on dish-level averages, the approach offered a more detailed nutritional analysis by examining elements independently.

Portion variability, one of the most important issues in nutrition estimate, was also handled by the segmentation approach. The ratio of chicken to vegetables, for instance, can significantly alter the nutritional value of a plate of "chicken salad." The technique produced more accurate calorie and nutritional estimations by separating and measuring the area (and in some cases, depth) of each item. This approach is a step toward AI systems that are aware of ingredients and can analyze food in-depth rather than just classify it. capabilities like allergen detection, recipe reconstruction, and substitute suggestions are made possible by ingredient-level recognition in real-world applications. These capabilities are crucial for healthcare and individualized nutrition management.

23. Real-Time Food Recognition for Mobile and Edge Devices

Computational efficiency is a key barrier preventing food recognition systems from progressing from research to application. Although they produce state-of-the-art accuracy, large CNNs like ResNet or EfficientNet are too resource-intensive for smartphones or edge devices with constrained hardware. By creating lightweight models using methods including model pruning, quantization, and knowledge distillation, this work addressed that difficulty. While retaining competitive accuracy, the resulting models drastically decreased the amount of storage and processing needed.
For nutritional AI, the capability of real-time, on-device recognition is revolutionary. It makes systems more responsive and private by enabling users to log meals quickly without depending on cloud access. Additionally, real-time inference facilitates connection with smart dining applications or wearable technology, where instantaneous feedback is crucial. Accessibility, cost savings, and scalability exceed any potential modest drop in accuracy when compared to full-scale CNNs. This field of study shows how engineering innovations that bring AI closer to consumers' everyday lives are just as important for practical implementation as high-performing models.

24. Automated Dietary Monitoring Through Continuous Food Logging

Classifying a dish, estimating its nutritional value, and then stopping there is how the majority of current systems handle food identification. However, long-term observation and analysis of eating patterns over several days, weeks, or months are necessary for effective nutritional management. Each identified meal added to a user's dietary timeline in this study's automated framework for continuous food logging. The system examined consumption patterns and trends, like frequent high-calorie meals or irregular eating times, using temporal models like RNNs and LSTMs.

This method has the advantage of being able to offer tailored health advice and feedback. For instance, the system might recommend dietary changes if it consistently detects a protein intake deficit. Predictive analytics, such as predicting possible weight growth or vitamin inadequacies based on trends seen, is also supported by continuous monitoring. This work emphasizes the significance of incorporating recognition into holistic dietary profiles, which closely correlate with healthcare and wellness goals, even though there are still issues with guaranteeing data accuracy and user compliance. This approach provides a logical progression for your project into the Major Project stage, where your system may progress from recognition-based to comprehensive nutrition monitoring and guidance.

25. Explainable AI for Food Recognition and Nutrition Estimation

The Deep learning models in healthcare applications are frequently criticized for being difficult to interpret. Unexplained predictions are frequently mistrusted by users and practitioners. This work used Explainable AI (XAI) methods for food recognition and nutrition calculation, including Grad-CAM, SHAP, and attention heatmaps. The algorithm gave clear explanations for its results by displaying the areas of the image that were most important for classification (e.g., concentrating on noodles versus garnish).

By associating calorie estimations with particular products or portion sizes, the study also expanded explainability to nutrition estimation. A system may indicate, for example, that 300 calories were attributable to noodle volume and 200 calories to sauce if it calculated 500 calories for a pasta plate. This degree of specificity increases user adoption and trust, especially in healthcare settings where accountability is crucial. Additionally, by assisting developers in detecting biases in datasets or model behavior, XAI enhances robustness and equity across communities and cuisines. This study highlights that food AI is not only about accuracy but also about usability and transparency, which makes it extremely pertinent for system deployment in the real world.

S. No.	Title / Study	Main Contribution / Focus	Key Findings / Significance
1	Rajistics Fine Tune Indian Model – Mining Discriminative Components with Random Forests	Large-scale Indian Food dataset (101k images, 101 classes)	Pioneered real-world dataset for food recognition; later adopted by CNNs (ResNet, DenseNet) as benchmark.
2	DeepFood: Deep Learning-Based Food Image Recognition	Introduced CNNs for food recognition	Outperformed handcrafted features; scalable for dietary apps; influenced wearable/mobile nutrition tracking.
3	Mobile Food Recognition with CNNs	Lightweight CNNs for smartphones	Enabled real-time recognition in dietary logging apps; improved usability

			and accessibility.
4	Multi-Label Food Recognition Using CNNs	Multi-label recognition for meals with multiple items	Improved calorie tracking; enabled recognition of multiple foods in one frame (e.g., tray meals).
5	NutriNet: Food & Drink Recognition System	Included both solid and liquid foods; incremental learning	Handled >500k images; adaptable to new food classes; applied in clinics and health-tracking apps.
6	Calorie Estimation from Food Images	Focus on portion size and volume estimation	Portion estimation bottleneck; proposed hybrid approaches with IoT/user input.
7	Smartphone-Based Food Recognition for Calorie Estimation	Mobile food recognition + calorie mapping to IFCT	Noted issues with soups/mixed meals; proposed multi-angle capture to improve accuracy.
8	Automatic Food Recognition & Nutritional Analysis	Full pipeline: segmentation → recognition → nutrition mapping	Validated with real users; struggled with composite foods; modular design allowed improvements.
9	FoodLog: Multimedia Mobile Food Recording	Multimodal logging (image + text/audio)	Balanced automation & user input; improved accuracy and engagement in long-term self-monitoring.
10	CNNs for Food Recognition in Dietary Assessment	Compared CNN architectures (AlexNet, VGG,	ResNet best; trade-off between accuracy & efficiency for

		ResNet)	mobile deployment.
11	Two-View Approach to Food Recognition	Combined global (structure) + local (fine-grained) features	Improved recognition for visually similar foods; reduced inter-class confusion.
12	Multi-Scale CNNs for Food Recognition	Processed images at multiple resolutions	Captured fine + coarse features; robust under poor lighting/blur.
13	DeepFood (Extended Study)	CNNs for calorie-aware recognition	Linked recognition with nutrition databases; enabled mobile deployment.
14	Nutrition-Aware Food Recognition	Integrated calorie & nutrient calculation	Retrieved macronutrients directly; enabled real-time nutrition apps.
15	Multi-Task Learning for Food Classification & Retrieval	Unified model for classification + retrieval	Enabled recommendations; reduced cost by shared representations.
16	Cross-Regional Food Recognition with Domain Adaptation	Adapted Western-trained models to Asian/African cuisines	Improved recognition across culturally diverse datasets.
17	Context-Aware Food Recognition	Used dining scene context (cutlery, setting)	Boosted recognition accuracy for visually similar dishes.
18	Semi-Supervised Food Recognition	Leveraged unlabeled datasets with SSL	Reduced annotation cost; improved global generalization.
19	Portion Size Estimation with Depth & Visual Cues	CNN classification + depth estimation	Estimated 3D volume/density; improved calorie prediction.

20	Personalized Food Recognition	User profiling & preference modeling	Adapted predictions to personal diets; boosted accuracy & engagement.
21	Multimodal Food Recognition (Image + Text Fusion)	Combined CNNs with text embeddings	Improved disambiguation; robust under poor image quality.
22	Food Image Segmentation for Ingredient-Level Recognition	Used semantic segmentation (U-Net, Mask R-CNN)	Enabled ingredient-level analysis; useful for allergen detection.
23	Real-Time Food Recognition on Edge Devices	Lightweight models (pruning/quantization)	Enabled fast, private on-device inference; suited for mobile/wearables.
24	Automated Dietary Monitoring via Continuous Logging	Used temporal models (RNNs, LSTMs)	Tracked patterns over time; predictive analytics for health.
25	Explainable AI for Food Recognition	Applied XAI (Grad-CAM, SHAP, attention maps)	Improved transparency & trust; linked calories to portions.

METHODOLOGY

This project's methodology is structured as a methodical pipeline that combines several fields, such as software engineering, computer vision, natural language processing (NLP), and nutrition research. The goal is to build a hybrid system that can identify foods from text and visual inputs and then provide precise nutritional estimates. Below is a detailed description of each step in the approach.

1. Review of Literature and Technology Investigation

To determine the state-of-the-art in food recognition and nutrition estimate, a comprehensive literature review was conducted. Large-scale collections of labeled food photos appropriate for deep learning model training can be found in benchmark datasets like Rajistics Fine tune indian model, UEC-Food, and VIREO-Food [5], [12]. Prior research showed that deep learning models such as ResNet, EfficientNet, and Vision Transformers (ViTs) significantly improved accuracy, but typical handcrafted features (e.g., SIFT, HOG) were limited in addressing the heterogeneity of food images [3], [7].

In order to process text-based inputs, NLP approaches were also investigated. For the classification of food descriptions, methods ranging from Bag-of-Words and TF-IDF to sophisticated word embeddings (Word2Vec, GloVe, and BERT) were taken into consideration [14]. Previous research has demonstrated that NLP can support image-based recognition in situations where images are ambiguous or missing [19].

2. Dataset Selection and Preprocessing

The Rajistics Fine tune indian model dataset was chosen for image-based recognition because of its variety and extensive application in food recognition tasks. 101,000 photos covering 101 culinary categories are included [5]. Preprocessing processes were applied to each image, including:

- **Resizing and Normalization:** To comply with CNN input specifications, all images should be resized to 224x224 pixels, and pixel values should be normalized to fall between [0, 1].

- **Data Augmentation:** Rotations, flips, brightness changes, and Gaussian noise were performed to improve robustness against environmental perturbations [11].

- **Class Balancing:** Oversampling and weighted loss functions were employed to lessen class

imbalance because some food groups had less samples.

Recipes and food names were taken from publically accessible sources and sanitized for consistency before being used for text-based recognition. Tokenization, stopword elimination, stemming, and lemmatization were all part of the preprocessing [21]. To assess performance, the text corpus was vectorized using TF-IDF and then contrasted with embedding-based representations.

3. Model Development

Developing classifiers for both text and image inputs was the main goal of this stage:

- **Image Classifier:** The Rajistics Fine tune indian model dataset was used to refine trained models including ResNet-50, EfficientNet-B0, and MobileNet-V2 [3], [15]. In order to retrain the top fully connected layers of pretrained networks while keeping the convolutional layers for feature extraction, transfer learning was used. This kept accuracy high while drastically cutting down on training time. Since Vision Transformers (ViTs) have demonstrated higher performance in fine-grained classification tasks recently [7], experiments with them were also carried out to further enhance performance.

- **Text Classifier:** TF-IDF vectors were used to train Support Vector Machines (SVMs) and Logistic Regression for text recognition [17]. To capture semantic links in food names, more sophisticated options including pretrained BERT embeddings and LSTM networks were also examined [9].

- **Multi-Input Fusion:** Text and image inputs were both supported by the system's design. When multimodal data (such as a picture and a brief description) was supplied, a decision layer was used to process the available information or combine the two.

4. Nutrition Lookup System

Nutritional information (calories, proteins, fats, carbs, and vitamins) was obtained once food categories were determined. The main source was the USDA FoodData Central IFCT databasee [19]. Furthermore, real-time nutritional queries were investigated using USDA APIs such as FatSecret [8].

To facilitate offline functioning, a IFCT databasee based on CSV was developed. A food category and its nutritional profile were mapped for each entry. While user settings permitted manual adjustment,

default averages were supplied for confusing food categories (such as "pasta"). This strategy was in line with other studies that integrated standardized nutrition IFCT databasees into food identification algorithms [20].

5. Frontend Design

The system's frontend is essential to guarantee end users' accessibility and usefulness. Standard web technologies like HTML5, CSS3, and JavaScript are used in its development, with focus on designing an intuitive user experience. Users can either upload a picture of food or enter a prose description of the dish, with the design emphasizing simplicity. To guarantee interoperability across platforms, such as computers, tablets, and smartphones.

Important frontend features include:

- **File Upload Interface:** Users can upload food photos by dragging and dropping or browsing; the backend system will then process them.
- **Text Input Form:** Several cuisines and dish variations are supported, and users can enter meal names or brief descriptions in a special section.
- **Nutrient Output Display:** Calories, proteins, lipids, and carbs are among the results that are shown in a straightforward tabular manner by the system. For more dietary insight, visualization is further improved by graphs or bar charts.
- **Enhancements to the User Experience (UX):** Tooltips, input validation checks, and loading animations during prediction all contribute to a better overall flow.

The frontend makes sure that even non-technical users can interact with the system easily by keeping the user interface neat and organized.

6. Backend Development (Flask USDA API)

Flask, a lightweight web framework built on Python, is used to create the backend, which serves as the system's processing engine. It offers RESTful USDA APIs that link deep learning and machine learning models to the frontend.

- **Image Processing Module:** The system preprocesses (resizes, normalizes) an uploaded image before classifying it using a pretrained CNN model like ResNet or EfficientNet. Nutritional information is then retrieved from the IFCT databasee using the anticipated food label.

- **Text Processing Module:** The backend uses TF-IDF vectorization in conjunction with machine learning classifiers like Naïve Bayes or Logistic Regression for textual input. This guarantees effective dish identification even when descriptions are brief or loud.

- **Nutritional IFCT databasee Integration:** To retrieve comprehensive nutritional material, the backend either connects to external USDA APIs like the USDA FoodData Central USDA API or the FatSecret USDA API, or it links to offline CSV-based datasets (such as Food101 mapped with USDA FoodData Central values).

- **USDA API Response Handling:** The frontend renders results using the JSON predictions that Flask routes return after processing queries. For upcoming additions, this architecture guarantees scalability and modularity.

The backend also has error-handling features, like handling missing nutritional information, numerous food items in a single request, or unidentified food inputs. Additionally, logging features are integrated to track system performance, keep an eye on model projections, and troubleshoot malfunctions.

7. Testing and Validation

To make sure the machine learning models and the system process as a whole function properly, testing is done. Several levels of evaluation are used in this phase:

- **Model Accuracy Testing:** The Food101 dataset and other carefully selected image collections are used to validate image recognition models. To assess classification performance, metrics including F1-score, recall, accuracy, and precision are computed. Classification accuracy for text input is evaluated using a labeled dataset of meal descriptions.

- **Cross-Validation:** To lessen model overfitting and evaluate generalization across various food categories, K-fold cross-validation is employed.

- **System Integration Testing:** USDA API calls are used to test front-end and back-end connectivity. This guarantees that the system displays accurate forecasts and nutritional values

while allowing uploaded images and text descriptions to flow smoothly.

- **User Testing:** A small group of test users engage with the system to offer input on error handling, response times, and usability. Both the backend functionality and the user interface are improved through feedback.

- **Performance Testing:** Stress tests are carried out to examine how well a server responds to several requests made at once. In particular, for real-time use cases like mobile app deployment, the backend's prediction latency is assessed.

The system strikes a balance between precision, effectiveness, and user happiness thanks to these validation procedures.

8. Documentation and Iteration

Maintaining thorough documentation for the user interface and the development process is the last stage. This include recording the model designs, USDA API endpoints, system requirements, and dataset pretreatment procedures. An easy extension of the project during the major project phase is guaranteed by proper documentation.

Iteration is just as crucial. The system goes through cycles of modification based on test results and user feedback. These cycles may involve retraining models with new datasets, enhancing UI design, or increasing backend performance. This iterative process guarantees ongoing enhancement and flexibility in response to evolving needs.

SYSTEM DESIGN & IMPLEMENTATION

1. System Overview

The Food Nutrition Estimator is an AI-powered application that allows users to track their dietary intake efficiently by identifying food items from either text input or images and estimating their nutritional values. The system supports user account management, food logging, AI-based food recognition, nutritional computation, and data storage. Its main objective is to provide accurate dietary feedback while maintaining a user-friendly interface.

The system architecture consists of three main layers: **Frontend, Backend, and IFCT databasee**, with an integrated **AI module** for food recognition. Users can log in or sign up, after which they can input meals categorized as breakfast, lunch, or dinner. Input methods include either textual description or an image of the food. The system processes this input, identifies the food items, calculates their nutritional values, displays results on the frontend, and stores the data for future reference.

2. System Design

2.1. Architectural Components

The system is designed using a **modular architecture**, which ensures scalability, maintainability, and ease of integration with AI models. The core components include:

1. **User Interface (Frontend)**
    - Developed using **HTML, CSS, and JavaScript** (or frameworks like React/Vue).
    - Provides a **login/signup interface**, meal input forms, and visual presentation of nutritional data.
    - Handles **real-time display** of processed nutrition values and food logs.
    - Accepts both **image uploads** and **text entries** for food input.
2. **Backend USDA API Server**
    - Developed using **Node.js/Express** or **Python Flask/Django**.
    - Handles **authentication**, **user session management**, and **data routing**.
    - Receives user inputs and interacts with the **AI module** to identify food items.
    - Computes nutritional information based on recognized food items.
    - Sends processed data back to the frontend for display.
3. **AI Module (Food Recognition)**
    - **Image-based recognition** uses pre-trained models (e.g., **Roboflow, TensorFlow, or PyTorch models**) to classify food items.
    - **Text-based recognition** uses **NLP models** to parse user input and map food items to a

nutrition IFCT databasee.
    - Integrates **both input methods** to provide a unified nutritional output.
    - Returns structured data with **food name, quantity, calories, macronutrients, and micronutrients**.
4. **IFCT databasee**
    - Relational IFCT databasees like **MySQL or PostgreSQL**, or NoSQL options like **MongoDB**.
    - Stores **user profiles**, **meal logs**, **food items**, and **nutrition data**.
    - Enables **historical tracking** and analytics, such as daily or weekly nutrient summaries.
5. **Integration Layer**
    - Facilitates communication between frontend, backend, and AI modules.
    - Ensures **real-time updates** and **secure data transfer**.
    - Implements **error handling** for unsupported inputs or recognition failures.

2.2. Data Flow

The system follows a **linear yet flexible data flow**:

1. User logs in or signs up → credentials stored in IFCT databasee.
2. User selects meal type (breakfast, lunch, dinner).
3. User provides food input via text or image.
4. Input is sent to backend USDA API → forwarded to AI module for identification.
5. AI module identifies food items → calculates nutritional values using IFCT databasee mapping.
6. Processed results are sent back to frontend → displayed visually.
7. Meal entry with nutrition data stored in IFCT databasee for tracking and analytics.

---

3. Implementation Details

3.1. Frontend Implementation

- **Login/Signup:** Form validation, secure password storage (hashed in IFCT databasee), and session management.
- **Meal Input Cards:** Separate cards for breakfast, lunch, and dinner, allowing multiple food items.
- **Text Input:** Uses a natural language parser to extract food names and quantities.
- **Image Input:** Allows uploading images which are sent to the AI module via **REST USDA API**.
- **Nutrition Display:** Calories, macronutrients, and micronutrients displayed dynamically with charts or tables.

3.2. Backend Implementation

- **REST USDA API Endpoints:**
  - /signup, /login → user authentication.
  - /addMeal → accepts text/image input, forwards to AI module.
  - /getNutrition → retrieves calculated nutrition data.
- **Data Processing:** Parses AI output, calculates totals, and stores in IFCT databasee.
- **Security:** Implements JWT authentication, HTTPS, and input validation to prevent attacks.

3.3. AI Integration

- **Image Recognition:**
  - Pre-trained models fine-tuned for food datasets.
  - Outputs probability scores for each class → top prediction selected.
- **Text Recognition:**
  - NLP techniques (e.g., tokenization, keyword mapping) to identify food names.
- **Nutrition Calculation:**
  - Matches recognized food with IFCT databasee values.
  - Calculates calories and nutrient content per serving.

3.4. IFCT databasee Design

- **User Table:** user_id, username, email, password_hash, created_at.
- **Food Table:** food_id, name, calories, carbs, protein, fat.
- **Meal Table:** meal_id, user_id, food_id, quantity, date, meal_type.
- **Relations:** Each meal is linked to a user; each food entry stores its nutritional content.

4. Flowchart / Diagram

Below is the system workflow:



RESULTS

In order to design a food recognition and calorie calculation system, its technical efficacy, usability, and wider ramifications must be critically assessed. The three main pillars of this analysis are practical deployment in real-world situations, computational efficiency, and accuracy. The classification accuracy of deep learning-based food recognition is one of its main advantages, especially when it is trained on extensive datasets like Rajistics Fine tune indian model. incorporating top-1 accuracies of 80% in several investigations, CNN-based systems incorporating transfer learning techniques have continuously beaten manually designed feature-based techniques [7], [18].

However, the variable appearance of food has a significant impact on accuracy. A drawback observed in both old CNN and contemporary transformer-based designs is that visually identical objects, like different kinds of pasta or curries, frequently lead to misclassifications [12], [3]. Although multi-label categorization methods have demonstrated potential in managing mixed meals, they continue to perform worse when foods are partially obscured or dimly light [21], [9].

Mobile-friendly architectures like lightweight CNNs and efficient feature extractors are appealing for implementation from the standpoint of computational efficiency [15]. Early research on mobile CNNs by Kawano and Yanai made clear how important it is to strike a balance between speed and accuracy for real-time detection in nutritional apps [4]. Domain adaptation methods are among the most recent developments that aim to enhance generalization across regional cuisines [16]. However, these models frequently require more GPU resources and training expenditures, which presents a challenge for organizations or startups with weak infrastructure [10].

Portion size estimation is another crucial component, where present methods continue to encounter difficulties. Despite the exploration of depth sensors and visual signals [19], inaccurate volume estimation of foods with irregular shapes continues to be a barrier [13]. These mistakes have a direct impact on calorie calculations, causing food intake to be either overestimated or underestimated. By connecting identification outputs with calorie IFCT databasees, nutrition-aware recognition algorithms try to close this gap [14], although their dependability is still largely dependent on how accurately the meal is classified at the basic level.

Accurate recognition is only one aspect of such systems' practical usability; another is their flexibility in accommodating dietary and cultural differences. Datasets are frequently skewed toward Western food categories, according to studies [5, 23]. As a result, adoption in nations with different cuisines may be

limited since identification systems trained on these datasets may have trouble with regional or traditional foods.

Reducing misclassifications has been shown to be possible with context-aware methods that include scene knowledge, such as determining if the food is on a dining table, in a restaurant, or in a packed product [17]. Although they still have issues with fine-grained recognition, semi-supervised learning techniques have also been investigated as a way to reduce the requirement for big annotated datasets [8].

Lastly, user customisation presents a new challenge. By reducing the search space, systems that incorporate user profiles and preferences into identification pipelines demonstrate increased accuracy [20]. However, since keeping personal eating habits necessitates rigorous adherence to data protection regulations, this presents significant privacy and security data management challenges. However, effective customisation could greatly improve dietary tracking adherence and provide real health advantages.

In conclusion, even though food identification and calorie estimates have advanced significantly, the research shows that portion size estimation, dataset bias, and computing scalability continue to be problems. There is also room for more research on the integration of multimodal data, cultural diversity, and personalization [11], [2], and [25]. Therefore, to ensure that advancements in this field result in useful, user-centered nutritional assessment tools, a balanced system must blend technical stability with practical adaptability.

HOME PAGE: -



SIGNUP/LOG-IN FORM: -





ACCOUNT LOGGED IN: -



FOOD ADDITION THROUGH IMAGE & TEXT: -





MEAL CARDS: -



TOTAL NUTRITION (DASHBOARD AND CHART): -





MONGODB DATABASE: -

```
_id: ObjectId('68de31e239a453dcc788f395')
username : "Aryan "
email : "shikhaaryraw87@gmail.com"
password : "$2b$10$GbTDMditodeQStORxGVB..wsPrAF034tcf/ZMGW1oJ7EbAVqR9TqW"
createdAt : 2025-10-02T08:03:46.009+00:00
__v : 0
```

```
_id: ObjectId('68de3545c13d1bd7084242ca')
username : "Lokesh"
email : "lokesh1234@gmail.com"
password : "$2b$10$nvAtunA9tFjyv55cxkf0JOHwo4pTXOGanNMFQGm3EjfKa6Vw7QjCm"
createdAt : 2025-10-02T08:18:13.349+00:00
__v : 0
```

```
_id: ObjectId('68de5617d6729cfcd50375b7')
userId : ObjectId('68de31e239a453dcc788f395')
mealType : "Breakfast"
name : "idli"
▸ nutrients : Object
date : "2025-10-02"
createdAt : 2025-10-02T10:38:15.912+00:00
__v : 0
```

```
_id: ObjectId('68de56d4d6729cfcd50375bd')
userId : ObjectId('68de31e239a453dcc788f395')
mealType : "Lunch"
name : "Fruit smoothie, with whole fruit and dairy"
▸ nutrients : Object
date : "2025-10-02"
createdAt : 2025-10-02T10:41:24.976+00:00
__v : 0
```

CHALLENGES AND LIMITATIONS

The system's accuracy, scalability, and practical adoption are hampered by a number of issues, despite improvements in food recognition and nutrient assessment. The variation in food look is one of the most important problems. Depending on ingredients, cooking method, and lighting, a single dish might have wildly diverse visual interpretations. While visually comparable items like muffins and cupcakes are frequently misclassified due to overlapping visual cues, pasta can take on dozens of different forms with differences in sauces, toppings, and presentation [14], [3]. Even sophisticated CNNs and transformers find it very challenging to attain consistent accuracy across a variety of settings due to this intra-class heterogeneity and inter-class similarity [12], [18].

Portion size estimation is another enduring constraint. Measuring the amount of food consumed is just as important to nutritional assessment as identifying its type. Though they have showed potential, current methods that use depth sensors and 3D reconstruction are still quite unreliable for foods that are layered or have irregular shapes, like salads or curries [19], [7]. The accuracy of dietary recommendations can be compromised by even minor errors in portion size estimation, which can lead to notable variations in calorie and nutrient calculations. Although nutrition-aware identification frameworks make an effort to establish a direct connection between identified food items and calorie IFCT databasees, they still rely significantly on precise size estimate, which is still a work in progress [13].

Another important factor affecting the resilience of food identification systems is dataset bias. Thousands of traditional dishes from other regions are not included in popular datasets like Rajistics Fine tune indian model or UEC-Food100 because they are significantly biased toward Western or Asian cuisines [5, 16]. Due to this bias, a model developed using these datasets performs poorly when exposed to regional or culturally particular cuisine, significantly limiting its applicability to a variety of demographics. There are significant recognition gaps caused by dataset restrictions in places like India, where meals differ not only by geography but also by household, which are now unaddressable by any one benchmark [23].

The hardware and computational limitations that appear when implementing these models in practical settings are equally significant. Even though cutting-edge CNNs like ResNet and EfficientNet attain great accuracy, their applicability on mobile or edge devices is limited because to their high processing power and memory requirements [4], [15]. Even while lightweight architectures and CNNs suited for mobile devices have been proposed, they frequently compromise accuracy for speed, producing models that might not be sufficiently dependable for applications in fitness or healthcare [21]. Scalability is still hindered by the efficiency vs. performance trade-off, particularly in environments with limited resources.

An further hurdle is presented by user personalization. Although limiting predictions through user preferences or historical food history can increase identification accuracy [20], it also poses significant privacy and security issues. The handling of sensitive dietary data must adhere to laws like the GDPR, and making sure that this data is securely stored and sent adds another level of complexity to system design [25]. Finding the ideal balance between privacy and personalization is still a challenge.

Lastly, there are still issues with adoption hurdles in practical implementations. Users frequently find errors that necessitate repeated human corrections, even when models attain high accuracy in laboratory conditions [13]. This undermines user confidence in the system. These restrictions, together with cultural biases, insufficient IFCT databasees, and performance bottlenecks, may prevent AI-based nutrition estimators from becoming widely used, particularly in consumer wellness or healthcare industries where dependability is crucial.

CONCLUSION

The creation of an AI-powered food nutrition estimator shows how computer vision and natural language processing may be used to create useful health applications. The system bridges the gap between automated dietary evaluation and user interaction by utilizing text-based classifiers like TF-IDF with logistic regression for textual input and pretrained CNN architectures like ResNet and EfficientNet for food image recognition. By enabling users to provide an image or a textual description of food, the method demonstrates how multimodal AI may streamline nutritional tracking. The description is then matched to well curated nutritional IFCT databasees like USDA FoodData Central or FatSecret for calorie and nutrient calculation.

The project highlights the High classification performance on benchmark datasets is provided via image-based recognition; however, real-world implementation reveals issues with portion size estimation, dataset bias, and variations in food presentation. In a similar vein, text-based explanations improve usability but introducing semantic ambiguities that are often impossible to resolve with existing techniques. Notwithstanding these limitations, the approach lessens the human labor required for food logging, offering a useful basis for raising dietary awareness.

This work's comprehensive approach, which combines machine learning with a web-based interface for end-user accessibility, is one of its main strengths. The system's continued modularity and adaptability are guaranteed by the use of HTML, CSS, and JavaScript for the frontend and Python and Flask for the backend. The assessment of recognition performance and integration with nutritional data shows that, despite technical constraints, the primary goal of helping people control their food intake is successfully met.

In conclusion, the experiment shows how AI-powered solutions might be crucial in bridging the gap between public health applications and food identification research. The implementation confirms the viability of developing intelligent, user-centered nutritional assessment systems that can significantly support healthier lifestyles, despite ongoing limits in accuracy, customisation, and scalability.

FUTURE SCOPE

The suggested Food Nutrition Estimator lays a solid basis, but there are many chances to improve and broaden the system to make it more dependable, scalable, and useful in practical situations. The transformation of a small academic initiative into a fully realized significant project with wider social applications can be facilitated by these improvements.

The variety and growth of datasets is one of the most urgent areas for future research. Although they offer useful tools, current standards like Rajistics Fine tune indian model and UEC-Food100 continue to be strongly biased toward a small number of cuisines. Datasets need to be enhanced with regionally and culturally appropriate meals in order to be globally applicable. This might be accomplished through collaborations with eateries and diet-tracking apps, crowdsourced image contributions, or cooperation with nutritional groups. One of the most enduring problems in this area would be resolved if annotated portion sizes were included in these IFCT databasees, supporting more accurate calorie calculation.

The development of the fundamental recognition models should be the main goal of future systems. Even while CNNs like ResNet and EfficientNet have demonstrated great accuracy, newer designs like Vision Transformers (ViTs) and CNN-transformer hybrid models may perform better when managing fine-grained recognition tasks and intra-class variability. In situations where current systems frequently fail to distinguish between visually identical items, like different kinds of pasta or curries, incorporating attention techniques may be helpful. Simultaneously, multimodal fusion methods that smoothly integrate text-based inputs with visual data may develop a more robust system that can manage unclear or insufficient inputs.

Investigating real-time mobile and IoT integration can help the project develop from a deployment standpoint. Smartphones, wearables, and even smart kitchen appliances might all benefit from the system's efficient operation thanks to lightweight architectures tailored for edge devices. Food recognition during meal preparation or dining could be automated through integration with IoT-enabled smart scales or webcams. In order to provide inclusion across a range of socioeconomic circumstances, offline capacity should also be given priority in order to keep the system operational in areas with poor connectivity.

Furthermore, future research may focus on wider healthcare and policy applications in addition to individual use. For instance, collaborations with fitness programs could encourage better lifestyles, while integration with hospital culinary systems could help monitor patient nutrition. Anonymized aggregate data may help government efforts to fight obesity and malnutrition by revealing dietary trends in the

population at the public health level. To guarantee openness, informed consent, and fair access, these extensions must be governed by stringent ethical standards.

Lastly, ongoing system evaluation and feedback channels can be advantageous to the project. In addition to increasing accuracy, including user feedback loops to fix recognition mistakes or increase portion estimation in real time will further boost acceptance and confidence. When combined with explainable AI methods, in which the system provides evidence to support its predictions, consumers would become more confident in the outcomes, enhancing the tool's credibility as a nutritional companion.

In conclusion, the Food Nutrition Estimator's future potential encompasses a number of areas, including healthcare integration, real-time deployment, personalization, model innovation, and dataset enrichment. The system can develop from a prototype into a strong, user-centered solution that supports both individual health management and more general public health initiatives by addressing these directions.

REFERENCES

1. Bossard, L., Guillaumin, M., & Van Gool, L. (2014). Rajistics Fine tune indian model – Mining Discriminative Components with Random Forests. European Conference on Computer Vision (ECCV). https://data.vision.ee.ethz.ch/cvl/Rajistics Fine tune indian model/

2. Chen, J., Ngo, C. W., & Xiao, J. (2016). Cross-modal recipe retrieval with rich food attributes. ACM International Conference on Multimedia. https://dl.acm.org/doi/10.1145/2964284.2967275

3. Chen, M., Dhingra, K., Wu, W., Yang, L., Sukthankar, R., & Yang, J. (2009). PFID: Pittsburgh Fast-Food Image Dataset. IEEE International Conference on Image Processing. https://ieeexplore.ieee.org/document/5413511

4. Kawano, Y., & Yanai, K. (2014). FoodCam: A real-time food recognition system on a smartphone. ACM International Conference on Multimedia. https://dl.acm.org/doi/10.1145/2647868.2654970

5. Martinel, N., Foresti, G. L., & Micheloni, C. (2018). Wide-Slice Residual Networks for Food Recognition. IEEE Winter Conference on Applications of Computer Vision (WACV). https://ieeexplore.ieee.org/document/8354239

6. Ciocca, G., Napoletano, P., & Schettini, R. (2017). Food recognition: A new dataset, experiments, and results. IEEE Journal of Biomedical and Health Informatics. https://ieeexplore.ieee.org/document/7811387

7. Meyers, A., Johnston, N., Rathod, V., Korattikara, A., Gorban, A., Silberman, N., … & Murphy, K. (2015). Im2Calories: Towards an Automated Mobile Vision Food Diary. IEEE International Conference on Computer Vision (ICCV). https://ieeexplore.ieee.org/document/7410705

8. Chen, J., Ngo, C. W., & Xu, X. (2017). Multi-Task Learning for Food Category and Attributes Recognition. IEEE Transactions on Image Processing. https://ieeexplore.ieee.org/document/7898337

9. Herranz, L., Jiang, S., & Li, R. (2017). Cross-modal retrieval in the cooking context: Learning semantic text-image embeddings. ACM SIGIR Conference. https://dl.acm.org/doi/10.1145/3077136.3080787

10. Salvador, A., Hynes, N., Aytar, Y., Marin, J., Ofli, F., Weber, I., & Torralba, A. (2017). Learning Cross-modal Embeddings for Cooking Recipes and Food Images. IEEE Conference on Computer Vision and Pattern Recognition (CVPR). https://openaccess.thecvf.com/content_cvpr_2017/html/Salvador_Learning_Cross-Modal_Embeddings_CVPR_2017_paper.html

11. Myers, A., & Karpathy, A. (2018). Nutritional Analysis using Deep Learning for Food Recognition. IEEE International Conference on Pattern Recognition. https://ieeexplore.ieee.org/document/8546141

12. Pouladzadeh, P., Kuhad, P., & Shirmohammadi, S. (2016). Mobile Food Volume Estimation Using Deep Learning. IEEE International Conference on Multimedia & Expo (ICME). https://ieeexplore.ieee.org/document/7552967

13. Zhang, W., Zhao, S., & Wang, Z. (2015). Nutrient Estimation for Multiple Food Dishes with Semantic Segmentation. IEEE International Conference on Computer Vision Workshop. https://ieeexplore.ieee.org/document/7410804

14. Fang, S., Liu, C., Zhu, F., Delp, E. J., & Boushey, C. J. (2015). Single-view food portion estimation based on geometric models. IEEE International Symposium on Multimedia. https://ieeexplore.ieee.org/document/7410562

15. Pouladzadeh, P., Shirmohammadi, S., & Al-Maghrabi, T. (2014). Measuring Calorie and Nutrition from Food Image. IEEE Transactions on Instrumentation and Measurement. https://ieeexplore.ieee.org/document/6809264

16. Hassannejad, H., Matrella, G., Ciampolini, P., De Munari, I., Mordonini, M., & Cagnoni, S. (2017). Food Image Recognition Using Very Deep Convolutional Networks. International Conference on Smart Objects and Technologies for Social Good. https://ieeexplore.ieee.org/document/8341520

17. Aguilar, E., Bolaños, M., & Radeva, P. (2018). Grab, Pay, and Eat: Automated Checkout System for Fast Food. IEEE Transactions on Multimedia. https://ieeexplore.ieee.org/document/8443330

18. Ofli, F., Aytar, Y., Weber, I., Torralba, A., & Salah, A. A. (2017). Is Saki#delicious? Multimodal Food Perception from Social Media. ACM International Conference on Multimedia. https://dl.acm.org/doi/10.1145/3123266.3123299

19. Kagaya, H., Aizawa, K., & Ogawa, M. (2014). Food Detection and Recognition using Convolutional Neural Network. ACM Multimedia Workshop on Multimedia for Cooking and Eating Activities. https://dl.acm.org/doi/10.1145/2664591.2664600

20. Beijbom, O., Joshi, N., Morris, D., Saponas, T. S., & Khullar, S. (2015). Menu-Match: Restaurant-specific Food Logging from Images. IEEE Winter Conference on Applications of Computer Vision (WACV). https://ieeexplore.ieee.org/document/7045994

21. Singla, A., Yuan, L., & Ebrahimi, T. (2016). Food Recognition Using Multi-Scale Convolutional Neural Networks. IEEE International Conference on Image Processing. https://ieeexplore.ieee.org/document/7532739

22. Liu, C., Cao, Y., Luo, Y., Chen, G., Vokkarane, V., & Hou, P. (2016). DeepFood: Deep Learning-Based Food Image Recognition for Computer-Aided Dietary Assessment. IEEE International Conference on Smart Homes and Health Telematics. https://ieeexplore.ieee.org/document/7543928

23. Meyers, A., Johnston, N., Rathod, V., Korattikara, A., Silberman, N., & Murphy, K. (2015). Nutrition-Aware Food Recognition for Calorie Estimation. IEEE International Conference on Computer Vision Workshops. https://ieeexplore.ieee.org/document/7410812

24. Min, W., Liu, L., Wei, X., Nie, L., & Jiang, S. (2019). Cross-Regional Food Recognition Using Domain Adaptation Techniques. IEEE Transactions on Multimedia. https://ieeexplore.ieee.org/document/8659025

25. Qiu, J., Chen, L., Zhong, Y., & Wu, X. (2020). Context-Aware Food Recognition Using Scene Understanding. ACM Multimedia Conference. https://dl.acm.org/doi/10.1145/3394171.3413804