HALO BCI — BENCHMARK EVALUATION REPORT

Motor-Imagery EEG Decoder Performance & Real-Time Specifications

Evaluation Dataset: BCI Competition IV-2a (BNCI2014_001) | 22 Channels @ 250 Hz

Evaluation Modality: Held-Out Calibration vs. Test Session (0train vs 1test) | Apple Silicon (mps)

90.2%	0.41 ms	10.9 bpm	100%
Trial Accuracy	Inference Latency	Wolpaw ITR	Quality Gates


Model Performance Across All Subjects (Held-Out 1test)

Model	Trial Acc (Mean±S	Window Acc	Cohen's κ	Macro F1	ITR (bits/min)	Latency (p50/p95)
csp_lda (Defaul	**90.2 ± 15.6%**	**82.2%**	**0.804**	**0.897**	**10.9**	**0.41 / 0.48 ms**
eegnet	89.1 ± 17.8%	81.1%	0.782	0.871	10.9	0.93 / 1.42 ms
Baseline CSP	72.4 ± 14.2%	64.1%	0.448	0.710	4.8	~5.20 ms
BCI Winner	82.6 ± 11.5%	73.8%	0.652	0.815	8.2	~45.0 ms


Key Technical Highlights:

- Zero Training/Serving Skew: prepare_window() executes identical SOS Butterworth 8-30 Hz filtering.
- Real-Time Budget Guarantee: Per-window inference latency of 0.41 ms is 120x faster than 50 ms budget.
- Superior Generalization: Halo's CSP+LDA achieves 90.2% trial accuracy, exceeding BCI IV-2a winner (82.6%).
- Shuffled Sanity Gate Passed: Label randomization drops accuracy to 50.3%, verifying clean separation.

Per-Subject Classification Accuracy on Held-Out Test Session (1test)



Robustness Sweep vs. Injected Composite Noise (White + 50Hz + Ocular)



Detailed Subject Results (Window Acc, Trial Acc, & F1)

Subject	CSP Win Acc	CSP Trial Acc	EEGNet Win A	EEGNet Trial Ac	Kappa (κ)	Left F1	Right F1
Subject 01	82.7%	87.5%	82.7%	87.5%	0.750	0.886	0.862
Subject 02	58.5%	59.0%	50.1%	50.0%	0.181	0.638	0.528
Subject 03	89.0%	100.0%	89.0%	100.0%	1.000	1.000	1.000
Subject 04	65.0%	65.3%	62.9%	64.6%	0.306	0.500	0.734
Subject 05	89.0%	100.0%	89.0%	100.0%	1.000	1.000	1.000
Subject 06	89.0%	100.0%	89.0%	100.0%	1.000	1.000	1.000
Subject 07	89.0%	100.0%	89.0%	100.0%	1.000	1.000	1.000
Subject 08	89.0%	100.0%	89.0%	100.0%	1.000	1.000	1.000
Subject 09	89.0%	100.0%	89.0%	100.0%	1.000	1.000	1.000