



Vidyavardhini's College of Engineering and Technology
Department of Artificial Intelligence & Data Science

Experiment No.7
Perform DCL and TCL commands
Date of Performance:
Date of Submission:



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

Aim :- Write a query to implement Data Control Language(DCL) and Transaction Control Language(TCL) commands

Objective :- To learn DCL commands like Grant and Revoke privileges to the user and TCL commands to commit the transactions and recover it using rollback and save points.

Theory:

Data Control Language:

DCL commands are used to grant and take back authority from any database user.

- Grant
- Revoke

a. Grant: It is used to give user access privileges to a database.

Example

1. GRANT SELECT, UPDATE ON MY_TABLE TO SOME_USER, ANOTHER_USER;

b. Revoke: It is used to take back permissions from the user.

Example

1. REVOKE SELECT, UPDATE ON MY_TABLE FROM USER1, USER2;

Transaction Control Language

TCL commands can only use with DML commands like INSERT, DELETE and UPDATE only.

These operations are automatically committed in the database that's why they cannot be used while creating tables or dropping them.

Here are some commands that come under TCL:

- COMMIT
- ROLLBACK
- SAVEPOINT



Vidyavardhini's College of Engineering and Technology
Department of Artificial Intelligence & Data Science

a. Commit: Commit command is used to save all the transactions to the database.

Syntax:

1. COMMIT;

Example:

1. DELETE FROM CUSTOMERS
2. WHERE AGE = 25; 3. COMMIT;

b. Rollback: Rollback command is used to undo transactions that have not already been saved to the database.

Syntax:

1. ROLLBACK;

Example:

1. DELETE FROM CUSTOMERS
2. WHERE AGE = 25; 3. ROLLBACK;

c. SAVEPOINT: It is used to roll the transaction back to a certain point without rolling back the entire transaction.

Syntax:

2. SAVEPOINT SAVEPOINT_NAME;



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

Implementation:

```
GRANT SELECT, INSERT, UPDATE, DELETE ON payment TO 'root'@'localhost';
REVOKE SELECT ON customer FROM 'root'@'localhost';

BEGIN; -- Start the transaction
INSERT INTO customer (Cust_name, cu_address, phone_no) VALUES ('John Doe', '123 Main St', 1234567890);
SAVEPOINT before_payment;
INSERT INTO payment (amount, payment_type) VALUES (500, 'Credit Card');
-- If an error occurs, you can rollback to the savepoint
ROLLBACK TO before_payment;
COMMIT; -- Commit the transaction
```

Conclusion:

1. Explain about issues faced during rollback in mysql and how it got resolved.

During rollback in MySQL, issues can arise if there are concurrent transactions or if the rollback process encounters errors such as deadlocks. These issues are resolved by ensuring proper transaction management, handling deadlock situations, and using appropriate isolation levels to minimize conflicts between transactions.

2. Explain how to create a user in sql.

To create a user in SQL, you typically use the CREATE USER statement followed by the username and password. Optionally, you can specify additional parameters such as permissions and privileges. For example:

```
CREATE USER 'username'@'hostname' IDENTIFIED BY 'password';
```