EXPERIMENT 8

Student Name: Aryan Yadav **UID: 24BCF10079**
Branch: AIT-CSE (FSD) **Section/Group: 24AIT_KRG-G2**
Semester: 4
Subject Name: Database Management System **Subject Code: 24CSH-298**

Experiment 8 – Design of a Parameterized PL/SQL Stored Procedure for Employee Count by Gender (CData, Toddle)

Experiment

Experiment 8: Designing and implementing a parameterized PL/SQL stored procedure that accepts gender as an input parameter and returns the total number of employees based on the given gender. This experiment demonstrates procedural programming, parameterized logic, and dynamic data retrieval in a database environment.

Aim

To design and implement a stored procedure that accepts gender as an input parameter and returns the total number of employees based on the gender passed, thereby demonstrating procedural programming and parameterized logic in PL/SQL.

Objective

- To understand the structure and components of a PL/SQL stored procedure.
- To implement IN and OUT parameters in stored procedures.
- To pass dynamic input values to procedures.
- To apply aggregate functions for data analysis.
- To develop reusable database logic for real-world business scenarios.

Software Requirements

Database Management System:

- Oracle Database Express Edition (Oracle XE)
- PostgreSQL Database

Database Administration Tool / Client Tool:

EXPERIMENT 8

- Oracle SQL Developer (for Oracle XE)
- pgAdmin (for PostgreSQL)

Problem Statement

Organizations often require flexible reporting mechanisms to analyze workforce distribution based on gender for compliance and internal analytics. A dynamic and reusable solution is needed to efficiently retrieve employee counts based on gender input.

Practical / Experiment Steps

- Create an employee table with relevant attributes.
- Insert sample data into the employee table.
- Design a stored procedure that accepts gender as an input parameter.
- Use an aggregate function to count employees based on the given gender.
- Return the result using an OUT parameter.
- Execute the stored procedure with different gender inputs.
- Analyze the output.

Procedure

1. Open Oracle SQL Developer or pgAdmin and connect to the database.
2. Create the employee table with fields such as id, name, and gender.
3. Insert sample records into the table.
4. Create a PL/SQL stored procedure with IN and OUT parameters.
5. Write a SELECT COUNT(*) query inside the procedure.
6. Compile the procedure successfully.
7. Execute the procedure using different gender values.
8. Display the output.
9. Capture results for documentation.

EXPERIMENT 8

Input / Output Details

Input

- Table:
  - employee (id, name, gender)
- Input Parameter:
  - Gender value (e.g., 'Male', 'Female')

Step-wise Output

Step 1 – Create Employee Table

Query Query History

```sql
CREATE TABLE employees (
    emp_id SERIAL PRIMARY KEY,
    emp_name VARCHAR(50),
    gender VARCHAR(10),
    salary NUMERIC(10,2)
);

INSERT INTO employees (emp_name, gender, salary) VALUES
('Amay', 'Male', 30000),
('Ria', 'Female', 35000),
('Amrit', 'Male', 28000),
('Sneha', 'Female', 40000)

--count numbe of employees based on Gender

SELECT * FROM EMPLOYEES;
```

Data Output Messages Notifications

```
CREATE TABLE

Query returned successfully in 250 msec.
```

EXPERIMENT 8

Step 2 – Insert Sample Data

Query Query History

```sql
CREATE TABLE employees (
    emp_id SERIAL PRIMARY KEY,
    emp_name VARCHAR(50),
    gender VARCHAR(10),
    salary NUMERIC(10,2)
);

INSERT INTO employees (emp_name, gender, salary) VALUES
('Amay', 'Male', 30000),
('Ria', 'Female', 35000),
('Amrit', 'Male', 28000),
('Sneha', 'Female', 40000)

--count numbe of employees based on Gender

SELECT * FROM EMPLOYEES;
```

Data Output Messages Notifications

```
INSERT 0 4

Query returned successfully in 101 msec.
```

Step 3 – Create Stored Procedure

Query Query History

```sql
--count numbe of employees based on Gender

SELECT * FROM EMPLOYEES;

CREATE OR REPLACE PROCEDURE get_Employee_Count_BY_Gender(IN P_GEN VARCHAR(20), OUT COUNT_EMP INT, INOUT STATUS
AS
    $$
        BEGIN

            SELECT COUNT(*) INTO COUNT_EMP FROM EMPLOYEES WHERE GENDER=P_GEN;
            STATUS:='SUCCESS';
        END;
     $$ LANGUAGE PLPGSQL


        DO
        $$
```

Data Output Messages Notifications

```
CREATE PROCEDURE

Query returned successfully in 281 msec.
```

Step 4 – Execute Stored Procedure

Query Query History

```
DO
$$
DECLARE
    GEN VARCHAR(20):='Male';
    COUNT_BY_GEN INT;
    STATUS VARCHAR(20):='Fail';
BEGIN

    CALL  get_Employee_Count_BY_Gender(GEN,COUNT_BY_GEN,STATUS);

    RAISE NOTICE 'GENDER IS % YOUR COUNT IS %  AND STATUS IS %',GEN,COUNT_BY_GEN,STATUS;

END;

$$
```

Data Output Messages Notifications

```
NOTICE:  GENDER IS Male YOUR COUNT IS 2  AND STATUS IS SUCCESS
DO

Query returned successfully in 93 msec.
```

Learning Outcome

After completing this experiment, the learner will be able to:

- Understand procedural programming in PL/SQL.
- Implement parameterized stored procedures using IN and OUT parameters.
- Perform dynamic data retrieval based on user input.
- Use aggregate functions like COUNT() within procedures.
- Develop reusable and efficient database logic for enterprise applications used in companies like CData and Toddle.