Experiment - 3

Home | Windows 10 | Aryan | FlareVM-Generic | Metasploitable2-Linu

linux_labs : zsh — Konsole

New Tab | Split View | Cop

```
┌──(kali㉿kali)-[~/AryanShukla_2301410018]
└─$ pwd
/home/kali/AryanShukla_2301410018

┌──(kali㉿kali)-[~/AryanShukla_2301410018]
└─$ ls
Lab1,  Lab2,  linux_labs  names_RollNo.txt

┌──(kali㉿kali)-[~/AryanShukla_2301410018]
└─$ ls -l
total 16
drwxrwxr-x 3 kali kali 4096 Apr 28 11:51 Lab1,
drwxrwxr-x 2 kali kali 4096 Apr 28 11:47 Lab2,
drwxrwxr-x 2 kali kali 4096 Apr 28 13:59 linux_labs
-rw-rw-r-- 1 kali kali  132 Apr 28 12:08 names_RollNo.txt

┌──(kali㉿kali)-[~/AryanShukla_2301410018]
└─$ mkdir linux_labs
mkdir: cannot create directory 'linux_labs': File exists

┌──(kali㉿kali)-[~/AryanShukla_2301410018]
└─$ mkdir linux_labs

┌──(kali㉿kali)-[~/AryanShukla_2301410018]
└─$ cd linux_labs

┌──(kali㉿kali)-[~/AryanShukla_2301410018/linux_labs]
└─$ touch file1.txt file2.txt

┌──(kali㉿kali)-[~/AryanShukla_2301410018/linux_labs]
└─$
```

```
└$ touch file1.txt file2.txt

┌──(kali㉿kali)-[~/AryanShukla_2301410018/linux_labs]
└─$ nano file

┌──(kali㉿kali)-[~/AryanShukla_2301410018/linux_labs]
└─$ nano file1.txt

┌──(kali㉿kali)-[~/AryanShukla_2301410018/linux_labs]
└─$
```

Home | Windows 10 | Aryan | FlareVM-Generic | Metasploitable2-Linux

linux_labs : vi — Konsole

New Tab | Split View | Copy | Paste | Find...

```
Kali Linux is an Ethical Hacking and Penetration Testing OS made with Linux.
~
~
~
~
~
~
~
```

```
┌──(kali㉿kali)-[~/AryanShukla_2301410018/linux_labs]
└─$ nano file2.txt

┌──(kali㉿kali)-[~/AryanShukla_2301410018/linux_labs]
└─$ vi file1.txt file2.txt
2 files to edit

┌──(kali㉿kali)-[~/AryanShukla_2301410018/linux_labs]
└─$
```

```
┌──(kali㉿kali)-[~/AryanShukla_2301410018/linux_labs]
└─$ vi file1.txt file2.txt
2 files to edit

┌──(kali㉿kali)-[~/AryanShukla_2301410018/linux_labs]
└─$ cat file1.txt
Kali Linux is an Ethical Hacking and Penetration Testing OS made with Linux.


┌──(kali㉿kali)-[~/AryanShukla_2301410018/linux_labs]
└─$ cat file2.txt
Kali Linux is preloaded with tools used in hacking and penetration testing.

┌──(kali㉿kali)-[~/AryanShukla_2301410018/linux_labs]
└─$
```

```
┌──(kali㉿kali)-[~/AryanShukla_2301410018/linux_labs]
└─$ cat file2.txt
Kali Linux is preloaded with tools used in hacking and penetration testing.

┌──(kali㉿kali)-[~/AryanShukla_2301410018/linux_labs]
└─$ ls -l
total 8
-rw-rw-r-- 1 kali kali 80 Apr 28 14:08 file1.txt
-rw-rw-r-- 1 kali kali 77 Apr 28 14:05 file2.txt

┌──(kali㉿kali)-[~/AryanShukla_2301410018/linux_labs]
└─$ chmod 755 file1.txt

┌──(kali㉿kali)-[~/AryanShukla_2301410018/linux_labs]
└─$ ls -l file1.txt
-rwxr-xr-x 1 kali kali 80 Apr 28 14:08 file1.txt

┌──(kali㉿kali)-[~/AryanShukla_2301410018/linux_labs]
└─$ stat file1.txt
  File: file1.txt
  Size: 80              Blocks: 8          IO Block: 4096   regular file
Device: 8,1     Inode: 1310848     Links: 1
Access: (0755/-rwxr-xr-x)  Uid: ( 1000/    kali)   Gid: ( 1000/    kali)
Access: 2026-04-28 14:09:11.883343518 +0530
Modify: 2026-04-28 14:08:26.061484904 +0530
Change: 2026-04-28 14:09:54.745718574 +0530
 Birth: 2026-04-28 14:08:26.061484904 +0530

┌──(kali㉿kali)-[~/AryanShukla_2301410018/linux_labs]
└─$
```