Experiment - 2

```
┌──(kali㉿kali)-[~/AryanShukla_2301410018]
└─$ pwd
/home/kali/AryanShukla_2301410018

┌──(kali㉿kali)-[~/AryanShukla_2301410018]
└─$ ls
Lab1,  Lab2,  names_RollNo.txt

┌──(kali㉿kali)-[~/AryanShukla_2301410018]
└─$ whoami
kali

┌──(kali㉿kali)-[~/AryanShukla_2301410018]
└─$ date
Tue Apr 28 01:47:55 PM IST 2026

┌──(kali㉿kali)-[~/AryanShukla_2301410018]
└─$ uptime
 13:47:59 up 50 min,  1 user,  load average: 0.30, 0.19, 0

┌──(kali㉿kali)-[~/AryanShukla_2301410018]
└─$ cd /home

┌──(kali㉿kali)-[/home]
└─$ cd ~
```

```
LS(1)                                User Commands                                LS(1

NAME
       ls - list directory contents

SYNOPSIS
       ls [OPTION]... [FILE]...

DESCRIPTION
       List  information  about the FILEs (the current directory by default).  Sort entrie
       alphabetically if none of -cftuvSUX nor --sort is specified.

       Mandatory arguments to long options are mandatory for short options too.

       -a, --all
              do not ignore entries starting with .

       -A, --almost-all
              do not list implied . and ..

       --author
              with -l, print the author of each file

       -b, --escape
              print C-style escapes for nongraphic characters

       --block-size=SIZE
              with -l, scale sizes by SIZE when printing them; e.g., '--block-size=M';  se
              SIZE format below

       -B, --ignore-backups
              do not list implied entries ending with ~

       -c     with -lt: sort by, and show, ctime (time of last change of file status infor
              mation);  with  -l:  show  ctime  and sort by name; otherwise: sort by ctime
              newest first

       -C     list entries by columns

       --color[=WHEN]
              color the output WHEN; more info below

       -d, --directory
 Manual page ls(1) line 1 (press h for help or q to quit)
```

New Tab Split View Copy Paste Find

```
┌──(kali㉿kali)-[~]
└─$ man ls

┌──(kali㉿kali)-[~]
└─$ ls --help
Usage: ls [OPTION]... [FILE]...
List information about the FILEs (the current directory by default).
Sort entries alphabetically if none of -cftuvSUX nor --sort is specified.

Mandatory arguments to long options are mandatory for short options too.
  -a, --all                  do not ignore entries starting with .
  -A, --almost-all           do not list implied . and ..
      --author               with -l, print the author of each file
  -b, --escape               print C-style escapes for nongraphic characters
      --block-size=SIZE      with -l, scale sizes by SIZE when printing them;
                             e.g., '--block-size=M'; see SIZE format below

  -B, --ignore-backups       do not list implied entries ending with ~
  -c                         with -lt: sort by, and show, ctime (time of last
                             change of file status information);
                             with -l: show ctime and sort by name;
                             otherwise: sort by ctime, newest first

  -C                         list entries by columns
      --color[=WHEN]         color the output WHEN; more info below
  -d, --directory            list directories themselves, not their contents
  -D, --dired                generate output designed for Emacs' dired mode
  -f                         same as -a -U
  -F, --classify[=WHEN]      append indicator (one of */=>@|) to entries WHEN
      --file-type            likewise, except do not append '*'
      --format=WORD          across,horizontal (-x), commas (-m), long (-l),
                             single-column (-1), verbose (-l), vertical (-C)

      --full-time            like -l --time-style=full-iso
  -g                         like -l, but do not list owner
      --group-directories-first
                             group directories before files
  -G, --no-group             in a long listing, don't print group names
  -h, --human-readable       with -l and -s, print sizes like 1K 234M 2G etc.
      --si                   likewise, but use powers of 1000 not 1024
  -H, --dereference-command-line
                             follow symbolic links listed on the command line
      --dereference-command-line-symlink-to-dir
```

1:50 PM
4/28/26

~ : systemctl — Konsole

```
┌──(kali㉿kali)-[~]
└─$ systemctl --help
systemctl [OPTIONS...] COMMAND ...

Query or send control commands to the system manager.

Unit Commands:
  list-units [PATTERN...]             List units currently in memory
  list-automounts [PATTERN...]        List automount units currently in memory,
                                      ordered by path
  list-paths [PATTERN...]             List path units currently in memory,
                                      ordered by path
  list-sockets [PATTERN...]           List socket units currently in memory,
                                      ordered by address
  list-timers [PATTERN...]            List timer units currently in memory,
                                      ordered by next elapse
  is-active PATTERN...                Check whether units are active
  is-failed [PATTERN...]              Check whether units are failed or
                                      system is in degraded state
  status [PATTERN...|PID...]          Show runtime status of one or more units
  show [PATTERN...|JOB...]            Show properties of one or more
                                      units/jobs or the manager
  cat PATTERN...                      Show files and drop-ins of specified units
  help PATTERN...|PID...              Show manual for one or more units
  list-dependencies [UNIT...]         Recursively show units which are required
                                      or wanted by the units or by which those
                                      units are required or wanted
  start UNIT...                       Start (activate) one or more units
  stop UNIT...                        Stop (deactivate) one or more units
  reload UNIT...                      Reload one or more units
  restart UNIT...                     Start or restart one or more units
  try-restart UNIT...                 Restart one or more units if active
  reload-or-restart UNIT...           Reload one or more units if possible,
                                      otherwise start or restart
  try-reload-or-restart UNIT...       If active, reload one or more units,
                                      if supported, otherwise restart
  isolate UNIT                        Start one unit and stop all others
  kill UNIT...                        Send signal to processes of a unit
  clean UNIT...                       Clean runtime, cache, state, logs or
                                      configuration of unit
  freeze PATTERN...                   Freeze execution of unit processes
  thaw PATTERN...                     Resume execution of a frozen unit
  set-property UNIT PROPERTY=VALUE... Sets one or more properties of a unit
```

```
  set-property UNIT PROPERTY=VALUE... Sets one or more properties of a unit
  bind UNIT PATH [PATH]               Bind-mount a path from the host into a
                                      unit's namespace

┌──(kali㉿kali)-[~]
└─$ systemctl get-default
graphical.target

┌──(kali㉿kali)-[~]
└─$
```