

**Product Category:** 09.22.16 - Non-Structural Metal Framing

**Product Name:** 350S125-18

**Available Finish:** G40, G60

\*Other standard coatings referenced in ASTM A1003

**Web Depth:** 3-1/2 in

**Flange Width:** 1-1/4 in

**Design Thickness:** 0.0188 in

**Gauge:** 18 mils or 25G

**Yield stress, Fy:** 33 ksi

**Weight:** 0.39 lb/ft


**Gross Section Properties**

Cross sectional area (A)	0.115 in <sup>2</sup>
Moment of inertia (Ix)	0.215 in <sup>4</sup>
Section Modulus (Sx)	0.123 in <sup>3</sup>
Radius of gyration (Rx)	1.366 in
Gross moment of inertia (Iy)	0.021 in <sup>4</sup>
Gross Radius of gyration (Ry)	0.423 in

**Effective Section Properties**

Moment of inertia for deflection (Ix)	0.197 in <sup>4</sup>
Section modulus (Sx)	0.072 in <sup>3</sup>
Allowable bending moment (Ma)	1.420 In-k
Allowable bending moment from distortional buckling (Mad)	1.33 In-k
Allowable strong axis shear away from punch-out (Vag)	180 lb
Allowable strong axis shear at punch out (Vanet)	159 lb

- Calculated properties are based on AISI S100-16/S2-20, North American Specification for Design of Cold-Formed Steel Structural Members and meets the requirements of the IBC 2021 Building Code.
- The centerline bend radius is based on inside corner radii shown in thickness chart.
- Effective properties incorporate the strength increase from the cold work of forming as applicable per AISI A7.2.
- Tabulated gross properties are based on full-unreduced cross section of the studs, away from punchouts.
- For deflection calculations, use the effective moment of inertia.
- Allowable moment includes cold-work of forming.


**Torsional Properties**

St. Venant torsion constant (J x 1000)	0.014 in <sup>4</sup>
Warping constant (Cw)	0.050 in <sup>6</sup>
Distance from shear center to neutral axis (Xo)	-0.798 in
Distance from shear center to mid-plane of web (m)	0.495 in
Radius of gyration (Ro)	1.638 in
Torsional flexural constant (β)	0.763
Unbraced Length (Lu)	28.8 in

**Fully Braced Non-Composite Limiting Heights Table Notes**

- 5 psf, 7.5 psf, and 10 psf loads have NOT been reduced for strength or deflection checks.
- Calculated properties are based on AISI S100-16/S2-20, North American Specification for Cold-Formed Steel Structural Members and meets the requirements of the IBC 2021 Building Code.
- Limiting heights are based on continuous support of each flange over the full length of the stud.
- Limiting heights are based on steel properties only (non-composite).
- Web crippling checks are based on end-one flange loading condition using 1-inch end bearing.

**Non-Composite Limiting Heights – Fully Braced**

Spacing (inches)	5psf L/120	5psf L/240	5psf L/360	7.5psf L/120	7.5psf L/240	7.5psf L/360	10psf L/120	10psf L/240	10psf L/360
12	13'-4"	13'-4"	11'-11"	10'-10"	10'-10"	10'-5"	9'-5"	9'-5"	9'-5"
16	11'-6"	11'-6"	10'-10"	9'-5"	9'-5"	9'-5"	8'-1"	8'-1"	8'-1"
24	9'-5"	9'-5"	9'-5"	7'-8"	7'-8"	7'-8"	6'-8"	6'-8"	6'-8"

**Interior Composite Limiting Heights**

Spacing (inches)	5psf L/120	5psf L/240	5psf L/360	7.5psf L/120	7.5psf L/240	7.5psf L/360	10psf L/120	10psf L/240	10psf L/360	15psf L/120	15psf L/240	15psf L/360
12	18' 3"	16' 4"	14' 4"	14' 11"	14' 4"	12' 6"	12' 11"	12' 11"	11' 4"	8' 5"	8' 5"	8' 5"
16	15' 10"	14' 10"	13' 0"	12' 11"	12' 11"	11' 4"	11' 2"	11' 2"	10' 3"			
24	12' 11"	12' 11"	11' 4"	10' 7"	10' 7"	9' 11"	9' 2"	9' 2"	9' 10"			

**Additional Information**

MRI Steel Framing, LLC is an SFIA member. MRI acts in accordance with the product and quality standards required by the SFIA program.

MRI meets or exceeds ASTM C645, C754, A653, and A1003.

Current LEED credits available upon request