


FINE FISSURED FINE FISSURED HIGH NRC FINE FISSURED CUSTOMLINE®

MINERAL FIBER FISSURED



A non-directional mineral fiber panel for all-around workability, affordability and great-looking installations.

FEATURES AND BENEFITS

- Non-directional fissured pattern
- High NRC panels comply with LEED v4 for School classroom acoustics prerequisite
- Customline options provide three dramatic geometric designs with discreet small-scale fissure pattern
- High humidity and sag resistant
- USDA Certified Biobased content at 98%
- Available in 6 standard colors for item numbers HHF-154, HHF-157, HHF-197, FFCL-224

ATTRIBUTES



NRC
UP TO 0.75



SAG RESISTANT



BIOSHIELD®
MOLD/MILDEW
RESISTANT



LOW
VOC
EMISSION
COMPLIANT
CERTIFIED



LR 0.83/0.84

LEED® v4

RECYCLED CONTENT		
FINE FISSURED	33%	
	PRE: 28%	POST: 5%
PROTECTONE	44%	
	PRE: 42%	POST: 2%
FINE FISSURED HIGH NRC	70%	
	PRE: 68%	POST: 2%

- ✓ MR: PBT Source Reduction (Healthcare)
- ✓ EQ: Acoustic Performance
- ✓ EQ: Prereq. Min. Acoustic Performance (Schools)
- ✓ EQ: Low-Emitting Materials
- ✓ EQ: Daylight
- ✓ MR: Material Ingredients (HPDs)
- ✓ MR: Sourcing Raw Materials
- ✓ MR: Environmental Product Declarations (EPDs)
- ✓ MR: Construction and Demolition Waste Management Planning

LEED® is a registered trademark of the U.S. Green Building Council.

CERTIFICATIONS & PRODUCT DECLARATIONS



EPD AVAILABLE


HPD AVAILABLE

ARCHITECTURAL


CertainTeed
SAINT-GOBAIN

FINE FISSURED | FINE FISSURED HIGH NRC


FINE FISSURED CUSTOMLINE®




CUSTOMLINE SCORING OPTIONS





FINE FISSURED HIGH NRC


			FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	UL FIRE-RATED	LR	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET
TRIM													
	NRC .75	HHF-457 HNRCX	Panels	24 x 24 x 3/4	0.75	35	70%	—	0.83	14	56	55	16
		HHF-497 HNRCX	Panels	24 x 48 x 3/4	0.75	35	70%	—	0.83	8	64	62	16

REVEAL													
	NRC .75	HHF-454 HNRCX	Panels	24 x 24 x 3/4	0.75	35	70%	—	0.83	14	56	55	16
		HHF-494 HNRCX	Panels	24 x 48 x 3/4	0.75	35	70%	—	0.83	8	64	62	16


FINE FISSURED

			FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	UL FIRE-RATED	LR	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET
TRIM													
	NRC .55	HHF-157	Panels	24 x 24 x 5/8	0.55	33	33%	—	0.84	16	64	50	20
		PFF-157	Panels	24 x 24 x 5/8	0.55	35	44%	YES*	0.84	16	64	70	20
		HHF-197	Panels	24 x 48 x 5/8	0.55	35	33%	—	0.84	8	64	45	20
		PFF-197	Panels	24 x 48 x 5/8	0.55	40	44%	YES*	0.84	8	64	70	20
		HHF-177	Panels	24 x 60 x 5/8	0.55	35	33%	—	0.84	8	80	51	20
		HHF-2067	Panels	20 x 60 x 5/8	0.55	35	33%	—	0.84	8	66.7	52	16

REVEAL													
	NRC .55	HHF-154	Panels	24 x 24 x 5/8	0.55	33	33%	—	0.84	16	64	45	20
		PFF-154	Panels	24 x 24 x 5/8	0.55	35	44%	YES*	0.84	16	64	70	20
		HHF-194	Panels	24 x 48 x 5/8	0.55	35	33%	—	0.84	8	64	45	20

NARROW REVEAL													
	NRC .55	HHF-150	Panels	24 x 24 x 5/8	0.55	35	33%	—	0.84	16	64	45	20

FINE FISSURED METRIC

			FORMAT	DIMENSIONS (MM)	NRC	CAC	RECYCLED CONTENT	UL FIRE-RATED	LR	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET
METRIC TRIM													
	NRC .55	HHF-2067M	Panels	500 x 1500 x 15	0.55	35	33%	—	0.84	8	6	52	20

* Protectone®: A fire-resistive ceiling when used in applicable UL/ULC assemblies. Protectone product is indicated by a Yes in the UL Fire-Rated column.


To specify color other than white, order by item number followed by color code. Example: HHF-154 BEB. Color List: Beige Breeze – BEB, Blondewood – BLW, Silver Lining – SIL, Wet Clay – WEC, White Wash – WIW. Only available for HHF-154, HHF-157, HHF-197, and FFCL-224 products.


CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990

FINE FISSURED | FINE FISSURED HIGH NRC

FINE FISSURED CUSTOMLINE®

FINE FISSURED CUSTOMLINE

			FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	UL FIRE-RATED	LR	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET
REVEAL													
	NRC .55	FFCL-224	Panels	24 x 48 x 3/4	0.55	38	33%	—	0.84	8	64	64	16
	NRC .50	FFCL-448	Panels	24 x 48 x 3/4	0.50	38	33%	—	0.84	8	64	60	16
		FFCL-812	Panels	24 x 48 x 3/4	0.50	38	33%	—	0.84	8	64	64	16
		PFFCL-224	Panels	24 x 48 x 3/4	0.50	40	33%	YES*	0.84	8	64	75	16


NARROW REVEAL													
	NRC .55	FFCLN-224	Panels	24 x 48 x 3/4	0.55	38	33%	—	0.84	8	64	64	16
	NRC .50	FFCLN-448	Panels	24 x 48 x 3/4	0.50	38	33%	—	0.84	8	64	60	16
		FFCLN-812	Panels	24 x 48 x 3/4	0.50	38	33%	—	0.84	8	64	64	16

* Protectone®: A fire-resistive ceiling when used in applicable UL assemblies. Protectone product is indicated by a Yes in the UL Fire-Rated column.


To specify color other than white, order by item number followed by color code. Example: HHF-154 BEB. Color List: Beige Breeze – BEB, Blondewood – BLW, Silver Lining – SIL, Wet Clay – WEC, White Wash – WIW. Only available for HHF-154, HHF-157, HHF-197, and FFCL-224 products.

CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990


EDGE DETAILS




Trim
9/16" EZ Stab
Elite Narrow




Trim -
15/16" EZ Stab
Classic




Reveal Beveled
15/16" EZ Stab
Classic




Narrow Reveal
Corner Bevel
9/16" EZ Stab
Elite Narrow



Narrow Reveal
Corner Bevel
9/16" EZ Stab
Bolt Slot



Narrow Reveal
Beveled (Customline)
9/16" EZ Stab
Elite Narrow



Narrow Reveal
Corner Bevel
9/16" EZ Stab
Tier Drop

Color-coordinated suspension systems available

PHYSICAL DATA

MATERIAL

Mineral Fiber

FIRE CLASS

All are Class A per ASTM E84 & CAN S102
Flame Spread: 25 or less
Smoke Developed: 50 or less

ASTM E1264 CLASSIFICATION

Type III, Form 2, Pattern C E
(Standard & High NRC)
Type III, Form 2, Pattern C E K (Customline)

VOC EMISSIONS

Independently certified compliant with
California Department of Public Health
CDPH/EHLB/Standard Method
Version 1.2, 2017.

INSTALLATION CONSIDERATION

Customline & Colors Note: Product is lot sensitive.
Differing manufacturing dates should not be mixed
in a single ceiling or unbroken area.

MAINTENANCE

Wipe with a soft cloth or vacuum
with brush attachment.

MOLD/MILDEW RESISTANCE

BioShield® treatment included for added mold
and mildew resistance.

WARRANTY

10-year 104/90 Limited Warranty increases
to 15 years when installed with CertainTeed
suspension systems. Full warranty information
can be found at [certainteed.com/warranty](https://www.certainteed.com/warranty).



CertainTeed ARCHITECTURAL

METAL • WOOD • FELT • FIBERGLASS & MINERAL FIBER • GYPSUM • SUSPENSION & INTEGRATED SYSTEMS
20 Moores Road, Malvern, PA 19355 800-233-8990 [certainteed.com/architectural](https://www.certainteed.com/architectural)

© 11/22 CertainTeed, Printed in the USA, Code No. 11-11-666-US-EN