



SOUNDSCAPES® Blades

Linear Acoustical Panels
fine texture

FAST134

Select Items Ship Fast

armstrongceilings.com/fast134



SoundScapes® Blades in White, Stone, and Black

CAD/Revit® drawings at:
armstrongceilings.com/cadrevit



Wall application

SoundScapes® Blades vertical panels achieve acoustical excellence in your space – with versatile ways to install on ceilings and walls.

KEY SELECTION ATTRIBUTES



- Now available in 15 colors inspired by nature
- Mix standard designs, lengths, and depths for dynamic visuals
- Sound absorption up to 1.80 NRC dependent on blade depth and spacing
- Select products included in the FAST134 program – ready to ship in 4 weeks or less




- Color-coordinated Prelude® suspension systems available
- Three installation options for maximum ceiling and wall design flexibility
 - From standard suspension system
 - From individual cable suspension
 - Direct-attach method using Axiom® wall molding
- 20 vertical panel sizes and shapes
- Mold- and mildew-resistant surface
- Linear, upscale visual
- Seismic-tested
- White embedded hanging clips
- CleanAssure™ family of products – includes disinfectable panels, suspension systems, and trim

- Custom panel options available
- Add scrim to top edge as a premium option
- ASTM E84 Class A Fire Performance

COLORS Due to printing limitations, shade may vary from actual product.



Painted



For premium and custom capabilities, contact ASQuote@armstrongceilings.com



Wood Looks Available!

TechLine 877 276-7876

armstrongceilings.com/soundscapesblades





Armstrong®
World Industries

SOUNDSCAPES® Blades

Linear Acoustical Panels
fine texture





ACOUSTIC INFORMATION



Panel Depth	NRC			
	6" O.C.	12" O.C.	18" O.C.	24" O.C.
5"	0.80	0.50	0.40	0.30
7-1/2"	1.00	0.65	0.50	0.40
10"	1.15	0.80	0.60	0.50
10-1/2"	1.15	0.80	0.60	0.50
16"	1.35	1.00	0.75	0.55
19-1/2"	1.40	1.00	0.75	0.60
22"	1.45	1.00	0.75	0.65
22-1/2"	1.45	1.00	0.80	0.65
28"	1.80	1.35	1.10	0.95

NOTE: Tested per ASTM C423 without infill panels. Spacing of blades, blade depth, and acoustical infill panels will impact acoustical performance. Contact TechLine for a custom reverberation time report at techline@armstrongceilings.com

CUSTOM PANEL DESIGN EXAMPLES



SOUNDSCAPES® Blades

Linear Acoustical Panels
fine texture



43% RECYCLED CONTENT



LOCATION DEPENDENT

VISUAL SELECTION Shown in elevation view

Item No.♦	Description	Dimensions (Inches)	Light Reflect	Fire Rating	Bio-Block*	Hum-Guard+	CleanAssure™ Disinfectable Panels	DURABILITY
8250F03RH05 (formerly item no. 7190)	Rectangular Vertical Panel	5 × 46 × 2"	0.88	Class A	*	*	Fog	Impact
8250F03RH06 (formerly item no. 7191)	Rectangular Vertical Panel	5 × 94 × 2"	0.88	Class A	*	*	Spray	Soil
8250F03RH01 (formerly item no. 3920)	Rectangular Vertical Panel	10 × 46 × 2"	0.88	Class A	*	*	Wash*	*
8250F03RH02 (formerly item no. 3921)	Rectangular Vertical Panel	10 × 94 × 2"	0.88	Class A	*	*	*	*
8250F03RH07 (formerly item no. 7192)	Rectangular Vertical Panel	16 × 46 × 2"	0.88	Class A	*	*	*	*
8250F03RH08 (formerly item no. 7193)	Rectangular Vertical Panel	16 × 94 × 2"	0.88	Class A	*	*	*	*
8250F03RH03 (formerly item no. 3922)	Rectangular Vertical Panel	22 × 46 × 2"	0.88	Class A	*	*	*	*

FAST 4 WEEKS or Less
FAST134 program items ready to ship from manufacturer in 4 weeks or less.
Up-to-date lead times and product options (sizes and colors) at armstrongceilings.com/fast134

NOTE: Scrimmed top edges offered as "Premium." contact ASQuote@armstrongceilings.com

♦ Add 3-letter color suffix to end of item number (e.g., 8250F03RH02 D_W_H = White)

* White only.

TechLine 877 276-7876

armstrongceilings.com/soundscapesblades

Armstrong®
World Industries

SOUNDSCAPES® Blades

Linear Acoustical Panels
fine texture



VISUAL SELECTION Shown in elevation view

Item No.◆ Description Dimensions (Inches)

8250F03RH04	Rectangular Vertical Panel	22 x 94 x 2"	
-------------	----------------------------	--------------	--

8250F03RH09	Rectangular Vertical Panel	28 x 46 x 2"	
-------------	----------------------------	--------------	--

8250F03RH10	Rectangular Vertical Panel	28 x 94 x 2"	
-------------	----------------------------	--------------	--

8250F03CH01	Hill Vertical Panel	7-1/2 x 46 x 2"	
-------------	---------------------	-----------------	--

8250F03CH02	Valley Vertical Panel	10-1/2 x 46 x 2"	
-------------	-----------------------	------------------	--

8250F03CH03	Hill Vertical Panel	19-1/2 x 46 x 2"	
-------------	---------------------	------------------	--

8250F03CH04	Valley Vertical Panel	22-1/2 x 46 x 2"	
-------------	-----------------------	------------------	--

PERFORMANCE Dots represent high level of performance.

(White only)	Bio-Block®	Humi-Guard+	CleanAssure™ Disinfectable Panels	DURABILITY
Light Reflect	Fire Rating	Anti-Mold/ Mildew	Sag Resist	
0.88 •	Class A	•	•	
0.88 •	Class A	•	•	

0.88 •	Class A	•	•	
0.88 •	Class A	•	•	
0.88 •	Class A	•	•	

0.88 •	Class A	•	•	
0.88 •	Class A	•	•	
0.88 •	Class A	•	•	

0.88 •	Class A	•	•	
0.88 •	Class A	•	•	
0.88 •	Class A	•	•	



FAST134 program items ready to ship from manufacturer in 4 weeks or less.
Up-to-date lead times and product options (sizes and colors) at armstrongceilings.com/fast134

NOTE: Scrimmed top edges offered as "Premium." contact ASQuote@armstrongceilings.com

◆ Add 3-letter color suffix to end of item number (e.g., 8250F03RH02 D W H = White)

* White only.

TechLine 877 276-7876

armstrongceilings.com/soundscapesblades

Armstrong®
World Industries

BLADES - Standard

SOUNDSCAPES® Blades

Linear Acoustical Panels

fine texture



43% RECYCLED CONTENT



LOCATION DEPENDENT

For LEED contribution contact TechLine

VISUAL SELECTION Shown in elevation view

Item No.◆


Description

Dimensions (Inches)

8250F03WH01
(formerly item no. 7244)

Wave Vertical Panel


10-1/2 x 94 x 2"



8250F03WH02
(formerly item no. 7245)

Wave Vertical Panel


22-1/2 x 94 x 2"



8250F03WH03
(formerly item no. 7246)

Wave Vertical Panel


10 x 46 x 2"



8250F03WH04
(formerly item no. 7247)

Wave Vertical Panel


22 x 46 x 2"



8250F03WH05
(formerly item no. 7248)

Double Wave Vertical Panel


10 x 94 x 2"



8250F03WH06
(formerly item no. 7249)

Double Wave Vertical Panel

22 x 94 x 2"



PERFORMANCE Dots represent high level of performance.

(White only) Bio-Block® Humi-Guard+ CleanAssure™ Disinfectable Panels DURABILITY

Light Reflect	Fire Rating	Anti-Mold/Mildew	Sag Resist	Fog	Spray	Wash*	Impact	Soil
0.88 * Class A	*	*	*	*	*	*	*	*

0.88 Class A



FAST134 program items ready to ship from manufacturer in 4 weeks or less.

Up-to-date lead times and product options (sizes and colors) at armstrongceilings.com/fast134

NOTE: Scrimmed top edges offered as "Premium," contact ASQuote@armstrongceilings.com

◆ Add 3-letter color suffix to end of item number (e.g., 8250F03RH02 D W H = White)

* White only.

TechLine 877 276-7876

armstrongceilings.com/soundscapesblades



Armstrong®
World Industries

SOUNDSCAPES® Blades

Linear Acoustical Panels
fine texture



THREE WAYS TO INSTALL




INSTALLATION OPTIONS

	Item No.◆	Description	LF/CTN
Direct to Grid Suspension System	7301 _ _ _	12' HD Main Beam	240
	XL7342 _ _ _	4' Cross Tee	240
	XL7328 _ _ _	2' Cross Tee	120
	7800 _ _ _	12' Angle Molding	360
360° Painted Direct to Grid Suspension System	730136 _ _	12' HD Main Beam (BL & WH)	240
	XL734036 _ _	4' Cross Tee (BL & WH)	240
	XL732036 _ _	2' Cross Tee (BL & WH)	120
	780036 _ _	12' Angle Molding (BL & WH)	360
	56418	12' HD Main Beam	240
	56421	4' Cross Tee	240
	56419	2' Cross Tee	120
	7800	12' Angle Molding	360
Floating Cloud Installations	AX4STR3 _ _	10' Axiom® Classic 4" Straight Trim	See note*

◆ When specifying or ordering items with a color, add the 2- or 3-digit suffix to the end of the item number (e.g. 7301_B_L)

* 360° Paint Recommended; order by the piece

Prelude® XL®



PHYSICAL DATA

Material

2" thick fiberglass with DuraBrite® scrim on face and sides.

Surface Finish

Colors: DuraBrite scrim with factory-applied paint on face and sides. Standard White has energy-saving, high light-reflective finish (LR 0.88). Top of panel is unfinished with white embedded hanging clips.

Fire Performance

SoundScapes® Blades panel material is ASTM E84 Class A: Flame Spread 25 or under and Smoke Developed 50 or less.

CAN/ULC S102 surface burning characteristics. Flame Spread Rating 25 or less. Smoke Developed Classification 50 or less.

SoundScapes Blades panels, as with other architectural features located in the ceiling plane, may obstruct or skew the existing or planned fire sprinkler water distribution pattern, or possibly delay the activation of the fire sprinkler or fire detection system. Consult a fire protection engineer, NFPA 13, and local codes for guidance on the proper installation techniques where fire detection or suppression systems are present.

Design Support

For custom design assistance contact ProjectWorks® Design Services or visit armstrongceilings.com/projectworks

Anti-Mold/Mildew

Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

Design Considerations

SoundScapes Blades panels maintain a natural bow that may be noticeable when installed 2" or less apart.

Special care in installation and handling must be taken with color panels to avoid surface damage to the paint finish.

Custom colors are available.

5' SoundScapes Blades can now be used on walls, but are not recommended for use in high-traffic or high-impact areas. For best results, install above 7' from floor level.

SoundScapes Blades panels can be ordered with scrim on top edge as a premium.

Seismic Restraint

SoundScapes Blades are approved for all seismic areas when installed per the seismic guidelines in the Armstrong Ceilings installation instructions.

Recommended Suspension Systems

SoundScapes Blades panels are pre-assembled with metal hanging clips in the top of the panels. See Installation Instructions BPLA-297844 for installation details.

Warranty

Details at armstrongceilings.com/warranty

Panel Weight

8250F03RH05 - 2.2 LBS per panel 8250F03CH01 - 2.9 LBS per panel

8250F03RH06 - 4.3 LBS per panel 8250F03CH02 - 3.5 LBS per panel

8250F03RH01 - 3.6 LBS per panel 8250F03CH03 - 4.6 LBS per panel

8250F03RH02 - 7.2 LBS per panel 8250F03CH04 - 7.3 LBS per panel

8250F03RH07 - 5.4 LBS per panel 8250F03WH01 - 7.5 LBS per panel

8250F03RH08 - 10.6 LBS per panel 8250F03WH02 - 14.4 LBS per panel

8250F03RH03 - 7.2 LBS per panel 8250F03WH03 - 3.6 LBS per panel

8250F03RH04 - 14.1 LBS per panel 8250F03WH04 - 7.2 LBS per panel

8250F03RH09 - 8.9 LBS per panel 8250F03WH05 - 7.2 LBS per panel

8250F03RH10 - 17.6 LBS per panel 8250F03WH06 - 14.1 LBS per panel

Panels/Carton

4

Minimum Order Quantity

1 carton