



Sound absorbing wall panel suitable for even the most demanding conditions, from intensive care units and operation rooms, to patient rooms and airtight laboratories.

FEATURES AND BENEFITS

- Designed to facilitate daily cleaning with strong sanitizers and disinfectant chemicals
- Virtually zero particle emission, ensuring high indoor air quality. Suitable as a clean room component (ISO Class 3)
- Fully encapsulated in a smooth, high-performance film that is impervious to particles and water to repel dirt
- Quick and easy installation; stainless steel wall brackets screw into place, and wall panel simply slides into the brackets
- Easy removability allows 360-degree cleaning of the panels and the wall behind them
- Satisfies 2018 FGI Guidelines for use in restricted areas (such as operating rooms)
- Excellent sound absorption with a 0.90 NRC
- VOC Compliant to CDPH v1.2, 2017

ATTRIBUTES



**MOLD/MILDEW
RESISTANT
INHERENT**



**LOW
VOC
EMISSION
COMPLIANT
CERTIFIED**



**RECYCLED
CONTENT**

LEED® v4


RECYCLED CONTENT	38%	
	PRE: 0%	POST: 38%

- ✓ MR: PBT Source Reduction (Healthcare)
- ✓ EQ: Acoustic Performance
- ✓ EQ: Prereq. Min. Acoustic Performance (Schools)
- ✓ EQ: Daylight
- ✓ MR: Sourcing Raw Materials
- ✓ MR: Construction and Demolition Waste Management Planning
- ✓ EQ: Low-emitting Materials


LEED® is a registered trademark of the U.S. Green Building Council.

ECOPHON® HYGIENE ADVANCE™ WALL


HYGIENE ADVANCE™ WALL

		COLOR	DIMENSIONS MM(IN.)	NRC	SABINS/ UNIT	LR	RECYCLED CONTENT	PIECES/ CARTON	SQ. M (FT.)/ CARTON	LBS./ CARTON
WALL PANEL										
	3513 8030	White	592 x 1192 (≈ 23-5/16 x 46-15/16)	0.90	6.8	0.73	38% post	6	46	39

ACCESSORIES

HYGIENE ADVANCE WALL ACCESSORIES	PRODUCT NAME	PIECES/ CARTON	USE
	2630 0716 Connect Wall Fixing (stainless steel)	12	2 per panel for vertical installation, 4 per panel for horizontal installation

EDGE DETAILS



PHYSICAL DATA

MATERIAL

Fiberglass
Fully-encapsulated in a smooth,
impervious high-performance film

FIRE CLASS (ASTM E1264)

CLASS A FOR US AND CANADA

Tested according to ASTM E84 & CAN S102
Flame Spread: 25 or less
Smoke Developed: 50 or less

MOLD/MILDEW RESISTANCE

Fiberglass substrate is fully-encapsulated
by water-impervious film.

MAINTENANCE

Refer to online maintenance instructions.

WARRANTY

10-year Ecophon Warranty.
Full warranty information can
be found at [certainteed.com/warranty](https://www.certainteed.com/warranty).

VOC EMISSIONS

Independently certified compliant
with California Department of Public
Health CDPH/EHLB/Standard
Method Version 1.2, 2017.



CertainTeed ARCHITECTURAL

METAL • WOOD • FELT • FIBERGLASS & MINERAL FIBER • GYPSUM • SUSPENSION & INTEGRATED SYSTEMS

20 Moores Road, Malvern, PA 19355 800-366-4327 [certainteed.com/architectural](https://www.certainteed.com/architectural)