

**Product Category:** 09.22.16 - Non-Structural Metal Framing

**Product Name:** 162S125-18

**Available Finish:** G40, G60

\*Other standard coatings referenced in ASTM A1003

**Web Depth:** 1-5/8 in

**Flange Width:** 1-1/4 in

**Design Thickness:** 0.0188 in

**Gauge:** 18 mils or 25G

**Yield stress, Fy:** 33 ksi

**Weight:** 0.27 lb/ft


**Gross Section Properties**

|                               |                       |
|-------------------------------|-----------------------|
| Cross sectional area (A)      | 0.080 in <sup>2</sup> |
| Moment of inertia (Ix)        | 0.038 in <sup>4</sup> |
| Section Modulus (Sx)          | 0.046 in <sup>3</sup> |
| Radius of gyration (Rx)       | 0.686 in              |
| Gross moment of inertia (Iy)  | 0.016 in <sup>4</sup> |
| Gross Radius of gyration (Ry) | 0.447 in              |

**Effective Section Properties**

|   |                       |
|---|-----------------------|
| Moment of inertia for deflection (Ix)                     | 0.034 in <sup>4</sup> |
| Section modulus (Sx)                                      | 0.031 in <sup>3</sup> |
| Allowable bending moment (Ma)                             | 0.610 In-k            |
| Allowable bending moment from distortional buckling (Mad) | 0.59 In-k             |
| Allowable strong axis shear away from punch-out (Vag)     | 302 lb                |
| Allowable strong axis shear at punch out (Vanet)          | 100 lb                |

- Calculated properties are based on AISI S100-16/S2-20, North American Specification for Design of Cold-Formed Steel Structural Members and meets the requirements of the IBC 2021 Building Code.
- The centerline bend radius is based on inside corner radii shown in thickness chart.
- Effective properties incorporate the strength increase from the cold work of forming as applicable per AISI A7.2.
- Tabulated gross properties are based on full-unreduced cross section of the studs, away from punchouts.
- For deflection calculations, use the effective moment of inertia.
- Allowable moment includes cold-work of forming.


**Torsional Properties**

|  |                       |
|--|-----------------------|
| St. Venant torsion constant (J x 1000)             | 0.009 in <sup>4</sup> |
| Warping constant (Cw)                              | 0.009 in <sup>6</sup> |
| Distance from shear center to neutral axis (Xo)    | -1.029 in             |
| Distance from shear center to mid-plane of web (m) | 0.594 in              |
| Radius of gyration (Ro)                            | 1.315 in              |
| Torsional flexural constant (β)                    | 0.388                 |
| Unbraced Length (Lu)                               | 29.0 in               |

**Fully Braced Non-Composite Limiting Heights Table Notes**

- 5 psf, 7.5 psf, and 10 psf loads have NOT been reduced for strength or deflection checks.
- Calculated properties are based on AISI S100-16/S2-20, North American Specification for Cold-Formed Steel Structural Members and meets the requirements of the IBC 2021 Building Code.
- Limiting heights are based on continuous support of each flange over the full length of the stud.
- Limiting heights are based on steel properties only (non-composite).
- Web crippling checks are based on end-one flange loading condition using 1-inch end bearing.

**Non-Composite Limiting Heights – Fully Braced**

| Spacing (inches) | 5psf L/120 | 5psf L/240 | 5psf L/360 | 7.5psf L/120 | 7.5psf L/240 | 7.5psf L/360 | 10psf L/120 | 10psf L/240 | 10psf L/360 |
|------------------|------------|------------|------------|--------------|--------------|--------------|-------------|-------------|-------------|
| 12               | 8'-10"     | 7'-7"      | 6'-7"      | 7'-3"        | 6'-7"        | 5'-9"        | 6'-3"       | 6'-0"       | 5'-3"       |
| 16               | 7'-8"      | 6'-11"     | 6'-0"      | 6'-3"        | 6'-0"        | 5'-3"        | 5'-5"       | 5'-5"       | 4'-9"       |
| 24               | 6'-3"      | 6'-0"      | 5'-3"      | 5'-1"        | 5'-1"        | 4'-7"        | 4'-5"       | 4'-5"       | 4'-2"       |

**Interior Composite Limiting Heights**

| Spacing (inches) | 5psf L/120 | 5psf L/240 | 5psf L/360 | 7.5psf L/120 | 7.5psf L/240 | 7.5psf L/360 | 10psf L/120 | 10psf L/240 | 10psf L/360 | 15psf L/120 | 15psf L/240 | 15psf L/360 |
|------------------|------------|------------|------------|--------------|--------------|--------------|-------------|-------------|-------------|-------------|-------------|-------------|
| 12               | 13' 0"     | 11' 1"     | 9' 10"     | 10' 8"       | 9' 8"        | 8' 7"        | 9' 3"       | 8' 9"       | 7' 9"       |             |             |             |
| 16               | 11' 3"     | 10' 1"     | 8' 11"     | 9' 3"        | 8' 9"        | 7' 9"        | 8' 0"       | 7' 11"      |             |             |             |             |
| 24               | 9' 3"      | 8' 9"      | 7' 9"      |              |              |              |             |             |             |             |             |             |

**Additional Information**

MRI Steel Framing, LLC is an SFIA member. MRI acts in accordance with the product and quality standards required by the SFIA program.

MRI meets or exceeds ASTM C645, C754, A653, and A1003.

Current LEED credits available upon request