Product Name: 600SLT300-30



## **Product Category:** 09.22.16 - Non-Structural Metal Framing

Available Finish:	G40, G60	<b>Gross Section Propert</b>	<u>ies</u>
*Other standard coatings refe Web Depth:	r standard coatings referenced in ASTM A1003  Depth: 6 in	Cross sectional area (A) Moment of inertia (Ix) Section Modulus (Sx) Radius of gyration (Rx) Gross moment of inertia (Iy) Gross Radius of gyration (Ry)	0.37 0.34 0.00 0.96 2.30 2.48
Flange Width: Slot Width: Design Thickness:	3 in 2 in 0.0312 in		
Gauge: Yield stress, Fy: Weight:	30 mils or 20G 33 ksi 1.274 lb/ft		

- Gross properties calculated at the gross section, away from slots.
- Web depth taken as nominal depth + (2 x thickness) + inside corner radius.
- Effective properties based on the 2007 NASPEC with 2010 Supplement and the following: net flange on tension side; effective flange on compression side, ignoring steel below the slot; effective web per NASPEC B2.3;  $\Omega$ b = 2.0 per AISI S100-16/S2-20, A1.2; meets the requirements of the IBC 2021 Building Code.
- Effective properties are not available for 6" x 18-mil products. Web h/t > 260.

## **Effective Section Properties**

Moment of inertia for deflection (Ix)	
Section modulus (Sx)	0.224 in <sup>3</sup>
Allowable bending moment (Ma)	
Allowable bending moment from distortional buckling (Mad)	
Allowable strong axis shear away from punch-out (Vag)	
Allowable strong axis shear at punch out (Vanet)	0 lb

## **Torsional Properties**

St. Venant torsion constant (J x 1000)	NA in <sup>4</sup>
Warping constant (Cw)	NA in <sup>6</sup>
Distance from shear center to neutral axis (Xo)	
Distance from shear center to mid-plane of web (m)	NA in
Radii of gyration (Ro)	NA in
Torsional flexural constant (β)	NA



0.374 in<sup>2</sup>
0.347 in<sup>4</sup>
0.000 in<sup>3</sup>
0.962 in
2.307 in<sup>4</sup>
2.482 in

## **Additional Information**

MRI Steel Framing, LLC is an SFIA member. MRI acts in accordance with the product and quality standards required by the SFIA program. MRI meets or exceeds ASTM C645, A653, and A1003.

Current LEED credits available upon request