

Corporate Headquarters

15 Salt Creek Lane, Suite 412 Hinsdale, IL 60521 Phone: 1.630.616.1850 Fax: 1.630.568.5979 info@mristeelframing.com

Produciton Facility

201 Mississippi St Dock #Q40 Gary, IN 46402 Phone: 1.630.616.1850 Fax: 1.219.886.3341 info@mristeelframing.com

GREEN Benefits & Recycled Content

March 18, 2024

Project:

MRI Steel Framing is committed to supplying quality products that contribute to developing greener building projects as well as sustainability and environmental management.

MRI Steel Framing has an Environmental Product Declaration (EPD), Number SCS-EPD-08959, covering our Cold-Formed Steel Framing Products, which conforms to ISO 14025, 14040, 14044, and ISO 21930. This EPD is a Product Specific Type III and has a Cradle to Gate scope. More specifically, this Type III EPD has been externally reviewed following ISO 14071 and externally verified, and as such, is eligible to contribute 150% of a product for the purposes of LEED® credits under the LEED® v4.1 standard.

The MRI Steel Framing Environmental Product Declaration (EPD) can help your building project qualify for the following LEED® v4.1 for BD+C points:

MATERIALS AND RESOURCES CREDIT (MR)

- Environmental Product Declarations Up to 2 Points
- Sourcing of Raw Materials Up to 2 Points
- Material Ingredients Up to 2 Points
- Construction and Demolition Waste Management Up to 2 Points

INDOOR ENVIRONMENTAL QUALITY CREDIT (EQ)

- Low-Emitting Materials Up to 3 Points
- Construction Indoor Air Quality Management Plan Up to 1 Point
- Indoor Air Quality Assessment Up to 2 Points

MRI Steel Framing products and accessories are manufactured from steel coil (100% by weight) containing 19.8% post-consumer recycled content and 14.4% post-industrial/pre-consumer recycled content for a total of 34.2% recycled content. These calculations are based upon information provided by the Steel Recycling Institute on minimum BOF (Basic Oxygen Furnace) steel recycled content.

In addition to the above mentioned EPD and LEED® information, MRI Steel Framing also has a Health Product Declaration (HPD) with a Unique Identifier Number of 27459 covering our full line of Interior Framing, Structural Framing, Slotted Deflection Track and Accessories; MasterSpec 05.40.00 and 09.22.16.



Product Name: 600T125-43



Product Category: 05.40.00 - Cold-Formed Metal Framing

Available Finish: G60, G90

*Other standard coatings referenced in ASTM A1003

Web Depth: 6 in

Flange Width: 1-1/4 in

Design Thickness: 0.0451 in

Gauge: 43 mils or 18


Yield stress, Fy: 33 ksi

Weight: 1.300 lb/ft

- Calculated properties are based on AISI S100-16/S240-20, North American Specification for Design of Cold-Formed Steel Structural Members and meets the requirements of the IBC 2021 Building Code.
- The centerline bend radius is based on inside corner radii shown in thickness chart.
- Effective properties incorporate the strength increase from the cold work of forming as applicable per AISI A7.2.
- Tabulated gross properties are based on full-unreduced cross section of the studs, away from punchouts.
- For deflection calculations, use the effective moment of inertia.
- Allowable moment includes coldwork of forming.
- Web depth for track sections is equal to the nominal height plus 2 times the design thickness plus the bend radius. Hems on nonstructural rack sections are ignored.

Gross Section Properties

Cross sectional area (A) 0.383 in^2 Moment of inertia (Ix) 1.862 in^4 Section Modulus (Sx) 0.604 in^3 Radius of gyration (Rx) 2.205 inGross moment of inertia (Iy) 0.044 in^4 Gross Radius of gyration (Ry) 0.337 in



Effective Section Properties

Moment of inertia for deflection (Ix)	1.768 in⁴
Section modulus (Sx)	0.461 in ³
Allowable bending moment (Ma)	9.11 ln-k
Allowable bending moment from distortional buckling (Mad)	0 ln-k
Allowable strong axis shear away from punch-out (Vag)	1377 lb
Allowable strong axis shear at punch out (Vanet)	0 lb

Torsional Properties

St. Venant torsion constant (J x 1000)	0.260 in⁴
Warping constant (Cw)	0.307 in ⁶
Distance from shear center to neutral axis (Xo)	-0.513 in
Distance from shear center to mid-plane of web (m)	0.335 in
Radii of gyration (Ro)	2.289 in
Torsional flexural constant (β)	0.950

Additional Information

MRI Steel Framing, LLC is an SFIA member. MRI acts in accordance with the product and quality standards required by the SFIA program. MRI meets or exceeds ASTM C955, A653, and A1003.

Current LEED credits available upon request