



Direct-to-deck ceiling solution, ideal for spaces where a traditional suspended ceiling is not possible or desired.

FEATURES AND BENEFITS

- Ideal for adding sound absorption (up to 0.80 NRC) to spaces with low or angled ceilings, exposed metal or wooden beams
- 3 direct-to-deck options available: trim, beveled or tongue & groove edges
- Direct-to-deck attachment with adhesive (Focus B, F, SQ)
- Direct-to-deck attachment by concrete screws or indirect attachment to wood furring (Focus F)
- Easy-to-clean Akutex™ FT surface in white finish has nearly perfect light diffusion (+99%)
- Fully encapsulated with tissue backing for maximum performance
- Painted, reinforced edges that resist damage from handling
- Available in 22 standard colors (Focus B & SQ Only)

ATTRIBUTES



**RECYCLED
CONTENT**



**MOLD/MILDEW
RESISTANT
INHERENT**



**LR 0.85
(WHITE ONLY)**



WASHABLE



**SAG
RESISTANT**

LEED® v4

RECYCLED CONTENT	51%	
	PRE: 0%	POST: 51%

- ✓ EQ: Optimize Energy Performance
- ✓ EA: Prereq. Min. Energy Performance
- ✓ EQ: Interior Lighting
- ✓ MR: PBT Source Reduction (Healthcare)
- ✓ EQ: Acoustic Performance
- ✓ EQ: Prereq. Min. Acoustic Performance (Schools)
- ✓ EQ: Daylight
- ✓ MR: Sourcing Raw Materials
- ✓ MR: Environmental Product Declarations (EPDs)
- ✓ MR: Construction and Demolition Waste Management Planning
- ✓ MR: Material Ingredients (HPDs)

LEED® is a registered trademark of the U.S. Green Building Council.

CERTIFICATIONS & PRODUCT DECLARATIONS



EPD AVAILABLE




HPD AVAILABLE


COLORS




FOCUS B

			FORMAT	DIMENSIONS MM (IN.)	NRC	CAC	RECYCLED CONTENT	PIECES/ CARTON	SQ. M (FT.)/ CARTON	LBS./ CARTON	CARTONS/ PALLET
BEVELED											
	NRC .75	3542 2900	Panels	600 x 600 x 20 (≈ 24 x 24 x 3/4)	0.75	—	51%	20	7.2 (≈ 77.5)	49	—

FOCUS F

			FORMAT	DIMENSIONS MM (IN.)	NRC	CAC	RECYCLED CONTENT	PIECES/ CARTON	SQ. M (FT.)/ CARTON	LBS./ CARTON	CARTONS/ PALLET
TONGUE & GROOVE											
	NRC .80	3542 2800	Panels	600 x 600 x 20 (≈ 24 x 24 x 3/4)	0.80	—	51%	20	7.2 (≈ 77.5)	47	—
		3542 2801	Panels	600 x 1200 x 20 (≈ 24 x 48 x 3/4)	0.80	—	51%	10	7.2 (≈ 77.5)	47	—





FOCUS SQ

			FORMAT	DIMENSIONS MM (IN.)	NRC	CAC	RECYCLED CONTENT	PIECES/ CARTON	SQ. M (FT.)/ CARTON	LBS./ CARTON	CARTONS/ PALLET
SQUARE											
	NRC .75	3540 3645	Panels	600 x 600 x 20 (≈ 24 x 24 x 3/4)	0.75	—	51%	20	7.2 (≈ 77.5)	41	—
		3540 3646	Panels	600 x 1200 x 20 (≈ 24 x 48 x 3/4)	0.75	—	51%	12	8.6 (≈ 93)	40	—

All Focus B and SQ panels listed above are white. To order colors please contact your local Sales Representative.


CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990.

ACCESSORIES

FOCUS B, F, & SQ ACCESSORIES		PRODUCT NAME	PIECES/ CARTON	USE
	2630 0691	Connect Edge Sealant White*	1	For re-sealing cut edges (typically 100-150 lf/container); 1 liter container
FOCUS F ACCESSORIES		PRODUCT NAME	PIECES/ CARTON	USE
	2630 1219	Connect Spine	50	Installed on 24 inch centers
	2630 0149	Connect Direct Fixing Plate (Focus F)	100	Installed on 24 inch centers
	2630 0187	Connect Wall Spring Spacer	24	For use when trim cutting panels at the perimeter

*Connect Edge Sealant is available in all standard colors. Please contact your local Sales Representative or call 800-233-8990.

EDGE DETAILS



PHYSICAL DATA

MATERIAL
Fiberglass

ASTM E1264 CLASSIFICATION
Type XII, Form 2, Pattern G

FIRE CLASS (ASTM E1264)
All are Class A per ASTM E84 & CAN S102
Flame Spread: 25 or less
Smoke Developed: 50 or less

MOLD/MILDEW RESISTANCE
Fiberglass substrate is inherently resistant to the growth of mold and mildew.

MAINTENANCE
Wipe with a soft cloth or vacuum with brush attachment. Cleanable with mild detergent.

WARRANTY
10-year Ecophon® Warranty.
Full warranty information can be found at [certainteed.com/warranty](https://www.certainteed.com/warranty).

