

# GYPSUM SMOOTH



Exceptional performance in high-moisture environments and exterior spaces.

#### **FEATURES AND BENEFITS**

- Paperless, glass mat faced gypsum board that is inherently mold-resistant
- Sag resistant with exceptional indoor/outdoor performance in applications up to 95% relative humidity
- Vinyl facing cleanable with most sanitizing chemicals
- Wash tested to 2,000+ cycles with no sign of wear
- Suited as clean room component to ISO Class 5
- Satisfies USDA/FSIS guidelines for sanitary applications
- Environmental Product Declaration (EPD) available for this product

## **ATTRIBUTES**



SAG RESISTANT





LR 0.78



WASHABLE W/ SANITIZING CHEMICALS



CERTIFIED

LEED® v4

U.S. Green Building Council.

RECYCLED CONTENT		93%						
		PRE: 93%	POST: 0%					
<b>~</b>	MR: PBT Source Reduction (Healthcare)							
<b>~</b>	EQ: Daylight							
<b>~</b>	EQ: Low-Emitting Materials							
<b>~</b>	MR: Sourcing Raw Materials							
~	MR: Environmental Product Declarations (EPDs)							
LEED® is	a registered trademark	of the						

CERTIFICATIONS & PRODUCT DECLARATIONS



EPD AVAILABLE



AQUAROCK™		FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	LR	PIECES/ CARTON	SQ. FT./ CARTON	LBS./ CARTON	CARTONS/ PALLET
REVEAL											
	1182-CRF-1SV	Panels	24 x 24 x 1/2	_	40	93%	0.78	8	32	65	44
	1180-CRF-1SV	Panels	24 x 48 x 1/2	-	42	93%	0.78	4	32	65	44

CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990

#### **EDGE DETAILS**



Trim 9/16" EZ Stab Elite Narrow



Trim 15/16" EZ Stab Classic

## **PHYSICAL DATA**

#### MATERIA

Paperless, moisture-resistant, glass mat faced gypsum board

#### FIRE CLASS

All are Class A per ASTM E84 & CAN S102 Flame Spread: 25 or less Smoke Developed: 50 or less

#### **ASTM E1264 CLASSIFICATION**

Type XX, Pattern G

#### **VOC EMISSIONS**

Independently certified compliant with California Departmenty of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017.

#### MAINTENANCE

Wash tested to 2,000+ cycles. Cleanable with sanitizing chemicals.

# MOLD/MILDEW RESISTANCE

Inherently mold-resistant.

### INSTALLATION CONSIDERATION

Consider use with EZ Stab Classic Environmental System if harsh chemicals or moisture will be present.

#### WARRANTY

10-year 104/90 Limited Warranty increases to 15 years when installed with CertainTeed suspension systems. Full warranty information can be found at certainteed.com/warranty.

