MRI STEEL FRAMING LLC

Corporate Headquarters: 15 Salt Creek Lane, Suite 412 Hinsdale, IL 60521 **P:** 630-616-1850 **F:** 630-568-5979
Production Facility: 201 Mississippi St, Dock #Q40, Gary, IN 46402 **P:** 630-616-1850 **F:** 219-886-3341

Product Category: 05.40.00 - Cold-Formed Metal Framing **Product Name:** 1000S300-97

Available Finish: G60, G90
*Other standard coatings referenced in ASTM A1003

Web Depth: 10 in
Flange Width: 3 in
Design Thickness: 0.1017 in
Gauge: 97 mils or 12G
Yield stress, Fy: 50 ksi
Weight: 5.71 lb/ft

- Calculated properties are based on AISI S100-16/S240-20, North American Specification for Design of Cold-Formed Steel Structural Members and meets the requirements of the IBC 2021 Building Code.
- The centerline bend radius is based on inside corner radii shown in thickness chart.
- Effective properties incorporate the strength increase from the cold work of forming as applicable per AISI A7.2.
- Tabulated gross properties are based on full-unreduced cross section of the studs, away from punchouts.
- For deflection calculations, use the effective moment of inertia.
- Allowable moment includes cold-work of forming.
- For the steels that have both 33 and 50 ksi listing, if the design is based on 50 ksi, the 50 ksi steel needs to be specified. (ex. 3.625S137 16-50 (50 ksi))

Gross Section Properties

Cross sectional area (A)	1.677 in^2
Moment of inertia (Ix)	24.325 in^4
Section Modulus (Sx)	4.865 in^3
Radius of gyration (Rx)	3.808 in
Gross moment of inertia (Iy)	1.703 in^4
Gross Radius of gyration (Ry)	1.007 in



Effective Section Properties

Moment of inertia for deflection (Ix)	23.972 in^4
Section modulus (Sx)	4.499 in^3
Allowable bending moment (Ma)	134.700 In-k
Allowable bending moment from distortional buckling (Mad)	111.66 In-k
Allowable strong axis shear away from punch-out (Vag)	9864 lb
Allowable strong axis shear at punch out (Vanet)	7177 lb

Torsional Properties

St. Venant torsion constant (J x 1000)	5.783 in^4
Warping constant (Cw)	33.570 in^6
Distance from shear center to neutral axis (Xo)	-1.838 in
Distance from shear center to mid-plane of web (m)	1.158 in
Radii of gyration (Ro)	4.347 in
Torsional flexural constant (β)	0.821
Unbraced Length (Lu)	57.4 in

Additional Information

MRI Steel Framing, LLC is an SFIA member. MRI acts in accordance with the product and quality standards required by the SFIA program.

MRI meets or exceeds ASTM C955, A653, and A1003.

Current LEED credits available upon request