



Fully concealed suspension system coupled with superior sound absorption in a wide selection of sizes and colors.

FEATURES AND BENEFITS

- Fully concealed, easy downward access
- Monolithic surface simulates drywall finished appearance
- Superior sound attenuation (40-44 CAC) with optional CAC Backer
- Terminus Fin Semi-concealed Trim available for finishing of cloud perimeter
- Easy-to-clean Akutex™ FT surface in white finish has nearly perfect light diffusion (+99%)
- Fully encapsulated with tissue backing for maximum performance
- Available in 22 standard colors

ATTRIBUTES



**RECYCLED
CONTENT**



**MOLD/MILDEW
RESISTANT
INHERENT**



**LR 0.85
(WHITE)**



WASHABLE



**SAG
RESISTANT**

LEED® v4

RECYCLED CONTENT	51%	
	PRE: 0%	POST: 51%

- ✓ EQ: Optimize Energy Performance
- ✓ EA: Prereq. Min. Energy Performance
- ✓ EQ: Interior Lighting
- ✓ MR: PBT Source Reduction (Healthcare)
- ✓ EQ: Acoustic Performance
- ✓ EQ: Prereq. Min. Acoustic Performance (Schools)
- ✓ EQ: Daylight
- ✓ MR: Sourcing Raw Materials
- ✓ MR: Environmental Product Declarations (EPDs)
- ✓ MR: Construction and Demolition Waste Management Planning
- ✓ MR: Material Ingredients (HPDs)

LEED® is a registered trademark of the U.S. Green Building Council.

CERTIFICATIONS & PRODUCT DECLARATIONS



EPD AVAILABLE




HPD AVAILABLE

COLORS



FOCUS DS














			FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET
FULLY-CONCEALED											
	NRC .85	3542 1511	Panels	24 x 24 x 3/4	0.85	25/40*	51%	20	80	44	n/a
		3542 1512	Panels	24 x 48 x 3/4	0.85	25/44*	51%	10	80	44	n/a
		3542 1516	Panels	48 x 48 x 3/4	0.85	25	51%	6	96	50	n/a
		3542 1513	Planks	24 x 60 x 3/4	0.85	25	51%	6	60	33	n/a
		3542 1514	Planks	24 x 72 x 3/4	0.85	25	51%	6	72	45	n/a
		3542 1515	Planks	24 x 96 x 3/4	0.85	25	51%	6	96	50	n/a

*Optional CAC Backer: CertainTeed Protectone

All Focus Ds products listed are white. To order colors please contact your local Sales Representative.


CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990.

ACCESSORIES


FOCUS DS ACCESSORIES		PRODUCT NAME	PIECES/ CARTON	USE
	2630 0547	Connect Dg 20 Support Clip	50	For support of any cut supporting edge on 3/4" Dg or Ds (typically 1 pc. every 12 - 18 inches)
	2630 0691	Connect Edge Sealant White*	1	For re-sealing cut edges (typically 100-150 lf/container); 1 liter container
	2630 0991	Connect Dg Cutting Tool	1	For rabbeting field-cut edges
	STBAR-2	CTC 2' Stabilizer Bar	40	For all 2x5, 2x6, 2x8 applications; typically 1 pc./panel for 2x5, 2x6, 2 pc./panel for 2x8
	STBAR-4	CTC 4' Stabilizer Bar	40	For all 2x6, 2x8 applications; typically 1 pc./panel for 2x6, 2 pc./panel for 2x8
	EZCS12-12-20	15/16" Classic Stab HD Main Runner	20	For use only with Connect Space Bar 0577
	2630 0577	Ecophon Connect Space Bar	10	For use only with CTC HD EZCS12-12-20, spaced every 48" on center, max 24" away from the wall (suitable for use in seismic categories A/B only)
	2630 0824	Connect Wall Bracket T-Profile	25	For main runner attachment to wall (typically 2/run of main runner)
	2630 0525	Connect Space Bar Wall Bracket	10	For attachment of space bar to wall (typically 2/run of space bar)
	2630 0553	Connect Space Bar Winch	100	For attachment of space bar to main runner (one pc. for each intersection)
	2630 0381	Connect Edge Stiffner	12	Required for Focus™ Ds 4x4 systems (2 pc./panel)
	2631 1080	Connect Perimeter Tile Clip	100	For attachment and securing of panels at the perimeter
	2630 0196	Connect Hold Down Clip Ds	100	For use as a hold down clip with Focus Dg and Focus Ds (typically 1 pc./sf for 2x2 and 0.65 pc./sf for 2x4)

*Connect Edge Sealant is available in all standard colors. Please contact your local Sales Representative or call 800-233-8990.

ACCESSORIES

FOCUS WING & WING ACCESSORIES		PRODUCT NAME	PIECES/ CARTON	USE
	2630 0187	Connect Wall Spring Spacer	24	For use when trim cutting panels at the perimeter

EDGE DETAILS



Fully-concealed
15/16" EZ Stab
Classic

PHYSICAL DATA

MATERIAL

Fiberglass

ASTM E1264 CLASSIFICATION

Type XII, Form 2, Pattern G

FIRE CLASS (ASTM E1264)

All are Class A per ASTM E84 & CAN/ULC S102

Flame Spread: 25 or less

Smoke Developed: 50 or less

MOLD/MILDEW RESISTANCE

Fiberglass substrate is inherently resistant to the growth of mold and mildew.

MAINTENANCE

Wipe with a soft cloth or vacuum with brush attachment. Cleanable with mild detergent.

WARRANTY

10-year Ecophon® Warranty increases to 15 years when installed with CertainTeed suspension systems. Full warranty information can be found at [certainteed.com/warranty](https://www.certainteed.com/warranty).

