

Specially designed for when low particulate emission and maximum cleanliness are essential.

FEATURES AND BENEFITS

- Encapsulated gypsum core-board. Vinyl face/back with sealed edges.
- Wash tested to 2,000+ cycles with no sign of wear
- Surface suitable for cleaning with common sanitizing chemicals
- Exceeds FGI guidelines for cleanability in healthcare spaces
- Satisfies USDA/FSIS guidelines for sanitary applications
- Suited as clean room component to ISO Class 5
- Environmental Product Declaration (EPD) available for this product

ATTRIBUTES







SAG RESISTANT



EMISSION COMPLIANT



WASHABLE



WASHABLE W/ SANITIZING

LEED® v4

	99%				
RECYCLED CONTENT	PRE: 94%	POST: 5%			
MD-DDT Course Deduction (Health cour)					

- MR: PBT Source Reduction (Healthcare)
- EQ: Low-Emitting Materials
- EQ: Daylight
- MR: Construction and Demolition Waste Management Planning
- MR: Sourcing Raw Materials
- MR: Environmental Product Declarations (EPDs)

 $\mathsf{LEED}^{\$}$ is a registered trademark of the U.S. Green Building Council.

CERTIFICATIONS & PRODUCT DECLARATIONS



EPD AVAILABLE





ENVIROGARD™		FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	PIECES/ CARTON	SQ. FT./ CARTON	LBS./ CARTON	CARTONS/ PALLET
TRIM										
	1192-CRF-1	Panels	24 x 24 x 1/2	-	34	99%	8	32	47	44
	1190-CRF-1	Panels	24 x 48 x 1/2	-	36	99%	4	32	47	44

CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990.

ACCESSORIES

ENVIROGARD ACCESSO	ENVIROGARD ACCESSORIES		PIECES/ CARTON	USE
119	90-SEL-1	Envirogard Edge Sealant	1	For re-sealing cut edges; 1 quart container

EDGE DETAILS



Trim 9/16" EZ Stab Elite Narrow



Trim 15/16" EZ Stab Classic

PHYSICAL DATA

MATERIAL

Gypsum

ASTM E1264 CLASSIFICATION Type XX, Pattern G

FIRE CLASS (ASTM E1264)

All are Class A per ASTM E84 & CAN S102 Flame Spread: 25 or less Smoke Developed: 50 or less

VOC EMISSIONS

Independently certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017.

MAINTENANCE

Wash tested to 2,000+ cycles. Cleanable with sanitizing chemicals.

INSTALLATION CONSIDERATION

Should be installed with an environmental suspension system such as EZ Stab Classic Environmental.

WARRANTY

10-year 104/90 Limited Warranty increases to 15 years when installed with CertainTeed suspension systems. Full warranty information can be found at certainteed.com/warranty.

