

Product Category: 05.40.00 - Cold-Formed Metal Framing

Product Name: 1400S200-118

Available Finish: G60, G90

*Other standard coatings referenced in ASTM A1003

Web Depth: 14 in

Flange Width: 2 in

Design Thickness: 0.1242 in

Gauge: 118 mils or 10G

Yield stress, Fy: 50 ksi

Weight: 7.74 lb/ft

Gross Section Properties

Cross sectional area (A)	2.276 in ²
Moment of inertia (Ix)	53.719 in ⁴
Section Modulus (Sx)	7.674 in ³
Radius of gyration (Rx)	4.858 in
Gross moment of inertia (Iy)	0.756 in ⁴
Gross Radius of gyration (Ry)	0.576 in

Effective Section Properties

Moment of inertia for deflection (I _x)	53.525 in ⁴
Section modulus (S _x)	7.097 in ³
Allowable bending moment (M _a)	212.480 In-k
Allowable bending moment from distortional buckling (M _{ad})	187.34 In-k
Allowable strong axis shear away from punch-out (V _{ag})	12745 lb
Allowable strong axis shear at punch out (V _{anet})	11287 lb

- Calculated properties are based on AISI S100-16/S240-20, North American Specification for Design of Cold-Formed Steel Structural Members and meets the requirements of the IBC 2021 Building Code.
- The centerline bend radius is based on inside corner radii shown in thickness chart.
- Effective properties incorporate the strength increase from the cold work of forming as applicable per AISI A7.2.
- Tabulated gross properties are based on full-unreduced cross section of the studs, away from punchouts.
- For deflection calculations, use the effective moment of inertia.
- Allowable moment includes cold-work of forming.
- For the steels that have both 33 and 50 ksi listing, if the design is based on 50 ksi, the 50 ksi steel needs to be specified. (ex. 3.625S137 16-50 (50 ksi))



Torsional Properties

St. Venant torsion constant (J x 1000)	11.704 in ⁴
Warping constant (C _w)	31.861 in ⁶
Distance from shear center to neutral axis (X _o)	-0.883 in
Distance from shear center to mid-plane of web (m)	0.598 in
Radii of gyration (R _o)	4.971 in
Torsional flexural constant (β)	0.968
Unbraced Length (L _u)	36.8 in

Additional Information

MRI Steel Framing, LLC is an SFIA member. MRI acts in accordance with the product and quality standards required by the SFIA program.

MRI meets or exceeds ASTM C955, A653, and A1003.

Current LEED credits available upon request