

Universal Starter Strip

One size fits all starter track that eliminates the need to inventory multiple sizes

Perimeter base support and casing bead for Exterior Insulation and Finish Systems (EIFS) which has been engineered to allow incidental moisture to escape through the weep holes. Caulk all intersections, butt joints, ends, and corners at the time of installation.

Product Data & Ordering Information:


Product code	Finish	Insulation	Flange (A)	Upper Weep (B)	Lower Weep (C)	Offset (D)	Pcs./Ctn
UNI-Track	1/16"	1" to 4"	2-7/8"	1/2"	1/2"	1/2"	40

Code Approvals & Performance Standards

- [ASTM C1861](#) Standard Specification for Lathing and Furring Accessories, and Fasteners, for Interior and Exterior Portland Cement-Based Plaster
- [ASTM D1784](#) Standard Classification System and Basis for Specification for Rigid Poly(Vinyl Chloride) (PVC) Compounds and Chlorinated Poly(Vinyl Chloride) (CPVC) Compounds
- [ASTM D4216](#) Standard Specification for Rigid Poly(Vinyl Chloride) (PVC) and Related PVC and Chlorinated Poly(Vinyl Chloride) (CPVC) Building Products Compounds
- [ASTM E2110](#) Standard Terminology for Exterior Insulation and Finish Systems (EIFS)
- [ASTM E2511](#) Standard Guide for Detailing of EIFS-Clad Barrier and Drainage Wall Assemblies
- [ASTM E2568](#) Standard Specification for PB Exterior Insulation and Finish Systems
- [SDS Vinyl Corp](#) PVC Compounds

Storage

All stored materials shall be kept dry. Materials shall be stacked off the ground, supported on a level platform, and protected from the weather.



Made in white or these standard thru-body colors:



Contact ClarkDietrich for pricing and availability

