



Akusto Wall C Super G fiberglass wall panel features an impact resistant surface.

#### FEATURES AND BENEFITS

- High impact resistance
- Use as a complement and/or alternative to acoustical ceiling panels for excellent acoustical performance within a space
- Moisture resistant
- Available in white only

#### ATTRIBUTES



LR 0.78



**MOLD/MILDEW  
RESISTANT  
INHERENT**



**WASHABLE**

#### LEED® v4

RECYCLED CONTENT	53%	
	PRE: 0%	POST: 53%

- ✓ MR: PBT Source Reduction (Healthcare)
- ✓ EQ: Acoustic Performance
- ✓ EQ: Prereq. Min. Acoustic Performance (Schools)
- ✓ MR: Sourcing Raw Materials
- ✓ MR: Environmental Product Declarations (EPDs)
- ✓ MR: Construction and Demolition Waste Management Planning

LEED® is a registered trademark of the U.S. Green Building Council.

#### CERTIFICATIONS & PRODUCT DECLARATIONS



EPD AVAILABLE

# ECOPHON® AKUSTO™ WALL C SUPER G

## COLORS




White

## AKUSTO™ WALL C SUPER G

			COLOR	DIMENSIONS MM (IN.)	NRC	LR	RECYCLED CONTENT	PIECES/ CARTON	SQ. M (FT.)/ CARTON	LBS./ CARTON
WALL PANEL										
	NRC .95	3557 7729	White	2700 x 600 x 40 (= 106 x 24 x 1-1/2)	0.95	0.78	53%	4	21.3 (= 70)	71

## EDGE DETAILS



Kerfed Edge

## PHYSICAL DATA

### MATERIAL

Fiberglass

### FIRE CLASS (ASTM E1264)

Tested according to ASTM E84 & CAN S102

Flame Spread: 25 or less

Smoke Developed: 50 or less

### MOLD/MILDEW RESISTANCE

Fiberglass substrate is inherently resistant to the growth of mold and mildew.

### MAINTENANCE

Wipe with a soft cloth or vacuum with brush attachment. Washable with mild detergent.

### WARRANTY

10-year Ecophon Warranty.

Full warranty information can be found at [certainteed.com/warranty](https://certainteed.com/warranty).



## CertainTeed ARCHITECTURAL

METAL • WOOD • FELT • FIBERGLASS & MINERAL FIBER • GYPSUM • SUSPENSION & INTEGRATED SYSTEMS

20 Moores Road, Malvern, PA 19355 800-366-4327 [certainteed.com/architectural](https://certainteed.com/architectural)