

FIBERGLASS TEXTURED





A high NRC fiberglass panel ideally suited for environments where economical installation, VOC compliance and low maintenance are primary considerations.

FEATURES AND BENEFITS

- VOC compliant to CDPH v1.2, 2017
- Complies with LEED v4 for Schools classroom acoustics prerequisite
- Embossed PVC-vinyl facer on fiberglass
- Excellent sound absorption
- High humidity resistance
- Ideal for economical installation and low maintenance environments

ATTRIBUTES







RESISTANT INHERENT



LR 0.73-0.79





EMISSION COMPLIANT CERTIFIED



WASHABLE

LEED® v4

	35%			
RECYCLED CONTENT	PRE: 0%	POST: 35%		
A 140 0070 0				

- MR: PBT Source Reduction (Healthcare)
- EQ: Acoustic Performance
- EQ: Prereq. Min. Acoustic Performance
- EQ: Low-Emitting Materials
- EQ: Daylight
- MR: Sourcing Raw Materials
- MR: Construction and Demolition Waste Management Planning

LEED® is a registered trademark of the U.S. Green Building Council.





COLORS



EDGE DETAILS



15/16" EZ Stab Classic

VERSATONE BLA	CK ASTRA	FORMAT	DIMENSIONS (IN.)	NRC	CAC	LR	RECYCLED CONTENT	PIECES/ CARTON	SQ. FT./ CARTON	LBS./ CARTON	CARTONS/ PALLET
TRIM											
NRC.70	1532-AST-5	Panels	24 x 24 x 5/8	0.70	-	_	35%	32	128	22	18
	1530-AST-5	Panels	24 x 48 x 5/8	0.70	-	-	35%	16	128	22	18
VERSATONE WHI	TE ASTRA	FORMAT	DIMENSIONS (IN.)	NRC	CAC	LR	RECYCLED CONTENT	PIECES/ CARTON	SQ. FT./ CARTON	LBS./ CARTON	CARTONS/ PALLET
TRIM											
NRC.70	1532-AST-1	Panels	24 x 24 x 5/8	0.70	-	0.78	35%	32	128	22	18
	1530-AST-1	Panels	24 x 48 x 5/8	0.70	-	0.78	35%	16	128	22	18
VERSATONE WHI	TE STIPPLE	FORMAT	DIMENSIONS (IN.)	NRC	CAC	LR	RECYCLED CONTENT	PIECES/ CARTON	SQ. FT./ CARTON	LBS./ CARTON	CARTONS/ PALLET
VERSATONE WHI	TE STIPPLE	FORMAT		NRC	CAC	LR				LBS./ CARTON	
TRIM		FORMAT Panels		NRC 0.70	CAC	LR 0.73				LBS./ CARTON	
			(IN.)				CONTENT	CARTON	CARTON	CARTÓN	PALLET
TRIM	1532-STP-1 1530-STP-1	Panels	(IN.) 24 x 24 x 5/8	0.70	-	0.73	CONTENT 35%	CARTON 32	128	CARTÓN 22	PALLET 18
TRIM	1532-STP-1 1530-STP-1	Panels Panels	(IN.) 24 x 24 x 5/8 24 x 48 x 5/8 DIMENSIONS	0.70 0.70	-	0.73 0.73	35% 35% RECYCLED	32 16	128 128 SQ. FT./	22 22 LBS./	PALLET 18 18 CARTONS/
VERSATONE WHI	1532-STP-1 1530-STP-1 TE VINTAGE	Panels Panels	(IN.) 24 x 24 x 5/8 24 x 48 x 5/8 DIMENSIONS	0.70 0.70	-	0.73 0.73	35% 35% RECYCLED	32 16	128 128 SQ. FT./	22 22 LBS./	PALLET 18 18 CARTONS/

CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990.

PHYSICAL DATA

MATERIAL

Fiberglass

FIRE CLASS (ASTM E1264)

All are Class A per ASTM E84 & CAN S102 Flame Spread: 25 or less Smoke Developed: 50 or less

ASTM E1264 CLASSIFICATION

Type XII, Pattern E

VOC EMISSIONS

Independently certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017.

MOLD/MILDEW RESISTANCE

Fiberglass substrate is inherently resistant to the growth of mold and mildew.

MAINTENANCE

Wipe with a soft cloth or vacuum with brush attachment.

WARRANTY

10-year 104/90 Limited Warranty increases to 15 years when installed with CertainTeed suspension systems. Full warranty information can be found at certainteed.com/warranty.

