



50SSH & 56SSH Stainless Steel Wall Guard with H-Bracket



50SSH WALL GUARD SECTION VIEW



56SSH WALL GUARD SECTION VIEW

- 4" (102mm) of wall protection, extends 3-1/4" (83mm) from wall
- 6" (152mm) of wall protection available
- 1/4" (6.4mm) thick standard Type 304 stainless steel in a No. 4 satin finish
- Features a new H-bracket and neoprene gasket
- Mounting design features hidden stud welds
- Pre-cut and pre-drilled for easy installation
- Made using 75% post-consumer recycled material -- may contribute to Recycled Content credit in the LEED® Rating Systems
- Provides superior impact resistance in kitchens, corridors, or other high abuse areas

IPC.3033/REV.3

50SSH & 56SSH Stainless Steel Wall Guard with H-Bracket

Suggested Specifications

PART 1 - GENERAL

1.01 SUMMARY

- A. Stainless Steel Wall Guard system for wall protection

1.02 SECTION INCLUDES

- A. 50SSH Stainless Steel Wall Guard System with H-Bracket

1.03 SUBMITTALS

- A. Product data for each type of wall guard specified.
- B. Detail drawings indicating mounting details with the appropriate fasteners for specific project substrates.
- C. Samples for verification purposes of wall guard, 6" (152mm) long, in full size profiles of each type indicated.
- D. Cleaning and maintenance instructions for door and wall protection systems.

1.04 DELIVERY, STORAGE AND HANDLING

- A. Deliver materials in unopened factory packaging to the jobsite and store in original packaging in a climate controlled location away from direct sunlight.

1.05 PROJECT CONDITIONS

- A. Products must be installed in an interior climate controlled environment.

1.06 WARRANTY

- A. Standard IPC Limited Lifetime Warranty against material and manufacturing defects.

PART 2 - PRODUCTS

2.01 MANUFACTURER

- A. Acceptable Manufacturer:
IPC Door and Wall Protection Systems,
Telephone: 800.222.5556, Fax: 888.715.8407,
www.inprocorp.com
- B. Substitutions: Not permitted
- C. Provide all wall guards and wall protection from a single source.

2.02 MANUFACTURED UNITS

- A. Wall Guards
 - 1. Stainless Steel Wall Guard with H-Shape mounting bracket and neoprene gasket.
 - Model Size 50SSH, 4" (102mm) h x 3-1/4" (83mm) deep
 - Model Size 56SSH, 6" (152mm) h x 3-1/4" (83mm) deep
 - Fabricated to field verified dimensions

2.03 MATERIALS

- A. Stainless Steel: Wall Guard shall be manufactured from type 304 Stainless Steel.
- B. Aluminum: Wall guard mounting bracket shall be extruded from 6063-T5 aluminum.
- C. Neoprene: Gasket shall be fabricated from 70A durometer neoprene.

2.04 FINISHES

- A. Stainless Steel: Stainless steel wall guard shall have a #4 satin finish.
- B. Aluminum: Aluminum bracket shall have a clear anodized finish.
- C. Neoprene: Neoprene gasket shall be black.

PART 3 - EXECUTION

3.01 EXAMINATION

- A. Examine areas and conditions in which the wall protection will be installed.
- 1. Complete all finishing operations, including painting, before beginning installation of wall protection materials.
- B. Wall surface shall be dry and free from dirt, grease and loose paint.

3.02 PREPARATION

- A. General: Prior to installation, clean substrate to remove dust, debris and loose particles.

3.03 INSTALLATION

- A. General: Locate product as indicated on the approved detail drawing for the appropriate substrate, and in compliance with the Inpro installation instructions. Install product level and plumb at the location indicated on the drawings.

3.04 CLEANING

- A. At completion of the installation, clean surfaces in accordance with the Inpro cleanup and maintenance instructions.