

#### **Corporate Headquarters**

15 Salt Creek Lane, Suite 412 Hinsdale, IL 60521 Phone: 1.630.616.1850 Fax: 1.630.568.5979 info@mristeelframing.com

## **Produciton Facility**

201 Mississippi St Dock #Q40 Gary, IN 46402 Phone: 1.630.616.1850 Fax: 1.219.886.3341 info@mristeelframing.com

# **GREEN Benefits & Recycled Content**

March 18, 2024

## Project:

MRI Steel Framing is committed to supplying quality products that contribute to developing greener building projects as well as sustainability and environmental management.

MRI Steel Framing has an Environmental Product Declaration (EPD), Number SCS-EPD-08959, covering our Cold-Formed Steel Framing Products, which conforms to ISO 14025, 14040, 14044, and ISO 21930. This EPD is a Product Specific Type III and has a Cradle to Gate scope. More specifically, this Type III EPD has been externally reviewed following ISO 14071 and externally verified, and as such, is eligible to contribute 150% of a product for the purposes of LEED® credits under the LEED® v4.1 standard.

The MRI Steel Framing Environmental Product Declaration (EPD) can help your building project qualify for the following LEED® v4.1 for BD+C points:

## MATERIALS AND RESOURCES CREDIT (MR)

- Environmental Product Declarations Up to 2 Points
- Sourcing of Raw Materials Up to 2 Points
- Material Ingredients Up to 2 Points
- Construction and Demolition Waste Management Up to 2 Points

## INDOOR ENVIRONMENTAL QUALITY CREDIT (EQ)

- Low-Emitting Materials Up to 3 Points
- Construction Indoor Air Quality Management Plan Up to 1 Point
- Indoor Air Quality Assessment Up to 2 Points

MRI Steel Framing products and accessories are manufactured from steel coil (100% by weight) containing 19.8% post-consumer recycled content and 14.4% post-industrial/pre-consumer recycled content for a total of 34.2% recycled content. These calculations are based upon information provided by the Steel Recycling Institute on minimum BOF (Basic Oxygen Furnace) steel recycled content.

In addition to the above mentioned EPD and LEED® information, MRI Steel Framing also has a Health Product Declaration (HPD) with a Unique Identifier Number of 27459 covering our full line of Interior Framing, Structural Framing, Slotted Deflection Track and Accessories; MasterSpec 05.40.00 and 09.22.16.



**Product Name: 250S162-43** 



### Product Category: 05.40.00 - Cold-Formed Metal Framing

Available Finish: G60, G90
\*Other standard coatings referenced in ASTM A1003

Web Depth: 2-1/2 in

Flange Width: 1-5/8 in

Design Thickness: 0.0451 in

 Gauge:
 43 mils or 18

 Yield stress, Fy:
 33 ksi

 Weight:
 0.98 lb/ft

- Calculated properties are based on AISI S100-16/S240-20, North American Specification for Design of Cold-Formed Steel Structural Members and meets the requirements of the IBC 2021 Building Code.
- The centerline bend radius is based on inside corner radii shown in thickness chart.
- Effective properties incorporate the strength increase from the cold work of forming as applicable per AISI A7.2.
- Tabulated gross properties are based on full-unreduced cross section of the studs, away from punchouts.
- For deflection calculations, use the effective moment of inertia.
- Allowable moment includes coldwork of forming.
- For the steels that have both 33 and 50 ksi listing, if the design is based on 50 ksi, the 50 ksi steel needs to be specified. (ex. 3.625S137 16-50 (50 ksi))

#### **Gross Section Properties**

Cross sectional area (A) 0.289 in²
Moment of inertia (Ix) 0.302 in⁴
Section Modulus (Sx) 0.242 in³
Radius of gyration (Rx) 1.022 in
Gross moment of inertia (Iy) 0.111 in⁴
Gross Radius of gyration (Ry) 0.620 in



#### **Effective Section Properties**

Moment of inertia for deflection (Ix)	0.302 in <sup>4</sup>
Section modulus (Sx)	0.240 in <sup>3</sup>
Allowable bending moment (Ma)	5.220 In-k
Allowable bending moment from distortional buckling (Mad)	4.72 ln-k
Allowable strong axis shear away from punch-out (Vag)	1265 lb
Allowable strong axis shear at punch out (Vanet)	394 lb

### **Torsional Properties**

St. Venant torsion constant (J x 1000)	0.196 in⁴
Warping constant (Cw)	0.184 in <sup>6</sup>
Distance from shear center to neutral axis (Xo)	-1.457 in
Distance from shear center to mid-plane of web (m)	0.852 in
Radii of gyration (Ro)	1.885 in
Torsional flexural constant (β)	0.402
Unbraced Length (Lu)	42.1 in

#### **Limiting Height Table Notes**

- Lateral loads have not been modified for strength checks: full loads are applied.
- Calculated properties are based on AISI S100-16/S240-20, North American Specification for Cold-Formed Steel Structural Members and meets the requirements of the IBC 2021 Building Code.
- 15 psf and higher wind pressures have been multiplied by 0.7 for deflection determination, in accordance with footnote f of IBC table 1604.3. The 5 psf live load has not been reduced for deflection checks.
- Limiting heights are based on continuous support of each flange over the full length of the stud.
- Limiting heights are based on steel properties alone (non-composite).
- Web crippling checks are based on end-one flange loading condition using 1-inch end bearing.
- End shear and web crippling capacity have not been reduced for punchouts.
   Punchouts are assumed to be at least 10-inches from the end of members, in accordance with ASTM C955, section 4.6.
- Where limiting heights are followed by "e", web stiffeners are required.

## Limiting Wall Heights - Curtain Wall 1-Span

Spacing (inches)	15psf L/240	15psf L/360	15psf L/600	20psf L/240	20psf L/360	20psf L/600	25psf L/240	25psf L/360	25psf L/600
12	12' 4"	10' 10"	9' 1"	11' 3"	9' 10"	8' 3"	10' 5"	9' 1"	7' 8"
16	11' 3"	9' 10"	8' 3"	10' 2"	8' 11"	7' 6"	9' 6"	8' 3"	7' 0"
24	9' 10"	8' 7"	7' 3"	8' 11"	7' 9"	6' 7"	8' 3"	7' 3"	6' 1"

Spacing (inches)	30psf L/240	30psf L/360	30psf L/600	35psf L/240	35psf L/360	35psf L/600	40psf L/240	40psf L/360	40psf L/600
12	9' 10"	8' 7"	7' 3"	9' 4"	8' 2"	6' 10"	8' 11"	7' 9"	6' 7"
16	8' 11"	7' 9"	6' 7"	8' 6"	7' 5"	6' 3"	8' 1"	7' 1"	6' 0"
24	7' 7"	6' 10"	5' 9"	7' 1"	6' 6"	5' 5"	6' 7"	6' 2"	5' 3"

#### **Additional Information**

MRI Steel Framing, LLC is an SFIA member. MRI acts in accordance with the product and quality standards required by the SFIA program. MRI meets or exceeds ASTM C955, A653, and A1003.