METALWORKS™ Concealed
smooth texture

MetalWorks™ Concealed 48" x 96" panels in Silver Grey

## Large-size panels with concealed suspension are 100% accessible.

KEY SELECTION ATTRIBUTES

- Narrow 1/4" reveal offers clean, monolithic look
- Hook-on panels provide safe and secure downward accessibility
- Create continuous look or use with clouds and perimeter trim

- CleanAssure™ family of products – includes disinfectable panels, suspension systems, and trim
- Lightweight panels install with standard 15/16" suspension system
- Complete standard system from one manufacturer

COLORS   Due to printing limitations, shade may vary from actual product.

White
(WH)

Silver Grey
(SG)

Gun Metal
Grey (MY)

PERFORATION OPTIONS (1:2 scale shown)

M1
(Unperforated)

M10
(Rg 2513)

Armstrong®
World Industries

METALWORKS™ Concealed

smooth texture

VISUAL SELECTION

PERFORMANCE
Dots represent high level of performance.

Item No.◆	Dimensions (Inches) W x L x H	Perforations	Fire Performance	Light Reflect (White only)	Fog	Spray	Wipe	Wash	Scrub	Impact	Soil
METALWORKS™ Concealed 1/4" Reveal											
6664_ _ _ _ _	24 × 96 × 5/8"	M1; M10	Class A	0.73 (M1)	•	•	•	•	•	•	•
6665_ _ _ _ _	24 × 120 × 5/8"	M1; M10	Class A	0.73 (M1)	•	•	•	•	•	•	•
6666_ _ _ _ _	48 × 48 × 5/8"	M1; M10	Class A	0.73 (M1)	•	•	•	•	•	•	•
6667_ _ _ _	48 × 96 × 5/8"	M1; M10	Class A	0.73 (M1)	•	•	•	•	•	•	•
6668_ _ _ _ _	48 × 120 × 5/8"	M1; M10	Class A	0.73 (M1)	•	•	•	•	•	•	•

CleanAssure™ Disinfectable Panels — DURABILITY

◆ When specifying or ordering, include the appropriate perforation and color suffix with the item number (e.g., 6664 M 1 M Y).

ACOUSTICAL INFORMATION

Perforation		NRC
M1	Unperforated	N/A
M10	Rg 25ℓ3	0.80 • / 0.90† •

Maximum NRC achieved with acoustical infill options.

† With BioAcoustic™ infill item 5479. NRC of 0.90 with fiberglass infill 8200T10, NRC 0.80 as sold.

EXAMPLE: **6664 M10 SG**

Panel Dimension/Type: 24" x 96" — Perforation: M10 — Finish: Silver Grey

ACCESSORIES

| Item No.◆	Description	Dimensions (Inches)	Color	Pieces/Carton
6656M1_ _	MetalWorks™ Concealed Trim	6" x 120"	WH, SG, MY	6
7842A_ _	Slip-on Molding	1/2 × 120 × 5/8"	WH, SG, MY	40
FXTBC	T-bar Connector Clip	–	–	10
FX4SPLICE	Splice Plate with Set Screws	–	–	10
8200T10	Fiberglass Infill Panel	24 × 24 × 1"	Black (Gloss)	12
5823	BioAcoustic™ Infill Panel	24 × 24 × 5/8"	Black	12
5479	BioAcoustic™ Infill Panel	24 × 24 × 5/8"	Beige	12
7239	Adjustable Trim Clip	–	N/A	50

NOTE: Adjustable Trim Clip used with standard Axiom® or MetalWorks Trim systems.

SUSPENSION SYSTEM

15/16" Heavy-duty Prelude® XL® Suspension System

5986	T-Bar Hook†	Nominal 4 × 2 × 3"	50
90190A242	#10 Pan Head Sheet Metal Screw	1/2"	100
6091	Safety Cable	24" x 3/32"	50
SH12	Support Hanger	144" x 2"	12

† For 24" x 96", 48" x 48", and 48" x 96" panels, install 4 hooks per panel; for 24" x 120" and 48" x 120" panels install 6 hooks per panel.
NOTE: Refer to installation instructions at armstrongceilings.com/installation for a better understanding of suspension requirements.

2' Cross-T — Grid Hook — Main Beam — 2.094" — Attach with Item 90190A242 Typ. x3 — 2 x 8 Panel

Installation Detail – Concealed Ceiling System

PHYSICAL DATA

Material
Aluminum composite – 0.57" thick

Surface Finish
Factory-applied powder-coated finish (post-coated)

Acoustical Performance
MetalWorks™ Concealed perforated panels provide outstanding sound absorption. NRC 0.95 achieved with acoustical infill Item 5823. See CS-4172 for more information on infill panels.

Fire Performance
Class A: ASTM E84 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed 50 or less.

Installation Considerations
Please refer to installation instructions LA-297890 before installing MetalWorks Concealed panels.

Not made for SingleSpan™ corridor applications.

Seismic Restraint
MetalWorks Concealed panels have been engineered, tested, and approved for application in all seismic areas when installed per Armstrong installation instructions.

Cleaning and Disinfecting
Cleaning and CDC approved disinfecting options available on armstrongceilings.com/cleaning

Warranty
Details at armstrongceilings.com/warranty

Weight; Square Feet/Carton
0.97 lbs/SF (Bulk packaged)

Armstrong®
World Industries

METALWORKS™ – Standard