



A humidity resistant fiberglass panel with excellent sound absorption that is available in a variety of finish textures and colors.

FEATURES AND BENEFITS

- Excellent sound absorption for speech privacy
- Higher R-Value can reduce energy costs
- Humidity resistant
- Available in durable Nubby glass cloth or cost-effective Elite vinyl
- Foil backing available as an option for increased CAC

ATTRIBUTES



**RECYCLED
CONTENT**



**MOLD/MILDEW
RESISTANT
INHERENT**



**LR
0.03-0.84**



**SAG
RESISTANT**

LEED® v4

RECYCLED CONTENT		
1"	31%	
	PRE: 0%	POST: 31%
1.5"	36%	
	PRE: 0%	POST: 36%
3"	46%	
	PRE: 0%	POST: 46%

- ✓ MR: PBT Source Reduction (Healthcare)
- ✓ EQ: Acoustic Performance
- ✓ EQ: Prereq. Min. Acoustic Performance (Schools)
- ✓ EQ: Daylight
- ✓ MR: Sourcing Raw Materials
- ✓ MR: Construction and Demolition Waste Management Planning

LEED® is a registered trademark of the U.S. Green Building Council.


COLORS



White Nubby




White Elite




Black Nubby

EDGE DETAILS




Trim
9/16" EZ Stab
Elite Narrow




Trim
15/16" EZ Stab
Classic


WHITE NUBBY

WHITE NUBBY			FORMAT	DIMENSIONS (IN.)	NRC	CAC*	LR	RECYCLED CONTENT	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET
TRIM												
	NRC 1.00	1462-NBY-1	Panels	24 x 24 x 1-1/2	1.00	26	0.84	36%	16	64	34	14
		1460-NBY-1	Panels	24 x 48 x 1-1/2	1.00	26	0.84	36%	8	64	34	14
		1469-NBY-1	Panels	30 x 60 x 1-1/2	1.00	26	0.84	36%	8	100	52	14
		1470-NBY-1	Panels	60 x 60 x 1-1/2	1.00	26	0.84	36%	8	200	104	7
		1466-NBY-1	Planks	24 x 96 x 1-1/2	1.00	26	0.84	36%	8	128	67	10
	NRC .95	1442-NBY-1	Panels	24 x 24 x 1	0.95	25	0.84	31%	24	96	34	14
		1440-NBY-1	Panels	24 x 48 x 1	0.95	25	0.84	31%	12	96	34	14
		1444-NBY-1	Panels	48 x 48 x 1	0.95	25	0.84	31%	12	192	67	7
		1446-NBY-1	Planks	24 x 96 x 1	0.95	25	0.84	31%	12	192	67	10


BLACK NUBBY

BLACK NUBBY		FORMAT	DIMENSIONS (IN.)	NRC	CAC*	LR	RECYCLED CONTENT	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET	
TRIM												
	NRC .95	1442-NBY-5	Panels	24 x 24 x 1	0.95	25	0.03	31%	24	96	34	14
		1440-NBY-5	Panels	24 x 48 x 1	0.95	25	0.03	31%	12	96	34	14
		1444-NBY-5	Panels	48 x 48 x 1	0.95	25	0.03	31%	12	192	67	7
		1446-NBY-5	Planks	24 x 96 x 1	0.95	25	0.03	31%	12	192	67	10

WHITE ELITE PERFORATED

WHITE ELITE PERFORMED			FORMAT	DIMENSIONS (IN.)	NRC	CAC*	LR	RECYCLED CONTENT	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET
TRIM												
	NRC1.05	1492-ELTP-1	Panels	24 x 24 x 3	1.05	30	0.82	46%	4	32	32	14
		1490-ELTP-1	Panels	24 x 48 x 3	1.05	30	0.82	46%	4	32	32	14

WHITE ELITE UNPERFORATED

WHITE ELITE UNPERFORATED			FORMAT	DIMENSIONS (IN.)	NRC	CAC*	LR	RECYCLED CONTENT	PIECES/CARTON	SQ. FT./ CARTON	LBS./ CARTON	CARTONS/ PALLET
TRIM												
	NRC .95	1492-ELT-1	Panels	24 x 24 x 3	0.95	26	0.82	46%	8	32	32	14
		1490-ELT-1	Panels	24 x 48 x 3	0.95	26	0.82	46%	4	32	32	7

*CAC foil-backing available at additional charge. Add an F to the end of the item number. Contact Customer Support for lead times.

CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990.

PHYSICAL DATA

MATERIAL

Fiberglass

R-VALUE

3-inch offers 13.60 / 1.5-inch offers 6.50

FIRE CLASS (ASTM E1264)

All are Class A per ASTM E84 & CAN S102
Flame Spread: 25 or less
Smoke Developed: 50 or less

ASTM E1264 CLASSIFICATION

White Elite Finish: Type XII, Form 1,
Pattern C E (perforated), E (unperforated);
Nubby Finishes: Type XII, Form 2, Pattern E

MAINTENANCE

Wipe with a soft cloth or vacuum
with brush attachment.

MOLD/MILDEW RESISTANCE

Fiberglass substrate is inherently resistant
to the growth of mold and mildew.

WARRANTY

10-year 104/90 Limited Warranty
increases to 15 years when installed
with CertainTeed suspension
systems. Full warranty
information can be found at
[certaanteed.com/warranty](https://www.certaanteed.com/warranty).

