

9/16" EZ STAB TIER DROP SYSTEM

CEILINGS & WALLS ACOUSTICAL SUSPENSION SYSTEMS

MAIN RUNNER

CROSS TEE

9/16" WALL ANGLE

7/8" WALL ANGLE

Create a smooth transition from ceiling to walls with wall angle products. Choose standard wall angles for popular interior designs or incorporate shadow moldings along perimeters for a reveal-edge look.

FEATURES AND BENEFITS

- Narrow 9/16" face features a 3/16" wide center bulb to create a double 1/8" wide reveal and compatible with many Narrow Reveal Edge panels
- New EZ Stab clip technology allows for a fast and strong connection on cross tees with enhanced removability
- Centering tab on web for use with Trim Edge ceiling panels
- Double-stitched web design for lasting durability and strength
- Unlimited intersections for flexible cross tee placement
- Grid features G30 hot-dipped galvanized steel construction that is fully painted for corrosion resistance
- Intermediate- and heavy-duty certified profiles available to satisfy all seismic applications
- ICC certified (ESR-3336) and City of Los Angeles Building Code compliant via ESR-3336 LABC Supplement
- Available in Standard White. Additional color options are offered through our Post-Paint process. See the Visual Options - Suspension Systems page for color option details.

LEED® v4

RECYCLED CONTENT


up to 86%

- ✓ MR: PBT Source Reduction (Healthcare)
- ✓ MR: Material Ingredients (HPDs)
- ✓ EQ: Low-Emitting Material
- ✓ MR: Sourcing Raw Materials
- ✓ MR: Environmental Product Declaration (EPDs)
- ✓ MR: Construction and Demolition Waste Management Planning


LEED® is a registered trademark of the U.S. Green Building Council.

MAIN RUNNER

WALL ANGLE



SHADOW MOLDING



CERTIFICATIONS & PRODUCT DECLARATIONS



EPD AVAILABLE

HPD AVAILABLE

DeclareSM
Living Building Challenge Red List Free[®]

ARCHITECTURAL

CertainTeed
SAINT-GOBAIN

9/16" EZ STAB TIER DROP SYSTEM

	GRID FACE (IN.)	DIMENSIONS (IN.)	SLOT SPACING (IN.)	PIECES/ CARTON	FT./ CARTON	SEISMIC DESIGN CATEGORY	STRUCTURAL CLASSIFICATION (ASTM C635)	RECYCLED CONTENT PRE*	RECYCLED CONTENT POST*	RECYCLED CONTENT TOTAL*	ALLOWABLE UNIFORM LOAD (PLF)	ALLOWABLE CONCENTRATED LOAD AT MIDSPAN (LBF)**
MAIN RUNNERS												
EZTD12-14-18	9/16	144 x 1-3/4 x 9/16	6 O.C.	20	240	A-F	HD	9%	77%	86%	16.5	41.2
EZTD12-14-15	9/16	144 x 1-3/4 x 9/16	6 O.C.	20	240	A-C	ID	9%	77%	86%	15	37.5
CROSS TEE												
EZTD0.33-14-18	9/16	4 x 1-3/4 x 9/16	—	60	20	—	—	9%	77%	86%	—	—
EZTD0.5-14-18	9/16	6 x 1-3/4 x 9/16	—	60	30	—	—	9%	77%	86%	—	—
EZTD2-14-18	9/16	24 x 1-3/4 x 9/16	—	60	120	—	HD	9%	77%	86%	75.8	75.8
EZTD2-14-15	9/16	24 x 1-3/4 x 9/16	—	60	120	—	ID	9%	77%	86%	55.8	55.8
EZTD2.5-14-15	9/16	30 x 1-3/4 x 9/16	—	60	150	—	ID	9%	77%	86%	42	52.5
EZTD4-14-18	9/16	48 x 1-3/4 x 9/16	12 O.C.	60	240	—	HD	9%	77%	86%	16.5	41.2
EZTD4-14-15	9/16	48 x 1-3/4 x 9/16	12 O.C.	60	240	—	ID	9%	77%	86%	15	37.5
EZTD5-14-15	9/16	60 x 1-3/4 x 9/16	12 O.C.	20	100	—	ID	9%	77%	86%	7.8	24.4
EZTD5-14-15-3S	9/16	60 x 1-3/4 x 9/16	3 slots at 20, 30, 40 O.C.	20	100	—	ID	9%	77%	86%	7.8	24.4
EZTD6-14-15	9/16	72 x 1-3/4 x 9/16	12 O.C.	20	120	—	ID	9%	77%	86%	4.6	17.2
EZTD8-14-15	9/16	96 x 1-3/4 x 9/16	12 O.C.	20	160	—	ID	9%	77%	86%	2.0	10.0
WALL ANGLE												
WA14-9	9/16	144 x 7/8 x 9/16	—	40	480	—	—	19%	69%	88%	—	—
WA14-14	7/8	144 x 7/8 x 7/8	—	40	480	—	—	19%	69%	88%	—	—
WA14-14-10	7/8	120 x 7/8 x 7/8	—	40	480	—	—	19%	69%	88%	—	—
WA32-32	2	120 x 2 x 2	—	20	200	—	—	19%	44%	53%	—	—
WA32-32-12	2	144 x 2 x 2	—	20	240	—	—	19%	44%	53%	—	—
WA32-15	2	120 x 15/16 x 2	—	20	200	—	—	19%	44%	53%	—	—
WA32-15-12	2	144 x 15/16 x 2	—	20	240	—	—	19%	44%	53%	—	—
FLEXIBLE WALL ANGLE*												
FWA14-9	9/16	96 x 1-1/8 x 9/16	—	63	504	—	—	19%	69%	88%	—	—
FWA14-14	7/8	96 x 1-1/8 x 7/8	—	63	504	—	—	19%	69%	88%	—	—
SHADOW MOLDING												
SM1000	—	120 x 3/4 x 3/8 x 3/8 x 9/16	—	40	400	—	—	19%	69%	88%	—	—
SM1020†	—	120 x 15/16 x 3/8 x 3/8 x 3/4	—	40	400	—	—	19%	69%	88%	—	—
SM1030	—	120 x 15/16 x 1/2 x 1/4 x 9/16	—	40	400	—	—	9%	44%	53%	—	—
SM1040	—	120 x 15/16 x 1/4 x 1/4 x 15/16	—	40	400	—	—	9%	44%	53%	—	—
SM1050	—	120 x 15/16 x 3/8 x 3/8 x 15/16	—	40	400	—	—	9%	44%	53%	—	—
SM1060	—	120 x 15/16 x 1/4 x 1/4 x 9/16	—	40	400	—	—	9%	44%	53%	—	—






*Flexible Wall Angle is made of Rigid PVC

†SM1020 is not hemmed along 3/4" side.

*Maximum recycled content percentage. Recycled content varies by manufacturing location.

**Allowable concentrated loads at midspan are determined in accordance with AC308 Section 3.2. For each framing member, the allowable concentrated load must not be combined with the allowable uniform load. Use standard 9/16" Wall Angle and Shadow Molding









MAXIMUM FIXTURE WEIGHT

ITEM NUMBER	CONFIGURATION A B	FIXTURE A B	HANGER SPACING A B	MAXIMUM WEIGHT A B
Main Runner to Main Runner – Drawing Key: Main Runner (I) Cross tee (---) Hanger wire (+)				
EZTD4-14-15		24" x 48"	48"	56.00 lbs.
EZTD4-14-18		24" x 48"	48"	56.00 lbs.
EZTD4-14-15		24" x 48"	48"	56.00 lbs.
EZTD4-14-18		24" x 48"	48"	56.00 lbs.
EZTD4-14-15		24" x 24"	48"	43.00 lbs.
EZTD4-14-18		24" x 24"	48"	48.50 lbs.

Cross tees tested as follows: EZTD4-14-15 tested at 15.00 lbs/LF to 1/360 of 4' span; EZTD4-14-18 tested at 16.50 lbs/LF to 1/360 of 4' span.

9/16" EZ STAB TIER DROP SYSTEM

ACCESSORIES

		ITEM NUMBER	PRODUCT NAME	DIMENSIONS L" X W" X H" (MM)	PIECES/ CARTON	LBS./ CARTON
SEISMIC		CTSPC-2	Seismic Perimeter Clip	3-1/16 x 2-1/4 x 1-1/16 (78 x 58 x 27)	100	9
		CTSTJ	Seismic Transition Joint Clip	3-1/2 x 3-1/2 x 1-3/16 (89 x 89 x 31)	100	10
		SLEEVE TD	Tier Drop Seismic Sleeve	3 x 9/16 x 3/8 (76.2 x 14.3 x 9.5)	100	1
STANDARD		AHD	Adjustable Hold Down Clip	1-1/8 x 1/2 x 1-11/16 (29 x 13 x 43)	1000	16
		HW12	Hanger Wire 12' (3660 mm) 12 Gage (2.05 mm)	144 x 12 gage x 12 gage (3658 x 12 gage x 12 gage)	141	50
		SFYK	SmartFit Yoke	8.55 x 1.25 x 9.56 (217 x 32 x 243)	20	9
		IC-9	9/16" Inside Corner	3 x 3 x 1/16 (76 x 76 x 1.52)	100	10
		OC-9	9/16" Outside Corner	3 x 3 x 1/16 (76 x 76 x 1.52)	100	10

PHYSICAL DATA

CROSS TEE/MAIN RUNNER MATERIAL

Fully painted and hot dipped galvanized steel (G30)

FACE DIMENSION

9/16"

CROSS TEE/MAIN RUNNER INTERFACE

Override

DUTY CLASSIFICATION

Heavy duty and Intermediate duty per ASTM C635

CROSS TEE/MAIN RUNNER

SURFACE FINISH

Fully Painted

PROFILE HEIGHT

1-3/4"

VOC EMISSIONS

Independently certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017.

END DETAIL

Main Runner: Integral Stab
Cross Tee: Staked-on Stab Clip

SEISMIC CATEGORY

A, B, C, D, E, F

WARRANTY

10-year Limited Suspension Systems warranty increases to 15 years when installed with CertainTeed Ceiling Panels. Full warranty information can be found at certainteed.com/warranty.

SEISMIC PERFORMANCE

MAIN RUNNERS:

All main runners

MINIMUM LBS. TO PULLOUT

COMPRESSION/TENSION:

180 lbs.

CROSS TEES:

All cross tees

ICC EVALUATION SERVICE, INC., REPORT COMPLIANCE

Suspension systems manufactured by CertainTeed Ceilings have been reviewed and are approved by listing in ICC-ES Evaluation Report ESR-3336. CertainTeed suspension systems have been reviewed and are approved by listing in the City of Los Angeles Building Code ESR-3336 LABC Supplement. Evaluation Reports are subject to reexamination, revision and possible cancellation. Refer to certainteed.com/architectural for current reports.




9/16" EZ STAB TIER DROP SYSTEM

VISUAL OPTIONS — SUSPENSION SYSTEMS


ACOUSTICAL AND DRYWALL SUSPENSION SYSTEMS AND TERMINUS TRIM

Our newly expanded post-paint process allows for any CertainTeed Suspension System product to be painted in a variety of new colors, matching all CertainTeed colors along with any Sherwin-Williams® colors requested by the customer. We can also match any color if a color sample is provided.


CERTAINTEED STANDARD



ECOPHON®



METAL CEILINGS



For Special color options, contact your local sales representative.


The colors shown have been reproduced with all the fidelity possible with commercial printing processes. Also, a specific color may appear different on one class of product than another.

When placing an order for either Standard or Special colors, please use the following naming process proceeding each catalog code:

Standard face paint: ST + 3-letter color code
Standard 360 paint: 3T + 3-letter color code
Special face paint: SP + 3-letter color code
Special 360 paint: 3P + 3-letter color code

Example:
EZCS4-12-12 ST WEC

Example: EZCS4-12-12 ST WEC



CertainTeed ARCHITECTURAL

METAL • WOOD • FELT • FIBERGLASS & MINERAL FIBER • GYPSUM • SUSPENSION & INTEGRATED SYSTEMS
20 Moores Road, Malvern, PA 19355 800-366-4327 certainteed.com/architectural