Photo: ©Geoff Lyons

The Symphony *m* Rx line provides a white, clean, monolithic ceiling visual. Design with other products in the Symphony Rx line for acoustical solutions.

FEATURES AND BENEFITS

- Excellent sound absorption (NRC 0.70 & 0.80) and sound blocking (CAC 33-42)
- Exceptional durability, combined with superior stain resistance, water repellency and humidity resistance
- Tested to 2,000 wash cycles and compatible with most sanitizing solutions
- Satisfies USDA/FSIS guidelines for sanitary applications (commercial kitchens)
- Exceeds FGI guidelines for cleanability and acoustic performance in most healthcare applications
- Suited as clean room component to ISO Class 3 (highest among comparable products)

ATTRIBUTES

NRC UP TO 0.80

SAG RESISTANT

BIOSHIELD® MOLD/MILDEW RESISTANT

LOW VOC — EMISSION COMPLIANT CERTIFIED

WASHABLE W/ SANITIZING CHEMICALS

LR 0.90

CertaSize® Program
Non-standard sizes made to order on select products. Lead time varies. Contact your local sales rep or Customer Support

CERTIFICATIONS & PRODUCT DECLARATIONS

EPD AVAILABLE

HPD AVAILABLE

USDA CERTIFIED BIOBASED PRODUCT — PRODUCT 98%

Declare℠
Living Building Challenge Red List Free®
Declare℠ is a service mark of The International Living Future Institute.

LEED® v4

RECYCLED CONTENT	62%	
	PRE: 60%	POST: 2%

- ✓ EQ: Optimize Energy Performance
- ✓ EA: Prereq. Min. Energy Performance
- ✓ EQ: Interior Lighting
- ✓ MR: PBT Source Reduction (Healthcare)
- ✓ EQ: Acoustic Performance
- ✓ EQ: Prereq. Min. Acoustic Performance (Schools)
- ✓ EQ: Low-Emitting Materials
- ✓ EQ: Daylight
- ✓ MR: Material Ingredients (HPDs)
- ✓ MR: Sourcing Raw Materials
- ✓ MR: Environmental Product Declarations (EPDs)
- ✓ MR: Construction and Demolition Waste Management Planning

LEED® is a registered trademark of the U.S. Green Building Council.

ARCHITECTURAL

CertainTeed
SAINT-GOBAIN

SYMPHONY® *m* 80 Rx
SYMPHONY® *m* 70 Rx

SYMPHONY *m* 80 Rx

		FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	PIECES/ CARTON	SQ. FT./ CARTON	LBS./ CARTON	CARTONS/ PALLET
TRIM										
NRC .80	1222-80-RXS-1	Panels	24 x 24 x 7/8	0.80	40	62%	14	56	64	16
	1220-80-RXS-1	Panels	24 x 48 x 7/8	0.80	42	62%	8	64	74	14
REVEAL										
NRC .80	1222B-80-RXS-1	Panels	24 x 24 x 7/8	0.80	40	62%	14	56	64	16
	1220B-80-RXS-1	Panels	24 x 48 x 7/8	0.80	42	62%	8	64	74	14
NARROW REVEAL										
NRC .80	1222F-80-RXS-1	Panels	24 x 24 x 7/8	0.80	40	62%	14	56	64	16
	1220F-80-RXS-1	Panels	24 x 48 x 7/8	0.80	42	62%	8	64	74	14

SYMPHONY *m* 70 Rx

		FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	PIECES/ CARTON	SQ. FT./ CARTON	LBS./ CARTON	CARTONS/ PALLET
TRIM										
NRC .70	1222-RXS-1	Panels	24 x 24 x 3/4	0.70	38	62%	14	56	56	16
	1220-RXS-1	Panels	24 x 48 x 3/4	0.70	38	62%	8	64	64	16
REVEAL										
NRC .70	1222B-RXS-1	Panels	24 x 24 x 3/4	0.70	38	62%	14	56	56	16
	1220B-RXS-1	Panels	24 x 48 x 3/4	0.70	38	62%	8	64	64	16
NARROW REVEAL										
NRC .70	1222F-RXS-1	Panels	24 x 24 x 3/4	0.70	38	62%	14	56	56	16
	1220F-RXS-1	Panels	24 x 48 x 3/4	0.70	38	62%	8	64	64	16

SYMPHONY® *m* 80 Rx
SYMPHONY® *m* 70 Rx

ACCESSORIES

SYMPHONY m ACCESSORIES		PRODUCT NAME	PIECES/ CARTON	USE
	1170-SEL-1	Mineral Fiber Edge Sealant	1	For re-sealing cut edges; 1 quart container

EDGE DETAILS

Trim
9/16" EZ Stab
Elite Narrow

Trim
15/16" EZ Stab
Classic

Reveal Corner Bevel
15/16" EZ Stab
Classic

Narrow Reveal
Corner Bevel
9/16" EZ Stab
Elite Narrow

Narrow Reveal
Corner Bevel
9/16" EZ Stab
Bolt Slot

Narrow Reveal
Corner Bevel
9/16" EZ Stab
Tier Drop

PHYSICAL DATA

MATERIAL
Mineral Fiber

FIRE CLASS (ASTM E1264)
All are Class A per ASTM E84 & CAN/ULC S102
Flame Spread: 25 or less
Smoke Developed: 50 or less

ASTM E1264 CLASSIFICATION
Type IV, Form 2, Pattern E

VOC EMISSIONS
Independently certified compliant with
California Department of Public Health
CDPH/EHLB/Standard Method
Version 1.2, 2017.

MOLD/MILDEW RESISTANCE
BioShield treatment included for added mold
and mildew resistance.

APPLICATION CONSIDERATIONS
Clean panel using a sponge/cloth
dampened with water and mild liquid
detergent solution. Do not soak panel.
Cleanable with sanitizing chemicals.

WARRANTY
10-year 104/90 Limited Warranty increases
to 15 years when installed with CertainTeed
suspension systems. Full warranty
information can be found at
certainteed.com/warranty.