

KEY FEATURES

- Continuous PETN core for fast, dependable energy transmission.
- Strong, flexible, and waterproof textile + plastic construction.
- Available in multiple charge weights for different applications.
- Easily initiated by No. 6 / No. 8 plain, electric, non-electric or electronic detonators.
- Suitable as trunkline or downline for initiating explosives and boosters.

STORAGE & HANDLING

- Store Neo Cord in a cool, dry, well-ventilated explosive magazine approved for detonating cord(Class 6).
- Maintain proper inventory rotation; follow FIFO to use older stock first. Under good storage conditions, shelf life is typically up to 3 years.
- Keep the cord protected from moisture, especially in wet environments—water absorption can reduce PETN sensitivity, leading to initiation failure from the wet portion.
- Handle and transport with care at all times; although generally resistant to accidental ignition from normal shock or friction, it can be initiated by intense impact, severe abrasion, or direct lightning.
- Avoid exposure to high temperatures; stable between -10°C to 60°C. If temperatures rise between 60–70°C, limit exposure to no more than 24 hours.

NEO CORD

TECHNICAL DATASHEET

Neo Cord is a flexible, waterproof detonating cord consisting of a continuous PETN explosive core enclosed within layers of high-strength textile fibres and a durable plastic jacket. The construction provides excellent tensile strength, abrasion resistance and stability under demanding field conditions. Neo Cord serves as a reliable trunkline or downline for the rapid and simultaneous initiation of multiple charges, as well as for transferring initiation energy to detonator-sensitive explosives. It can be initiated by standard plain, electric or non-electric detonators and is available in a range of PETN charge weights to suit various blasting applications.





TECHNICAL DETAILS

NAME OF PRODUCT	PETN CORE LOAD (G/M)	LENGTH PER SPOOL (M)	DIAMETER (MM)	NO. OF SPOOL PER BOX	AVG. WEIGHT PER BOX (KGS)	VOD (M/S)	BREAKING LOAD (KGS)
NEOCORD 8	08 +/- 0.5	375	4.7 +/- 0.2	04	28	7000 +/- 500	55 - 65
NEOCORD 10	10 +/- 0.5	250 (export) 375	5.0 +/- 0.2	04	28	7000 +/- 500	55 - 65
NEOCORD 12	12 +/- 0.5	250 (export) 375	5.2 +/- 0.2	04	28	7000 +/- 500	60 - 65
NEOCORD 20	20 +/- 0.5	125	6.2 +/- 0.2	04	28	7000 +/- 500	65 - 70
NEOCORD 40	40 +/- 0.5	100	8.5 +/- 0.2	04	28	7000 +/- 500	90 - 95

Transport
Classification

Class

UN
Number

Standard
Packaging

1.1D

UN 0065





RECOMMENDATIONS FOR USE

- Cut the cord only with a sharp single-blade cutter or knife on a non-sparking (non-ferrous) surface; avoid scissors or any tool with a shearing action.
- Downlines must be one continuous length inside the blasthole—never use knots, joins, or splices underground.
- Initiate the Cord only with a suitable detonator (e.g., #8 / #6 strength electric or another cord with ≥ 5 g/m PETN core).
- Ensure all trunkline and branchline connections are made at right angles to minimize approach-type cut-offs.
- Pull all knots tight and trim excess tail so they don't cross or interfere with other cords or downlines.
- Lay surface trunklines straight, avoiding loops, sharp bends, kinks, or unnecessary slack. A closed-loop configuration may be used as added initiation security.
- Prevent kinks and loops in downlines by keeping them firm but not overstretched.
- When attaching cord to explosive cartridges or primers, tie it securely around the cartridge or pass it through the designated hole (depending on the primer type).
- Never pull cord off the reel over the end flange, as this may create tight bends and kinks, increasing misfire risk.

PRODUCT DISCLAIMER

© 2025 SBL Energy Ltd. All rights reserved. The details presented in this document ("Information") are intended to provide general technical guidance regarding the referenced products ("Products"). While reasonable care has been taken in compiling this Information, SBL Energy Ltd does not guarantee its accuracy, consistency, or applicability to every operational environment, and the Information may be updated or amended without prior notice. Explosive Products must only be handled, transported, and used by personnel who are properly trained, certified, and authorized to work with such materials. Users are responsible for assessing site-specific conditions, verifying regulatory requirements, and ensuring that all procedures align with applicable safety standards and legal obligations. To the extent permitted by law, SBL Energy Ltd rejects any form of warranty—statutory, express, or implied—relating to the Information or the Products, including but not limited to performance guarantees or suitability for a particular use. The company shall not be held liable for any loss, damage, injury, or operational consequence arising from reliance on this Information or from misuse or improper handling of the Products.

This document is provided solely for reference and shall not be interpreted as a contractual commitment, product guarantee, or legally binding representation by SBL Energy Ltd.

